



Castrol Activ 4T 20W-40

With ActiBond

Description

Castrol Activ 4T with ActiBond™ is a modern, high quality engine oil developed specifically for 4-stroke motorcycle engines. The special ActiBond™ clings and protects critical engine components, providing continuous protection in all riding conditions. Castrol Trizone Technology™ protects the engine, clutch and gears and allows the best functionality of these three critical areas of the motorcycle.

Application

Castrol Activ 4T is suitable for all modern motorcycle engines where API SL (and below) and/or JASO MA specifications are recommended.

Advantages

- Provides continuous protection even when the engine is off.
- Actibond™ molecules cling and protect during all riding conditions.
- Trizone Technology™ for protection of the engine, clutch and gears.
- Complies with requirements of catalyst equipped engines.

Typical Characteristics

Name	Method	Units	Typical
Density @ 15C, Relative	ASTM D4052	g/ml	0.88
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.0
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	189
Viscosity, CCS -15C (20W)	ASTM D5293	mPa.s (cP)	9000
Viscosity Index	ASTM D2270	None	114
Total Base Number, TBN	ASTM D2896	mg KOH/g	9.8

Product Performance Claims

API SL
JASO MA2

Castrol Activ 4T 20W-40
14 Apr 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Philippines Inc, 32nd Floor, LKG Tower, 6801 Ayala Avenue, Makati City, Philippines 1226
Technical Advice Line: +63 2 8841478 Customer Service: +63 2 8841478 Fax No. +63 2 8841911
www.castrol.com