

CRB Mini Truck 15W-40 CNG

For long and healthy engine life

Description

Castrol CRB Mini Truck 15W-40 CNG with Heatshield boosters is engineered specifically to fight heat in your CNG mini truck engine.

Mini-Trucks are unique and subjected to special driving conditions. CRB Mini Truck is specially formulated for natural gas engines operating in mini truck driving conditions, offering excellent protection with its optimised formulation



Advantages

Castro CRB Mini Truck 15W-40 CNG delivers 3 times better heat protection.*

Typical Characteristics

Name	Method	Units	CRB Mini Truck 15W-40 CNG
Density @ 15C	ASTM D4052	g/ml	0.873
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.5
Viscosity, CCS -20C	ASTM D5293	mPa.s (cP)	6400
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	112
Viscosity Index	ASTD2270		132
Ash, Sulphated	ASTM D874	% wt	0.64
Total Base Number, TBN	ASTM D2896	mg KOH/g	4.6
Pour Point	ASTM D97	°C	-36
Flash Point	ASTM D93	°C	214

*(In Industry oxidation testing CRB Mini Truck lasted three times longer than a conventional API CF-4 oil)

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

CRB Mini Truck 15W-40 CNG

14 Jun 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd, Technopolis Knowledge Park, PO Box. 19411, 1st Floor, Mahakali Caves Road, Mumbai - 400093, India
Technical Advice Line: Customer Service - 1800 209 8100 (Tata Indicom), Phone: 022-6783 9800
Customer Service: www.castrol.co.in Email: customercare.india@castrol.com