

Castrol GTX SUV 5W-30

Helps extend engine life of SUVs and Pick-ups

Description

Castrol GTX is one of the world's most trusted engine oils.

The modern world creates difficult challenges for SUV engines. SUVs usually operate under heavy loads which can produce harmful deposits, thicken the oil to restrict flow causing damage to critical engine components. This can significantly reduce the life of an engine.

Application

Castrol GTX SUV 5W-30 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an ACEA A3/B4 5W-30 lubricant.

Advantages

Castrol GTX SUV with Double Action formula and synthetic technology:

1. Provides 30% better protection against deposits in gasoline and diesel engines under heavy load*.
2. Helps extend engine life of SUVs and Pick-ups in heavily loaded conditions

*as tested in Sequence IIIG vs API SL limits and OM646LA Bio vs ACEA A3/B4-16 industry standard engine tests.

Typical Characteristics

Name	Method	Units	Castrol GTX SUV 5W-30
Density @ 15C, Relative	ASTM D4052	g/ml	0.855
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	12.1
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	6200
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	73
Viscosity Index	ASTM D2270	None	166
Pour Point	ASTM D97	°C	-39
Flash Point	ASTM D92	°C	232
Ash, Sulphated	ASTM D874	% wt	1.2

Product Performance Claims

ACEA A3/B4

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol GTX SUV 5W-30

31 Oct 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd, Technopolis Knowledge Park, PO Box. 19411, 1st Floor, Mahakali Caves Road, Mumbai - 400093, India

Technical Advice Line: Customer Service - 1800 209 8100 (Tata Indicom), Phone: 022-6783 9800

Customer Service: www.castrol.co.in Email: customercare.india@castrol.com