



## Castrol GTX 15W-40 A3/B3

SUPERIOR SLUDGE PROTECTION TO HELP EXTEND ENGINE LIFE

### Description

Castrol GTX is one of the world's most trusted motor oils.

It's more than just oil. It's liquid engineering that protects against problems, like sludge, that your engine faces every day.

Severe driving conditions such as every day stop-and-go/stop-start traffic, harsh weather conditions and extended drain intervals, can all cause the build-up of a thick, tar-like substance called sludge. You can't see this sludge build-up but it can damage your engine's performance and cause premature engine failure.

Protect your car from harmful sludge build-up with Castrol GTX.

### Application

GTX 15W-40 A3/B3 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an ACEA A3/B4, API SP or earlier specification 15W-40 lubricant.

GTX 15W-40 A3/B3 is also approved for use in VW group vehicles that require a VW 501 01/ 505 00 lubricant and meets FIAT 9.55535-D2. It is suitable for use in Mercedes-Benz vehicles requiring MB 229.1.

### Advantages

Castrol GTX 15W-40 A3/B3

- Contains anti-sludge formula that provide better sludge protection compared to tough industry standards\*
- Superior protection against viscosity and thermal breakdown
- Anti-wear additives that extend the life of your engine

\*API SP

## Typical Characteristics

Name	Method	Units	Castrol GTX 15W-40 A3/B3
Density @ 15C, Relative	ASTM D4052	g/ml	0.870
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	14.6
Viscosity, CCS -20C (15W)	ASTM D5293	mPa.s (cP)	5800
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	110
Viscosity Index	ASTM D2270	None	137
Pour Point	ASTM D97	°C	-36
Flash Point, PMCC	ASTM D93	°C	208
Ash, Sulphated	ASTM D874	% wt	1.2

## Product Performance Claims

ACEA A3/B4

API SP

Meets - Fiat 9.55535-D2

VW 501.01/ 505 00

Suitable for use in vehicles requiring MB 229.1

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol GTX 15W-40 A3/B3

02 Dec 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

[www.castrol.com](http://www.castrol.com)