



Castrol Power 1 Racing 4T 5W-40

Race Derived Technology

Description

Castrol POWER1 Racing 4T 5W-40 is fully synthetic 4-stroke engine oil for modern high performance sports bikes that increases engine acceleration and power right up to maximum rpm.

Its Race Derived Technology based on Castrol's racing history and testing experience ensures maximum engine performance without sacrificing engine durability thus giving a significant benefit over other types of engine oils.

Castrol POWER1 Racing 4T 5W-40's formula employs the very latest Trizone Technology™ for 4-stroke motorcycles, providing optimum protection of the engine, clutch and gears even under the most arduous riding conditions including sustained operation at high rpm.

Application

Castrol POWER1 Racing 4T 5W-40 is designed for high performance sports bikes to deliver optimum power and protection in all conditions where API SL (and below) and JASO MA2 are recommended.

Advantages

- Fully synthetic 4-stroke motorcycle engine oil featuring Trizone Technology™
- Race derived formulation technology for maximum engine acceleration
- Extreme high temperature air-cooled and water-cooled engine performance
- Excellent oil consumption and volatility control at high speeds
- Excellent shear stability to prevent viscosity break down
- Complies with requirements of catalyst equipped engines

Typical Characteristics

| Name | Method | Units | POWER1 Racing 4T 5W-40 |
|------------------------------|------------|--------------------|------------------------|
| Appearance | Visual | - | Clear & Bright |
| Viscosity, Kinematic @ 100°C | ASTM D445 | mm ² /s | 13.0 |
| Viscosity, Kinematic @ 40°C | ASTM D445 | mm ² /s | 75 |
| Viscosity Index | ASTM D2270 | - | 175 |
| Pour Point | ASTM D97 | °C | -39 |
| Flash Point, PMCC | ASTM D93 | °C | 205 |

Product Performance Claims

API SL
JASO MA2

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Power 1 Racing 4T 5W-40

18 Sep 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 132 McCredie Road, Guildford NSW 2161, Australia
Technical Advice Line 1300 557 998 Customer Service 1300 554 890
www.castrol.com.au www.msds.castrol.com.au