



Castrol POWER1 4T 15W-50

Power Sustain Technology™

Description

Castrol POWER1 4T with **Power Sustain Technology™** is designed specifically for bikers who love the exhilaration of riding

New Castrol POWER1 4T with **Power Sustain Technology™** manages heat and friction, ensuring continuous power delivery and provides on-demand acceleration.

Application

Castrol POWER1 4T 15W-50 is designed to manage heat & friction to provide sustained power delivery and on-demand acceleration.

It is suitable for all 4-stroke motorcycle engines, both carburetor and fuel injected where API SN (or below) and JASO MA or MA2 are recommended.

Advantages

- Manages heat and friction in the engine, to ensure continuous power delivery and gives on-demand acceleration. It is specially formulated to suit long riding conditions.
- New POWER1 4T 15W-50 resists oil thickening caused by high temperatures
- New POWER1 4T 15W-50 maintains your bikes performance during long rides.
- Complies with requirements of catalyst equipped engines

Typical Characteristics

Name	Method	Units	POWER1 4T 15W-50
Density @ 15C, Relative	ASTM D4052	g/ml	0.874
Appearance	Visual	-	Clear & Bright
Viscosity, Kinematic 100°C	ASTM D445	cSt	17.86
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	139.4
Viscosity Index	ASTM D2270	None	142
Pour Point	ASTM D97	°C	-36
Flash Point, PMCC	ASTM D93	°C	206.5

Product Performance Claims

API SN
JASO MA2

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol POWER1 4T 15W-50

28 May 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This Data Sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a valid license. It is the User's obligation to evaluate and use products safely and within the scope advised in the Data Sheet, to assess suitability for the intended application, and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the products. The Seller shall not be responsible for any loss, damage or injury resulting from any abnormal use of the product, from any failure to adhere to recommendations, nor from any hazards or risks which are i) identified in the Data Sheet, ii) inherent in the nature of petroleum products or iii) associated with the petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned). All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road , Wayne, NJ 07470

www.castrol.com