



## GTX High Mileage 25W-60

HELPS PREVENT EMISSION SYSTEM FAILURE

### Description

It's more than just oil. It's liquid engineering.

#### Get more life from your vehicle with Castrol GTX High Mileage

All motor oils contain phosphorous to help prevent engine wear. Phosphorous is an industry recognized catalyst poison. To help prevent catalytic converter and emission system failure, Castrol GTX High Mileage's patented advanced technology is specially formulated with less phosphorous than other leading oils while still delivering unsurpassed protection against sludge, wear and oil-burn-off. (1)

### Application

Castrol GTX High Mileage 25W-50 is suitable for use in automotive gasoline engines where the manufacturer recommends an API SP or earlier specification 25W-50 lubricant.

### Advantages

#### Castrol GTX High Mileage also delivers:

- Superior dispersancy that fights sludge build-up (2)
- Exceptional oil burn-off protection exceeding industry standards (3)
- Seal conditioners to help reduce leaks
- Advanced additives to minimize engine wear
- An ingredient to help improve fuel economy

(1) Based in SqVH Sludge Test and SqIVA Wear Test in 5W-30 and Noack Volatility test

(2) Based in SqVHTest in 5W-30

(3) Based on API and ACEA volatility specification

## Typical Characteristics

Name	Method	Units	Castrol GTX High Mileage 25W-50
Density @ 15C, Relative	ASTM D4052	g/ml	0.881
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	24.3
Viscosity, CCS -10C (25W)	ASTM D5293	mPa.s (cP)	6011
Pour Point	ASTM D97	°C	-20
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	240
Viscosity Index	ASTM D2270	None	127
Flash Point, PMCC	ASTM D93	°C	265
Ash, Sulphated	ASTM D874	% wt	0.73

## Product Performance Claims

API SP

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.