



Agri Power Plus 15W-40

Agricultural engine oil

Description

High protection against wear and other contaminants in modern petrol and diesel engines.

Application

- One oil for farm and on road vehicles
- Prevents engine wear to prolong component life
- Potential to extend oil drains keeping vehicles in the field

Typical Characteristics

Name	Method	Units	Agri Power Plus
Density @ 15C, Relative	ASTM D4052	g/ml	0.885
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.2
Viscosity, CCS -20C	ASTM D5293	mPa.s (cP)	6600
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	106
Viscosity Index	ASTM D2270	None	137
Ash, Sulphated	ASTM D874	% wt	1.37
Total Base Number, TBN	ASTM D2896	mg KOH/g	10.6
Pour Point	ASTM D97	°C	-36
Flash Point, PMCC	ASTM D93	°C	221

Product Performance Claims

ACEA E3, E5, E7

API CH-4/SJ

CAT ECF-1-A

Castrol recommends the use of Agri Power Plus 15W-40 in tractor engines requiring lubricants meeting specification JDQ78A

for John Deere models 6020, 6120, 6220, 6320, 6420 & 6420S that can be operated with a maximum 500 hour drain interval

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Agri Power Plus 15W-40

04 Sep 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

www.castrol.com/uk