



Product Data

## Castrol Vecton Long Drain 10W-40 E7

For longer useful oil life

### Description

Castrol VECTON® Long Drain 10W-40 E7 is an advanced synthetic heavy duty diesel engine oil that is specifically engineered to deliver longer useful oil life.

### Application

Castrol VECTON® Long Drain 10W-40 E7 is suitable for use in highly rated diesel engines meeting Euro I to Euro V emission requirements. It is suitable for engines without particulate filters, for some EGR engines and some engines fitted with SCR NOx reduction systems.

### Advantages

Castrol VECTON Long Drain 10W-40 E7 with System Pro Technology™ is specifically engineered and tested for extended drains up to 120,000 km\*.

Modern trucks use new technologies to make as much as 30% higher torque, but that also means higher engine temperatures and pressures. This punishes the oil, pushing it closer to breakdown, and reducing its useful life and ability to extend drains. Castrol VECTON Long Drain 10W-40 E7 fights oil breakdown by:

- Combating oxidation and deposits
- Neutralizing harmful acids
- Controlling oil aeration
- Adapting to increased temperatures, resisting viscosity loss through shear.

All of this means longer useful oil life giving you the confidence in your maximum drain interval.

\* is approved by MAN for oil drain up to 120,000km, in accordance with their specifications. Actual oil drain depends on engine type, operating conditions, service history, OBD and fuel quality. Always consult your manufacturer's handbook.

## Typical Characteristics

| Name                      | Method     | Units              | Vecton Long Drain 10W-40 E7 |
|---------------------------|------------|--------------------|-----------------------------|
| Density @ 15C             | ASTM D4052 | g/ml               | 0.865                       |
| Viscosity, Kinematic 100C | ASTM D445  | mm <sup>2</sup> /s | 14.4                        |
| Viscosity, Kinematic 40C  | ASTM D445  | mm <sup>2</sup> /s | 97                          |
| Viscosity Index           | ASTM D2270 | None               | 155                         |
| Pour Point                | ASTM D97   | °C                 | -45                         |
| Viscosity, CCS -25C (10W) | ASTM D5293 | mPa.s (cP)         | 5700                        |
| Flash Point, PMCC         | ASTM D93   | °C                 | 215                         |
| Total Base Number, TBN    | ASTM D2896 | mg KOH/g           | 12                          |
| Ash, Sulphated            | ASTM D874  | % w t              | 1.85                        |

## Performance

ACEA E4, E7  
API CF  
Deutz DQC III-18  
DTFR 15B120  
Mack EO-N,  
MAN M 3277  
MTU Oil Category 3  
RVI RLD-2  
Scania LDF-3  
Volvo VDS-3  
Meets DAF requirements

## Additional Information

Castrol Vecton Long Drain 10W-40 E7 is also suitable for use where older specifications are recommended that are backwards compatible from the latest specs and approvals held by this product. This includes Deutz DQC III-10, MAN M3275-1, MTU Categories 2 &1, RVI RLD, Volvo VDS-2

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Vecton Long Drain 10W-40 E7

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW  
Orders/Enquiries: 0845 6008125 Technical Enquiries: 0845 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353  
[www.castrol.com/uk](http://www.castrol.com/uk)