



Product Data

## Brayco Micronic 881

Low Temperature Hydraulic Fluid

### Description

Castrol Brayco<sup>®</sup> Micronic 881 is a fire resistant, synthetic hydrocarbon base, low temperature ISO viscosity Grade 7, red-colored hydraulic fluid for aircraft, missile, ordnance, and industrial use. It is specifically designed for low temperature applications where low temperature stability is particularly important. This product also provides controlled rubber swell for long seal life, low foaming properties, excellent anti-wear, corrosion protection, and oxidation stability.

### Application

Castrol Brayco Micronic 881 is designed as a low temperature fire resistant hydraulic fluid for aircraft and missile use, but has use in many industrial applications as well. Temperature Range -54°C TO 135°C (-65°F TO 275°F)  
Castrol Brayco Micronic 881 is qualified to MIL-PRF-87257F.

### Typical Characteristics

Name	Method	Units	Result
Kinematic Viscosity @ 100°C @ 40°C @ -40°C @ -54°C 3 hour soak @ -54°C 72 hour soak @ -54°C	ASTM D 445/ISO 3104	mm <sup>2</sup> /s	2.21 7.2 492 2350 2354 2377
Evaporation, % wt 6.5 hrs @ 135°C	FTM 350	%	15
Flash Point, COC	ASTM D 92/ISO 2592	°C / °F	172 / 342
Fire Point, COC	ASTM D 92/ISO 2592	°C / °F	190 / 375
Four Ball Wear, wear scar diameter 1 kg load / 10 kb load / 40 kg load	ASTM D 4172	mm	0.12 / 0.22 / 0.56
Neutralization Number	ASTM D 664	mg KOH/g	0.11
Water Content	ASTM D 1744/ISO 6296	ppm	46
Rubber Swell, "L"	FTM 3603	%	28
Low Temperature Stability 72 hrs @ -54°C	FTM 3465	Pass/Fail	Pass
High Temperature Stability Viscosity Change @ 40°C Acid or Base Number Increase Precipitate or Insoluble material	Spec 4.4.5	% % None	2.25 0 None
Foaming Characteristics Sequence I, Foaming Tendency	ASTM D 892/ISO 6247	mls / mls	25 / 0
Viscosity Index	ASTM D 2270/ISO 2909	-	115
API Gravity	ASTM D 287	degrees	36.3

Name	Method	Units	Result
Specific Gravity	ASTM D 1298/ISO 3675	-	0.843
Density	ASTM D 4052/ISO 12185	lbs/gal	7.02
Corrosion and Oxidation Stability, 168 hrs @ 135°C Corrosion, pitting, etching Corrosion weight change Copper Steel Aluminum Magnesium Cadmium Viscosity Change @ 40°C Acid or Base Number Increase Evidence of separation	FTM 3603	mg/cm <sup>2</sup> mg/cm <sup>2</sup> mg/cm <sup>2</sup> mg/cm <sup>2</sup> mg/cm <sup>2</sup> mm <sup>2</sup> /s mg KOH/g	None -0.02 0.01 -0.01 -0.01 0.02 +2 0.0 Pass
Copper Strip Corrosion	ASTM D 130/ISO 2160	-	2A
Solid Particle Contamination Size Autocount 5 - 15 µm 16 - 25 µm 26 - 50 µm 51 - 100 µm Over 100 µm Gravimetric Residue Filtration Time	Table VII Spec 4.4.6	mg solids minutes	2237 120 40 10 0 0.1 7
Pour Point	ASTM D 97/ISO 3016	°C / °F	-66 / -85
Bulk Modulus (Isothermal Secant) 0 to 6.9x10 <sup>4</sup> KpA @ 40°C 10,000 PSI @ 38°C	Spec 4.4.4	KpA psi	1.379x10 <sup>6</sup> min 200,000 min
High Temperature, High Pressure Spray Ignition	FTM 6052	-	No burn after ignition source is removed
Flame Propagation Rate	Spec.	cm/s	0.26
Auto-Ignition Temperature	ASTM E 659	°C / °F	345 / 653
Low Temperature Viscosity Stability 3 hrs @ -54°C 72 hrs @ -54°C	ASTM D 445/ISO 3104	cSt	2297 2331
ASTM Color - Basestock Color	ASTM D 1500	-	<0.5
Color, Finished Fluid	Spec. 4.4.7	-	Red

Subject to usual manufacturing tolerances

Brayco Micronic 881

07 Jan 2026

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre, Whitchurch Hill, Pangbourne, Reading, RG8 7QR, United Kingdom

<http://msdspds.castrol.com>