

Castrol Optitemp RB 1

Light-beige special grease for cable lubrication in robots

Description

OPTITEMP™ RB 1 is a light-beige special grease based on polyalphaolefins for the lubrication of cables in robots.

Application

- Lifetime lubrication of cables
- Easy application (manual or with spraying gun) due to the soft structure of the product
- OPTITEMP RB 1 guarantees an easy, low-friction shifting and sliding of cables at rails, walls and of insulating plastic tubes
- Grease-lubricated sliding surfaces
- Temperature application range: - 30°C/- 22°F to + 130°C/+ 266°F

Advantages

- OPTITEC™ - OPTIMOL technology
- compatible with elastomers and plastics such as PUR, PVC, Polyester, used in modern robots due to a high number of different elastomer qualities we recommend compatibility test with original elastomers
- no impairment if in contact with two-component sliding lacquers, top coat RAL
- compatible with paints i.e. no impairment of car body surfaces
- resistant to weld chips i.e. red hot metal chips generated during welding do not ignite the grease or the base oil
- optimum wear protection
- good water resistance
- no drying of the product
- no skin irritations

Typical Characteristics

Test	Method	Unit	Value
CASTROL OPTITEMP RB 1	-	-	-
Color	visual	-	light-beige
Base	-	-	lithium
Consistency/NLGI grade	DIN 51818	-	2
Worked penetration Pw 60	DIN ISO 2137	0.1 mm	296
Dropping point	DIN ISO 2176	°C	192
Water resistance at + 50°C	DIN 51807 T. 1	-	0
Corrosion protection (SKF Emscor)	DIN 51802	-	0 - 0
Copper corrosion at + 100°C	DIN 51811	-	0
Oil separation 168 h/+ 40°C	DIN 51817	%	3.7

Subject to usual manufacturing tolerances

Additional Information

- OPTITEMP RB 1 must not be mixed with other greases.
- Mixing with other greases may lead to decreased performance.

Castrol, Optitemp, and the Castrol logo are trademarks of Castrol Limited, used under licence

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Limited, Pipers Way, Swindon, Wiltshire SN3 1RE, UK
www.castrol.com/industrial