



Transmax Manual E Long Life 40

Synthetic transmission fluid

Description

Transmax Manual E Long Life 40 is a specially formulated synthetic lubricant designed for fuel efficiency, extended drain intervals and severe service in heavy duty commercial vehicle transmissions which require a non-EP transmission lubricant. It is specially formulated to protect higher torque transmissions coupled with increased horsepower engines. It is approved for use in Eaton transmissions such as Ultrashift Plus, Fuller Advantage, FR and RT Series transmissions.

Advantages

- Proven to provide better fuel economy versus earlier PS-164rev7 transmission fluids
- High performance and extended drain capabilities in transmissions
- Excellent thermal and oxidation stability which resists deposit and sludge formation
- Excellent protection from corrosion, foaming, rust, and wear
- Superb high and low temperature performance
- Friction retention, friction durability, and excellent shear stability to ensure and maintain smooth transmission operation throughout the extended service interval
- Formulated to reduce sump operating temperatures

Typical Characteristics

Name	Method	Units	Transmax Manual E Long Life 40
Density @ 15.6°C	ASTM D1298	kg/m ³	0.850
Viscosity, Kinematic 100°C	ASTM D445	cSt	14.8
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	95.1
Viscosity Index	ASTM D2270	None	163
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	51900
Flash Point, COC	ASTM D92	°C	238
Pour Point	ASTM D97	°C	-42

Product Performance Claims

Eaton PS 386 approved

Transmax Manual E Long Life 40

13 Oct 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 132 McCredie Road, Guildford NSW 2161, Australia
Technical Advice Line 1300 557 998 Customer Service 1300 554 890
www.castrol.com.au www.msds.castrol.com.au