



POWER1 4T 15W-50

THE OIL THAT OFFERS OUTSTANDING PERFORMANCE AND PROTECTION.

Description

New Castrol POWER1 with 3-in-1 FORMULA is engineered to deliver outstanding performance and protection.

Application

Castrol POWER1 is suitable for motorcycles which require API SN (or lower) and JASO MA2 engine oils.

Advantages

Castrol POWER1 with the power of 3-in-1 FORMULA delivers:

- Excellent acceleration
8 meters ahead of a competitor's oil for bikes*
- Excellent protection
- Smooth riding Complies with requirements of catalyst equipped engines

* Tested using 10W-40 oils in a Honda CB125F at wide-open throttle for 30 seconds from a rolling start. Acceleration benefits will be subject to riding style and oil viscosity grade.

Typical Characteristics

Name	Method	Units	Castrol POWER1 4T 15W-50
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	136
Flash Point, PMCC	ASTM D93	°C	217
Density @ 15C, Relative	ASTM D4052	g/ml	0.86
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	17.7
Appearance	Visual		Clear & Bright
Flash Point, COC	ASTM D92	°C	247
Viscosity Index	ASTM D2270	None	144

Performance

API SN
JASO MA2

POWER1 4T 15W-50

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com