



Castrol GTX ESSENTIAL SG 20W-50

Protection to help extend engine life

Description

It's more than just oil. It's liquid engineering.

Castrol GTX is one of the world's most trusted engine oils.

It's more than just oil. It's liquid engineering that protects against the problems your engine faces every day.

Car maintenance can be expensive, but poor engine oils can risk the life of your engine and hurt the value of your investment.

New GTX ESSENTIAL does essential maintenance of your engine by helping keep it clean and fighting wear, bringing with it the trust of a brand used by millions of mechanics worldwide.

Help extend the life of your engine with Castrol GTX ESSENTIAL.

Application

Castrol GTX Essential's CNG variant is suitable for use in CNG/LPG engines including 3-wheelers.

Advantages

Castrol GTX ESSENTIAL provides:

- Protection against engine sludge
- Viscosity stability
- Pressure control
- Helps minimize oil consumption

Typical Characteristics

Name	Method	Units	Castrol GTX ESSENTIAL SG 20W-50
Density @ 15C, Relative	ASTM D4052	g/ml	0.889
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	17.7
Viscosity, CCS -15C (20W)	ASTM D5293	mPa.s (cP)	9000
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	160
Viscosity Index	ASTM D2270	None	122
Pour Point	ASTM D97	°C	-27
Flash Point, PMCC	ASTM D93	°C	218
Ash, Sulphated	ASTM D874	% wt	0.76

Product Performance Claims

API SG/CD

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol GTX ESSENTIAL SG 20W-50

26 Feb 2021

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd, Technopolis Knowledge Park, PO Box. 19411, 1st Floor, Mahakali Caves Road, Mumbai - 400093, India

Technical Advice Line: Customer Service - 1800 209 8100 (Tata Indicom), Phone: 022-6783 9800

Customer Service: www.castrol.co.in Email: customercare.india@castrol.com