



## Agri Hydraulic Oil Plus

Tractor hydraulic oil

### Description

Castrol Agri Hydraulic Oil Plus is a high viscosity index mineral oil that ensures excellent hydraulic response over a wide temperature range.

### Application

Castrol Hydraulic Oil Plus satisfies the lubrication requirements of virtually all agricultural hydraulic systems, giving improved levels of protection. Along with ISO VG 46, its wide span viscosity characteristics also make it suitable for use in certain applications where an ISO VG 32 or 68 fluid is required.

### Advantages

Castrol Agri Hydraulic Oil Plus offers the following benefits:

- Excellent shear stability, maintaining VI throughout the life of the fluid and giving low viscosity change with temperature fluctuation
- High anti-wear performance, reduced component wear
- Excellent thermal stability and oxidation resistance, with extended drain potential
- Excellent water tolerance and demulsification characteristics, reduced oil consumption

### Typical Characteristics

Name	Method	Units	Agri Hydraulic Oil Plus
Density @ 15C, Relative	ASTM D1298	g/ml	0.88
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	46
Viscosity Index	ASTM D2270	None	153
Pour Point	ASTM D5985	°C	-36
Flash Point, PMCC	ASTM D93	°C	220
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	8.2

ISO VG 46; DIN 51524 Part 3; BS 5063 Class HV; DIN Classification HVLP

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Agri Hydraulic Oil Plus

01 Feb 2016

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

[www.castrol.com/uk](http://www.castrol.com/uk)