



Castrol POWER1 4T 10W-40

Power Release Formula

Description

Castrol POWER 1 4T 10W-40 is advanced, premium quality engine oil designed for the latest generation of 4-stroke motorcycle engines. It's 'Power Release Formula' helps the lubricant to flow fast and reduces internal engine losses to friction, giving maximum and sustained power right up to very high operating rpm.

Castrol POWER 1 4T 10W-40 has been tested and proven to deliver superior acceleration at the touch of the throttle.

The added Castrol advantage of Trizone Technology™ ensures uncompromised performance protection.

Castrol POWER 1 4T 10W-40 - engineered for performance.

Application

Castrol POWER 1 4T 10W-40 is designed to optimise performance for motorcycle engines.

It is suitable for all makes of 4-stroke bikes, both carburettor or fuel injected where API SL (or below) and JASO MA or MA2 are recommended

Advantages

- Tested and proven to deliver superior acceleration at the touch of the throttle
- Power Release formula helps to flows fast and reduces internal engine losses to friction
- Trizone Technology™ for protection of engine, clutch and gears
- Suitable for use in catalyst equipped engines

Typical Characteristics

Name	Method	Units	POWER1 4T 10W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.8
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	13.5
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	90
Viscosity Index	ASTM D2270	None	155
Pour Point	ASTM D97	°C	-36
Flash Point, PMCC	ASTM D93	°C	205

Product Performance Claims

API SL
JASO MA2

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol POWER1 4T 10W-40
28 Dec 2018
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com