



Radicool SF

Antifreeze Coolant

Description

Castrol Radicool SF is a long-life coolant based on monoethyleneglycol with advanced organic acid inhibitor technology. In contrast to traditional antifreeze coolants, Castrol Radicool SF does not contain amines, nitrites, phosphates, silicates or other inorganic inhibitors.

Castrol Radicool SF provides excellent corrosion protection particularly to those engines employing light metals. It is suitable for a wide range of OEMs equipment.

Castrol Radicool SF works over a wide operating temperature range for effective engine cooling in all climates.

Application

The special inhibitor package used in Castrol Radicool SF enables longer drain intervals with excellent protection against corrosion, cooling system blockage, overheating and freezing.

It is especially suitable for use in engines employing cast iron, aluminium, copper or combinations of these metals used in modern engine designs. It is also compatible with all standard rubber hoses, gaskets and seals used within the cooling system.

Castrol Radicool SF possesses a longer operational life by allowing extended drain intervals of 3 years plus. Longer drain intervals mean reduced cost and less possibility of harm to the environment.

Castrol Radicool SF provides excellent protection against cavitation corrosion and effective water pump lubrication, reducing wear and noise.

The additive technology used in Castrol Radicool SF prevents the build up of calcium deposits (scale) from use of hard water, thereby reducing possibility of radiator blocking and restricted flow of coolant. This technology also improves the fluids heat transfer properties ensuring engines run at optimum temperatures.

Castrol Radicool SF contains a bittering agent to deter from accidental ingestion.

Typical Characteristics

Name	Method	Units	Castrol Radicool SF
Boiling Point of Engine Coolants	ASTM D1120	°C	175
Density at 20°C	IP 160	g/ml	1.113
Foam, Tendency of Engine Coolants	ASTM D1881	ml	<50
Foam, break time	ASTM D1881	seconds	<5
Water	ASTM D1123	% wt	2.6
pH, Aqueous Solution (33%)	ASTM D1287	pH	8
Reserve Alkalinity	ASTM D1121	ml 0.1N HCl	5.6
Appearance	Visual	-	Pink mobile liquid, clear & bright
Freezing point at 50% dilution	ASTM D3321	°C	-37
Flash Point, COC	ISO 2592	°C	>120

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Product Performance Claims

D3306 (I), D4985, D6210

BS - BS 6580:2010

JASO JIS K2234

Approved - Ford WSS-M97B44-D, MAN 324 Typ SNF, MB-Approval 325.3, VW TL-774F (G12+)

User Advice

Castrol Radicool SF should be diluted between 33% and 50% concentration, with deionised/distilled water. For best all round performance, it is recommended that a 50% mixture in water is used. Concentrations higher than 70% volume are not recommended.

To maintain its performance, Castrol Radicool SF should not be mixed with other coolants. It is recommended that cooling systems should be drained and flushed before re-filling with diluted Castrol Radicool SF.

This product has a 2 year shelf life when stored in its original container below 60°C, and under cover protection from hot sun and freezing conditions. Where outside storage is unavoidable, drums should be stored in a horizontal position to avoid the possibility of water ingress.

As with most antifreezes, the use of galvanised containers and components should be avoided.

Removal

Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Radicool SF

28 Apr 2016

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

www.castrol.com/marine