



Product Data

## Radicool SF Premix Go

Ready to use. Cools and protects for up to 3 Years.

### Description

Castrol Radicool SF Premix Go is a ready to use coolant based on monoethylene glycol with organic acid inhibitor technology. In contrast to traditional antifreeze coolants, Castrol Radicool SF Premix Go does not contain amines, nitrites, phosphates, silicates or borates.

Castrol Radicool SF Premix Go works over a wide operating temperature range for effective engine cooling in all climates, and offers freezing protection down to  $-38^{\circ}\text{C}$ .

### Application

Castrol Radicool SF Premix Go has been designed for use in engines employing cast iron, aluminium, copper or combinations of these metals used in modern engine designs. Compatible with standard rubber hoses, gaskets and seals used within the cooling system.

In the majority of cases, coolants are not compatible and should not be mixed with other coolants unless directed by the equipment manufacturer. If using Radicool SF Premix Go for the first time, ensure that the cooling system has been adequately flushed with clean water.

### Advantages

Castrol Radicool SF Premix Go:

- Helps protect engine against corrosion, overheating and frost damage, enabling the cooling system of the vehicle to work efficiently all year round.
- Helps prevent the build-up of calcium deposits (scale) from use of hard water, thereby reducing possibility of radiator blocking and restricted flow of coolant.
- Good heat transfer properties helps the engine run at optimum temperatures.

## Typical Characteristics

Name	Method	Units	Castrol Radicool SF Premix Go
Boiling Point of Engine Coolants	ASTM D1120; Supplier	°C	min. 105
Appearance	Visual		Clear & Bright
Colour	Visual		Pink
Freezing Point, Coolant 50% vol in w ater	ASTM D1177; Supplier	°C	-38

## Performance

ASTM D3306(III)  
ASTM D4985  
ASTM D6210  
BS 6580:2010  
MAN 324 Typ SNF  
DTFR 29D110  
VW TL 774F (G12+)  
Deutz DQC CB-14  
DAF 74002

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Radicool SF Premix Go  
22 Nov 2023  
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

[www.castrol.com](http://www.castrol.com)