# SAFETY DATA SHEET



Molub-Alloy OG 3710-0/00

#### Safety Data Sheet according to GB/T 16483-2008 and GB/ T 17519-2013

#### Section 1. Identification

**GHS** product identifier Molub-Alloy OG 3710-0/00

**Product code** 468749-DE03

SDS no. 468749

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/ Grease for industrial applications

For specific application advice see appropriate Technical Data Sheet or consult our mixture

company representative.

Castrol (Shanghai) Management Co., Ltd. **Supplier** 

3F, Building 5, No. 255 of Guigiao Road,

Shanghai P.R.C. 201206 Tel:+86 21 38605888 +86 0532 8388 9090

**EMERGENCY TELEPHONE** 

NUMBER

### Section 2. Hazards identification

Classification of the SKIN CORROSION/IRRITATION - Category 3

SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 substance or mixture

**GHS** label elements **Hazard pictograms** 



Signal word Danger

**Hazard statements** H316 - Causes mild skin irritation. H318 - Causes serious eve damage.

**Precautionary statements** 

**Prevention** P280 - Wear eye or face protection.

Response P332 + P313 - If skin irritation occurs: Get medical attention.

> P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or physician.

Not applicable. **Storage Disposal** Not applicable. Other hazards which do not

result in classification

None known.

# Section 3. Composition/information on ingredients

Substance/mixture Mixture

Highly refined mineral oil and additives. Thickening agent.

Ingredient name **CAS** number

Product name Molub-Alloy OG 3710-0/00 Product code 468749-DE03 Page: 1/9

Version 3.03 Date of issue 4/15/2021 **Format China** Language ENGLISH

> China (ENGLISH)

# Section 3. Composition/information on ingredients

Residual oils (petroleum), solvent-dewaxed	≥10 - ≤25	64742-62-7
Residual oils (petroleum), hydrotreated	≥10 - ≤25	64742-57-0
Distillates (petroleum), hydrotreated heavy naphthenic	≤10	64742-52-5
calcium hydroxide	<10	1305-62-0
molybdenum, bis[O,O-bis(2-ethyl-hexyl)phosphorodithioato-s,s']dioxodi-m-	≤3	68958-92-9 /
thioxodi.(mo-mo)		72030-25-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

#### Section 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact** In case of contact, immediately flush eyes with plenty of water for at least 15

minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention immediately.

Chemical burns must be treated promptly by a physician.

Inhalation If inhaled, remove to fresh air. In case of inhalation of decomposition products in a

fire, symptoms may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours. Get medical attention immediately.

**Skin contact** Get medical attention immediately. In case of contact, immediately flush skin with

plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Wash clothing before reuse. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Clean shoes thoroughly before reuse. Chemical

burns must be treated promptly by a physician.

**Ingestion** Do not induce vomiting unless directed to do so by medical personnel. Never give

anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention immediately.

Chemical burns must be treated promptly by a physician.

Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician**Treatment should in general be symptomatic and directed to relieving any effects.

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Note: High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discoloured and extremely painful with

extensive subcutaneous necrosis.

Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimise tissue loss and prevent or limit permanent damage. Note that high pressure may force the

product considerable distances along tissue planes.

**Specific treatments** No specific treatment.

**Protection of first-aiders**No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

Most important symptoms/effects, acute and delayed

Version 3.03 Date of issue 4/15/2021

See Section 11 for more detailed information on health effects and symptoms.

Product name Molub-Alloy OG 3710-0/00 Product code 468749-DE03

Format China Language ENGLISH

China (ENGLISH)

Page: 2/9

### Section 5. Firefighting measures

**Extinguishing media** 

Suitable extinguishing

Unsuitable extinguishing

media

In case of fire, use water fog, alcohol resistant foam, dry chemical or carbon dioxide

extinguisher or spray. Do not use water jet.

media

Specific hazards arising

from the chemical

No specific fire or explosion hazard.

Hazardous thermal decomposition products Combustion products may include the following:

phosphorus oxides metal oxide/oxides

carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)

sulphur oxides (SO, SO<sub>2</sub>, etc.) nitrogen oxides (NO, NO2 etc.)

**Special protective actions** 

for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if

there is a fire.

**Special protective** equipment for fire-fighters Fire-fighters should wear positive pressure self-contained breathing apparatus

(SCBA) and full turnout gear.

#### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and material for containment and cleaning up

**Small spill** 

Move containers from spill area. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. If emergency personnel are unavailable, contain spilt material. Suction or scoop the spill into appropriate disposal or recycling vessels, then cover spill area with oil absorbent. Dispose of via a licensed waste disposal contractor. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container.

# Section 7. Handling and storage

#### **Precautions for safe handling**

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Product code 468749-DE03

Product name Molub-Alloy OG 3710-0/00

**Format China** 

Page: 3/9

Version 3.03 Date of issue 4/15/2021

Language ENGLISH

China

(ENGLISH)

# Section 7. Handling and storage

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits

Ingredient name	Exposure limits
Residual oils (petroleum), solvent-dewaxed	ACGIH TLV (United States).
	TWA: 5 mg/m³ 8 hours. Issued/Revised:
	11/2009 Form: Inhalable fraction
Residual oils (petroleum), hydrotreated	ACGIH TLV (United States).
	TWA: 5 mg/m³ 8 hours. Issued/Revised:
	11/2009 Form: Inhalable fraction
Distillates (petroleum), hydrotreated heavy naphthenic	ACGIH TLV (United States).
	TWA: 5 mg/m³ 8 hours. Issued/Revised:
	11/2009 Form: Inhalable fraction
calcium hydroxide	ACGIH TLV (United States).
	TWA: 5 mg/m³ 8 hours. Issued/Revised:
	9/1994
molybdenum, bis[O,O-bis(2-ethyl-hexyl)phosphorodithioato-s,s']	GBZ 2.1 (China).
dioxodi-m-thioxodi,(mo-mo)	STEL: 10 mg/m³ 15 minutes. Form: All
	forms
	TWA: 4 mg/m³ 8 hours. Form: All forms

# Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

# **Environmental exposure** controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

Product name Molub-Alloy OG 3710-0/00 Version 3.03 Date of issue 4/15/2021 Product code 468749-DE03

Page: 4/9

**Format China** 

Language ENGLISH

China

(ENGLISH)

### Section 8. Exposure controls/personal protection

**Hygiene measures** 

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection Skin protection

**Hand protection** 

Chemical splash goggles.

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

**Skin protection** 

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

**Respiratory protection** 

In case of insufficient ventilation, wear suitable respiratory equipment. For protection against metal working fluids, respiratory protection that is classified as "resistant to oil" (class R) or oil proof (class P) should be selected where appropriate. Depending on the level of airborne contaminants, an air-purifying, half-mask respirator (with HEPA filter) including disposable (P- or R-series) (for oil mists less than 50mg/m3), or any powered, air-purifying respirator equipped with hood or helmet and HEPA filter (for oil mists less than 125 mg/m3).

Where organic vapours are a potential hazard during metalworking operations, a combination particulate and organic vapour filter may be necessary

combination particulate and organic vapour filter may be necessary.

The correct choice of respiratory protection depends upon the chemicals being

handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

# Section 9. Physical and chemical properties

**Appearance** 

Physical state Grease
Colour Beige.

Odour Not available.
Odour threshold Not available.

PH Not applicable.

Melting point Not available.

Boiling point Not available.

Drop Point Not available.

Flash point Open cup: 260°C (500°F) [Estimated. Based on Lubricants - Base Oils]

**Evaporation rate** Not available.

Flammability (solid, gas) Not applicable. Based on - Physical state

Product name Molub-Alloy OG 3710-0/00 Product code 468749-DE03 Page: 5/9

Version 3.03 Date of issue 4/15/2021 Format China Language ENGLISH

China (ENGLISH)

# Section 9. Physical and chemical properties

Lower and upper explosive

(flammable) limits

Not available.

Vapour pressureNot available.Vapour densityNot available.Relative densityNot available.

**Density** <1000 kg/m³ (<1 g/cm³) at 20°C

Solubility insoluble in water.

Partition coefficient: n- Not available.

octanol/water

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

# Section 10. Stability and reactivity

Reactivity No specific test data available for this product. Refer to Conditions to avoid and

Incompatible materials for additional information.

**Chemical stability** The product is stable.

Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not

occur.

Conditions to avoid No specific data.

**Incompatible materials** Reactive or incompatible with the following materials: oxidising materials.

Hazardous decomposition Under normal conditions of storage and use, hazardous decomposition products

**products** should not be produced.

# Section 11. Toxicological information

#### Information on toxicological effects

Specific target organ toxicity (single exposure)

Name	• •	Route of exposure	Target organs
calcium hydroxide	Category 3		Respiratory tract irritation

Information on likely routes

of exposure

Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

**Eye contact** Causes serious eye damage.

**Inhalation** May give off gas, vapour or dust that is very irritating or corrosive to the respiratory

system. Exposure to decomposition products may cause a health hazard. Serious

effects may be delayed following exposure.

**Skin contact**Causes mild skin irritation. Defatting to the skin. **Ingestion**May cause burns to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** Adverse symptoms may include the following:

pain watering redness

Inhalation No specific data.

Product name Molub-Alloy OG 3710-0/00 Product code 468749-DE03 Page: 6/9

Version 3.03 Date of issue 4/15/2021 Format China Language ENGLISH

China (ENGLISH)

# **Section 11. Toxicological information**

**Skin contact** Adverse symptoms may include the following:

irritation redness dryness cracking

**Ingestion** Adverse symptoms may include the following:

stomach pains

**Short term exposure** 

Potential immediate Not available.

effects

Potential delayed effects Not available.

Long term exposure

Potential immediate Not available.

effects

Potential delayed effects Not available.

Potential chronic health effects

GeneralNo known significant effects or critical hazards.CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.TeratogenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

# Section 12. Ecological information

**Toxicity** 

**Environmental effects** No known significant effects or critical hazards.

#### Persistence/degradability

Not expected to be rapidly degradable.

#### **Bioaccumulative potential**

Not available.

**Mobility in soil** 

**Mobility** 

Soil/water partition Not available.

coefficient (Koc)

Other adverse effects

Grease. insoluble in water.

# Section 13. Disposal considerations

#### **Disposal methods**

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This

Product name Molub-Alloy OG 3710-0/00 Product code 468749-DE03 Page: 7/9

No known significant effects or critical hazards.

Version 3.03 Date of issue 4/15/2021 Format China Language ENGLISH

China (ENGLISH)

# Section 13. Disposal considerations

material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	China	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Additional information	-	-	-

Special precautions for user

Matters needing attention for

transportation

Not available.

Ensure that any additional local government transport conditions are met

### Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

No known specific national and/or regional regulations applicable to this product (including its ingredients).

#### Regulation according to other foreign laws

**REACH Status** 

The company, as identified in Section 1, sells this product in the EU in compliance

with the current requirements of REACH.

Australia inventory (AICS) Canada inventory China inventory (IECSC)

All components are listed or exempted.

All components are listed or exempted.

China inventory (IECSC)
Japan inventory (ENCS)
Korea inventory (KECI)
Philippines inventory

All components are listed or exempted.
All components are listed or exempted.
All components are listed or exempted.

(PICCS)

All components are listed or exempted.

Taiwan Chemical Substances Inventory (TCSI) All components are listed or exempted.

United States inventory (TSCA 8b)

All components are active or exempted.

Product name Molub-Alloy OG 3710-0/00

Format China Lang

Product code 468749-DE03

Version 3.03 Date of issue 4/15/2021

Language ENGLISH

China

(ENGLISH)

Page: 8/9

### Section 16. Other information

#### **History**

Date of printing 4/15/2021

Date of issue/Date of 4/15/2021

revision

**Date of previous issue** 3/11/2021 **Version** 3.03

Prepared by Product Stewardship

Key to abbreviations ACGIH = American Conference of Industrial Hygienists

CAS Number = Chemical Abstracts Service Registry Number

GHS = Global Harmonised System

IATA = International Air Transport Association, the organisation

IMDG = International Maritime Organization Rules, rules governing shipment of

goods by water.

OEL = Occupational Exposure Limit

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

Regulation [Regulation (EC) No. 1907/2006]

SDS = Safety Data Sheet

STEL = Short term exposure limit TWA = Time weighted average

UN Number = United Nations Number, a four digit number assigned by the United

Nations Committee of Experts on the Transport of Dangerous Goods. Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0,

72623-87-1

References

Not available.

Indicates information that has changed from previously issued version.

#### **Notice to reader**

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Date of issue/Date of revision : 4/15/2021 Date of previous issue : 3/11/2021 Version : 3.03 9/9

Product name Molub-Alloy OG 3710-0/00 Version 3.03 Date of issue 4/15/2021

Format China Language ENGLISH

Product code 468749-DE03

China (ENGLISH)

Page: 9/9