# SAFETY DATA SHEET



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Magna CL 220
Product code 468795-DE04
SDS # 468795
Product type Liquid.

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/

Steam Reciprocating Engine Oils.

mixture

For specific application advice see appropriate Technical Data Sheet or consult our company

representative.

## 1.3 Details of the supplier of the safety data sheet

Supplier Castrol Sweden AB

c/o WeWork Regeringsgatan 29 111 53 Stockholm

Sweden

+46 (0)770456711 MSDSadvice@bp.com

## 1.4 Emergency telephone number

**EMERGENCY** Carechem: +44 (0) 1235 239 670 (24/7)

**TELEPHONE NUMBER** 

E-mail address

# **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

Product definition Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

# 2.2 Label elements

Signal word No signal word.

**Hazard statements** No known significant effects or critical hazards.

**Precautionary statements** 

PreventionNot applicable.ResponseNot applicable.StorageNot applicable.DisposalNot applicable.Hazardous ingredientsNot applicable.Supplemental labelNot applicable.

elements

# EU Regulation (EC) No. 1907/2006 (REACH)

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

**Special packaging requirements** 

Product nameMagna CL 220Product code468795-DE04Page: 1/11Version 5.01Date of issue 30 August 2023FormatSwedenLanguageENGLISH

Date of previous issue 9 November 2022. (Sweden)

## **SECTION 2: Hazards identification**

Containers to be fitted with child-resistant

Not applicable

fastenings

Tactile warning of danger Not applicable.

2.3 Other hazards

Results of PBT and vPvB

assessment

Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006,

Annex XIII.

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do Defatting to the skin.

not result in classification NOTE: This product should not be used in compressors producing breathable air.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Product definition

Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Distillates (petroleum), solvent- dewaxed heavy paraffinic	REACH #: 01-2119471299-27 EC: 265-169-7 CAS: 64742-65-0 Index: 649-474-00-6	≥75 - ≤90	Not classified.	-	[1]
Distillates (petroleum), hydrotreated heavy paraffinic	REACH #: 01-2119484627-25 EC: 265-157-1 CAS: 64742-54-7 Index: 649-467-00-8	≥10 - ≤25	Not classified.	-	[1]

**Type** 

[1] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

# **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids

should be held away from the eyeball to ensure thorough rinsing. Check for and remove any

contact lenses. Get medical attention.

Skin contact Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove

contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before

reuse. Get medical attention if irritation develops.

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms occur.

**Ingestion** Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if

symptoms occur.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training.

## 4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

#### Potential acute health effects

Inhalation Vapour inhalation under ambient conditions is not normally a problem due to low vapour

pressure.

**Ingestion** No known significant effects or critical hazards.

**Skin contact** Defatting to the skin. May cause skin dryness and irritation.

**Eye contact** No known significant effects or critical hazards.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Inhalation** Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the

respiratory tract.

**Ingestion** Ingestion of large quantities may cause nausea and diarrhoea.

Product nameMagna CL 220Product code468795-DE04Page: 2/11Version 5.01Date of issue 30 August 2023FormatSwedenLanguageENGLISHDate of previous issue9 November 2022.(Sweden)

## **SECTION 4: First aid measures**

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs.

## 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician Treatment should in general be symptomatic and directed to relieving any effects.

# **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing media

In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.

**Unsuitable extinguishing** 

media

Do not use water jet. The use of a water jet may cause the fire to spread by splashing the

burning product.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous combustion** 

products

Combustion products may include the following: carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)

#### 5.3 Advice for firefighters

Special precautions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

# **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Put on appropriate personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

# 6.3 Methods and material for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other

sections

See Section 1 for emergency contact information.

See Section 5 for firefighting measures.

See Section 8 for information on appropriate personal protective equipment.

See Section 12 for environmental precautions.

See Section 13 for additional waste treatment information.

Product nameMagna CL 220Product code468795-DE04Page: 3/11Version 5.01Date of issue 30 August 2023FormatSwedenLanguageENGLISH

Date of previous issue 9 November 2022. (Sweden)

# SECTION 7: Handling and storage

## 7.1 Precautions for safe handling

**Protective measures** Advice on general occupational hygiene Put on appropriate personal protective equipment.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional

information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/ containers designed for use with this product. Do not store in unlabelled containers.

7.3 Specific end use(s)

Recommendations

See section 1.2 and Exposure scenarios in annex, if applicable.

# SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

paraffinic

# Occupational exposure limits

Product/ingredient name Distillates (petroleum), solvent-dewaxed heavy

## **Exposure limit values**

Work environment authority Regulation 2018:1 (Sweden). [old used mineral oil] Absorbed through skin.

Work environment authority Regulation 2018:1 (Sweden). [oil mist,

incl. oil fumes]

TWA: 1 mg/m³ 8 hours. Issued/Revised: 8/2018 Form: mist and fume STEL: 3 mg/m<sup>3</sup> 15 minutes. Issued/Revised: 8/2018 Form: mist and fume

Distillates (petroleum), hydrotreated heavy paraffinic Work environment authority Regulation 2018:1 (Sweden). [old used mineral oil] Absorbed through skin.

Work environment authority Regulation 2018:1 (Sweden). [oil mist,

incl. oil fumes]

TWA: 1 mg/m³ 8 hours. Issued/Revised: 8/2018 Form: mist and fume STEL: 3 mg/m<sup>3</sup> 15 minutes. Issued/Revised: 8/2018 Form: mist and fume

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

**Recommended monitoring** procedures

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

## **Biological exposure indices**

Product/ingredient name

**Exposure indices** 

Language ENGLISH

No exposure indices known.

**Derived No Effect Level** 

No DNELs/DMELs available.

## **Predicted No Effect Concentration**

No PNECs available

## 8.2 Exposure controls

Version 5.01

**Appropriate engineering** controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Format Sweden

Product name Magna CL 220 Product code 468795-DE04 Page: 4/11

(Sweden) 9 November 2022 Date of previous issue

Date of issue 30 August 2023

# **SECTION 8: Exposure controls/personal protection**

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

#### **Individual protection measures**

#### **Hygiene measures**

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

## **Respiratory protection**

In case of insufficient ventilation, wear suitable respiratory equipment.

For protection against metal working fluids, respiratory protection that is classified as "resistant to oil" (class R) or oil proof (class P) should be selected where appropriate. Depending on the level of airborne contaminants, an air-purifying, half-mask respirator (with HEPA filter) including disposable (P- or R-series) (for oil mists less than 50mg/m3), or any powered, air-purifying respirator equipped with hood or helmet and HEPA filter (for oil mists less than 125 mg/m3). Where organic vapours are a potential hazard during metalworking operations, a combination particulate and organic vapour filter may be necessary.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

# Eye/face protection Skin protection Hand protection

Safety glasses with side shields.

#### **General Information:**

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile gloves.

## Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:

#### Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained.

If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.

It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

## **Glove Thickness:**

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required

Product nameMagna CL 220Product code468795-DE04Page: 5/11Version 5.01Date of issue 30 August 2023FormatSwedenLanguageENGLISHDate of previous issue9 November 2022.(Sweden)

# SECTION 8: Exposure controls/personal protection

for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

Use of protective clothing is good industrial practice. Skin and body

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Refer to standards: Respiratory protection: EN 529

Gloves: EN 420, EN 374 Eve protection: EN 166 Filtering half-mask: EN 149

Filtering half-mask with valve: EN 405

Half-mask: EN 140 plus filter Full-face mask: EN 136 plus filter Particulate filters: EN 143 Gas/combined filters: EN 14387

**Environmental exposure** 

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

**Physical state** Liquid. Colour Amber. Odour Not available. **Odour threshold** Not available. pН Not applicable. Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

**Pour point** -9 °C

Open cup: 286°C (546.8°F) [Cleveland] Flash point

Not available. **Flammability** Not available. Lower and upper explosion

limit

Vapour pressure

	Vapour Pressure at 20°C			Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<0.08	<0.011	ASTM D 5191			
Distillates (petroleum), hydrotreated heavy paraffinic	<0.08	<0.011	ASTM D 5191			

Relative vapour density **Density and/or Relative density** 

Not available. Not available.

**Density and/or Relative density** <1000 kg/m³ (<1 g/cm³) at 15°C

Solubility

Product name Magna CL 220 Product code 468795-DE04 Page: 6/11 Format Sweden Language ENGLISH Version 5.01 Date of issue 30 August 2023 (Sweden) 9 November 2022 Date of previous issue

# **SECTION 9: Physical and chemical properties**

Media	Result
water	Not soluble

Partition coefficient n-octanol/

water (log value)

Not applicable.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Kinematic viscosity

Kinematic: 220.1 mm²/s (220.1 cSt) at 40°C

Kinematic: 19.03 mm<sup>2</sup>/s (19.03 cSt) at 100°C

Particle characteristics

Median particle size Not applicable.

9.2 Other information

Evaporation rateNot available.Explosive propertiesNot available.Oxidising propertiesNot available.

# **SECTION 10: Stability and reactivity**

10.1 Reactivity

No specific test data available for this product. Refer to Conditions to avoid and Incompatible

materials for additional information.

**10.2 Chemical stability** The product is stable.

10.3 Possibility of hazardous reactions
 Under normal conditions of storage and use, hazardous reactions will not occur.
 Under normal conditions of storage and use, hazardous polymerisation will not occur.

10.4 Conditions to avoid Avoid all possible sources of ignition (spark or flame).

10.5 Incompatible materials Reactive or incompatible with the following materials: oxidising materials.

**10.6 Hazardous**Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

## **Acute toxicity estimates**

Not available.

Information on likely routes of exposure

Routes of entry anticipated: Dermal, Inhalation, Eyes.

#### Potential acute health effects

Inhalation Vapour inhalation under ambient conditions is not normally a problem due to low vapour

pressure.

**Ingestion** No known significant effects or critical hazards.

Skin contact Defatting to the skin. May cause skin dryness and irritation.

Eye contact No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal

decomposition products occurs.

Ingestion No specific data.

**Skin contact** Adverse symptoms may include the following:

irritation dryness cracking

Eve contact No specific data.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Inhalation** Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the

respiratory tract.

**Ingestion** Ingestion of large quantities may cause nausea and diarrhoea.

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

Product nameMagna CL 220Product code468795-DE04Page: 7/11Version 5.01Date of issue 30 August 2023FormatSwedenLanguageENGLISHDate of previous issue9 November 2022.(Sweden)

# **SECTION 11: Toxicological information**

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs.

## Potential chronic health effects

GeneralNo known significant effects or critical hazards.CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

#### 11.2 Information on other hazards

## 11.2.1 Endocrine disrupting properties

Not available.

Remarks - Endocrine disruptor - Health 11.2.2 Other information

Not available.

Not available.

# SECTION 12: Ecological information

# 12.1 Toxicity

Environmental hazards Not classified as dangerous

#### 12.2 Persistence and degradability

Expected to be biodegradable.

## 12.3 Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

#### 12.4 Mobility in soil

Soil/water partition

Not available.

coefficient (Koc)

**Mobility** Spillages may penetrate the soil causing ground water contamination.

# 12.5 Results of PBT and vPvB assessment

Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.

12.6 Endocrine disrupting

properties

Not available.

Remarks - Endocrine

disruptor - Environment

Not available.

Other ecological information

mation Spills may form a film on water surfaces causing physical damage to organisms. Oxygen

transfer could also be impaired.

**12.7 Other adverse effects** No known significant effects or critical hazards.

# SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

**Product** 

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/

licensed waste disposal contractor in accordance with local regulations.

Hazardous waste Yes
European waste catalogue (EWC)

Waste code	Waste designation
13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

**Packaging** 

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/

licensed waste disposal contractor in accordance with local regulations.

Product name Magna CL 220 Product code 468795-DE04 Page: 8/11

Version 5.01 Date of issue 30 August 2023 Format Sweden Language ENGLISH

Date of previous issue 9 November 2022. (Sweden)

# **SECTION 13: Disposal considerations**

Waste code	European waste catalogue (EWC)
15 01 10*	packaging containing residues of or contaminated by hazardous substances

## **Special precautions**

This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

#### Methods of disposal

The regulations regarding manufacturers' responsibility for packaging material waste is regulated in "Förordningen om producentansvar för förpackningar". Packaging materials are to be reused or recycled in accordance with the goals outlined in this regulation. The company complies with this manufacturer's responsibility through its association with REPA, which is a subsidiary company of four materials handling companies. The materials handling companies collect, remove and process used and sorted packaging materials through the employment of contractors. Questions regarding collection of packaging materials on a local basis may be directed to the materials company and its contractors. For further information, contact REPA, www.repa.se.

Drums and containers are placed in a tilted position, approx 10°, drums are turned with the bungholes downwards and the 2" bunghole in the lowest position, containers with the valve downwards. Other packages are placed upside down for eduction. Let stand at temperatures above 15°C until drip dry or at least 30 minutes. Recover and add the remainders in the process where the product is used, or send for special waste treatment. Send empty packages to a certified recycler/receiver for recycling.

References

Commission 2014/955/EU Directive 2008/98/EC

# **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

14.6 Special precautions for user

Not available.

14.7 Maritime transport in bulk according to IMO instruments

Not available.

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

**Annex XIV - List of substances subject to authorisation** 

**Annex XIV** 

None of the components are listed.

Substances of very high concern

None of the components are listed.

EU Regulation (EC) No. 1907/2006 (REACH)

Product nameMagna CL 220Product code468795-DE04Page: 9/11Version 5.01Date of issue 30 August 2023FormatSwedenLanguageENGLISHDate of previous issue9 November 2022.(Sweden)

# SECTION 15: Regulatory information

**Annex XVII - Restrictions** on the manufacture, placing on the market

and use of certain dangerous substances, mixtures and articles

**Other regulations** 

**REACH Status** The company, as identified in Section 1, sells this product in the EU in compliance with the

current requirements of REACH.

All components are active or exempted.

**United States inventory** 

(TSCA 8b)

Australia inventory (AIIC) All components are listed or exempted. Canada inventory All components are listed or exempted. China inventory (IECSC) All components are listed or exempted. Japan inventory (CSCL) All components are listed or exempted. All components are listed or exempted. Korea inventory (KECI) All components are listed or exempted.

Not applicable.

**Philippines inventory** 

(PICCS)

All components are listed or exempted.

**Taiwan Chemical Substances Inventory** 

(TCSI)

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

**Persistent Organic Pollutants** 

Not listed.

EU - Water framework directive - Priority substances

None of the components are listed.

**Seveso Directive** 

This product is not controlled under the Seveso Directive.

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

# **SECTION 16: Other information**

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by

Road

ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment CSR = Chemical Safety Report DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978. ("Marpol" = marine pollution) OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

Product name Magna CL 220 Product code 468795-DE04 Page: 10/11

Format Sweden Language ENGLISH Version 5.01 Date of issue 30 August 2023

(Sweden) 9 November 2022 Date of previous issue

# **SECTION 16: Other information**

PNEC = Predicted No Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation

[Regulation (EC) No. 1907/2006]

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SADT = Self-Accelerating Decomposition Temperature

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVCB = Complex hydrocarbon substance

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4/ RRN

01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN

01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN

01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN

01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN

01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8,

64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 /

RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN

01-2119474889-13

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

Full text of abbreviated H

statements

Not applicable.

**Full text of classifications** 

[CLP/GHS]

Not applicable.

**History** 

Date of issue/ Date of

revision

30/08/2023.

Date of previous issue 09/11/2022.

Prepared by Product Stewardship

Indicates information that has changed from previously issued version.

# **Notice to reader**

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product nameMagna CL 220Product code468795-DE04Page: 11/11Version 5.01Date of issue 30 August 2023FormatSwedenLanguageENGLISHDate of previous issue9 November 2022.(Sweden)