

SAFETY DATA SHEET



Hyspin VG 220

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier Hyspin VG 220
SDS # 465329
Code 465329-AR08

Relevant identified uses of the substance or mixture and uses advised against

Product use Hydraulic fluid.
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

Manufacturer BP Lubricants USA Inc.
1500 Valley Road
Wayne, NJ 07470
Telephone: +1-888-CASTROL

Supplier PAN AMERICAN ENERGY S.L., SUCURSAL
ARGENTINA AV. LEANDRO N. ALEM 1180
PISO 11 – C1001AAT
CIUDAD AUTÓNOMA DE BUENOS AIRES.

EMERGENCY HEALTH INFORMATION:

Consultas Técnicas 0800-888-8088
TELÉFONO PARA EMERGENCIAS (24 HORAS) CIQUIME: 0800-222-2933
+1-800-424-9300 (CHEMTREC USA)
+1-703-527-3887 (CHEMTREC outside the US)

EMERGENCY TELEPHONE NUMBER

SECTION 2: Hazards identification

Classification of the substance or mixture AQUATIC HAZARD (ACUTE) - Category 3
AQUATIC HAZARD (LONG-TERM) - Category 3

GHS label elements

Signal word No signal word.

Hazard statements H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention P273 - Avoid release to the environment.

Response Not applicable.

Storage Not applicable.

Disposal P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not result in classification

Defatting to the skin.
Note: High Pressure Applications
Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency.
See 'Notes to physician' under First-Aid Measures, Section 4 of this Safety Data Sheet.

Product name Hyspin VG 220

Product code 465329-AR08

Page: 1/12

Date of issue 12/09/2025.

Format Argentina

Language ENGLISH

Version 4.02

(AR)

(ENGLISH)

SECTION 3: Composition/information on ingredients

Substance/mixture Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Other means of identification Not available.

Ingredient name	%	CAS number
Distillates (petroleum), solvent-refined heavy paraffinic	≥50 - ≤75	CAS: 64741-88-4
Distillates (petroleum), solvent-refined heavy paraffinic	≥25 - ≤50	CAS: 64741-88-4
2,6-di-tert-butylphenol	≤0.3	CAS: 128-39-2
N-1-naphthylaniline	≤0.3	CAS: 90-30-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

Description of necessary first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur. If skin irritation or rash occurs: Get medical advice/attention.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if adverse health effects persist or are severe.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects. Note: High Pressure Applications Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discolored and extremely painful with extensive subcutaneous necrosis. Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimize tissue loss and prevent or limit permanent damage. Note that high pressure may force the product considerable distances along tissue planes.
Specific treatments	No specific treatment.

Product name Hyspin VG 220

Product code 465329-AR08

Page: 2/12

Date of issue 12/09/2025.

Format Argentina

Language ENGLISH

Version 4.02

(AR)

(ENGLISH)

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media

Use foam or all-purpose dry chemical to extinguish.

Unsuitable extinguishing media

Do not use water jet.

Specific hazards arising from the chemical

Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects.

Hazardous thermal decomposition products

Combustion products may include the following:
carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

Special protective actions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

For emergency responders

Entry into a confined space or poorly ventilated area contaminated with vapor, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilled product. Dispose of via a licensed waste disposal contractor.

SECTION 7: Handling and storage

Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Avoid contact of spilled material and runoff with soil and surface waterways.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. Contaminated work clothing should not be allowed out of the workplace. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.
Not suitable	Prolonged exposure to elevated temperature

SECTION 8: Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), solvent-refined heavy paraffinic	Ministry of Labor, Employment and Social Security. Argentina (Resolution 295,11/2003) (Argentina) [Aceite mineral] TWA 8 hours: 5 mg/m³. Form: mist. Issued/Revised: 11/2003. STEL 15 minutes: 10 mg/m³. Form: mist. Issued/Revised: 11/2003.
Distillates (petroleum), solvent-refined heavy paraffinic	Ministry of Labor, Employment and Social Security. Argentina (Resolution 295,11/2003) (Argentina) [Aceite mineral] TWA 8 hours: 5 mg/m³. Form: mist. Issued/Revised: 11/2003. STEL 15 minutes: 10 mg/m³. Form: mist. Issued/Revised: 11/2003.

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Biological exposure indices

No exposure indices known.

Appropriate engineering controls	All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on
----------------------------------	--

SECTION 8: Exposure controls/personal protection

Environmental exposure controls

selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety glasses with side shields.

Skin protection

Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Body protection

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state

Liquid.

Color

Amber.

Odor

Not available.

Odor threshold

Not available.

Product name Hyspin VG 220

Product code 465329-AR08

Page: 5/12

Date of issue 12/09/2025.

Format Argentina

Language ENGLISH

Version 4.02

(AR)

(ENGLISH)

SECTION 9: Physical and chemical properties

pH	Not applicable.																											
Melting point/freezing point	Not available.																											
Boiling point or initial boiling point and boiling range	Not available.																											
Flash point	Closed cup: >190°C (>374°F) [Pensky-Martens]																											
Pour point	-12 °C																											
Evaporation rate	Not available.																											
Flammability	Not available.																											
Lower and upper explosion limit/flammability limit	Not available.																											
Vapor pressure	<table><tr><th rowspan="2">Ingredient name</th><th colspan="3">Vapor Pressure at 20°C</th><th colspan="3">Vapor pressure at 50°C</th></tr><tr><th>mm Hg</th><th>kPa</th><th>Method</th><th>mm Hg</th><th>kPa</th><th>Method</th></tr><tr><td>Distillates (petroleum), solvent-refined heavy paraffinic</td><td><0.07501</td><td><0.01</td><td>ASTM D 5191</td><td></td><td></td><td></td></tr><tr><td>Distillates (petroleum), solvent-refined heavy paraffinic</td><td><0.07501</td><td><0.01</td><td>ASTM D 5191</td><td></td><td></td><td></td></tr></table>	Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C			mm Hg	kPa	Method	mm Hg	kPa	Method	Distillates (petroleum), solvent-refined heavy paraffinic	<0.07501	<0.01	ASTM D 5191				Distillates (petroleum), solvent-refined heavy paraffinic	<0.07501	<0.01	ASTM D 5191			
Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C																								
	mm Hg	kPa	Method	mm Hg	kPa	Method																						
Distillates (petroleum), solvent-refined heavy paraffinic	<0.07501	<0.01	ASTM D 5191																									
Distillates (petroleum), solvent-refined heavy paraffinic	<0.07501	<0.01	ASTM D 5191																									
Relative vapor density	Not available.																											
Density	<1000 kg/m³ (<1 g/cm³) at 15°C																											
Solubility(ies)	<table><tr><th>Media</th><th>Result</th></tr><tr><td>water</td><td>Not soluble</td></tr></table>	Media	Result	water	Not soluble																							
Media	Result																											
water	Not soluble																											
Partition coefficient: n-octanol/water	Not applicable.																											
Auto-ignition temperature	Not available.																											
Decomposition temperature	Not available.																											
Viscosity	Kinematic: 224.5 mm²/s (224.5 cSt) at 40°C																											
Particle characteristics																												
Median particle size	Not applicable.																											

SECTION 10: Stability and reactivity

Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur.
Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
Incompatible materials	Reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name

2,6-di-tert-butylphenol

N-1-naphthylaniline

Result

Rat - Oral - LD50

>5000 mg/kg

OECD 401

Rabbit - Dermal - LD50

>5000 mg/kg

Rat - Oral - LD50

1625 mg/kg

Rabbit - Dermal - LD50

>5000 mg/kg

Rat - Inhalation - LC50 Dusts and mists

>5.2 mg/l [4 hours]

EPA OPPTS 870.1300

Skin corrosion/irritation

Product/ingredient name

2,6-di-tert-butylphenol

N-1-naphthylaniline

Result

Rabbit - Skin - Irritant

OECD 404

Rabbit - Skin - Not irritant

OECD 404

Serious eye damage/eye irritation

Product/ingredient name

2,6-di-tert-butylphenol

N-1-naphthylaniline

Result

Rabbit - Eyes - Non-irritating to the eyes.

OECD 405

Rabbit - Eyes - Not irritant

OECD 405

Respiratory corrosion/irritation

Not available.

Respiratory or skin sensitization

Product/ingredient name

2,6-di-tert-butylphenol

N-1-naphthylaniline

Result

Guinea pig - skin

OECD 406

Result: Not sensitizing

Guinea pig - skin

OECD 406

Result: Sensitizing

Germ cell mutagenicity

Product/ingredient name

Result

Product name Hyspin VG 220

Product code

465329-AR08

Page: 7/12

Date of issue 12/09/2025.

Format Argentina

Language ENGLISH

Version 4.02

(AR)

(ENGLISH)

SECTION 11: Toxicological information

2,6-di-tert-butylphenol	In vitro - Bacteria OECD [Bacterial Reverse Mutation Test] <u>Result</u> : Negative
	In vitro - Mammal - species unspecified OECD [In vitro Mammalian Chromosomal Aberration Test] <u>Result</u> : Negative
N-1-naphthylaniline	In vitro - Bacteria OECD 471 <u>Result</u> : Negative
	In vitro - Mammalian-Animal OECD 473 <u>Result</u> : Negative
	In vitro - Mammalian-Animal OECD 476 <u>Result</u> : Negative

Carcinogenicity

Not available.

Reproductive toxicity

Product/ingredient name

2,6-di-tert-butylphenol

Result

Rat - Oral

OECD 421
Maternal toxicity: Positive
Fertility effects: Negative
Developmental: Equivocal

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name

N-1-naphthylaniline

Result

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

Aspiration hazard

Not available.

Information on the likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact

No known significant effects or critical hazards.

Skin contact

Defatting to the skin. May cause skin dryness and irritation.

Inhalation

Vapor inhalation under ambient conditions is not normally a problem due to low vapor pressure.

Ingestion

No known significant effects or critical hazards.

SECTION 11: Toxicological information

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	No specific data.
Skin contact	Adverse symptoms may include the following: irritation dryness cracking
Inhalation	No specific data.
Ingestion	No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects	Not available.
Potential delayed effects	Not available.

Long term exposure

Potential immediate effects	Not available.
Potential delayed effects	Not available.

Potential chronic health effects

General	No known significant effects or critical hazards.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route

Not available.

SECTION 12: Ecological information

Toxicity

Product/ingredient name

2,6-di-tert-butylphenol

Result

Acute - EL50

OECD 201

Algae

1.2 mg/l [96 hours]

Acute - EL50

OECD 202

Daphnia

0.45 mg/l [48 hours]

Acute - LC50

OECD 203

Fish

1.4 mg/l [96 hours]

Chronic - NOEC

OECD 201

Algae

0.64 mg/l [96 hours]

Product name Hyspin VG 220

Product code

465329-AR08

Page: 9/12

Date of issue 12/09/2025.

Format Argentina

Language ENGLISH

Version 4.02

(AR)

(ENGLISH)

SECTION 12: Ecological information

N-1-naphthylaniline	Chronic - NOEC
	OECD 211
	Daphnia
	0.035 mg/l [21 days]
	Acute - ErC50
	OECD 201
	Algae
	0.93 mg/l [96 hours]
	Acute - EC50
	OECD 202
	Daphnia
	0.3 mg/l [48 hours]
	Acute - LC50
	OECD 203
	Fish
	0.44 mg/l [96 hours]
	Chronic - NOEC
	OECD 211
	Daphnia
	0.032 mg/l [21 days]

Environmental effects

This material is harmful to aquatic life with long lasting effects.

Persistence and degradability

Not expected to be rapidly degradable.

Product/ingredient name	Result
2,6-di-tert-butylphenol	OECD 301B
	24% [28 days] - Not readily
N-1-naphthylaniline	0% [28 days] - Not readily

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Mobility in soil

Soil/Water partition coefficient	Not available.
Mobility	Spillages may penetrate the soil causing ground water contamination.

Other adverse effects	No known significant effects or critical hazards.
Other ecological information	Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

SECTION 13: Disposal considerations

Disposal methods	The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty
-------------------------	---

Product name	Hyspin VG 220	Product code	465329-AR08	Page:	10/12
Date of issue	12/09/2025.	Format	Argentina	Language	ENGLISH
Version	4.02		(AR)		(ENGLISH)

SECTION 13: Disposal considerations

containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA/ICAO
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

Special precautions for user Not available.

Transport in bulk according to IMO instruments Not available.

SECTION 15: Regulatory information

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Other regulations

Australia inventory (AIRC) Not determined.

Canada inventory Not determined.

China inventory (IECSC) Not determined.

Japan inventory (CSCL) Not determined.

Korea inventory (KECI) Not determined.

Philippines inventory (PICCS) Not determined.

Product name Hyspin VG 220

Product code 465329-AR08

Page: 11/12

Date of issue 12/09/2025.

Format Argentina

Language ENGLISH

Version 4.02

(AR)

(ENGLISH)

SECTION 15: Regulatory information

Taiwan Chemical Substances Inventory (TCSI)	Not determined.
United States inventory (TSCA 8b)	Not determined.
REACH Status	The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

SECTION 16: Other information

History

Date of issue/Date of revision 12/09/2025.

Date of previous issue 12/05/2025.

Prepared by Product Stewardship

Key to abbreviations

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
UN = United Nations
VOC = Volatile Organic Compound
Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.