

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

|              |   |
|--------------|---|
| Product name | Castrol Radicool Premix                                 |
| UFI:         | <input checked="" type="checkbox"/> MSX2-70MD-Q004-Y8Y7 |
| Product code | 467203-DE51   |
| SDS #        | 467203  |
| Product type | Liquid.   |

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

|                                  |  |
|----------------------------------|--|
| Use of the substance/<br>mixture | Coolant and antifreeze.<br>For specific application advice see appropriate Technical Data Sheet or consult our company representative. |
|----------------------------------|--|

### 1.3 Details of the supplier of the safety data sheet

|                |  |
|----------------|--|
| Supplier       | Castrol Holdings Europe B.V.,<br>d'Arcyweg 76, 3198NA<br>Europort<br>Rotterdam |
|                | Castrol CEE sp z.o.o,<br>Ul. Grzybowska 62,<br>00 844 Warszawa                 |
|                | +36 06 80 021 211  |
| E-mail address | MSDSadvice@bp.com  |

### 1.4 Emergency telephone number

|                               |   |
|-------------------------------|---|
| EMERGENCY<br>TELEPHONE NUMBER | Carechem: +44 (0) 1235 239 670 (24/7)   |
| Hungary Poison Center         | Emergency information service in case of poisoning or suspicion of poisoning:<br><b>+36 80 201 199 (0-24 hours, free of charge - only in Hungary)</b><br>+36 1 476 6464 (0-24 hours, can be called for a standard fee - also from abroad) |

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

|   |         |
|---|---------|
| Product definition  | Mixture |
| <a href="#">Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]</a> |         |

Acute Tox. 4, H302  
STOT RE 2, H373

See Section 16 for the full text of the H statements declared above.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

### 2.2 Label elements

|                   |   |
|-------------------|---|
| UFI:              | <input checked="" type="checkbox"/> MSX2-70MD-Q004-Y8Y7   |
| Hazard pictograms |   |

Signal word  Warning

Hazard statements  H302 - Harmful if swallowed.  
H373 - May cause damage to organs through prolonged or repeated exposure.

#### Precautionary statements

|         |   |
|---------|---|
| General | P102 - Keep out of reach of children.<br>P101 - If medical advice is needed, have product container or label at hand. |
|---------|---|

|                        |                         |               |                |          |           |
|------------------------|-------------------------|---------------|----------------|----------|-----------|
| Product name           | Castrol Radicool Premix | Product code  | 467203-DE51    | Page:    | 1/12      |
| Version                | 2                       | Date of issue | 4 October 2023 | Format   | Hungary   |
| Date of previous issue | 4 March 2022.           |               |                | Language | ENGLISH   |
|                        |                         |               |                |          | (Hungary) |

## SECTION 2: Hazards identification

|                                    |   |
|------------------------------------|---|
| <b>Prevention</b>                  | <input checked="" type="checkbox"/> P260 - Do not breathe vapour.<br>P270 - Do not eat, drink or smoke when using this product.<br>P264 - Wash hands thoroughly after handling. |
| <b>Response</b>                    | <input checked="" type="checkbox"/> P301 + P312, P330 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.<br>Rinse mouth.  |
| <b>Storage</b>                     | <input checked="" type="checkbox"/> Not applicable.   |
| <b>Disposal</b>                    | P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.  |
| <b>Hazardous ingredients</b>       | <input checked="" type="checkbox"/> Ethylene glycol   |
| <b>Supplemental label elements</b> | Not applicable.   |

### EU Regulation (EC) No. 1907/2006 (REACH)

|   |   |
|---|---|
| <b>Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles</b> | <input checked="" type="checkbox"/> Not applicable. |
|---|---|

### Special packaging requirements

|  |   |
|--|---|
| <b>Containers to be fitted with child-resistant fastenings</b> | <input checked="" type="checkbox"/> Not applicable. |
| <b>Tactile warning of danger</b>                               | Yes, applicable.                                    |

### 2.3 Other hazards

|  |  |
|--|--|
| <b>Results of PBT and vPvB assessment</b>  | Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII. |
| <b>Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII</b> | This mixture does not contain any substances that are assessed to be a PBT or a vPvB.                      |

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

|                           |                      |
|---------------------------|----------------------|
| <b>Product definition</b> | Mixture              |
| Ethylene glycol           | Corrosion inhibitor. |

| Product/ingredient name                             | Identifiers  | %         | Classification  | Specific Conc. Limits, M-factors and ATEs | Type    |
|---|--|-----------|---|---|---------|
| <input checked="" type="checkbox"/> Ethylene glycol | REACH #: 01-2119456816-28<br>EC: 203-473-3<br>CAS: 107-21-1<br>Index: 603-027-00-1 | ≥50 - ≤75 | Acute Tox. 4, H302<br>STOT RE 2, H373<br>(kidneys) (oral) | ATE [Oral] = 500 mg/kg                    | [1] [2] |

See Section 16 for the full text of the H statements declared above.

#### Type

- [1] Substance classified with a health or environmental hazard
  - [2] Substance with a workplace exposure limit
- Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

|                     |  |
|---------------------|--|
| <b>Eye contact</b>  | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention if irritation develops.                                   |
| <b>Skin contact</b> | <input checked="" type="checkbox"/> In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops. |
| <b>Inhalation</b>   | <input checked="" type="checkbox"/> Inhaled, remove to fresh air. Get medical attention if symptoms occur.   |

|   |                                     |                         |
|---|-------------------------------------|-------------------------|
| <b>Product name</b> Castrol Radicool Premix | <b>Product code</b> 467203-DE51     | <b>Page:</b> 2/12       |
| <b>Version</b> 2                            | <b>Date of issue</b> 4 October 2023 | <b>Format</b> Hungary   |
| <b>Date of previous issue</b> 4 March 2022. |                                     | <b>Language</b> ENGLISH |
|   |                                     | <b>(Hungary)</b>        |

## SECTION 4: First aid measures

|                                   |  |
|-----------------------------------|--|
| <b>Ingestion</b>                  | Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention. If ingested, call a physician or Poison Control Center immediately. Get medical attention urgently informing the doctor that a product containing ethylene glycol has been ingested and specific treatment may be required. Transport casualty together with the product container, its label, or the safety data sheet urgently to hospital. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. |
| <b>Protection of first-aiders</b> | No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.   |

### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

#### Potential acute health effects

|                     |   |
|---------------------|---|
| <b>Inhalation</b>   | Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.  |
| <b>Ingestion</b>    | Harmful if swallowed. Ethylene glycol: Ingestion of ethylene glycol can cause metabolic acidosis, kidney damage, central nervous system depression, and convulsions. The estimated human lethal dose is approximately 100 ml (3.4 ounces for an adult). |
| <b>Skin contact</b> | No known significant effects or critical hazards.   |
| <b>Eye contact</b>  | No known significant effects or critical hazards.   |

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

|                     |  |
|---------------------|--|
| <b>Inhalation</b>   | Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. |
| <b>Ingestion</b>    | Ingestion of large quantities may cause nausea and diarrhoea.  |
| <b>Skin contact</b> | Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.                     |
| <b>Eye contact</b>  | Potential risk of transient stinging or redness if accidental eye contact occurs.                              |

### 4.3 Indication of any immediate medical attention and special treatment needed

#### Notes to physician

|                            |  |
|----------------------------|--|
| <b>Specific treatments</b> | Ethylene Glycol: Gastric irrigation, ethanol or fomepizole may have value in treatment. Consult physician. |
|----------------------------|--|

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

|                                       |   |
|---------------------------------------|---|
| <b>Suitable extinguishing media</b>   | In case of fire, use water fog, alcohol resistant foam, dry chemical or carbon dioxide extinguisher or spray. |
| <b>Unsuitable extinguishing media</b> | Do not use water jet. The use of a water jet may cause the fire to spread by splashing the burning product.   |

### 5.2 Special hazards arising from the substance or mixture

|  |  |
|--|--|
| <b>Hazards from the substance or mixture</b> | In a fire or if heated, a pressure increase will occur and the container may burst.                                      |
| <b>Hazardous combustion products</b>         | Combustion products may include the following:<br>carbon oxides (CO, CO <sub>2</sub> ) (carbon monoxide, carbon dioxide) |

### 5.3 Advice for firefighters

|   |   |
|---|---|
| <b>Special precautions for fire-fighters</b>          | No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.   |
| <b>Special protective equipment for fire-fighters</b> | Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents. |

|   |                                     |                         |
|---|-------------------------------------|-------------------------|
| <b>Product name</b> Castrol Radicool Premix | <b>Product code</b> 467203-DE51     | <b>Page:</b> 3/12       |
| <b>Version</b> 2                            | <b>Date of issue</b> 4 October 2023 | <b>Format</b> Hungary   |
| <b>Date of previous issue</b> 4 March 2022. |                                     | <b>Language</b> ENGLISH |
|   | <b>(Hungary)</b>                    |                         |

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment.

#### For emergency responders

Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

#### Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

### 6.4 Reference to other sections

See Section 1 for emergency contact information.  
See Section 5 for firefighting measures.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 12 for environmental precautions.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Protective measures

Put on appropriate personal protective equipment. Do not breathe vapour or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Empty containers retain product residue and can be hazardous.

#### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/containers designed for use with this product. Do not store in unlabelled containers.

#### Not suitable

Prolonged exposure to elevated temperature

### 7.3 Specific end use(s)

#### Recommendations

See section 1.2 and Exposure scenarios in annex, if applicable.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

##### Product/ingredient name

##### Exposure limit values

Ethylene glycol

5/2020. (II. 6.) ITM Decree (Hungary). Absorbed through skin. Skin sensitiser. Inhalation sensitiser.

TWA: 52 mg/m<sup>3</sup> 8 hours. Issued/Revised: 2/2020

PEAK: 104 mg/m<sup>3</sup> 15 minutes. Issued/Revised: 2/2020

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

**Product name** Castrol Radicool Premix

**Product code** 467203-DE51

**Page:** 4/12

**Version** 2 **Date of issue** 4 October 2023

**Format** Hungary

**Language** ENGLISH

**Date of previous issue** 4 March 2022.

(Hungary)

**SECTION 8: Exposure controls/personal protection**

**Recommended monitoring procedures**

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**Biological exposure indices**

**Product/ingredient name**

**Exposure indices**

No exposure indices known.

**Derived No Effect Level**

| Product/ingredient name | Type | Exposure               | Value                | Population         | Effects  |
|-------------------------|------|------------------------|----------------------|--------------------|----------|
| Ethylene glycol         | DNEL | Long term Inhalation - | 35 mg/m <sup>3</sup> | Workers            | Local    |
|                         | DNEL | Long term Dermal -     | 106 mg/kg bw/day     | Workers            | Systemic |
|                         | DNEL | Long term Inhalation - | 7 mg/m <sup>3</sup>  | General population | Local    |
|                         | DNEL | Long term Dermal -     | 53 mg/kg bw/day      | General population | Systemic |

**Predicted No Effect Concentration**

No PNECs available

**8.2 Exposure controls**

**Appropriate engineering controls**

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

**Individual protection measures**

**Hygiene measures**

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

**Respiratory protection**

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

**Eye/face protection**

Safety glasses with side shields.

**Skin protection**

**Hand protection**

**General Information:**

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Butyl gloves.  
Neoprene gloves.

**Breakthrough time:**

Breakthrough time data are generated by glove manufacturers under laboratory test conditions

|   |                                     |                       |
|---|-------------------------------------|-----------------------|
| <b>Product name</b> Castrol Radicool Premix | <b>Product code</b> 467203-DE51     | <b>Page:</b> 5/12     |
| <b>Version</b> 2                            | <b>Date of issue</b> 4 October 2023 | <b>Format</b> Hungary |
| <b>Date of previous issue</b> 4 March 2022. | <b>Language</b> ENGLISH             | <b>(Hungary)</b>      |

## SECTION 8: Exposure controls/personal protection

and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained.

If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.

It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

### Glove Thickness:

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.

- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

### Skin and body

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

### Refer to standards:

Respiratory protection: EN 529

Gloves: EN 420, EN 374

Eye protection: EN 166

Filtering half-mask: EN 149

Filtering half-mask with valve: EN 405

Half-mask: EN 140 plus filter

Full-face mask: EN 136 plus filter

Particulate filters: EN 143

Gas/combined filters: EN 14387

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**Product name** Castrol Radicool Premix

**Product code** 467203-DE51

**Page:** 6/12

**Version** 2 **Date of issue** 4 October 2023

**Format** Hungary

**Language** ENGLISH

**Date of previous issue** 4 March 2022.

(Hungary)



**SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

**9.1 Information on basic physical and chemical properties**

|  |  |
|--|--|
| <b>Physical state</b>                          | Liquid.  |
| <b>Colour</b>                                  | Blue. Green. [Light]   |
| <b>Odour</b>                                   | Not available.   |
| <b>Odour threshold</b>                         | Not available.   |
| <b>Melting point/freezing point</b>            | Not available.   |
| <b>Initial boiling point and boiling range</b> | Not available.   |
| <b>Flammability</b>                            | Not available.   |
| <b>Lower and upper explosion limit</b>         | Not available.   |
| <b>Flash point</b>                             | Closed cup: Not applicable. [Water content interferes with flash point determination.] |

| <b>Auto-ignition temperature</b> | <table border="1"> <thead> <tr> <th>Ingredient name</th> <th>°C</th> <th>°F</th> <th>Method</th> </tr> </thead> <tbody> <tr> <td>Ethylene glycol</td> <td>398</td> <td>748.4</td> <td></td> </tr> </tbody> </table> |       |        | Ingredient name | °C | °F | Method | Ethylene glycol | 398 | 748.4 |  |
|----------------------------------|---|-------|--------|-----------------|----|----|--------|-----------------|-----|-------|--|
| Ingredient name                  | °C  | °F    | Method |                 |    |    |        |                 |     |       |  |
| Ethylene glycol                  | 398   | 748.4 |        |                 |    |    |        |                 |     |       |  |

|                                  |                           |
|----------------------------------|---------------------------|
| <b>Decomposition temperature</b> | Not available.            |
| <b>pH</b>                        | 8.5 [Conc. (% w/w): 100%] |
| <b>Kinematic viscosity</b>       | Not available.            |
| <b>Solubility</b>                |                           |

| Media | Result             |
|-------|--------------------|
| Water | Miscible in water. |

|  |                 |
|--|-----------------|
| <b>Partition coefficient n-octanol/water (log value)</b> | Not applicable. |
|--|-----------------|

| <b>Vapour pressure</b> | <table border="1"> <thead> <tr> <th rowspan="2">Ingredient name</th> <th colspan="2">Vapour Pressure at 20°C</th> <th colspan="3">Vapour pressure at 50°C</th> </tr> <tr> <th>mm Hg</th> <th>kPa</th> <th>Method</th> <th>mm Hg</th> <th>kPa</th> <th>Method</th> </tr> </thead> <tbody> <tr> <td>Ethylene glycol</td> <td>0.09</td> <td>0.012</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Water</td> <td>23.8</td> <td>3.2</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table> |       |                         |       |     |        | Ingredient name | Vapour Pressure at 20°C |  | Vapour pressure at 50°C |  |  | mm Hg | kPa | Method | mm Hg | kPa | Method | Ethylene glycol | 0.09 | 0.012 |  |  |  |  | Water | 23.8 | 3.2 |  |  |  |  |
|------------------------|--|-------|-------------------------|-------|-----|--------|-----------------|-------------------------|--|-------------------------|--|--|-------|-----|--------|-------|-----|--------|-----------------|------|-------|--|--|--|--|-------|------|-----|--|--|--|--|
| Ingredient name        | Vapour Pressure at 20°C  |       | Vapour pressure at 50°C |       |     |        |                 |                         |  |                         |  |  |       |     |        |       |     |        |                 |      |       |  |  |  |  |       |      |     |  |  |  |  |
|                        | mm Hg  | kPa   | Method                  | mm Hg | kPa | Method |                 |                         |  |                         |  |  |       |     |        |       |     |        |                 |      |       |  |  |  |  |       |      |     |  |  |  |  |
| Ethylene glycol        | 0.09   | 0.012 |                         |       |     |        |                 |                         |  |                         |  |  |       |     |        |       |     |        |                 |      |       |  |  |  |  |       |      |     |  |  |  |  |
| Water                  | 23.8   | 3.2   |                         |       |     |        |                 |                         |  |                         |  |  |       |     |        |       |     |        |                 |      |       |  |  |  |  |       |      |     |  |  |  |  |

|  |  |
|--|--|
| <b>Density and/or Relative density</b> | 1000 kg/m <sup>3</sup> (>1 g/cm <sup>3</sup> ) at 20°C |
|--|--|

|                                |                |
|--------------------------------|----------------|
| <b>Relative vapour density</b> | Not available. |
|--------------------------------|----------------|

**Particle characteristics**

|                             |                 |
|-----------------------------|-----------------|
| <b>Median particle size</b> | Not applicable. |
|-----------------------------|-----------------|

**9.2 Other information**

|                         |                |
|-------------------------|----------------|
| <b>Evaporation rate</b> | Not available. |
|-------------------------|----------------|

|                             |                |
|-----------------------------|----------------|
| <b>Explosive properties</b> | Not available. |
|-----------------------------|----------------|

|                             |                |
|-----------------------------|----------------|
| <b>Oxidising properties</b> | Not available. |
|-----------------------------|----------------|

**SECTION 10: Stability and reactivity**

|                        |   |
|------------------------|---|
| <b>10.1 Reactivity</b> | No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information. |
|------------------------|---|

|                                |                        |
|--------------------------------|------------------------|
| <b>10.2 Chemical stability</b> | The product is stable. |
|--------------------------------|------------------------|

|  |   |
|--|---|
| <b>10.3 Possibility of hazardous reactions</b> | Under normal conditions of storage and use, hazardous reactions will not occur.<br>Under normal conditions of storage and use, hazardous polymerisation will not occur. |
|--|---|

|                                 |  |
|---------------------------------|--|
| <b>10.4 Conditions to avoid</b> | Avoid all possible sources of ignition (spark or flame). |
|---------------------------------|--|

|                                    |  |
|------------------------------------|--|
| <b>10.5 Incompatible materials</b> | Reactive or incompatible with the following materials: oxidising materials.<br>Hazardous reactions are possible with concentrated mineral acids, strong oxidizing agents, alkali metals and isocyanates. Combustible material. |
|------------------------------------|--|

|  |  |
|--|--|
| <b>10.6 Hazardous decomposition products</b> | Under normal conditions of storage and use, hazardous decomposition products should not be produced. |
|--|--|

|   |                                     |                         |
|---|-------------------------------------|-------------------------|
| <b>Product name</b> Castrol Radicool Premix | <b>Product code</b> 467203-DE51     | <b>Page:</b> 7/12       |
| <b>Version</b> 2                            | <b>Date of issue</b> 4 October 2023 | <b>Format</b> Hungary   |
| <b>Date of previous issue</b> 4 March 2022. |                                     | <b>Language</b> ENGLISH |
|   |                                     | <b>(Hungary)</b>        |

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity estimates

| Product/ingredient name                    | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|--|--------------|----------------|--------------------------|-----------------------------|-------------------------------------|
| Castrol Radicool Premix<br>Ethylene glycol | 968.7<br>500 | N/A<br>N/A     | N/A<br>N/A               | N/A<br>N/A                  | N/A<br>N/A                          |

#### Information on likely routes of exposure

Routes of entry anticipated: Dermal, Inhalation, Eyes.

#### Potential acute health effects

##### Inhalation

Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.

##### Ingestion

Harmful if swallowed. Ethylene glycol: Ingestion of ethylene glycol can cause metabolic acidosis, kidney damage, central nervous system depression, and convulsions. The estimated human lethal dose is approximately 100 ml (3.4 ounces for an adult).

##### Skin contact

No known significant effects or critical hazards.

##### Eye contact

No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

##### Inhalation

May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.

##### Ingestion

No specific data.

##### Skin contact

No specific data.

##### Eye contact

No specific data.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

##### Inhalation

Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

##### Ingestion

Ingestion of large quantities may cause nausea and diarrhoea.

##### Skin contact

Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

##### Eye contact

Potential risk of transient stinging or redness if accidental eye contact occurs.

#### Potential chronic health effects

##### General

May cause damage to organs through prolonged or repeated exposure. May cause damage to organs through prolonged or repeated exposure. (kidney)

##### Carcinogenicity

No known significant effects or critical hazards.

##### Mutagenicity

No known significant effects or critical hazards.

##### Developmental effects

Birth defects and decreased fetal weight have been observed in laboratory animals fed ethylene glycol in large amounts repeatedly during pregnancy.

##### Fertility effects

No known significant effects or critical hazards.

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

#### Remarks - Endocrine disruptor - Health

Not available.

#### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Environmental hazards

Not classified as dangerous

### 12.2 Persistence and degradability

Expected to be biodegradable.

### 12.3 Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

### 12.4 Mobility in soil

|   |                                     |                         |
|---|-------------------------------------|-------------------------|
| <b>Product name</b> Castrol Radicool Premix | <b>Product code</b> 467203-DE51     | <b>Page:</b> 8/12       |
| <b>Version</b> 2                            | <b>Date of issue</b> 4 October 2023 | <b>Format</b> Hungary   |
| <b>Date of previous issue</b> 4 March 2022. |                                     | <b>Language</b> ENGLISH |
|   | <b>(Hungary)</b>                    |                         |



## SECTION 12: Ecological information

|  |  |
|--|--|
| <b>Soil/water partition coefficient (K<sub>oc</sub>)</b> | Not available.   |
| <b>Mobility</b>  | Spillages may penetrate the soil causing ground water contamination. |

### 12.5 Results of PBT and vPvB assessment

Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.

|  |   |
|--|---|
| <b>12.6 Endocrine disrupting properties</b>        | Not available.                                    |
| <b>Remarks - Endocrine disruptor - Environment</b> | Not available.                                    |
| <b>Other ecological information</b>                | Miscible in water.                                |
| <b>12.7 Other adverse effects</b>                  | No known significant effects or critical hazards. |

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

|                            |   |
|----------------------------|---|
| <b>Methods of disposal</b> | Undiluted fluid Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.<br>Diluted Fluid Diluted fluid should not be discharged into sewage systems unless provided for by local regulations. Dispose under conditions approved by the local authority or via a licensed waste disposal contractor. |
|----------------------------|---|

**Hazardous waste** Yes.

#### European waste catalogue (EWC)

| Waste code | Waste designation                                 |
|------------|---|
| 16 01 14*  | antifreeze fluids containing hazardous substances |

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

#### Packaging

|                            |   |
|----------------------------|---|
| <b>Methods of disposal</b> | Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.   |
| <b>Special precautions</b> | This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Empty containers represent a fire hazard as they may contain flammable product residues and vapour. Never weld, solder or braze empty containers. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. |
| <b>Other information</b>   | Undiluted fluid Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.<br><br>Diluted Fluid Diluted fluid should not be discharged into sewage systems unless provided for by local regulations. Dispose under conditions approved by the local authority or via a licensed waste disposal contractor.   |
| <b>References</b>          | Commission 2014/955/EU<br>Directive 2008/98/EC  |

## SECTION 14: Transport information

|  | ADR/RID        | ADN            | IMDG           | IATA           |
|--|----------------|----------------|----------------|----------------|
| <b>14.1 UN number or ID number</b>     | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| <b>14.2 UN proper shipping name</b>    | -              | -              | -              | -              |
| <b>14.3 Transport hazard class(es)</b> | -              | -              | -              | -              |
| <b>14.4 Packing group</b>              | -              | -              | -              | -              |
| <b>14.5 Environmental hazards</b>      | No.            | No.            | No.            | No.            |

|   |                                     |                         |
|---|-------------------------------------|-------------------------|
| <b>Product name</b> Castrol Radicool Premix | <b>Product code</b> 467203-DE51     | <b>Page:</b> 9/12       |
| <b>Version</b> 2                            | <b>Date of issue</b> 4 October 2023 | <b>Format</b> Hungary   |
| <b>Date of previous issue</b> 4 March 2022. |                                     | <b>Language</b> ENGLISH |
|   |                                     | <b>(Hungary)</b>        |

## SECTION 14: Transport information

|                        |   |   |   |   |
|------------------------|---|---|---|---|
| Additional information | - | - | - | - |
|------------------------|---|---|---|---|

**14.6 Special precautions for user** Not available.

**14.7 Maritime transport in bulk according to IMO instruments** Not available.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

##### Annex XIV

None of the components are listed.

##### Substances of very high concern

None of the components are listed.

#### EU Regulation (EC) No. 1907/2006 (REACH)

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles**  Not applicable.

#### Other regulations

##### REACH Status

The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

##### United States inventory (TSCA 8b)

At least one component is not listed.

##### Australia inventory (AIC)

At least one component is not listed.

##### Canada inventory

At least one component is not listed.

##### China inventory (IECSC)

All components are listed or exempted.

##### Japan inventory (CSCL)

All components are listed or exempted.

##### Korea inventory (KECI)

All components are listed or exempted.

##### Philippines inventory (PICCS)

All components are listed or exempted.

##### Taiwan Chemical Substances Inventory (TCSI)

All components are listed or exempted.

#### Ozone depleting substances (1005/2009/EU)

Not listed.

#### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

#### Persistent Organic Pollutants

Not listed.

#### EU - Water framework directive - Priority substances

None of the components are listed.

#### Seveso Directive

This product is not controlled under the Seveso Directive.

##### References

Act No. XXV of 2000 on chemical safety  
 Decree No. 25/2000 (IX.30.) EüM of the Ministry of Health on chemical safety at work plus amendments  
 Decree No. 44/2000 (XII.27.) EüM of the Ministry of Health on detailed arrangements for certain procedures, activities relating to dangerous substances and dangerous preparations plus amendments  
 38/2009 (VII.7) The International Carriage of Dangerous Goods by the European Agreement (ADR) "A" and "B" on the application of national annex plus amendments

|   |                                     |                         |
|---|-------------------------------------|-------------------------|
| <b>Product name</b> Castrol Radicool Premix | <b>Product code</b> 467203-DE51     | <b>Page:</b> 10/12      |
| <b>Version</b> 2                            | <b>Date of issue</b> 4 October 2023 | <b>Format</b> Hungary   |
| <b>Date of previous issue</b> 4 March 2022. |                                     | <b>Language</b> ENGLISH |
|   |                                     | <b>(Hungary)</b>        |

**SECTION 15: Regulatory information**

**15.2 Chemical safety assessment**

A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

**SECTION 16: Other information**

**Abbreviations and acronyms**

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
 ATE = Acute Toxicity Estimate  
 BCF = Bioconcentration Factor  
 CAS = Chemical Abstracts Service  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 CSA = Chemical Safety Assessment  
 CSR = Chemical Safety Report  
 DMEL = Derived Minimal Effect Level  
 DNEL = Derived No Effect Level  
 EINECS = European Inventory of Existing Commercial chemical Substances  
 ES = Exposure Scenario  
 EUH statement = CLP-specific Hazard statement  
 EWC = European Waste Catalogue  
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
 IATA = International Air Transport Association  
 IBC = Intermediate Bulk Container  
 IMDG = International Maritime Dangerous Goods  
 LogPow = logarithm of the octanol/water partition coefficient  
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
 OECD = Organisation for Economic Co-operation and Development  
 PBT = Persistent, Bioaccumulative and Toxic  
 PNEC = Predicted No Effect Concentration  
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]  
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
 RRN = REACH Registration Number  
 SADT = Self-Accelerating Decomposition Temperature  
 SVHC = Substances of Very High Concern  
 STOT-RE = Specific Target Organ Toxicity - Repeated Exposure  
 STOT-SE = Specific Target Organ Toxicity - Single Exposure  
 TWA = Time weighted average  
 UN = United Nations  
 UVCB = Complex hydrocarbon substance  
 VOC = Volatile Organic Compound  
 vPvB = Very Persistent and Very Bioaccumulative  
 Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4/ RRN 01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN 01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN 01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN 01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN 01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8, 64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 / RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN 01-2119474889-13

**Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

| Classification                        | Justification                            |
|---------------------------------------|--|
| Acute Tox. 4, H302<br>STOT RE 2, H373 | Calculation method<br>Calculation method |

**Full text of abbreviated H statements**

H302  
H373

Harmful if swallowed.  
May cause damage to organs through prolonged or repeated exposure.

**Full text of classifications [CLP/GHS]**

Acute Tox. 4  
STOT RE 2

ACUTE TOXICITY - Category 4  
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2

**History**

**Date of issue/ Date of revision** 04/10/2023.  
**Date of previous issue** 04/03/2022.

|   |                                     |                         |
|---|-------------------------------------|-------------------------|
| <b>Product name</b> Castrol Radicool Premix | <b>Product code</b> 467203-DE51     | <b>Page:</b> 11/12      |
| <b>Version</b> 2                            | <b>Date of issue</b> 4 October 2023 | <b>Format</b> Hungary   |
| <b>Date of previous issue</b> 4 March 2022. |                                     | <b>Language</b> ENGLISH |
|   | <b>(Hungary)</b>                    |                         |

## SECTION 16: Other information

Prepared by Product Stewardship Group

✔ Indicates information that has changed from previously issued version.

### Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

**Product name** Castrol Radicool Premix

**Product code** 467203-DE51

**Page:** 12/12

**Version** 2 **Date of issue** 4 October 2023

**Format** Hungary

**Language** ENGLISH

**Date of previous issue** 4 March 2022.

**(Hungary)**