

SAFETY DATA SHEET**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Product name Castrol Transmax Offroad 50
UFI: P0Q0-R0FN-P00S-5R6S
Product code 467241-DE04
SDS no. 467241
Product type Liquid.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses
<input checked="" type="checkbox"/> General use of lubricants and greases in vehicles or machinery-Industrial General use of lubricants and greases in vehicles or machinery-Professional

**Use of the substance/
mixture** Automatic transmission fluid
For specific application advice see appropriate Technical Data Sheet or consult our company representative.
Automatic transmission fluid
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

1.3 Details of the supplier of the safety data sheet

Supplier Castrol
En division inom Nordic Lubricants AB
Box 491 04
100 28 Stockholm

Telefon : +46 (0)8-441 11 00
Fax.: +46 (0)8-651 01 35

E-mail address MSDSadvice@bp.com

1.4 Emergency telephone number

**EMERGENCY
TELEPHONE NUMBER** Carechem: +44 (0) 1235 239 670 (24/7)
Finland Poison Center (09) 471 977 / (09) 4711

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Product definition Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Repr. 1B, H360F

See Section 16 for the full text of the H statements declared above.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements

UFI: P0Q0-R0FN-P00S-5R6S

Hazard pictograms



Signal word Danger

Hazard statements H360F - May damage fertility.

Precautionary statements

General P102 - Keep out of reach of children.
P101 - If medical advice is needed, have product container or label at hand.

Product name Castrol Transmax Offroad 50	Product code 467241-DE04	Page: 1/16
Version 4	Date of issue 11 November 2021	Format Finland
Date of previous issue 7 October 2021.		Language ENGLISH
	(Finland)	

SECTION 2: Hazards identification

Prevention	P201 - Obtain special instructions before use. P280 - Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection.
Response	P308 + P313 - IF exposed or concerned: Get medical attention.
Storage	P405 - Store locked up.
Disposal	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	Phenol, dodecyl-, branched
Supplemental label elements	Not applicable.

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Restricted to professional users.
---	-----------------------------------

Special packaging requirements

Containers to be fitted with child-resistant fastenings	Yes, applicable.
Tactile warning of danger	Yes, applicable.

2.3 Other hazards

Results of PBT and vPvB assessment	Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	Defatting to the skin. Experimental data on one or more of the components has been used to determine all or part of the hazard classification of this product.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product definition Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type
Residual oils (petroleum), solvent-dewaxed	REACH #: 01-2119480472-38 EC: 265-166-0 CAS: 64742-62-7 Index: 649-471-00-X	≥10 - ≤25	Not classified.	[2]
Residual oils (petroleum), hydrotreated	REACH #: 01-2119489287-22 EC: 265-160-8 CAS: 64742-57-0 Index: 649-470-00-4	≥10 - ≤25	Not classified.	[2]
Distillates (petroleum), hydrotreated heavy paraffinic	REACH #: 01-2119484627-25 EC: 265-157-1 CAS: 64742-54-7 Index: 649-467-00-8	≥10 - ≤25	Not classified.	[2]
Distillates (petroleum), solvent-dewaxed heavy paraffinic	REACH #: 01-2119471299-27 EC: 265-169-7 CAS: 64742-65-0 Index: 649-474-00-6	≥10 - ≤25	Not classified.	[2]
Zinc bis[O,O-bis(2-ethylhexyl)] bis (dithiophosphate)	REACH #: 01-2119493635-27 EC: 224-235-5 CAS: 4259-15-8	≤3	Eye Dam. 1, H318 Aquatic Chronic 2, H411	[1]
Phenol, paraalkylation products with C10-15 branched olefins (C12 rich)	REACH #: 01-2119524004-56 EC: -	≤3	Aquatic Chronic 4, H413	[1]

Product name Castrol Transmax Offroad 50	Product code 467241-DE04	Page: 2/16
Version 4	Date of issue 11 November 2021	Format Finland
Date of previous issue 7 October 2021.		Language ENGLISH
	(Finland)	

SECTION 3: Composition/information on ingredients

derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50

Phenol, dodecyl-, branched

CAS: -
REACH #: 01-2119513207-49 <1
EC: 310-154-3
CAS: 121158-58-5
Index: 604-092-00-9

Skin Corr. 1C, H314 [1] [5]
Eye Dam. 1, H318
Repr. 1B, H360F
Aquatic Acute 1, H400 (M=10)
Aquatic Chronic 1, H410 (M=10)

See Section 16 for the full text of the H statements declared above.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.

Skin contact

Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention.

Inhalation

Inhaled, remove to fresh air. Get medical attention immediately.

Ingestion

Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention immediately.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Potential acute health effects

Inhalation

Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.

Ingestion

No known significant effects or critical hazards.

Skin contact

Defatting to the skin. May cause skin dryness and irritation.

Eye contact

No known significant effects or critical hazards.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation

Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

Ingestion

Ingestion of large quantities may cause nausea and diarrhoea.

Skin contact

Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

Eye contact

Potential risk of transient stinging or redness if accidental eye contact occurs.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

Treatment should in general be symptomatic and directed to relieving any effects.

Product name Castrol Transmax Offroad 50

Product code 467241-DE04

Page: 3/16

Version 4 **Date of issue** 11 November 2021

Format Finland

Language ENGLISH

Date of previous issue 7 October 2021.

(Finland)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.

Unsuitable extinguishing media

Do not use water jet. The use of a water jet may cause the fire to spread by splashing the burning product.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products

Combustion products may include the following:
carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)
phosphorus oxides
sulphur oxides (SO, SO₂, etc.)

5.3 Advice for firefighters

Special precautions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

☑ Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment.

For emergency responders

☑ Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Small spill

☑ Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

☑ Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

See Section 1 for emergency contact information.
See Section 5 for firefighting measures.
See Section 8 for information on appropriate personal protective equipment.
See Section 12 for environmental precautions.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Product name Castrol Transmax Offroad 50	Product code 467241-DE04	Page: 4/16
Version 4	Date of issue 11 November 2021	Format Finland
Date of previous issue 7 October 2021.		Language ENGLISH
	(Finland)	

SECTION 7: Handling and storage

Protective measures

Put on appropriate personal protective equipment. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Store locked up. Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/containers designed for use with this product. Do not store in unlabelled containers.

Not suitable

Prolonged exposure to elevated temperature.

7.3 Specific end use(s)

Recommendations

See section 1.2 and Exposure scenarios in annex, if applicable.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Residual oils (petroleum), solvent-dewaxed	Institute of Occupational Health, Ministry of Social Affairs (Finland). TWA: 5 mg/m ³ 8 hours. Issued/Revised: 12/2011 Form: Mist
Residual oils (petroleum), hydrotreated	Institute of Occupational Health, Ministry of Social Affairs (Finland). TWA: 5 mg/m ³ 8 hours. Issued/Revised: 12/2011 Form: Mist
Distillates (petroleum), hydrotreated heavy paraffinic	Institute of Occupational Health, Ministry of Social Affairs (Finland). TWA: 5 mg/m ³ 8 hours. Issued/Revised: 12/2011 Form: Mist
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Institute of Occupational Health, Ministry of Social Affairs (Finland). TWA: 5 mg/m ³ 8 hours. Issued/Revised: 12/2011 Form: Mist

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived No Effect Level

No DNELs/DMELs available.

Predicted No Effect Concentration

No PNECs available

8.2 Exposure controls

Product name Castrol Transmax Offroad 50	Product code 467241-DE04	Page: 5/16
Version 4	Date of issue 11 November 2021	Format Finland
Date of previous issue 7 October 2021.		Language ENGLISH
	(Finland)	

SECTION 8: Exposure controls/personal protection

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Eye/face protection

Safety glasses with side shields.

Skin protection

Hand protection

General Information:

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile gloves.

Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained.

If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.

It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

Glove Thickness:

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Product name Castrol Transmax Offroad 50

Product code 467241-DE04

Page: 6/16

Version 4 **Date of issue** 11 November 2021

Format Finland

Language ENGLISH

Date of previous issue 7 October 2021.

(Finland)

SECTION 8: Exposure controls/personal protection

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.

- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

Skin and body

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Refer to standards:

- Respiratory protection: EN 529
- Gloves: EN 420, EN 374
- Eye protection: EN 166
- Filtering half-mask: EN 149
- Filtering half-mask with valve: EN 405
- Half-mask: EN 140 plus filter
- Full-face mask: EN 136 plus filter
- Particulate filters: EN 143
- Gas/combined filters: EN 14387

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state	Liquid.
Colour	<input checked="" type="checkbox"/> Brown.
Odour	Not available.
Odour threshold	Not available.
pH	Not applicable.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Pour point	<-12 °C
Flash point	<input checked="" type="checkbox"/> Open cup: >220°C (>428°F) [Cleveland]
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	Not available.

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method

SECTION 9: Physical and chemical properties

<input checked="" type="checkbox"/> Residual oils (petroleum), solvent-dewaxed	<0.08	<0.011	ASTM D 5191			
Residual oils (petroleum), hydrotreated	<0.08	<0.011	ASTM D 5191			
Distillates (petroleum), hydrotreated heavy paraffinic	<0.08	<0.011	ASTM D 5191			
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<0.08	<0.011	ASTM D 5191			
zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	0	0	EU A.4	0	0	EU A.4

- Vapour density** Not available.
- Relative density** Not available.
- Density** <1000 kg/m³ (<1 g/cm³) at 15°C
- Solubility(ies)** insoluble in water.
- Partition coefficient: n-octanol/water** Not applicable.
- Auto-ignition temperature** Not available.
- Decomposition temperature** Not available.
- Viscosity** Kinematic: 207.9 mm²/s (207.9 cSt) at 40°C
Kinematic: 17.5 to 19 mm²/s (17.5 to 19 cSt) at 100°C
- Explosive properties** Not available.
- Oxidising properties** Not available.

Particle characteristics

Median particle size Not applicable.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

- 10.1 Reactivity** No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
- 10.2 Chemical stability** The product is stable.
- 10.3 Possibility of hazardous reactions** Under normal conditions of storage and use, hazardous reactions will not occur.
Under normal conditions of storage and use, hazardous polymerisation will not occur.
- 10.4 Conditions to avoid** Avoid all possible sources of ignition (spark or flame).
- 10.5 Incompatible materials** Reactive or incompatible with the following materials: oxidising materials.
- 10.6 Hazardous decomposition products** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
<input checked="" type="checkbox"/> zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	2500	N/A	N/A	N/A	N/A

Information on likely routes of exposure Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Product name Castrol Transmax Offroad 50	Product code 467241-DE04	Page: 8/16
Version 4	Date of issue 11 November 2021	Format Finland
Date of previous issue 7 October 2021.		Language ENGLISH
		(Finland)

SECTION 11: Toxicological information

Inhalation	Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.
Ingestion	No known significant effects or critical hazards.
Skin contact	Defatting to the skin. May cause skin dryness and irritation.
Eye contact	<input checked="" type="checkbox"/> No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation	May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
Ingestion	No specific data.
Skin contact	Adverse symptoms may include the following: irritation dryness cracking
Eye contact	No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.

Potential chronic health effects

General	No known significant effects or critical hazards.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	<input checked="" type="checkbox"/> May damage fertility.

SECTION 12: Ecological information

12.1 Toxicity

Environmental hazards	Not classified as dangerous <input checked="" type="checkbox"/> Product not classified for environmental effects. Based on data available for this or related materials.
------------------------------	---

12.2 Persistence and degradability

Expected to be biodegradable.

12.3 Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc})	Not available.
Mobility	Spillages may penetrate the soil causing ground water contamination.

12.5 Results of PBT and vPvB assessment

Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.

12.6 Other adverse effects

Other ecological information	Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.
-------------------------------------	--

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal	Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.
----------------------------	---

Product name Castrol Transmax Offroad 50	Product code 467241-DE04	Page: 9/16
Version 4	Date of issue 11 November 2021	Format Finland
Date of previous issue 7 October 2021.		Language ENGLISH
	(Finland)	

SECTION 13: Disposal considerations

Hazardous waste Yes.

European waste catalogue (EWC)

Waste code	Waste designation
13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

Packaging

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Special precautions This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Empty containers represent a fire hazard as they may contain flammable product residues and vapour. Never weld, solder or braze empty containers. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

References Commission 2014/955/EU
Directive 2008/98/EC

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

14.6 Special precautions for user Not available.

14.7 Transport in bulk according to IMO instruments Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

Toxic to reproduction

Ingredient name	Status	Reference number
Phenol, dodecyl-, branched	Candidate	D(2021)4569-DC

Substance of equivalent concern for human health

Ingredient name	Status	Reference number
Alkyl phenol	Candidate	D(2021)4569-DC

Substance of equivalent concern for environment

Product name Castrol Transmax Offroad 50	Product code 467241-DE04	Page: 10/16
Version 4	Date of issue 11 November 2021	Format Finland
Date of previous issue 7 October 2021.	(Finland)	Language ENGLISH

SECTION 15: Regulatory information

Ingredient name	Status	Reference number
Alkyl phenol	Candidate	D(2021)4569-DC

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Restricted to professional users.

Other regulations

REACH Status The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

United States inventory (TSCA 8b) All components are active or exempted.

Australia inventory (AIC) All components are listed or exempted.

Canada inventory All components are listed or exempted.

China inventory (IECSC) At least one component is not listed.

Japan inventory (CSCL) All components are listed or exempted.

Korea inventory (KECI) All components are listed or exempted.

Philippines inventory (PICCS) All components are listed or exempted.

Taiwan Chemical Substances Inventory (TCSI) All components are listed or exempted.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

EU - Water framework directive - Priority substances

None of the components are listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

SECTION 16: Other information

Abbreviations and acronyms	<p>ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway</p> <p>ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road</p> <p>ATE = Acute Toxicity Estimate</p> <p>BCF = Bioconcentration Factor</p> <p>CAS = Chemical Abstracts Service</p> <p>CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]</p> <p>CSA = Chemical Safety Assessment</p> <p>CSR = Chemical Safety Report</p> <p>DMEL = Derived Minimal Effect Level</p> <p>DNEL = Derived No Effect Level</p> <p>EINECS = European Inventory of Existing Commercial chemical Substances</p> <p>ES = Exposure Scenario</p> <p>EUH statement = CLP-specific Hazard statement</p> <p>EWC = European Waste Catalogue</p> <p>GHS = Globally Harmonized System of Classification and Labelling of Chemicals</p> <p>IATA = International Air Transport Association</p> <p>IBC = Intermediate Bulk Container</p> <p>IMDG = International Maritime Dangerous Goods</p>
-----------------------------------	--

Product name Castrol Transmax Offroad 50	Product code 467241-DE04	Page: 11/16
Version 4	Date of issue 11 November 2021	Format Finland
Date of previous issue 7 October 2021.		Language ENGLISH
	(Finland)	

SECTION 16: Other information

LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 OECD = Organisation for Economic Co-operation and Development
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
 RRD = REACH Registration Number
 SADT = Self-Accelerating Decomposition Temperature
 SVHC = Substances of Very High Concern
 STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
 STOT-SE = Specific Target Organ Toxicity - Single Exposure
 TWA = Time weighted average
 UN = United Nations
 UVCB = Complex hydrocarbon substance
 VOC = Volatile Organic Compound
 vPvB = Very Persistent and Very Bioaccumulative
 Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4/ RRN 01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN 01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN 01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN 01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN 01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8, 64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 / RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN 01-2119474889-13

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Repr. 1B, H360F	Calculation method
Full text of abbreviated H statements	H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage. H360F May damage fertility. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H413 May cause long lasting harmful effects to aquatic life.
Full text of classifications [CLP/GHS]	Aquatic Acute 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 Aquatic Chronic 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 Aquatic Chronic 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 Aquatic Chronic 4 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4 Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 Repr. 1B REPRODUCTIVE TOXICITY - Category 1B Skin Corr. 1C SKIN CORROSION/IRRITATION - Category 1C

History

Date of issue/ Date of revision 11/11/2021.
Date of previous issue 07/10/2021.
Prepared by Product Stewardship

 **Indicates information that has changed from previously issued version.**

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Castrol Transmax Offroad 50	Product code 467241-DE04	Page: 12/16
Version 4	Date of issue 11 November 2021	Format Finland
Date of previous issue 7 October 2021.		Language ENGLISH
		(Finland)

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition	Mixture
Code	467241-DE04
Product name	Castrol Transmax Offroad 50

Section 1: Title

Short title of the exposure scenario	General use of lubricants and greases in vehicles or machinery - Industrial
List of use descriptors	<p>Identified use name: General use of lubricants and greases in vehicles or machinery-Industrial</p> <p>Process Category: PROC01, PROC02, PROC08b, PROC09</p> <p>Sector of end use: SU03</p> <p>Subsequent service life relevant for that use: No.</p> <p>Environmental Release Category: ERC04, ERC07</p> <p>Specific Environmental Release Category: ATIEL-ATC SPERC 4.Biv1</p>

Processes and activities covered by the exposure scenario	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.
--	---

Section 2 Operational conditions and risk management measures

Section 2.1 Control of worker exposure

Product characteristics:

Physical state:	Liquid, vapour pressure < 0.5 kPa
Concentration of substance in product:	Covers use of substance/product up to 100 % (unless stated differently)
Frequency and duration of use:	Covers daily exposures up to 8 hours
Other conditions affecting workers exposure:	Assumes use at not more than 20°C above ambient temperature. Assumes a good basic standard of occupational hygiene is implemented

Contributing scenarios: Operational conditions and risk management measures

General measures (Reproductive toxin):

Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.

General measures applicable to all activities:

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Avoid direct eye contact with product also via contamination on hands.

General exposures (closed systems):

No other specific measures identified.

Initial factory fill of equipment Use in contained systems:

No other specific measures identified.

Initial factory fill of equipment Open systems:

Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Avoid carrying out operation for more than 4 hours.

Operation of equipment containing engine oils and similar Use in contained systems:

No other specific measures identified.

Equipment cleaning and maintenance:

Drain down system prior to equipment break-in or maintenance. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training. Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Equipment cleaning and maintenance Operation is carried out at elevated temperature (> 20°C above ambient temperature):

Drain down and flush system prior to equipment break-in or maintenance. Provide extract ventilation to emission points when contact with warm (>50°C) lubricant is likely. Wear chemical-resistant gloves (tested to EN374) in combination with intensive management supervision controls. Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Storage:

Store substance within a closed system.

Section 2.2: Control of environmental exposure

No exposure scenario is presented because the product is not classified for the Environment

Section 3: Exposure estimation and reference to its source

Exposure estimation and reference to its source - Environment

Exposure assessment (environment):

No exposure scenario is presented because the product is not classified for the Environment

Exposure estimation and reference to its source - Workers

Exposure assessment (human):

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 4: Guidance to check compliance with the exposure scenario

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.ATIEL.org/REACH_GES

Health

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Annex to the extended Safety Data Sheet (eSDS)

Professional

Identification of the substance or mixture

Product definition	Mixture
Code	467241-DE04
Product name	Castrol Transmax Offroad 50

Section 1: Title

Short title of the exposure scenario General use of lubricants and greases in vehicles or machinery - Professional

List of use descriptors **Identified use name:** General use of lubricants and greases in vehicles or machinery-Professional
Process Category: PROC01, PROC02, PROC08a, PROC08b, PROC20
Sector of end use: SU22
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC09a, ERC09b
Specific Environmental Release Category: ESVOC SpERC 9.6b.v1

Processes and activities covered by the exposure scenario Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

Section 2 Operational conditions and risk management measures

Section 2.1 Control of worker exposure

Product characteristics:

Physical state: Liquid, vapour pressure < 0.5 kPa

Concentration of substance in product: Covers use of substance/product up to 100 % (unless stated differently)

Frequency and duration of use: Covers daily exposures up to 8 hours

Other conditions affecting workers exposure: Assumes use at not more than 20°C above ambient temperature. Assumes a good basic standard of occupational hygiene is implemented

Contributing scenarios: Operational conditions and risk management measures

General measures (Reproductive toxin):

Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.

General measures applicable to all activities:

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Use suitable eye protection. Avoid direct eye contact with product also via contamination on hands.

Operation of equipment containing engine oils and similar Use in contained systems:
No other specific measures identified.

Material transfers Non-dedicated facility:

Avoid carrying out activities involving exposure for more than 4 hours per day. Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

Equipment cleaning and maintenance Dedicated facility:

Drain down system prior to equipment break-in or maintenance. Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Storage:
Store substance within a closed system.

Section 2.2: Control of environmental exposure

No exposure scenario is presented because the product is not classified for the Environment

Section 3: Exposure estimation and reference to its source

Exposure estimation and reference to its source - Environment

Exposure assessment (environment):

No exposure scenario is presented because the product is not classified for the Environment

Exposure estimation and reference to its source - Workers

Exposure assessment (human):

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 4: Guidance to check compliance with the exposure scenario

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.ATIEL.org/REACH_GES

Health

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.