# **SAFETY DATA SHEET**



**Duratec LFG 40** 

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier Duratec LFG 40

**SDS #** 467623 **Code** 467623-US31

Relevant identified uses of the substance or mixture and uses advised against

Product use Engine Oils.

For specific application advice see appropriate Technical Data Sheet or consult our

company representative.

Manufacturer BP Lubricants USA Inc.

1500 Valley Road Wayne, NJ 07470

Telephone: +1-888-CASTROL

Supplier PAN AMERICAN ENERGY S.L., SUCURSAL

ARGENTINA AV. LEANDRO N. ALEM 1180

PISO 11 - C1001AAT

CIUDAD AUTÓNOMA DE BUENOS AIRES.

Consultas Técnicas 0800-888-8088

EMERGENCY HEALTH TELÉFONO PARA EMERGENCIAS (24 HORAS) CIQUIME: 0800-222-2933

INFORMATION: +1-800-424-9300 (CHEMTREC USA)

+1-703-527-3887 (CHEMTREC outside the US)

**EMERGENCY TELEPHONE** 

**NUMBER** 

### SECTION 2: Hazards identification

Classification of the Not classified.

substance or mixture

**GHS** label elements

Signal word No signal word.

**Hazard statements** No known significant effects or critical hazards.

**Precautionary statements** 

Prevention
Response
Storage
Disposal

Other hazards which do not

Not applicable.
Not applicable.
Not applicable.
Not applicable.
None known.

result in classification

Product nameDuratec LFG 40Product code467623-US31Page: 1/9Date of issue03/12/2025.Format ArgentinaLanguage ENGLISH

Version 1.01 (AR) (ENGLISH)

### **SECTION 3: Composition/information on ingredients**

Substance/mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Other means of Not available.

identification

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

#### **Description of necessary first aid measures**

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15

minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing.

Check for and remove any contact lenses. Get medical attention.

Skin contact Wash skin thoroughly with soap and water or use recognized skin cleanser.

> Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.

Inhalation If inhaled, remove to fresh air. In case of inhalation of decomposition products in a

> fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.

Do not induce vomiting unless directed to do so by medical personnel. Get medical Ingestion

attention if symptoms occur.

**Protection of first-aiders** No action shall be taken involving any personal risk or without suitable training.

#### Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

#### Indication of immediate medical attention and special treatment needed, if necessary

Treatment should in general be symptomatic and directed to relieving any effects. Notes to physician

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

No specific treatment. Specific treatments

### **SECTION 5: Firefighting measures**

**Extinguishing media** 

Suitable extinguishing

In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.

media

**Unsuitable extinguishing** 

media

Do not use water jet.

Specific hazards arising

from the chemical

**Hazardous thermal** 

decomposition products

Combustion products may include the following:

metal oxide/oxides

carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)

nitrogen oxides (NO, NO<sub>2</sub> etc.)

Special protective actions

for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if

In a fire or if heated, a pressure increase will occur and the container may burst.

there is a fire.

**Product name** Duratec LFG 40

**Product code** 

467623-US31

Page: 2/9

**Format Argentina** 

Date of issue 03/12/2025.

Language ENGLISH

Version 1.01

(AR)

(ENGLISH)

### **SECTION 5: Firefighting measures**

Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

### **SECTION 6: Accidental release measures**

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

### **SECTION 7: Handling and storage**

#### Precautions for safe handling

Protective measures
Advice on general
occupational hygiene

Put on appropriate personal protective equipment (see Section 8).

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Not suitable Prolonged exposure to elevated temperature

### **SECTION 8: Exposure controls/personal protection**

**Control parameters** 

**Occupational exposure limits** 

Product name Duratec LFG 40

Product code 467623-US31

Page: 3/9

Date of issue 03/12/2025.

Format Argentina

Language ENGLISH

Version 1.01

(AR)

(ENGLISH)

### **SECTION 8: Exposure controls/personal protection**

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy paraffinic	Ministry of Labor, Employment and Social Security. Argentina (Resolution 295,11/2003) (Argentina).  TWA: 5 mg/m³ 8 hours. Issued/Revised: 11/2003 Form: mist  STEL: 10 mg/m³ 15 minutes. Issued/ Revised: 11/2003 Form: mist
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Ministry of Labor, Employment and Social Security. Argentina (Resolution 295,11/2003) (Argentina).  TWA: 5 mg/m³ 8 hours. Issued/Revised: 11/2003 Form: mist  STEL: 10 mg/m³ 15 minutes. Issued/ Revised: 11/2003 Form: mist

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

#### **Biological exposure indices**

No exposure indices known.

# Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

# **Environmental exposure** controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Skin protection

Hand protection

Safety glasses with side shields.

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the

Product name Duratec LFG 40

Product code 467623-US31

Page: 4/9

Date of issue 03/12/2025.

Format Argentina

Language ENGLISH

Version 1.01

(AR)

(ENGLISH)

### **SECTION 8: Exposure controls/personal protection**

working conditions.

**Body protection** Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist

before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons

and/or impervious chemical suits and boots will be required.

Other skin protection Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

### **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Appearance**

Physical state
Color
Brown.

Odor
Not available.

Odor threshold
PH
Not applicable.

Melting point/freezing point
Boiling point, initial boiling
point, and boiling range

Liquid.
Brown.
Not available.
Not available.
Not available.

Flash point Closed cup: 216°C (420.8°F) [Pensky-Martens]

Pour point <-18 °C

Evaporation rate Not available.

Flammability Not available.

Lower and upper explosion Not available.

Vapor pressure

limit/flammability limit

	Vapor Pressure at 20°C			Vapor pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
Distillates (petroleum), hydrotreated heavy paraffinic	<0.08	<0.011	ASTM D 5191			
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<0.08	<0.011	ASTM D 5191			
bis(nonylphenyl)amine	<0.01	<0.0013	EU A.4	0	0	EU A.4

Relative vapor density Not available.

**Density** <1000 kg/m³ (<1 g/cm³) at 15°C

Solubility(ies)

Partition coefficient: n- Not applicable.

octanol/water

Product nameDuratec LFG 40Product code467623-US31Page: 5/9Date of issue 03/12/2025.Format ArgentinaLanguage ENGLISH

Version 1.01 (AR) (ENGLISH)

### **SECTION 9: Physical and chemical properties**

**Auto-ignition temperature** Ingredient name °F Method 440 EU A.15 824 bis(nonylphenyl)amine

**Decomposition temperature** 

Not available.

**Viscosity** 

Kinematic: 121 mm<sup>2</sup>/s (121 cSt) at 40°C

Kinematic: 12.5 to 13.5 mm<sup>2</sup>/s (12.5 to 13.5 cSt) at 100°C

Particle characteristics

Median particle size Not applicable.

# **SECTION 10: Stability and reactivity**

Reactivity No specific test data available for this product. Refer to Conditions to avoid and

Incompatible materials for additional information.

**Chemical stability** The product is stable.

Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not

occur.

**Conditions to avoid** Avoid all possible sources of ignition (spark or flame).

**Incompatible materials** Reactive or incompatible with the following materials: oxidizing materials.

**Hazardous decomposition** 

products

Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

### **SECTION 11: Toxicological information**

#### Information on toxicological effects

Information on the likely

routes of exposure

Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Eye contact No known significant effects or critical hazards.

Skin contact Defatting to the skin. May cause skin dryness and irritation.

Inhalation Exposure to decomposition products may cause a health hazard. Serious effects

may be delayed following exposure.

No known significant effects or critical hazards. Ingestion

### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact No specific data.

**Skin contact** Adverse symptoms may include the following:

> irritation dryness cracking

Inhalation No specific data. Ingestion No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

**Product code Product name** Duratec LFG 40 467623-US31 Page: 6/9 Date of issue 03/12/2025. **Format Argentina** Language ENGLISH Version 1.01 (AR) (ENGLISH)

### **SECTION 11: Toxicological information**

**Potential immediate** 

effects

effects

Not available.

**Potential delayed effects** 

Not available.

**Long term exposure** 

**Potential immediate** 

•

Not available.

Potential delayed effects

Not available.

Potential chronic health effects

General USED ENGINE OILS

Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a

high standard of personal hygiene maintained.

Carcinogenicity
No known significant effects or critical hazards.

Mutagenicity
No known significant effects or critical hazards.

Teratogenicity
No known significant effects or critical hazards.

Developmental effects
No known significant effects or critical hazards.

Fertility effects
No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

Route

Not available.

### **SECTION 12: Ecological information**

**Toxicity** 

**Environmental effects** No known significant effects or critical hazards.

#### Persistence and degradability

Expected to be biodegradable.

#### **Bioaccumulative potential**

This product is not expected to bioaccumulate through food chains in the environment.

**Mobility in soil** 

Soil/water partition coefficient (Koc)

Not available.

**Mobility** Spillages may penetrate the soil causing ground water contamination.

Other adverse effects No known significant effects or critical hazards.

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms.

Oxygen transfer could also be impaired.

Product name Duratec LFG 40

Product code 467623-US31

Page: 7/9

Date of issue 03/12/2025.

Format Argentina

Language ENGLISH

Version 1.01

(AR)

(ENGLISH)

### **SECTION 13: Disposal considerations**

#### **Disposal methods**

The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA/ICAO
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

Special precautions for user Not available.

Transport in bulk according to IMO instruments

Not available.

### to into instruments

### **SECTION 15: Regulatory information**

#### International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### **Montreal Protocol**

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

#### **Other regulations**

Australia inventory (AIIC) All components are listed or exempted.

Product name Duratec LFG 40

Product code 467623-US31

Page: 8/9

Date of issue 03/12/2025.

Format Argentina

(AR)

(ENGLISH)

### **SECTION 15: Regulatory information**

**Canada inventory** All components are listed or exempted. **China inventory (IECSC)** All components are listed or exempted. Japan inventory (CSCL) All components are listed or exempted. All components are listed or exempted. **Korea inventory (KECI)** 

**Philippines inventory** 

(PICCS)

All components are listed or exempted.

All components are listed or exempted.

**Taiwan Chemical Substances Inventory** 

(TCSI)

**United States inventory** 

(TSCA 8b)

All components are active or exempted.

**REACH Status** For the REACH status of this product please consult your company contact, as

identified in Section 1.

### SECTION 16: Other information

#### **History**

Date of issue/Date of

revision

04/13/2022.

03/12/2025.

Date of previous issue

**Product Stewardship** 

Prepared by

Key to abbreviations

ADN = European Provisions concerning the International Carriage of Dangerous

Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous

Goods by Road

ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

VOC = Volatile Organic Compound

Varies = may contain one or more of the following 64741-88-4, 64741-89-5. 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

#### Indicates information that has changed from previously issued version.

#### Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.