

Almaredge 51 FF

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

**Product identifier** Almaredge 51 FF  
**SDS #** 464962  
**Code** 464962-FR01

### Relevant identified uses of the substance or mixture and uses advised against

**Product use** Metalworking fluid - soluble.  
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

**Manufacturer** BP Lubricants USA Inc.  
1500 Valley Road  
Wayne, NJ 07470  
Telephone: +1-888-CASTROL

**Supplier** PAN AMERICAN ENERGY S.L., SUCURSAL  
ARGENTINA AV. LEANDRO N. ALEM 1180  
PISO 11 – C1001AAT  
CIUDAD AUTÓNOMA DE BUENOS AIRES.

Consultas Técnicas 0800-888-8088

**EMERGENCY HEALTH INFORMATION:** TELÉFONO PARA EMERGENCIAS (24 HORAS) CIQUIME: 0800-222-2933  
+1-800-424-9300 (CHEMTREC USA)  
+1-703-527-3887 (CHEMTREC outside the US)

**EMERGENCY TELEPHONE NUMBER**

## SECTION 2: Hazards identification

**Classification of the substance or mixture**  SKIN IRRITATION - Category 2  
EYE IRRITATION - Category 2A  
AQUATIC HAZARD (ACUTE) - Category 2  
AQUATIC HAZARD (LONG-TERM) - Category 3

### GHS label elements

**Hazard pictograms**



**Signal word** Warning

**Hazard statements**  H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H401 - Toxic to aquatic life.  
H412 - Harmful to aquatic life with long lasting effects.

### Precautionary statements

**Prevention** P280 - Wear protective gloves. Wear eye or face protection.  
P273 - Avoid release to the environment.  
P264 - Wash hands thoroughly after handling.

**Product name** Almaredge 51 FF

**Product code** 464962-FR01

**Page:** 1/11

**Date of issue** 10/04/2024.

**Format** Argentina

**Language** ENGLISH

**Version** 1.02

(AR)

(ENGLISH)

## SECTION 2: Hazards identification

<b>Response</b>	P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of soap and water. P332 + P313 - If skin irritation occurs: Get medical attention. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical attention.
<b>Storage</b>	Not applicable.
<b>Disposal</b>	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
<b>Other hazards which do not result in classification</b>	Defatting to the skin. This product contains complex ionic mixtures within the fluid matrix which are an intrinsic part of the product and cannot be separated from the fluid matrix. Toxicology testing has shown the ionic-mixture containing products exhibit skin and eye irritation properties that are notably attenuated when compared to the individual acid and base components.

## SECTION 3: Composition/information on ingredients

<b>Substance/mixture</b>	Mixture
	Highly refined base oil (IP 346 DMSO extract < 3%), emulsifiers and additives.
<b>Other means of identification</b>	Not available.

Ingredient name	%	CAS number
Distillates (petroleum), hydrotreated heavy naphthenic	≥25 - ≤50	64742-52-5
Amine carbamate	≤10	174125-97-4
2,2',2"-nitrioltriethanol	≤10	102-71-6
2-aminoethanol	<5	141-43-5
Boric acid	≤5	10043-35-3
Alcohols, C16-18 and C18-unsatd., ethoxylated	≤3	68920-66-1
Alcohols, C16-18, ethoxylated propoxylated	≤3	68002-96-0
2-n-butyl-benzo[d]isothiazol-3-one	≤0.3	4299-07-4

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### Description of necessary first aid measures

<b>Eye contact</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
<b>Skin contact</b>	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention. If skin irritation or rash occurs: Get medical advice/attention.
<b>Inhalation</b>	If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.

<b>Product name</b> Almaredge 51 FF	<b>Product code</b> 464962-FR01	<b>Page:</b> 2/11
<b>Date of issue</b> 10/04/2024.	<b>Format</b> Argentina	<b>Language</b> ENGLISH
<b>Version</b> 1.02	<b>(AR)</b>	<b>(ENGLISH)</b>

## SECTION 4: First aid measures

### Ingestion

Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Wash out mouth with water if person is conscious. Get medical attention if adverse health effects persist or are severe.

### Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

### Indication of immediate medical attention and special treatment needed, if necessary

#### Notes to physician

Treatment should in general be symptomatic and directed to relieving any effects. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

#### Specific treatments

No specific treatment.

## SECTION 5: Firefighting measures

### Extinguishing media

#### Suitable extinguishing media

In case of fire, use water fog, alcohol resistant foam, dry chemical or carbon dioxide extinguisher or spray.

#### Unsuitable extinguishing media

Do not use water jet.

#### Specific hazards arising from the chemical

Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life. This material is harmful to aquatic life with long lasting effects.

#### Hazardous thermal decomposition products

Combustion products may include the following:  
carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)  
nitrogen oxides (NO, NO<sub>2</sub> etc.)

#### Special protective actions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

#### Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

#### For emergency responders

Entry into a confined space or poorly ventilated area contaminated with vapor, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

**Product name** Almaredge 51 FF

**Product code** 464962-FR01

**Page:** 3/11

**Date of issue** 10/04/2024.

**Format** Argentina

**Language** ENGLISH

**Version** 1.02

(AR)

(ENGLISH)

## SECTION 6: Accidental release measures

**Environmental precautions** Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### Methods and materials for containment and cleaning up

**Small spill** Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilled product. Dispose of via a licensed waste disposal contractor.

## SECTION 7: Handling and storage

### Precautions for safe handling

**Protective measures** Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Avoid contact of spilled material and runoff with soil and surface waterways. Avoid prolonged or repeated contact with skin. During metal working, solid particles from workpieces or tools will contaminate the fluid and may cause abrasions of the skin. Where such abrasions result in a penetration of the skin, first aid treatment should be applied as soon as reasonably possible. The presence of certain metals in the workpiece or tool, such as chromium, cobalt and nickel, can contaminate the metalworking fluid and as a result may induce allergic skin reactions. Evaporation of water from soluble cutting fluids during use may lead to an increase in concentration which may result in the development of skin conditions due to irritation and defatting. It is important to monitor fluid strength on a regular basis with a refractometer and maintain it at the recommended concentration. Lubricants from other sources and other contaminants should be minimized. Swarf and other debris should be removed. To maintain optimum performance and minimize bacterial spoilage, machine tool coolant systems should be cleaned on a regular basis.

**Advice on general occupational hygiene** Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. Contaminated work clothing should not be allowed out of the workplace. See also Section 8 for additional information on hygiene measures.

**Conditions for safe storage, including any incompatibilities** Store between the following temperatures: 10 to 40°C (50 to 104°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. DO NOT ADD NITRITES TO THIS FLUID.

**Product name** Almaredge 51 FF

**Product code** 464962-FR01

**Page:** 4/11

**Date of issue** 10/04/2024.

**Format** Argentina

**Language** ENGLISH

**Version** 1.02

(AR)

(ENGLISH)

## SECTION 8: Exposure controls/personal protection

### [Control parameters](#)

#### [Occupational exposure limits](#)

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy naphthenic	<b>Ministry of Labor, Employment and Social Security. Argentina (Resolution 295,11/2003) (Argentina). [Aceite mineral]</b> TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/Revised: 11/2003 Form: mist STEL: 10 mg/m <sup>3</sup> 15 minutes. Issued/Revised: 11/2003 Form: mist
2,2',2''-nitrioltriethanol	<b>Ministry of Labor, Employment and Social Security. Argentina (Resolution 295,11/2003) (Argentina).</b> TWA: 5 mg/m <sup>3</sup> 8 hours. Issued/Revised: 11/2003
2-aminoethanol	<b>Ministry of Labor, Employment and Social Security. Argentina (Resolution 295,11/2003) (Argentina).</b> TWA: 3 ppm 8 hours. Issued/Revised: 11/2003 STEL: 6 ppm 15 minutes. Issued/Revised: 11/2003
Boric acid	<b>ACGIH TLV (United States). [Borate compounds, Inorganic]</b> STEL: 6 mg/m <sup>3</sup> 15 minutes. Issued/Revised: 1/2005 Form: Inhalable fraction TWA: 2 mg/m <sup>3</sup> 8 hours. Issued/Revised: 1/2005 Form: Inhalable fraction

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

#### [Biological exposure indices](#)

No exposure indices known.

#### [Appropriate engineering controls](#)

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

#### [Environmental exposure controls](#)

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### [Individual protection measures](#)

**Product name** Almaredge 51 FF

**Product code** 464962-FR01

**Page:** 5/11

**Date of issue** 10/04/2024.

**Format** Argentina

**Language** ENGLISH

**Version** 1.02

**(AR)**

**(ENGLISH)**

## SECTION 8: Exposure controls/personal protection

### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### Eye/face protection

Undiluted fluid: Chemical goggles.  
Diluted fluid: Safety glasses with side shields.

### Skin protection

#### Hand protection

Wear suitable gloves. Undiluted fluid: Wear chemical resistant gloves. Recommended: nitrile gloves.  
Diluted fluid: Wear protective gloves if prolonged or repeated contact is likely. Recommended: nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

#### Body protection

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

#### Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. For protection against metal working fluids, respiratory protection that is classified as "resistant to oil" (class R) or oil proof (class P) should be selected where appropriate. Depending on the level of airborne contaminants, an air-purifying, half-mask respirator (with HEPA filter) including disposable (P- or R-series) (for oil mists less than 50mg/m<sup>3</sup>), or any powered, air-purifying respirator equipped with hood or helmet and HEPA filter (for oil mists less than 125 mg/m<sup>3</sup>). Where organic vapours are a potential hazard during metalworking operations, a combination particulate and organic vapour filter may be necessary. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

Physical state	Liquid.
Color	Amber. [Light]
Odor	Unfragranced
Odor threshold	Not available.
pH	9.2 [Conc. (% w/w): 4%]
Melting point/freezing point	Not available.

Product name Almareedge 51 FF

Product code 464962-FR01

Page: 6/11

Date of issue 10/04/2024.

Format Argentina

Language ENGLISH

Version 1.02

(AR)

(ENGLISH)

## SECTION 9: Physical and chemical properties

<b>Boiling point, initial boiling point, and boiling range</b>	Not available.
<b>Flash point</b>	Closed cup: >100°C (>212°F) [Estimated. Water content interferes with flash point determination.]
<b>Evaporation rate</b>	Not available.
<b>Flammability</b>	Not available.
<b>Lower and upper explosion limit/flammability limit</b>	Not available.

### Vapor pressure

Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Distillates (petroleum), hydrotreated heavy naphthenic	<0.07501	<0.01	ASTM D 5191			
Water	17.5	2.3				
Tall oil	0.000029	0.0000039				
2,2',2''-nitrioltriethanol	<0.0075	<0.001				
2-aminoethanol	0.4	0.053				

<b>Relative vapor density</b>	Not available.
<b>Density</b>	<1000 kg/m <sup>3</sup> (<1 g/cm <sup>3</sup> ) at 20°C
<b>Solubility(ies)</b>	

Media	Result
water	Soluble

<b>Partition coefficient: n-octanol/water</b>	Not applicable.
---	-----------------

### Auto-ignition temperature

Ingredient name	°C	°F	Method
2,2',2''-nitrioltriethanol	324	615.2	
2-aminoethanol	410	770	

<b>Decomposition temperature</b>	Not available.
----------------------------------	----------------

<b>Viscosity</b>	Kinematic: 140 mm <sup>2</sup> /s (140 cSt) at 40°C
------------------	---

### Particle characteristics

<b>Median particle size</b>	Not applicable.
-----------------------------	-----------------

## SECTION 10: Stability and reactivity

<b>Reactivity</b>	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
-------------------	---

<b>Chemical stability</b>	The product is stable.
---------------------------	------------------------

<b>Possibility of hazardous reactions</b>	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur.
---	---

<b>Conditions to avoid</b>	Avoid excessive heat.
----------------------------	-----------------------

<b>Incompatible materials</b>	Reactive or incompatible with the following materials: oxidizing materials. Slightly reactive or incompatible with the following materials: acids.
-------------------------------	---

**Product name** Almaredge 51 FF

**Product code** 464962-FR01

**Page:** 7/11

**Date of issue** 10/04/2024.

**Format** Argentina

**Language** ENGLISH

**Version** 1.02

(AR)

(ENGLISH)

## SECTION 10: Stability and reactivity

### Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### Information on toxicological effects

#### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
2-aminoethanol	Category 3	-	Respiratory tract irritation

### Information on the likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

### Potential acute health effects

#### Eye contact

Causes serious eye irritation.

#### Skin contact

Causes skin irritation. Defatting to the skin.

#### Inhalation

Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

#### Ingestion

Irritating to mouth, throat and stomach.

### Symptoms related to the physical, chemical and toxicological characteristics

#### Eye contact

Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

#### Skin contact

Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking

#### Inhalation

No specific data.

#### Ingestion

No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

##### Potential immediate effects

Not available.

##### Potential delayed effects

Not available.

#### Long term exposure

##### Potential immediate effects

Not available.

##### Potential delayed effects

Not available.

#### Potential chronic health effects

##### General

No known significant effects or critical hazards.

##### Carcinogenicity

No known significant effects or critical hazards.

##### Mutagenicity

No known significant effects or critical hazards.

##### Teratogenicity

No known significant effects or critical hazards.

##### Developmental effects

No known significant effects or critical hazards.

##### Fertility effects

No known significant effects or critical hazards.



## SECTION 11: Toxicological information

### [Numerical measures of toxicity](#)

#### [Acute toxicity estimates](#)

Route	ATE value
<input checked="" type="checkbox"/> Dermal	22719.49 mg/kg
<input type="checkbox"/> Inhalation (vapors)	227.19 mg/l

## SECTION 12: Ecological information

### [Toxicity](#)

#### [Environmental effects](#)

This material is toxic to aquatic life. This material is harmful to aquatic life with long lasting effects.

#### [Persistence and degradability](#)

Expected to be biodegradable.

#### [Bioaccumulative potential](#)

Not available.

#### [Mobility in soil](#)

##### [Soil/water partition coefficient \(K<sub>oc</sub>\)](#)

Not available.

##### [Mobility](#)

Liquid. Soluble in water.

#### [Other adverse effects](#)

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### [Disposal methods](#)

The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Diluted Fluid The spent diluted fluid comprises a relatively stable emulsion. Dispose of via an authorised person/ licensed waste disposal contractor or by other suitable waste treatment techniques (e.g. emulsion splitting, coagulation and filtration) approved by the local authority. Spent fluid should never be disposed of down the drain. The aqueous phase should not be discharged into sewage systems unless provided for by local regulations; the non-aqueous phase should be disposed of as undiluted fluid. Note that separated aqueous solutions or effluents may contain metal salts as well as traces of oil and must be checked for conformity in these respects against consents given by the authorities before disposal. Further treatment may be required.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA/ICAO
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

Special precautions for user Not available.

Transport in bulk according to IMO instruments Not available.

## SECTION 15: Regulatory information

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

List name	Ingredient name	Status
<input checked="" type="checkbox"/> Schedule III	Triethanolamine	Listed

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### Other regulations

<a href="#">Australia inventory (AIIC)</a>	At least one component is not listed.
<a href="#">Canada inventory</a>	At least one component is not listed.
<a href="#">China inventory (IECSC)</a>	All components are listed or exempted.
<a href="#">Japan inventory (CSCL)</a>	All components are listed or exempted.
<a href="#">Korea inventory (KECI)</a>	All components are listed or exempted.
<a href="#">Philippines inventory (PICCS)</a>	At least one component is not listed.
<a href="#">Taiwan Chemical Substances Inventory (TCSI)</a>	All components are listed or exempted.

Product name Almaredge 51 FF

Product code 464962-FR01

Page: 10/11

Date of issue 10/04/2024.

Format Argentina

Language ENGLISH

Version 1.02

(AR)

(ENGLISH)

## SECTION 15: Regulatory information

### United States inventory (TSCA 8b)

At least one component is not listed.

### REACH Status

The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

## SECTION 16: Other information

### History

#### Date of issue/Date of revision

10/04/2024.

#### Date of previous issue

07/29/2024.

#### Prepared by

Product Stewardship

#### Key to abbreviations

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

VOC = Volatile Organic Compound

Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

✔ Indicates information that has changed from previously issued version.

### Notice to reader

*All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.*

*The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.*

*It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.*