

## 1. Product and company identification

**Product name** Castrol High Temperature Grease  
**Product code** 467200-SG01  
**SDS #** 467200  
**Original preparation date** 03/12/2019  
**Supplier** BP Castrol K.K.  
 1-11-2, Osaki, Shinagawaku, Tokyo, 141-0032  
 East Tower 20F, Gate City Osaki  
 Telephone : 03-5719-7860 (days & hours of operation : Monday - Friday, 09:00 - 17:00)  
 Carechem: 0120-015-230 (Operation time: 24 hrs)  
**EMERGENCY TELEPHONE NUMBER**

### Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Grease for industrial applications.  
 For specific application advice see appropriate Technical Data Sheet or consult our company representative.

### Uses advised against

Use advised against: Consult with experts for use other than relevant identified use

## 2. Hazards identification

**GHS Classification** Not classified.  
**GHS label elements**  
**Signal word** No signal word.  
**Hazard statements** No known significant effects or critical hazards.  
**Precautionary statements**  
**Prevention** Not applicable.  
**Response** Not applicable.  
**Storage** Not applicable.  
**Disposal** Not applicable.  
**Other hazards which do not result in classification** Defatting to the skin.  
 Note: High Pressure Applications  
 Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency.  
 See 'Notes to physician' under First-Aid Measures, Section 4 of this Safety Data Sheet.

### 3. Composition/information on ingredients

#### Substance/mixture

Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Thickening agent. Proprietary performance additives.

| Ingredient name   | %         | CAS number      | Official Gazette notice reference number |                |
|---|-----------|-----------------|--|----------------|
|   |           |                 | CSCL                                     | ISHL           |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | ≥25 - ≤50 | CAS: 64742-65-0 | Not available.                           | Not available. |
| Residual oils (petroleum), solvent refined                | ≥25 - ≤50 | CAS: 64742-01-4 | Not available.                           | Not available. |
| Distillates (petroleum), hydrotreated heavy naphthenic    | ≤10       | CAS: 64742-52-5 | (9)-1689                                 | Not available. |
| dilithium sebacate  | ≤3.0      | CAS: 19370-86-6 | Not available.                           | Not available. |
| 4,4'-methylene bis(dibutylthiocarbamate)                  | ≤3.0      | CAS: 10254-57-6 | 2-3522                                   | Not available. |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Applicability to local regulations are determined with consideration of reactions of constituents included in the formulation. Please see section 15 for regulatory information.

### 4. First aid measures

#### Description of necessary first aid measures

##### Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.

##### Inhalation

If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.

##### Skin contact

Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur. If skin irritation or rash occurs: Get medical advice/attention.

##### Ingestion

Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

#### Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

#### Indication of immediate medical attention and special treatment needed, if necessary

##### Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training.

##### Notes to physician

Treatment should in general be symptomatic and directed to relieving any effects. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Note: High Pressure Applications

Injects through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discoloured and extremely painful with

**Product name** Castrol High Temperature Grease

**Product code** 467200-SG01

Page: 2/14

**Version** 3

**Date of issue** 2025 September 29

**Format Japan**

**Language**

**ENGLISH**

**Date of** 2025 February 27.

**Build** 6.2

**(Japan)**

**(ENGLISH)**

**previous issue**

**Original preparation date**

12/2/2019

## 4. First aid measures

extensive subcutaneous necrosis.

Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimise tissue loss and prevent or limit permanent damage. Note that high pressure may force the product considerable distances along tissue planes.

### Specific treatments

No specific treatment.

## 5. Firefighting measures

### Extinguishing media

#### Suitable

In case of fire, use water fog, alcohol resistant foam, dry chemical or carbon dioxide extinguisher or spray.

#### Not suitable

Do not use water jet.

### Specific hazards arising from the chemical

No specific fire or explosion hazard.

#### Hazardous thermal decomposition products

Combustion products may include the following:  
metal oxide/oxides  
carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)  
sulphur oxides (SO, SO<sub>2</sub>, etc.)  
nitrogen oxides (NO, NO<sub>2</sub> etc.)

### Special protective actions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

### Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

#### For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and material for containment and cleaning up

#### Small spill

Move containers from spill area. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.

#### Large spill

Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. If emergency personnel are unavailable, contain spilt material. Suction or scoop the spill into appropriate disposal or recycling vessels, then cover spill area with oil absorbent. Dispose of via a licensed waste disposal contractor.

|                     |                                  |                               |                     |                     |                         |
|---------------------|----------------------------------|-------------------------------|---------------------|---------------------|-------------------------|
| <b>Product name</b> | Castrol High Temperature Grease  |                               | <b>Product code</b> | 467200-SG01         | Page: 3/14              |
| <b>Version</b>      | 3                                | <b>Date of issue</b>          | 2025 September 29   | <b>Format Japan</b> | <b>Language ENGLISH</b> |
|                     |                                  | <b>Date of previous issue</b> | 2025 February 27.   | Build 6.2 (Japan)   | (ENGLISH)               |
|                     | <b>Original preparation date</b> |                               | 12/2/2019           |                     |                         |

## 6. Accidental release measures

In the case of spillage at sea approved dispersants may be used where authorised by the appropriate government/regulatory authorities.

## 7. Handling and storage

### Protective measures

Put on appropriate personal protective equipment (see Section 8).

### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. Contaminated work clothing should not be allowed out of the workplace. See also Section 8 for additional information on hygiene measures.

### Conditions for safe storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

### Not suitable

Prolonged exposure to elevated temperature

## 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

| Ingredient name   | Exposure limits  |
|---|--|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | <b>Japan Society for Occupational Health (Japan) [Mineral oils]</b> Carc 1.<br><b>Japan Society for Occupational Health (Japan) [Soots]</b> Carc 1.<br><b>Japan Society for Occupational Health (Japan) [Oil mist, mineral]</b><br>OEL-M 8 hours: 3 mg/m <sup>3</sup> . Form: Mist.<br>Issued/Revised: 5/2010. |
| Residual oils (petroleum), solvent refined                | <b>Japan Society for Occupational Health (Japan) [Mineral oils]</b> Carc 1.<br><b>Japan Society for Occupational Health (Japan) [Soots]</b> Carc 1.<br><b>Japan Society for Occupational Health (Japan) [Oil mist, mineral]</b><br>OEL-M 8 hours: 3 mg/m <sup>3</sup> . Form: Mist.<br>Issued/Revised: 5/2010. |
| Distillates (petroleum), hydrotreated heavy naphthenic    | <b>Japan Society for Occupational Health (Japan) [Mineral oils]</b> Carc 1.<br><b>Japan Society for Occupational Health (Japan) [Soots]</b> Carc 1.<br><b>Japan Society for Occupational Health (Japan) [Oil mist, mineral]</b><br>OEL-M 8 hours: 3 mg/m <sup>3</sup> . Form: Mist.<br>Issued/Revised: 5/2010. |

**Product name** Castrol High Temperature Grease

**Product code** 467200-SG01

Page: 4/14

**Version** 3 **Date of issue** 2025 September 29

**Format Japan**

**Language** ENGLISH

**Date of previous issue** 2025 February 27.

Build 6.2 (Japan)

(ENGLISH)

**Original preparation date** 12/2/2019

## 8. Exposure controls/personal protection

### Recommended monitoring procedures

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Biological exposure indices

No exposure indices known.

### Individual protection measures

#### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

#### Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

#### Eye protection

Safety glasses with side shields.

#### Skin protection

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when

|                     |                                 |                                  |                     |                     |                         |
|---------------------|---------------------------------|----------------------------------|---------------------|---------------------|-------------------------|
| <b>Product name</b> | Castrol High Temperature Grease |                                  | <b>Product code</b> | 467200-SG01         | Page: 5/14              |
| <b>Version</b>      | 3                               | <b>Date of issue</b>             | 2025 September 29   | <b>Format Japan</b> | <b>Language ENGLISH</b> |
|                     |                                 | <b>Date of previous issue</b>    | 2025 February 27.   | Build 6.2 (Japan)   | (ENGLISH)               |
|                     |                                 | <b>Original preparation date</b> | 12/2/2019           |                     |                         |

## 8. Exposure controls/personal protection

cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

### Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

Physical state

Grease

Colour

Amber.

Odour

Characteristic.

pH

Not applicable.

Melting point/freezing point

Not available.

Softening point

Not available.

Boiling point or initial boiling point and boiling range

Not available.

Flash point

Closed cup: >200°C (>392°F) [Pensky-Martens ASTM D 93]

Fire point

Not available.

Evaporation rate

Not available.

Flammability

Not available.

Lower and upper explosive (flammable) limits

Not available.

Vapour pressure

Not available.

| Ingredient name | Vapour Pressure at 20°C |     |        | Vapour pressure at 50°C |     |        |
|-----------------|-------------------------|-----|--------|-------------------------|-----|--------|
|                 | mm Hg                   | kPa | Method | mm Hg                   | kPa | Method |
|                 |                         |     |        |                         |     |        |

Relative vapour density

Not applicable.

Relative Density

Not available.

Density

Not available.

Auto-ignition temperature

>300°C (>572°F)

| Ingredient name | °C | °F | Method |
|-----------------|----|----|--------|
| Not listed.     |    |    |        |

Decomposition temperature

Not available.

Lower and upper explosion limit/flammability limit

Not applicable.

Critical temperature

Not available.

Oxidising properties

Not available.

Viscosity

Not available.

Drop Point

Not available.

Density

Not available.

Solubility(ies)

**Product name** Castrol High Temperature Grease

**Product code** 467200-SG01

Page: 6/14

**Version** 3 **Date of issue** 2025 September 29

**Format Japan**

**Language** ENGLISH

**Date of** 2025 February 27.

**Build 6.2 (Japan)**

**(ENGLISH)**

**previous issue**

**Original preparation date** 12/2/2019

## 9. Physical and chemical properties

|                                      |                              |
|--------------------------------------|------------------------------|
| <b>Media</b><br>water                | <b>Result</b><br>Not soluble |
| Solubility at room temperature (g/l) | Not available.               |
| Partition coefficient (LogKow)       | Not applicable.              |
| Remarks                              | Not available.               |
| <b>Particle characteristics</b>      |                              |
| Median particle size                 | Not available.               |


## 10. Stability and reactivity

|   |   |
|---|---|
| <b>Reactivity</b>                         | No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.                                   |
| <b>Chemical stability</b>                 | The product is stable.  |
| <b>Possibility of hazardous reactions</b> | Under normal conditions of storage and use, hazardous reactions will not occur.<br>Under normal conditions of storage and use, hazardous polymerisation will not occur. |
| <b>Conditions to avoid</b>                | Avoid all possible sources of ignition (spark or flame).  |
| <b>Incompatible materials</b>             | Reactive or incompatible with the following materials: oxidising materials.   |
| <b>Hazardous decomposition products</b>   | Under normal conditions of storage and use, hazardous decomposition products should not be produced.  |

## 11. Toxicological information

### Acute toxicity

#### Product/ingredient name

 Distillates (petroleum), solvent-dewaxed heavy paraffinic

#### Result

##### Rat - Oral - LD50

>5000 mg/kg  
OECD 401

##### Rat - Dermal - LD50

>2000 mg/kg  
OECD 402

##### Rat - Inhalation - LC50 Dusts and mists

>5.53 mg/l [4 hours]  
OECD 403

4,4'-methylene bis(dibutyldithiocarbamate)


##### Rat - Oral - LD50

>5000 mg/kg  
OECD 401

##### Rabbit - Dermal - LD50

>2000 mg/kg  
OECD 402

### Acute toxicity estimates

| Product/ingredient name  | Oral (mg/kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|--|--------------|----------------|--------------------------|-----------------------------|-------------------------------------|
|  Castrol High Temperature Grease (R09215A) - Parent (DIS) | 21760.9      | N/A            | N/A                      | N/A                         | N/A                                 |
| dilithium sebacate   | 500          | N/A            | N/A                      | N/A                         | N/A                                 |

|                     |                                 |                                  |                   |                          |
|---------------------|---------------------------------|----------------------------------|-------------------|--------------------------|
| <b>Product name</b> | Castrol High Temperature Grease | <b>Product code</b>              | 467200-SG01       | Page: 7/14               |
| <b>Version</b>      | 3                               | <b>Date of issue</b>             | 2025 September 29 | <b>Format Japan</b>      |
|                     |                                 | <b>Date of previous issue</b>    | 2025 February 27. | <b>Language</b>          |
|                     |                                 | <b>Original preparation date</b> | 12/2/2019         | <b>ENGLISH (ENGLISH)</b> |

## 11. Toxicological information

### [Skin corrosion/irritation](#)

#### Product/ingredient name

Distillates (petroleum), solvent-dewaxed heavy paraffinic  
4,4'-methylene bis(dibutyldithiocarbamate)

#### Result

**Rabbit - Skin - Non-irritant to skin.**

**Rabbit - Skin - Not irritant**  
OECD 404

### [Serious eye damage/eye irritation](#)

#### Product/ingredient name

Distillates (petroleum), solvent-dewaxed heavy paraffinic  
4,4'-methylene bis(dibutyldithiocarbamate)

#### Result

**Rabbit - Eyes - Non-irritating to the eyes.**

OECD 405  
**Rabbit - Eyes - Not irritant**  
OECD 405

### [Respiratory corrosion/irritation](#)

Not available.

### [Respiratory or skin sensitization](#)

#### Product/ingredient name

Distillates (petroleum), solvent-dewaxed heavy paraffinic  
  
4,4'-methylene bis(dibutyldithiocarbamate)

#### Result

**Guinea pig - skin**  
OECD 406  
Result: Not sensitising  
**Mouse - skin**  
OECD 429  
Result: Not sensitising

### [Germ cell mutagenicity](#)

#### Product/ingredient name

Distillates (petroleum), solvent-dewaxed heavy paraffinic

4,4'-methylene bis(dibutyldithiocarbamate)

#### Result

**In vitro - Bacteria**  
OECD [Bacterial Reverse Mutation Test]  
Result: Negative  
**In vitro - Mammal - species unspecified**  
OECD [In vitro Mammalian Chromosomal Aberration Test]  
Result: Negative  
**In vitro - Bacteria**  
OECD 471  
Result: Negative  
**In vitro - Mammalian-Animal**  
OECD 473  
Result: Negative  
**In vitro - Mammalian-Animal**  
OECD 476  
Result: Negative

**Product name** Castrol High Temperature Grease

**Version** 3 **Date of issue** 2025 September 29

**Date of previous issue** 2025 February 27.

**Original preparation date** 12/2/2019

**Product code** 467200-SG01

Page: 8/14

**Format Japan**  
Build 6.2 (Japan)

**Language** ENGLISH  
(ENGLISH)

## 11. Toxicological information

### [Carcinogenicity](#)

#### [Product/ingredient name](#)

Distillates (petroleum), solvent-dewaxed heavy paraffinic

#### [Result](#)

**Mouse - Dermal - Unspecified**

OECD 451

Result: Negative

### [Reproductive toxicity](#)

#### [Product/ingredient name](#)

Distillates (petroleum), solvent-dewaxed heavy paraffinic

#### [Result](#)

**Rat - Oral**

OECD 421

Maternal toxicity: Negative

Fertility effects: Negative

Developmental: Negative

4,4'-methylene bis(dibutylidithiocarbamate)

**Rat - Oral**

OECD 422

Maternal toxicity: Negative

Fertility effects: Negative

Developmental: Negative

### [Specific target organ toxicity \(single exposure\)](#)

Not available.

### [Specific target organ toxicity \(repeated exposure\)](#)

Not available.

### [Aspiration hazard](#)

Not available.

### [Information on likely routes of exposure](#)

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

### [Potential acute health effects](#)

#### [Eye contact](#)

No known significant effects or critical hazards.

#### [Inhalation](#)

Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

#### [Skin contact](#)

Defatting to the skin. May cause skin dryness and irritation.

#### [Ingestion](#)

No known significant effects or critical hazards.

### [Symptoms related to the physical, chemical and toxicological characteristics](#)

#### [Eye contact](#)

No specific data.

#### [Inhalation](#)

No specific data.

#### [Skin contact](#)

Adverse symptoms may include the following:  
irritation  
dryness  
cracking

|                     |                                 |                                  |                     |                     |                         |
|---------------------|---------------------------------|----------------------------------|---------------------|---------------------|-------------------------|
| <b>Product name</b> | Castrol High Temperature Grease |                                  | <b>Product code</b> | 467200-SG01         | Page: 9/14              |
| <b>Version</b>      | 3                               | <b>Date of issue</b>             | 2025 September 29   | <b>Format Japan</b> | <b>Language</b> ENGLISH |
|                     |                                 | <b>Date of previous issue</b>    | 2025 February 27.   | Build 6.2 (Japan)   | (ENGLISH)               |
|                     |                                 | <b>Original preparation date</b> | 12/2/2019           |                     |                         |

## 11. Toxicological information

Ingestion No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs.

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Ingestion Ingestion of large quantities may cause nausea and diarrhoea.

### Potential chronic health effects

General No known significant effects or critical hazards.

Carcinogenicity No known significant effects or critical hazards.

Mutagenicity No known significant effects or critical hazards.

Developmental effects No known significant effects or critical hazards.

Fertility effects No known significant effects or critical hazards.

## 12. Ecological information

Environmental effects No known significant effects or critical hazards.

### Ecotoxicity

#### Product/ingredient name

Distillates (petroleum), solvent-dewaxed heavy paraffinic

#### Result

##### **Acute - EL50**

OECD 201

Algae

>100 mg/l [72 hours]

##### **Acute - EL50**

OECD 202

Daphnia

>10000 mg/l [48 hours]

##### **Acute - LL50**

OECD 203

Fish

>100 mg/l [96 hours]

##### **Chronic - NOEL**

OECD 201

Algae

≥100 mg/l [72 hours]

##### **Chronic - NOEL**

OECD 211

Daphnia

10 mg/l [21 days]

4,4'-methylene bis(dibutylthiocarbamate)

##### **Acute - ErC50**

OECD 201

Algae

>0.0325 mg/l [72 hours]

##### **Acute - EC50**

OECD 202

Daphnia

>0.052 mg/l [48 hours]

##### **Acute - EL50**

OECD 203

Fish

**Product name** Castrol High Temperature Grease

**Product code** 467200-SG01

Page: 10/14

**Version** 3 **Date of issue** 2025 September 29

**Format** Japan

**Language** ENGLISH

**Date of** 2025 February 27.

**Build** 6.2 (Japan)

**(ENGLISH)**

**previous issue**

**Original preparation date** 12/2/2019

## 12. Ecological information

>0.06 mg/l [96 hours]

**Chronic - NOEC**

OECD 211

Daphnia

0.247 mg/l [21 days]

**Chronic - NOEC**

OECD 201

Algae

0.0325 mg/l [72 hours]

**Persistence and degradability** Expected to be biodegradable.

**Product/ingredient name**

**Result**

Distillates (petroleum), solvent-dewaxed  
heavy paraffinic  
4,4'-methylene bis(dibutyldithiocarbamate)

OECD 301F  
31% [28 days] - Not readily  
OECD 301B  
21% [28 days] - Not readily

**Bioaccumulative potential**

**Bioaccumulative potential**

This product is not expected to bioaccumulate through food chains in the environment.

| Product/ingredient name                        | LogP <sub>ow</sub> | BCF   | Potential |
|--|--------------------|-------|-----------|
| 4,4'-methylene bis<br>(dibutyldithiocarbamate) | 8.42               | 10.86 | Low       |

**Mobility**

Spillages are unlikely to penetrate the soil.

**Hazardous to the ozone layer**

Not applicable.

**Other ecological information**

This product is unlikely to disperse in water.

## 13. Disposal considerations

**Disposal methods**

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## 14. Transport information

|                            | IMDG           | IATA           |
|----------------------------|----------------|----------------|
| UN number                  | Not regulated. | Not regulated. |
| UN proper shipping name    | -              | -              |
| Transport hazard class(es) | -              | -              |
| Packing group              | -              | -              |
| Environmental hazards      | No.            | No.            |
| Additional information     | -              | -              |

Special precautions for user Not available.

[Transport in bulk according to IMO instruments](#)

Not available.

## 15. Regulatory information


[Fire Service Law](#)

| Category        | Substance name/Type | Danger category | Signal word | Designated quantity |
|-----------------|---------------------|-----------------|-------------|---------------------|
| Not applicable. |                     |                 |             |                     |

[Industrial Safety and Health Act](#)


Special Organic Solvents, etc. Not available.

[Substances requiring labelling](#)


| Ingredient name   | Name on list | CAS no. | Conc.   | Status |
|---|--------------|---------|---------|--------|
|  | Mineral oil  | -       | 80 - 90 | Listed |

\*Chemicals damaging skin/eye and Skin-absorbable harmful substances based on Article 594-2 are disclosed in the above table.

[Chemicals requiring notification](#)

| Ingredient name   | Name on list      | CAS no.   | Conc.    | Status |
|---|-------------------|-----------|----------|--------|
|  | Mineral oil       | -         | 80 - 90  | Listed |
| Lithium hydroxide   | Lithium hydroxide | 1310-65-2 | 0.1 - <1 | Listed |

[Carcinogens based on Article 577-2 of the Ordinance on ISH](#)

| Ingredient name  | %   | Status | Reference number |
|--|-----|--------|------------------|
|  distillates (petroleum), hydrotreated heavy naphthenic | ≤10 | Listed | -                |

[Carcinogens based on Paragraph 3, Article 28 of the Law](#)

|                     |                                 |                                  |                   |                         |
|---------------------|---------------------------------|----------------------------------|-------------------|-------------------------|
| <b>Product name</b> | Castrol High Temperature Grease | <b>Product code</b>              | 467200-SG01       | Page: 12/14             |
| <b>Version</b>      | 3                               | <b>Date of issue</b>             | 2025 September 29 | <b>Format</b> Japan     |
|                     |                                 | <b>Date of previous issue</b>    | 2025 February 27. | <b>Language</b> ENGLISH |
|                     |                                 | <b>Original preparation date</b> | 12/2/2019         | (ENGLISH)               |

## 15. Regulatory information

| Ingredient name                    | % | Status | Reference number |
|------------------------------------|---|--------|------------------|
| None of the components are listed. |   |        |                  |

### Poisonous and Deleterious Substances

| Ingredient name                                  | %   | Status      | Reference number |
|--|-----|-------------|------------------|
| Lithium hydroxide and preparations containing it | 0.1 | Deleterious | 2-1-68-2         |

### Pollutant Release and Transfer Registers (PRTR)

None of the components are listed.

### Pollutant Release and Transfer Registers (PRTR)

None of the components are listed.

### Other regulations

|   |   |
|---|---|
| Australia inventory (AIIC)                  | All components are listed or exempted.  |
| Canada inventory                            | All components are listed or exempted.  |
| China inventory (IECSC)                     | All components are listed or exempted.  |
| Japan inventory (CSCL)                      | At least one component is not listed.   |
| Korea inventory (KECI)                      | At least one component is not listed.   |
| Philippines inventory (PICCS)               | All components are listed or exempted.  |
| Taiwan Chemical Substances Inventory (TCSI) | All components are listed or exempted.  |
| United States inventory (TSCA 8b)           | All components are active or exempted.  |
| REACH Status                                | For the REACH status of this product please consult your company contact, as identified in Section 1. |

## 16. Other information

### History

|                                |  |
|--------------------------------|--|
| Date of issue/Date of revision | 2025 September 29.   |
| Date of previous issue         | 2025 February 27.  |
| Prepared by                    | Product Stewardship  |
|                                | The Japan key to abbreviations is as follows:  |
|                                | GHS = Global Harmonized System   |
|                                | CAS Number = Chemical Abstracts Service Registry Number  |
|                                | ISHL = Industrial Safety and Health Law  |
|                                | OSHL = Occupational Safety and Health Law  |
|                                | PRTR = Law Concerning Reporting of the Release into the Environment of Specific Chemical Substances and Promoting Improvements in Their Management |
|                                | ENCS = Existing and New Chemical Substances  |
|                                | METI = Ministry of Economy, Trade and Industry   |
|                                | OEL = Occupational Exposure Limit  |
|                                | JSOH = Japan Society for Occupational Health   |
|                                | REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]                            |
|                                | TWA = Time weighted average  |

|                     |                                 |                                  |                   |                     |
|---------------------|---------------------------------|----------------------------------|-------------------|---------------------|
| <b>Product name</b> | Castrol High Temperature Grease | <b>Product code</b>              | 467200-SG01       | Page: 13/14         |
| <b>Version</b>      | 3                               | <b>Date of issue</b>             | 2025 September 29 | <b>Format Japan</b> |
|                     |                                 | <b>Date of previous issue</b>    | 2025 February 27. | <b>Language</b>     |
|                     |                                 | <b>Original preparation date</b> | 12/2/2019         | <b>ENGLISH</b>      |
|                     |                                 |                                  | Build 6.2         | <b>(ENGLISH)</b>    |
|                     |                                 |                                  | <b>(Japan)</b>    |                     |

## 16. Other information

STEL = Short term exposure limit

IMDG = International Maritime Organization Rules, rules governing shipment of goods by water.

IATA = International Air Transport Association, the organization

UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods.

Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

### [Procedure used to derive the classification](#)

| Classification  | Justification |
|-----------------|---------------|
| Not classified. |               |

📌 Indicates information that has changed from previously issued version.

### [Notice to reader](#)

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

|                     |                                 |                                  |                     |                     |                         |
|---------------------|---------------------------------|----------------------------------|---------------------|---------------------|-------------------------|
| <b>Product name</b> | Castrol High Temperature Grease |                                  | <b>Product code</b> | 467200-SG01         | Page: 14/14             |
| <b>Version</b>      | 3                               | <b>Date of issue</b>             | 2025 September 29   | <b>Format Japan</b> | <b>Language</b> ENGLISH |
|                     |                                 | <b>Date of previous issue</b>    | 2025 February 27.   | Build 6.2 (Japan)   | (ENGLISH)               |
|                     |                                 | <b>Original preparation date</b> | 12/2/2019           |                     |                         |