

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name	Techniclean MP
UFI:	21G1-F0QT-F00C-DACU
Product code	451317-FR01
SDS #	451317
Product type	Liquid.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Use of lubricants and greases in open systems-Industrial
Use of lubricants and greases in open systems-Professional
Handling and dilution of metal working fluid concentrates-Industrial

Use of the substance/ mixture	Cleaner. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
--	---

1.3 Details of the supplier of the safety data sheet

Supplier	Lubricants UK Limited, Chertsey Road, Sunbury On Thames, Middlesex, TW16 7BP
E-mail address	+44 (0)345 600 8125 MSDSadvice@bp.com

1.4 Emergency telephone number

EMERGENCY TELEPHONE NUMBER	Carechem: +44 (0) 1235 239 670 (24/7)
---------------------------------------	---------------------------------------

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition	Mixture
Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]	

Skin Irrit. 2, H315
Eye Dam. 1, H318

Additional information CLP: Not classified as hazardous when diluted below 5%

See Section 16 for the full text of the H statements declared above.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements

UFI:	21G1-F0QT-F00C-DACU
Hazard pictograms	



Signal word	Danger
Hazard statements	H315 - Causes skin irritation. H318 - Causes serious eye damage.

Precautionary statements

Product name Techniclean MP	Product code 451317-FR01	Page: 1/19
Version 9	Date of issue 28 December 2023	Format United Kingdom (UK) (United Kingdom)
Date of previous issue 2 December 2022.		Language ENGLISH

SECTION 2: Hazards identification

Prevention	P280 - Wear protective gloves. Wear eye or face protection. P264 - Wash hands thoroughly after handling.
Response	P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.
Storage	Not applicable.
Disposal	Not applicable.
Hazardous ingredients	Potassium hydroxide 3,5,5-trimethylhexanoic acid
Supplemental label elements	Not applicable.

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Not applicable.
---	-----------------

Special packaging requirements

Containers to be fitted with child-resistant fastenings	Not applicable.
Tactile warning of danger	Not applicable.

2.3 Other hazards

Results of PBT and vPvB assessment	Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	Defatting to the skin. This product contains complex ionic mixtures within the fluid matrix which are an intrinsic part of the product and cannot be separated from the fluid matrix. Toxicology testing has shown the ionic-mixture containing products exhibit skin and eye irritation properties that are notably attenuated when compared to the individual acid and base components.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product definition Mixture
Alkalis and additives in aqueous solution.

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Potassium carbonate	REACH #: 01-2119532646-36 EC: 209-529-3 CAS: 584-08-7	≤10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335	-	[1]
Potassium hydroxide	REACH #: 01-2119487136-33 EC: 215-181-3 CAS: 1310-58-3 Index: 019-002-00-8	≤10	Met. Corr. 1, H290 Acute Tox. 4, H302 Skin Corr. 1A, H314 Eye Dam. 1, H318	ATE [Oral] = 500 mg/kg Skin Corr. 1A, H314: C ≥ 5% Skin Corr. 1B, H314: 2% ≤ C < 5% Skin Irrit. 2, H315: 0.5% ≤ C < 2% Eye Dam. 1, H318: C ≥ 2% Eye Irrit. 2, H319: 0.5% ≤ C < 2%	[1] [2]
nitrilotrimethylenetris	REACH #:	≤10	Met. Corr. 1, H290	-	[1]

Product name Techniclean MP	Product code 451317-FR01	Page: 2/19
Version 9	Date of issue 28 December 2023	Format United Kingdom (UK)
Date of previous issue 2 December 2022.	Language ENGLISH	(United Kingdom)

SECTION 3: Composition/information on ingredients

(phosphonic acid)	01-2119487988-08 EC: 229-146-5 CAS: 6419-19-8		Eye Irrit. 2, H319	
3,5,5-trimethylhexanoic acid	REACH #: 01-2119517580-45 EC: 221-975-0 CAS: 3302-10-1	≤5	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318	ATE [Oral] = 500 mg/ [1] kg
undecanedioic acid	REACH #: 01-2119983505-29 EC: 217-440-6 CAS: 1852-04-6	≤3	Eye Irrit. 2, H319	- [1]
Alcohols, C8-10, ethers with polyethylene-polypropylene glycol monobenzyl ether	CAS: 68154-99-4	≤3	Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Dam. 1, H318	ATE [Dermal] = 1100 [1] mg/kg

See Section 16 for the full text of the H statements declared above.

Type

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Chemical burns must be treated promptly by a physician. Get medical attention immediately.

Skin contact

Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention.

Inhalation

If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.

Ingestion

Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Wash out mouth with water if person is conscious. Get medical attention if symptoms occur.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Potential acute health effects

Inhalation

May give off gas, vapour or dust that is very irritating or corrosive to the respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure. May cause irritation to eyes, nose and throat due to exposure to vapour, mists or fumes.

Ingestion

Irritating to mouth, throat and stomach.

Skin contact

Causes skin irritation. Defatting to the skin.

Eye contact

Causes serious eye damage.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation

Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

Ingestion

Ingestion of large quantities may cause nausea and diarrhoea.

Skin contact

Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

Eye contact

Potential risk of transient stinging or redness if accidental eye contact occurs.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

Treatment should in general be symptomatic and directed to relieving any effects. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Product name Techniclean MP	Product code 451317-FR01	Page: 3/19
Version 9	Date of issue 28 December 2023	Format United Kingdom (UK)
Date of previous issue 2 December 2022.	Language ENGLISH	(United Kingdom)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.

Unsuitable extinguishing media

Do not use water jet. The use of a water jet may cause the fire to spread by splashing the burning product.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products

Combustion products may include the following:
 carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)
 metal oxide/oxides
 nitrogen oxides (NO, NO₂ etc.)
 phosphorus oxides

5.3 Advice for firefighters

Special precautions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Do not breathe vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment.

For emergency responders

Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

See Section 1 for emergency contact information.
 See Section 5 for firefighting measures.
 See Section 8 for information on appropriate personal protective equipment.
 See Section 12 for environmental precautions.
 See Section 13 for additional waste treatment information.

Product name	Techniclean MP	Product code	451317-FR01	Page:	4/19
Version	9	Date of issue	28 December 2023	Format	United Kingdom (UK) (United Kingdom)
Date of previous issue	2 December 2022.			Language	ENGLISH

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment. Do not breathe vapour or mist. Do not ingest. Avoid contact of spilt material and runoff with soil and surface waterways. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Empty containers retain product residue and can be hazardous. Use only with adequate ventilation. Do not get in eyes, on skin or on clothing.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 5 to 40°C (41 to 104°F). Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Store locked up. Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/containers designed for use with this product. Do not store in unlabelled containers.

7.3 Specific end use(s)

Recommendations

See section 1.2 and Exposure scenarios in annex, if applicable.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name

Exposure limit values

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Recommended monitoring procedures

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived No Effect Level

Product/ingredient name	Type	Exposure	Value	Population	Effects	
5,5-trimethylhexanoic acid	DNEL	Long term Inhalation	-	4.4 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	-	10 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	-	10 mg/m ³	Workers	Local
	DNEL	Long term Dermal	-	1.25 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	-	1.1 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	-	5 mg/m ³	General population	Local
	DNEL	Short term Inhalation	-	5 mg/m ³	General population	Local
	DNEL	Long term Dermal	-	0.6 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	-	0.6 mg/kg bw/day	General population	Systemic
undecanedioic acid	DNEL	Long term Inhalation	-	70 mg/m ³	Workers	Systemic

SECTION 8: Exposure controls/personal protection

	DNEL	Long term Dermal -	10 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation -	17.4 mg/m ³	General population	Systemic
	DNEL	Long term Dermal -	5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral -	5 mg/kg bw/day	General population	Systemic

Predicted No Effect Concentration

Product/ingredient name	Compartment Detail	Value	Method Detail	
5,5-trimethylhexanoic acid	Fresh water	0.068 mg/l	-	
	Marine water	0.007 mg/l	-	
	Sewage Treatment Plant	23 mg/l	-	
	Fresh water sediment	1.08 mg/kg dwt	-	
	Marine water sediment	0.108 mg/kg dwt	-	
	Soil	0.176 mg/kg dwt	-	
	undecanedioic acid	Fresh water	0.039 mg/l	-
		Marine water	0.004 mg/l	-
		Sewage Treatment Plant	10 mg/l	-
		Fresh water sediment	0.064 mg/kg dwt	-
Marine water sediment		0.006 mg/kg dwt	-	
Soil		0.047 mg/kg dwt	-	

8.2 Exposure controls

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

Use with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Recommended: half-face mask - inorganic gases/vapor filter (Type B) - particulate filter. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Eye/face protection

Chemical splash goggles.

Skin protection

Hand protection

General Information:

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Wear suitable gloves. Recommended: Butyl gloves.

Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It

Product name Techniclean MP	Product code 451317-FR01	Page: 6/19
Version 9	Date of issue 28 December 2023	Format United Kingdom (UK)
Date of previous issue 2 December 2022.	Language ENGLISH	(United Kingdom)

SECTION 8: Exposure controls/personal protection

is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained.

If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.

It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

Glove Thickness:

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

Skin and body

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Refer to standards:

- Respiratory protection: EN 529
- Gloves: EN 420, EN 374
- Eye protection: EN 166
- Filtering half-mask: EN 149
- Filtering half-mask with valve: EN 405
- Half-mask: EN 140 plus filter
- Full-face mask: EN 136 plus filter
- Particulate filters: EN 143
- Gas/combined filters: EN 14387

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Product name	Techniclean MP	Product code	451317-FR01	Page:	7/19
Version	9	Date of issue	28 December 2023	Format	United Kingdom (UK) (United Kingdom)
Date of previous issue	2 December 2022.			Language	ENGLISH

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Physical state	Liquid.
Colour	Yellow. [Light]
Odour	Not available.
Odour threshold	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	100°C (212°F)
Flammability	Not available.
Lower and upper explosion limit	Not available.
Flash point	Closed cup: Not applicable. [Water content interferes with flash point determination.]
Auto-ignition temperature	

Ingredient name	°C	°F	Method
2,2',2"-nitrioltriethanol	324	615.2	

Decomposition temperature	Not available.
pH	10.2 [Conc. (% w/w): 2%]
Kinematic viscosity	Not available.
Solubility	

Media	Result
water	Soluble

Partition coefficient n-octanol/water (log value)	Not applicable.
--	-----------------

Vapour pressure	Vapour Pressure at 20°C		Vapour pressure at 50°C			
	mm Hg	kPa	Method	mm Hg	kPa	Method
Water	23.8	3.2				
nitrioltrimethylenetris (phosphonic acid)	0	0				
2,2',2"-nitrioltriethanol	<0.0075	<0.001				
sodium hydrogencarbonate	0.5	0.067	EU A.4			
undecanedioic acid	<0.075	<0.01	OECD 104			

Density and/or Relative density	>1000 kg/m ³ (>1 g/cm ³) at 15°C
--	---

Relative vapour density	Not available.
--------------------------------	----------------

Particle characteristics	
Median particle size	Not applicable.

9.2 Other information

Evaporation rate	Not available.
-------------------------	----------------

Explosive properties	Not available.
-----------------------------	----------------

Oxidising properties	Not available.
-----------------------------	----------------

SECTION 10: Stability and reactivity

10.1 Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
------------------------	---

10.2 Chemical stability	The product is stable.
--------------------------------	------------------------

10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
--	---

10.4 Conditions to avoid	High temperatures
---------------------------------	-------------------

Product name Techniclean MP	Product code 451317-FR01	Page: 8/19
Version 9	Date of issue 28 December 2023	Format United Kingdom (UK)
Date of previous issue 2 December 2022.		Language ENGLISH
		(United Kingdom)

SECTION 10: Stability and reactivity

10.5 Incompatible materials Reactive or incompatible with the following materials: oxidising materials.
Slightly reactive or incompatible with the following materials: acids.

10.6 Hazardous decomposition products Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Techniclean MP	N/A	110132.0	N/A	N/A	N/A
Potassium hydroxide	500	N/A	N/A	N/A	N/A
3,5,5-trimethylhexanoic acid	500	N/A	N/A	N/A	N/A
Alcohols, C8-10, ethers with polyethylene-polypropylene glycol monobenzyl ether	2500	1100	N/A	N/A	N/A

Information on likely routes of exposure Routes of entry anticipated: Dermal, Inhalation, Eyes.

Potential acute health effects

Inhalation May give off gas, vapour or dust that is very irritating or corrosive to the respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure. May cause irritation to eyes, nose and throat due to exposure to vapour, mists or fumes.

Ingestion Irritating to mouth, throat and stomach.

Skin contact Causes skin irritation. Defatting to the skin.

Eye contact Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation No specific data.

Ingestion Adverse symptoms may include the following:
stomach pains

Skin contact Adverse symptoms may include the following:
pain or irritation
redness
dryness
cracking
blistering may occur

Eye contact Adverse symptoms may include the following:
pain
watering
redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

Ingestion Ingestion of large quantities may cause nausea and diarrhoea.

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs.

Potential chronic health effects

General No known significant effects or critical hazards.

Carcinogenicity No known significant effects or critical hazards.

Mutagenicity No known significant effects or critical hazards.

Developmental effects No known significant effects or critical hazards.

Fertility effects No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Product name Techniclean MP	Product code 451317-FR01	Page: 9/19
Version 9	Date of issue 28 December 2023	Format United Kingdom (UK)
Date of previous issue 2 December 2022.	Language ENGLISH	(United Kingdom)

SECTION 11: Toxicological information

Remarks - Endocrine disruptor - Health Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Environmental hazards Not classified as dangerous

12.2 Persistence and degradability

Expected to be biodegradable.

12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) Not available.

Mobility Liquid. Soluble in water.

12.5 Results of PBT and vPvB assessment

Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.

12.6 Endocrine disrupting properties Not available.

Remarks - Endocrine disruptor - Environment Not available.

12.7 Other adverse effects No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Hazardous waste Yes.

European waste catalogue (EWC)

Waste code	Waste designation
12 03 01*	aqueous washing liquids

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

Packaging

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Waste code	European waste catalogue (EWC)
15 01 10*	packaging containing residues of or contaminated by hazardous substances

Special precautions

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Empty containers represent a fire hazard as they may contain flammable product residues and vapour. Never weld, solder or braze empty containers. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

References

Commission 2014/955/EU
Directive 2008/98/EC

Product name Techniclean MP	Product code 451317-FR01	Page: 10/19
Version 9	Date of issue 28 December 2023	Format United Kingdom (UK) (United Kingdom)
Date of previous issue 2 December 2022.		Language ENGLISH

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	Remarks Corrosive to metals

14.6 Special precautions for user Not available.

14.7 Maritime transport in bulk according to IMO instruments Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Not applicable.

Other regulations

REACH Status The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

United States inventory (TSCA 8b) All components are active or exempted.

Australia inventory (AIC) All components are listed or exempted.

Canada inventory All components are listed or exempted.

China inventory (IECSC) All components are listed or exempted.

Japan inventory (CSCL) At least one component is not listed.

Korea inventory (KECI) All components are listed or exempted.

Philippines inventory (PICCS) All components are listed or exempted.

Taiwan Chemical Substances Inventory (TCSI) All components are listed or exempted.

Ozone depleting substances (1005/2009/EU)

Not listed.

Product name Techniclean MP	Product code 451317-FR01	Page: 11/19
Version 9	Date of issue 28 December 2023	Format United Kingdom (UK) (United Kingdom)
Date of previous issue 2 December 2022.		Language ENGLISH

SECTION 15: Regulatory information

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

EU - Water framework directive - Priority substances

None of the components are listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

SECTION 16: Other information

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 CAS = Chemical Abstracts Service
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 CSA = Chemical Safety Assessment
 CSR = Chemical Safety Report
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EINECS = European Inventory of Existing Commercial chemical Substances
 ES = Exposure Scenario
 EUH statement = CLP-specific Hazard statement
 EWC = European Waste Catalogue
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 OECD = Organisation for Economic Co-operation and Development
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
 RRN = REACH Registration Number
 SADT = Self-Accelerating Decomposition Temperature
 SVHC = Substances of Very High Concern
 STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
 STOT-SE = Specific Target Organ Toxicity - Single Exposure
 TWA = Time weighted average
 UN = United Nations
 UVCB = Complex hydrocarbon substance
 VOC = Volatile Organic Compound
 vPvB = Very Persistent and Very Bioaccumulative
 Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4 / RRN 01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN 01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN 01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN 01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN 01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8, 64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 / RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN 01-2119474889-13

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Product name	Techniclean MP	Product code	451317-FR01	Page:	12/19
Version	9	Date of issue	28 December 2023	Format	United Kingdom (UK)
Date of previous issue	2 December 2022.		Language	ENGLISH	
			(United Kingdom)		

SECTION 16: Other information

Classification	Justification
Skin Irrit. 2, H315 Eye Dam. 1, H318	Expert judgment Calculation method

Full text of abbreviated H statements	H290 H301 H302 H311 H312 H314 H315 H317 H318 H319 H331 H335 H341 H350	May be corrosive to metals. Toxic if swallowed. Harmful if swallowed. Toxic in contact with skin. Harmful in contact with skin. Causes severe skin burns and eye damage. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Toxic if inhaled. May cause respiratory irritation. Suspected of causing genetic defects. May cause cancer.
Full text of classifications [CLP/GHS]	Acute Tox. 3 Acute Tox. 4 Carc. 1B Eye Dam. 1 Eye Irrit. 2 Met. Corr. 1 Muta. 2 Skin Corr. 1A Skin Corr. 1B Skin Irrit. 2 Skin Sens. 1 STOT SE 3	ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4 CARCINOGENICITY - Category 1B SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 CORROSIVE TO METALS - Category 1 GERM CELL MUTAGENICITY - Category 2 SKIN CORROSION/IRRITATION - Category 1A SKIN CORROSION/IRRITATION - Category 1B SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

History

Date of issue/ Date of revision	28/12/2023.
Date of previous issue	02/12/2022.
Prepared by	Product Stewardship

 **Indicates information that has changed from previously issued version.**

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Techniclean MP	Product code 451317-FR01	Page: 13/19
Version 9	Date of issue 28 December 2023	Format United Kingdom (UK) (United Kingdom)
Date of previous issue 2 December 2022.		Language ENGLISH

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition	Mixture
Code	451317-FR01
Product name	Techniclean MP

Section 1: Title

Short title of the exposure scenario	Use of lubricants and greases in open systems - Industrial
List of use descriptors	<p>Identified use name: Use of lubricants and greases in open systems-Industrial</p> <p>Process Category: PROC01, PROC02, PROC07, PROC08b, PROC09, PROC10, PROC13</p> <p>Sector of end use: SU03</p> <p>Subsequent service life relevant for that use: No.</p> <p>Environmental Release Category: ERC04</p> <p>Specific Environmental Release Category: ATIEL-ATC SPERC 4.Ci.v1</p>

Processes and activities covered by the exposure scenario	Covers use of lubricants and greases in open systems, including application of lubricant to work pieces or equipment by dipping, brushing or spraying (without exposure to heat), e.g. mould releases, corrosion protection, slideways. Includes associated product storage, material transfers, sampling and maintenance activities.
--	---

Section 2 Operational conditions and risk management measures

Section 2.1 Control of worker exposure

Product characteristics:

Physical state:	Liquid, vapour pressure < 0.5 kPa
Concentration of substance in product:	Covers use of substance/product up to 100 % (unless stated differently)
Frequency and duration of use:	Covers daily exposures up to 8 hours
Other conditions affecting workers exposure:	Assumes use at not more than 20°C above ambient temperature. Assumes a good basic standard of occupational hygiene is implemented

Contributing scenarios: Operational conditions and risk management measures

The following information provides minimum risk management measures for the contributing scenarios identified within this lubricant use group. However, more detailed information on control measures e.g. specific glove types may be documented in Section 8 of the main body of this safety data sheet.

Please review Section 8 in conjunction with the information on this Generic Exposure Scenario.

General measures applicable to all activities:

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying.

Material transfers Manual:

Avoid carrying out activities involving exposure for more than 1 hour per day.

Material transfers Automated process with (semi) closed systems:

Ensure material transfers are under containment or extract ventilation.

Roller, spreader, flow application:

Provide extract ventilation to points where emissions occur.

Spraying:

Carry out in a vented booth or extracted enclosure.

Treatment by dipping and pouring:

Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

Techniclean MP

Use of lubricants and greases in open systems - Industrial

Equipment cleaning and maintenance:

Drain down system prior to equipment break-in or maintenance. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training. Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Storage:

Store substance within a closed system.

Section 2.2: Control of environmental exposure

No exposure scenario is presented because the product is not classified for the Environment

Section 3: Exposure estimation and reference to its source

Exposure estimation and reference to its source - Environment

Exposure assessment (environment):

No exposure scenario is presented because the product is not classified for the Environment

Exposure estimation and reference to its source - Workers

Exposure assessment (human):

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 4: Guidance to check compliance with the exposure scenario

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.ATIEL.org/REACH_GES

Health

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Annex to the extended Safety Data Sheet (eSDS)

Professional

Identification of the substance or mixture

Product definition	Mixture
Code	451317-FR01
Product name	Techniclean MP

Section 1: Title

Short title of the exposure scenario	Use of lubricants and greases in open systems - Professional
List of use descriptors	<p>Identified use name: Use of lubricants and greases in open systems-Professional</p> <p>Process Category: PROC01, PROC02, PROC08a, PROC10, PROC11, PROC13</p> <p>Sector of end use: SU22</p> <p>Subsequent service life relevant for that use: No.</p> <p>Environmental Release Category: ERC08a, ERC08d</p> <p>Specific Environmental Release Category: ATIEL-ATC SPERC 8.Cp.v1</p>

Processes and activities covered by the exposure scenario	Covers use of lubricants and greases in open systems, including application of lubricant to work pieces or equipment by dipping, brushing or spraying (without exposure to heat), e.g. mould releases, corrosion protection, slideways. Includes associated product storage, material transfers, sampling and maintenance activities.
--	---

Section 2 Operational conditions and risk management measures

Section 2.1 Control of worker exposure

Product characteristics:

Physical state:	Liquid, vapour pressure < 0.5 kPa
Concentration of substance in product:	Covers use of substance/product up to 100 % (unless stated differently)
Frequency and duration of use:	Covers daily exposures up to 8 hours
Other conditions affecting workers exposure:	Assumes use at not more than 20°C above ambient temperature. Assumes a good basic standard of occupational hygiene is implemented

Contributing scenarios: Operational conditions and risk management measures

General measures applicable to all activities:

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Use suitable eye protection. Avoid direct eye contact with product also via contamination on hands.

Material transfers Manual:

Avoid carrying out activities involving exposure for more than 1 hour per day.

Roller, spreader, flow application:

Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Avoid carrying out activities involving exposure for more than 4 hours per day. Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

Spraying:

Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Avoid carrying out activities involving exposure for more than 1 hour per day. Wear a respirator conforming to EN140 with type A/P2 filter or better. Wear suitable coveralls to prevent exposure to the skin. Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

Treatment by dipping and pouring:

Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Equipment cleaning and maintenance:

Drain down system prior to equipment break-in or maintenance. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Avoid carrying out activities involving exposure for more than 4 hours per day. Retain drain-downs in sealed storage pending disposal or for subsequent

Techniclean MP

Use of lubricants and greases in open systems - Professional

recycle.

Storage:

Store substance within a closed system.

Section 2.2: Control of environmental exposure

No exposure scenario is presented because the product is not classified for the Environment

Section 3: Exposure estimation and reference to its source

Exposure estimation and reference to its source - Environment

Exposure assessment (environment):

No exposure scenario is presented because the product is not classified for the Environment

Exposure estimation and reference to its source - Workers

Exposure assessment (human):

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 4: Guidance to check compliance with the exposure scenario

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.ATIEL.org/REACH_GES

Health

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition	Mixture
Code	451317-FR01
Product name	Techniclean MP

Section 1: Title

Short title of the exposure scenario	Handling and dilution of metal working fluid concentrates - Industrial
List of use descriptors	<p>Identified use name: Handling and dilution of metal working fluid concentrates-Industrial</p> <p>Process Category: PROC01, PROC02, PROC08b, PROC05</p> <p>Sector of end use: SU03</p> <p>Subsequent service life relevant for that use: No.</p> <p>Environmental Release Category: ERC02</p> <p>Specific Environmental Release Category: ATIEL-ATC SPERC 2.Ei.v1</p>

Processes and activities covered by the exposure scenario	Handling and dilution of metal working fluid concentrates. Includes associated product storage, material transfers, sampling and maintenance activities.
--	--

Section 2 Operational conditions and risk management measures

Section 2.1 Control of worker exposure

Product characteristics:

Physical state:	Liquid, vapour pressure < 0.5 kPa
Concentration of substance in product:	Covers use of substance/product up to 100 % (unless stated differently)
Frequency and duration of use:	Covers daily exposures up to 8 hours
Other conditions affecting workers exposure:	Assumes use at not more than 20°C above ambient temperature. Assumes a good basic standard of occupational hygiene is implemented

Contributing scenarios: Operational conditions and risk management measures

General measures applicable to all activities:
Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Use suitable eye protection. Avoid direct eye contact with product also via contamination on hands.

Filling of equipment from drums or containers:
Avoid carrying out activities involving exposure for more than 4 hours per day.

Process sampling:
Avoid carrying out activities involving exposure for more than 4 hours per day.

Equipment cleaning and maintenance:
Drain down system prior to equipment break-in or maintenance. Avoid carrying out activities involving exposure for more than 4 hours per day. Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Storage:
Store substance within a closed system.

Section 2.2: Control of environmental exposure

No exposure scenario is presented because the product is not classified for the Environment

Section 3: Exposure estimation and reference to its source

Exposure estimation and reference to its source - Environment

Exposure assessment (environment):

No exposure scenario is presented because the product is not classified for the Environment

Exposure estimation and reference to its source - Workers

Exposure assessment (human):

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 4: Guidance to check compliance with the exposure scenario

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.ATIEL.org/REACH_GES

Health

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.