

# SAFETY DATA SHEET



Castrol Transmax CVT

## Section 1. Identification

**GHS product identifier** Castrol Transmax CVT  
**Product type** Liquid.  
**Product code** 467204-MY01  
**SDS no.** 467204

### Relevant identified uses of the substance or mixture and uses advised against

**Product use** Automatic transmission fluid  
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

**Supplier** Castrol Singapore Pte. Limited (202034037D)  
7 Straits View  
Marina One East Tower  
#26-01, Singapore 018936

**EMERGENCY TELEPHONE NUMBER** Toll Free : 800-120-7082  
Carechem: +65 3158 1074 (24/7)

## Section 2. Hazards identification

**Classification of the substance or mixture** Not classified.

### GHS label elements

**Signal word** No signal word.  
**Hazard statements** No known significant effects or critical hazards.  
**Precautionary statements**  
**Prevention** Not applicable.  
**Response** Not applicable.  
**Storage** Not applicable.  
**Disposal** Not applicable.

**Other hazards which do not result in classification** Defatting to the skin.

## Section 3. Composition/information on ingredients

**Substance/mixture** Mixture  
Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

**Product name** Castrol Transmax CVT **Product code** 467204-MY01 **Page:** 1/10  
**Version** 7.01 **Date of issue** 02/22/2024. **Format** Singapore **Language** ENGLISH  
**(Singapore)** **(ENGLISH)**

## Section 3. Composition/information on ingredients

Ingredient name	%	CAS number
Distillates (petroleum), hydrotreated light paraffinic	≥50 - ≤75	64742-55-8
Distillates (petroleum), hydrotreated heavy paraffinic	≥25 - ≤50	64742-54-7
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	≤3	72623-86-0
Distillates (petroleum), hydrotreated light paraffinic	≤3	64742-55-8
dimantine	≤0.3	124-28-7
2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	<0.1	95-38-5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

<b>Eye contact</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
<b>Inhalation</b>	In case of inhalation of decomposition products in a fire, symptoms may be delayed. If inhaled, remove to fresh air. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.
<b>Skin contact</b>	Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.
<b>Ingestion</b>	Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

### Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

### Indication of immediate medical attention and special treatment needed, if necessary

<b>Notes to physician</b>	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Treatment should in general be symptomatic and directed to relieving any effects.
<b>Specific treatments</b>	No specific treatment.
<b>Protection of first-aiders</b>	No action shall be taken involving any personal risk or without suitable training.

## Section 5. Firefighting measures

### Extinguishing media

<b>Suitable extinguishing media</b>	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
<b>Unsuitable extinguishing media</b>	Do not use water jet.

### Specific hazards arising from the chemical

<b>Hazardous thermal decomposition products</b>	In a fire or if heated, a pressure increase will occur and the container may burst. Combustion products may include the following: carbon oxides (CO, CO <sub>2</sub> ) (carbon monoxide, carbon dioxide) nitrogen oxides (NO, NO <sub>2</sub> etc.)
---	---

<b>Product name</b> Castrol Transmax CVT	<b>Product code</b> 467204-MY01	<b>Page:</b> 2/10	
<b>Version</b> 7.01	<b>Date of issue</b> 02/22/2024.	<b>Format</b> Singapore	<b>Language</b> ENGLISH
		<b>(Singapore)</b>	<b>(ENGLISH)</b>

## Section 5. Firefighting measures

### Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

### Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

#### For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and material for containment and cleaning up

#### Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

## Section 7. Handling and storage

### Precautions for safe handling

#### Protective measures

Put on appropriate personal protective equipment (see Section 8).

#### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

#### Not suitable

Prolonged exposure to elevated temperature

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

##### Ingredient name

##### Exposure limits

Distillates (petroleum), hydrotreated light paraffinic

**Workplace Safety and Health Act (Singapore). [Oil Mist, mineral]**

PEL (long term): 5 mg/m<sup>3</sup> 8 hours. Issued/Revised: 1/1997 Form: Mist

PEL (short term): 10 mg/m<sup>3</sup> 15 minutes. Issued/Revised: 1/1997 Form: Mist

Distillates (petroleum), hydrotreated heavy paraffinic

**Workplace Safety and Health Act (Singapore). [Oil Mist, mineral]**

PEL (long term): 5 mg/m<sup>3</sup> 8 hours. Issued/Revised: 1/1997 Form: Mist

PEL (short term): 10 mg/m<sup>3</sup> 15 minutes. Issued/Revised: 1/1997 Form: Mist

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

**Workplace Safety and Health Act (Singapore). [Oil Mist, mineral]**

PEL (long term): 5 mg/m<sup>3</sup> 8 hours. Issued/Revised: 1/1997 Form: Mist

PEL (short term): 10 mg/m<sup>3</sup> 15 minutes. Issued/Revised: 1/1997 Form: Mist

Distillates (petroleum), hydrotreated light paraffinic

**Workplace Safety and Health Act (Singapore). [Oil Mist, mineral]**

PEL (long term): 5 mg/m<sup>3</sup> 8 hours. Issued/Revised: 1/1997 Form: Mist

PEL (short term): 10 mg/m<sup>3</sup> 15 minutes. Issued/Revised: 1/1997 Form: Mist

#### Biological exposure indices

No exposure indices known.

#### Recommended monitoring procedures

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

#### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

**Product name** Castrol Transmax CVT

**Product code** 467204-MY01 **Page:** 4/10

**Version** 7.01 **Date of issue** 02/22/2024.

**Format** Singapore

**Language** ENGLISH

(Singapore)

(ENGLISH)

## Section 8. Exposure controls/personal protection

### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### Eye/face protection

Safety glasses with side shields.

### Skin protection

#### Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

#### Skin protection

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

### Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

#### Physical state

Liquid.

#### Colour

Red. [Light]

#### Odour

Not available.

#### Odour threshold

Not available.

#### pH

Not applicable.

#### Melting point/freezing point

Not available.

#### Boiling point, initial boiling point, and boiling range

Not available.

#### Flash point

Closed cup: 200.5°C (392.9°F) [Pensky-Martens]  
Open cup: 214°C (417.2°F) [Cleveland]

#### Evaporation rate

Not available.

#### Flammability

Not applicable. Based on - Physical state

#### Lower and upper explosion limit/flammability limit

Not available.

#### Vapour pressure

**Product name** Castrol Transmax CVT

**Product code** 467204-MY01 **Page:** 5/10

**Version** 7.01 **Date of issue** 02/22/2024.

**Format** Singapore

**Language** ENGLISH

(Singapore)

(ENGLISH)

## Section 9. Physical and chemical properties

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Distillates (petroleum), hydrotreated light paraffinic	<0.08	<0.011	ASTM D 5191			
Distillates (petroleum), hydrotreated heavy paraffinic	<0.08	<0.011	ASTM D 5191			
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	<0.08	<0.011	ASTM D 5191			
Distillates (petroleum), hydrotreated light paraffinic	<0.08	<0.011	ASTM D 5191			

**Relative vapour density**

Not available.

**Relative density**

Not available.

**Density**

<1000 kg/m<sup>3</sup> (<1 g/cm<sup>3</sup>) at 15°C

**Solubility(ies)**

Media	Result
water	Not soluble

**Partition coefficient: n-octanol/water**

Not applicable.

**Auto-ignition temperature**

Not available.

**Decomposition temperature**

Not available.

**Viscosity**

Kinematic: 34.2 mm<sup>2</sup>/s (34.2 cSt) at 40°C  
Kinematic: 7.152 mm<sup>2</sup>/s (7.152 cSt) at 100°C

**Particle characteristics**

**Median particle size**

Not applicable.

## Section 10. Stability and reactivity

**Reactivity**

No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.

**Chemical stability**

The product is stable.

**Possibility of hazardous reactions**

Under normal conditions of storage and use, hazardous reactions will not occur.  
Under normal conditions of storage and use, hazardous polymerisation will not occur.

**Conditions to avoid**

Avoid all possible sources of ignition (spark or flame).

**Incompatible materials**

Reactive or incompatible with the following materials: oxidising materials.

**Hazardous decomposition products**

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**Product name** Castrol Transmax CVT

**Product code** 467204-MY01 **Page:** 6/10

**Version** 7.01 **Date of issue** 02/22/2024.

**Format** Singapore

**Language** ENGLISH

(Singapore)

(ENGLISH)

## Section 11. Toxicological information

### Information on toxicological effects

#### Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	Category 2	oral	digestive system, thymus

#### Aspiration hazard

Name	Result
Distillates (petroleum), hydrotreated light paraffinic Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

### Information on likely routes of exposure

Routes of entry anticipated: Dermal, Inhalation, Eyes.

### Potential acute health effects

#### Eye contact

No known significant effects or critical hazards.

#### Inhalation

Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

#### Skin contact

Defatting to the skin. May cause skin dryness and irritation.

#### Ingestion

No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

#### Eye contact

No specific data.

#### Inhalation

May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.

#### Skin contact

Adverse symptoms may include the following:  
irritation  
dryness  
cracking

#### Ingestion

No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Eye contact

Potential risk of transient stinging or redness if accidental eye contact occurs.

#### Skin contact

Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

#### Ingestion

Ingestion of large quantities may cause nausea and diarrhoea.

### Potential chronic health effects

#### General

No known significant effects or critical hazards.

#### Carcinogenicity

No known significant effects or critical hazards.

#### Mutagenicity

No known significant effects or critical hazards.

#### Teratogenicity

No known significant effects or critical hazards.

#### Developmental effects

No known significant effects or critical hazards.

#### Fertility effects

No known significant effects or critical hazards.



## Section 12. Ecological information

### Toxicity

**Environmental effects** No known significant effects or critical hazards.

### Persistence/degradability

Not expected to be rapidly degradable.

### Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

### Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** Not available.

**Mobility** Spillages may penetrate the soil causing ground water contamination.

### Other ecological information

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

## Section 13. Disposal considerations

### Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	<b>ADR/RID</b>	<b>ADN</b>	<b>IMDG</b>	<b>IATA/ICAO</b>
<b>UN number</b>	Not regulated.	Not regulated.	Not regulated.	Not regulated.
<b>UN proper shipping name</b>	-	-	-	-
<b>Transport hazard class(es)</b>	-	-	-	-
<b>Packing group</b>	-	-	-	-
<b>Environmental hazards</b>	No.	No.	No.	No.
<b>Additional information</b>	-	-	-	-

**Special precautions for user** Not available.

**Product name** Castrol Transmax CVT

**Product code** 467204-MY01 **Page: 8/10**

**Version** 7.01 **Date of issue** 02/22/2024.

**Format** Singapore

**Language** ENGLISH

(Singapore)

(ENGLISH)



## Section 15. Regulatory information

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### **Safety, health and environmental regulations specific for the product**

No known specific national and/or regional regulations applicable to this product (including its ingredients).

### **Regulation according to other foreign laws**

#### **REACH Status**

For the REACH status of this product please consult your company contact, as identified in Section 1.

#### **United States inventory (TSCA 8b)**

All components are active or exempted.

#### **Australia inventory (AIC)**

All components are listed or exempted.

#### **Canada inventory**

All components are listed or exempted.

#### **China inventory (IECSC)**

All components are listed or exempted.

#### **Japan inventory (CSCL)**

All components are listed or exempted.

#### **Korea inventory (KECI)**

All components are listed or exempted.

#### **Philippines inventory (PICCS)**

All components are listed or exempted.

#### **Taiwan Chemical Substances Inventory (TCSI)**

All components are listed or exempted.

## Section 16. Other information

### History

**Date of issue/Date of revision** 2024 February 22

**Date of previous issue** 2023 October 10

**Version** 7.01

**Prepared by** Product Stewardship

### **Key to abbreviations**

ACGIH = American Conference of Industrial Hygienists  
CAS Number = Chemical Abstracts Service Registry Number  
GHS = Global Harmonised System  
IATA = International Air Transport Association, the organisation  
IMDG = International Maritime Organization Rules, rules governing shipment of goods by water.  
OEL = Occupational Exposure Limit  
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]  
SDS = Safety Data Sheet

**Product name** Castrol Transmax CVT

**Product code** 467204-MY01 **Page:** 9/10

**Version** 7.01 **Date of issue** 02/22/2024.

**Format** Singapore

**Language** ENGLISH

(Singapore)

(ENGLISH)

## Section 16. Other information

STEL = Short term exposure limit

TWA = Time weighted average

UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods.

Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

✔ Indicates information that has changed from previously issued version.

### Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

**Product name** Castrol Transmax CVT

**Product code** 467204-MY01 **Page:** 10/10

**Version** 7.01 **Date of issue** 02/22/2024.

**Format** Singapore

**Language** ENGLISH

(Singapore)

(ENGLISH)