# **SAFETY DATA SHEET**



#### Castrol Transmax Axle 85W-140

### **Section 1. Identification**

GHS product identifier Castrol Transmax Axle 85W-140

**Product code** 469574-TH01 **SDS no.** 469574

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/ Gear lubricant

mixture For specific application advice see appropriate Technical Data Sheet or consult our

company representative.

Manufacturer BP - Castrol (Thailand) Limited

Samut Sakon Industrial Estate, 39/77-78 Moo 2 Rama II Road,

Bangkachao Amphur Muang, Samut Sakorn 74000

Tel. +66 34 419666, Fax. +66 34 419666

Supplier BP - Castrol (Thailand) Limited

3 Rajanakarn Building, 23rd Floor South Sathon Road Yannawa, Sathon Bangkok 10120

Tel. +66 02 6843555, Fax. +66 02 684 3646

**EMERGENCY TELEPHONE** 

**NUMBER** 

Carechem: 001800 1 2066 6751 (tollfree, access from Thailand only)

### Section 2. Hazards identification

GHS Classification SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 3

**GHS** label elements

Signal word No signal word.

**Hazard statements** H402 - Harmful to aquatic life.

**Precautionary statements** 

General P102 - Keep out of reach of children.

P101 - If medical advice is needed, have product container or label at hand.

**Prevention** P273 - Avoid release to the environment.

Response Not applicable.
Storage Not applicable.

Disposal P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Other hazards which do not

result in classification

Defatting to the skin.

# Section 3. Composition/information on ingredients

Substance/mixture

Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Ingredient name	%	CAS number	
Residual oils (petroleum), solvent-dewaxed	≥25 - ≤50	64742-62-7	
Residual oils (petroleum), hydrotreated	≥25 - ≤50	64742-57-0	
Distillates (petroleum), hydrotreated heavy paraffinic	≤10	64742-54-7	
1-Propene, 2-methyl-, sulfurized	≤5	68511-50-2	
Amines, C12-14-alkyl, isooctyl phosphates	<1	68187-67-7	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Product nameCastrol Transmax Axle 85W-140Product code469574-TH01Page: 1/8Version 10.02Date of issue 29/07/2025.Format GHS - ThailandLanguage ENGLISHBuild 5.0.4(GHS - Thailand)(ENGLISH)

### Section 4. First aid measures

#### **Description of necessary first aid measures**

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. Never give

anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if adverse

health effects persist or are severe.

Skin contact Wash skin thoroughly with soap and water or use recognised skin cleanser.

Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur. If skin

irritation or rash occurs: Get medical advice/attention.

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for

and remove any contact lenses. Get medical attention.

#### Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

#### Indication of immediate medical attention and special treatment needed, if necessary

**Specific treatments** No specific treatment.

Notes to physician Treatment should in general be symptomatic and directed to relieving any effects.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training.

Use foam or all-purpose dry chemical to extinguish.

### Section 5. Firefighting measures

#### **Extinguishing media**

Suitable extinguishing

media

**Unsuitable extinguishing** 

media

Do not use water jet.

Specific hazards arising from the chemical

Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic

life.

Hazardous thermal decomposition products

Combustion products may include the following: carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)

**Special protective actions** 

for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Special protective

equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus

(SCBA) and full turnout gear.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

For emergency responders

Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

**Environmental precautions** 

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### Methods and material for containment and cleaning up

Product nameCastrol Transmax Axle 85W-140Product code469574-TH01Page: 2/8Version 10.02Date of issue 29/07/2025.Format GHS - ThailandLanguage ENGLISHBuild 5.0.4(GHS - Thailand)(ENGLISH)

### Section 6. Accidental release measures

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

## Section 7. Handling and storage

#### **Precautions for safe handling**

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Avoid contact of spilt material and runoff with soil and surface waterways.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. Contaminated work clothing should not be allowed out of the workplace. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Not suitable

Prolonged exposure to elevated temperature

# Section 8. Exposure controls/personal protection

### **Control parameters**

Occupational exposure limits

Ingredient name	Exposure limits
Residual oils (petroleum), solvent-dewaxed	ACGIH TLV (United States). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m³ 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction
Residual oils (petroleum), hydrotreated	ACGIH TLV (United States). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m³ 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction
Distillates (petroleum), hydrotreated heavy paraffinic	ACGIH TLV (United States). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m³ 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction

#### **Biological exposure indices**

No exposure indices known.

# Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained

Your supplier of personal protective equipment should be consulted for advice on

Product nameCastrol Transmax Axle 85W-140Product code469574-TH01Page: 3/8Version 10.02Date of issue 29/07/2025.Format GHS - ThailandLanguage ENGLISHBuild 5.0.4(GHS - Thailand)(ENGLISH)

### Section 8. Exposure controls/personal protection

selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

**Environmental exposure** controls

**Hand protection** 

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Eye protection Skin protection Safety glasses with side shields.

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Skin protection

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons

and/or impervious chemical suits and boots will be required.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

# Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Appearance**

Physical state
Colour
Amber.
Odour
Not available.
Odour threshold
Not applicable.
Melting point/freezing point
Boiling point, initial boiling
point, and boiling range
Liquid.
Amber.
Not available.
Not available.
Not available.

**Drop Point** Not available.

Flash point Open cup: 236°C (456.8°F) [Cleveland ASTM D 92]

Evaporation rate Not available.
Flammability Not available.
Lower and upper explosion Not available.

Vapour pressure

limit/flammability limit

Product name Castrol Transmax Axle 85W-140Product code469574-TH01Page: 4/8Version 10.02Date of issue 29/07/2025.Format GHS - ThailandLanguage ENGLISHBuild 5.0.4(GHS - Thailand)(ENGLISH)

### Section 9. Physical and chemical properties

	Vapour Pressure at 20°C		Vapour pressure at 50°C			
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
esidual oils (petroleum), solvent-dewaxed	<0.07501	<0.01	ASTM D 5191			
Residual oils (petroleum), hydrotreated	<0.07501	<0.01	ASTM D 5191			
Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191			

Relative vapour density Not available. Relative density Not available.

<1000 kg/m3 (<1 g/cm3) at 15°C **Density** 

Solubility(ies)

Media	Result
water	Not soluble

Partition coefficient: n-

octanol/water

Not applicable.

**Auto-ignition temperature** 

Not available. Not available.

**Decomposition temperature Viscosity** 

Kinematic: 367.3 mm<sup>2</sup>/s (367.3 cSt) at 40°C

Kinematic: 25 to 28 mm<sup>2</sup>/s (25 to 28 cSt) at 100°C

Particle characteristics

Median particle size : Not applicable.

### Section 10. Stability and reactivity

Reactivity No specific test data available for this product. Refer to Conditions to avoid and

Incompatible materials for additional information.

**Chemical stability** 

Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.

Conditions to avoid

Avoid all possible sources of ignition (spark or flame).

Incompatible materials

**Hazardous decomposition** 

products

Reactive or incompatible with the following materials: oxidising materials.

Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

The product is stable.

# Section 11. Toxicological information

#### Information on toxicological effects

Information on likely routes

of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Eve contact No known significant effects or critical hazards.

Inhalation Vapour inhalation under ambient conditions is not normally a problem due to low

vapour pressure.

Skin contact Defatting to the skin. May cause skin dryness and irritation.

Ingestion No known significant effects or critical hazards. Symptoms related to the physical, chemical and toxicological characteristics

Eve contact No specific data.

Inhalation May be harmful by inhalation if exposure to vapour, mists or fumes resulting from

thermal decomposition products occurs.

Skin contact Adverse symptoms may include the following:

> irritation dryness cracking

Product name Castrol Transmax Axle 85W-140 469574-TH01 Product code Page: 5/8 Language ENGLISH Version 10.02 Date of issue 29/07/2025. Format GHS - Thailand (GHS - Thailand) (ENGLISH) Build 5.0.4

### Section 11. Toxicological information

Ingestion No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs. Inhalation

Overexposure to the inhalation of airborne droplets or aerosols may cause irritation

of the respiratory tract.

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/

or dermatitis.

Ingestion Ingestion of large quantities may cause nausea and diarrhoea.

Potential chronic health effects

General No known significant effects or critical hazards. No known significant effects or critical hazards. Carcinogenicity Mutagenicity No known significant effects or critical hazards. No known significant effects or critical hazards. **Teratogenicity Developmental effects** No known significant effects or critical hazards. **Fertility effects** No known significant effects or critical hazards.

### Section 12. Ecological information

**Environmental effects** This material is harmful to aquatic life.

Persistence and degradability

Expected to be biodegradable.

**Bioaccumulative potential** 

This product is not expected to bioaccumulate through food chains in the environment.

**Mobility** Spillages may penetrate the soil causing ground water contamination.

Other adverse effects No known significant effects or critical hazards.

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms.

Oxygen transfer could also be impaired.

### Section 13. Disposal considerations

**Disposal methods** 

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	UN	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	•
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Special precautions for user Not available.

Product name Castrol Transmax Axle 85W-140 469574-TH01 Product code Page: 6/8 Language ENGLISH Version 10.02 Date of issue 29/07/2025. Format GHS - Thailand Build 5.0.4 (GHS - Thailand) (ENGLISH)

### **Section 14. Transport information**

Transport in bulk according Not available. to IMO instruments

### Section 15. Regulatory information

Regulation according to other foreign laws

Australia inventory (AIIC) All components are listed or exempted.

Canada inventory status At least one component is not listed in DSL but all such components are listed in

NDSL.

China inventory (IECSC) At least one component is not listed.

**REACH Status** For the REACH status of this product please consult your company contact, as

All components are listed or exempted.

identified in Section 1.

Not determined.

Japan inventory (CSCL) All components are listed or exempted. Korea inventory (KECI) All components are listed or exempted. **Philippines inventory** At least one component is not listed.

(PICCS)

**United States inventory** (TSCA 8b)

**Taiwan Chemical** 

**Substances Inventory** (TCSI)

**Harmful Chemicals List** 

International regulations **Montreal Protocol** 

Not listed.

Listed

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)** 

Not listed.

### Section 16. Other information

**History** 

Date of issue/Date of 29/07/2025.

revision

07/04/2025. Date of previous issue

Prepared by Product Stewardship Group

Key to abbreviations ACGIH = American Conference of Industrial Hygienists

CAS Number = Chemical Abstracts Service Registry Number

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

OEL = Occupational Exposure Limit

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

Regulation (EC) No. 1907/2006]

SDS = Safety Data Sheet STEL = Short term exposure limit TWA = Time weighted average

UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods. Varies = may

contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

References Not available

▼ Indicates information that has changed from previously issued version.

**Notice to reader** 

Product name Castrol Transmax Axle 85W-140 Product code 469574-TH01 Page: 7/8 Date of issue 29/07/2025. Language ENGLISH Version 10.02 Format GHS - Thailand Build 5.0.4 (GHS - Thailand) (ENGLISH)

### Section 16. Other information

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.