

SAFETY DATA SHEET



Castrol Brake Fluid DOT 4

Section 1. Identification

GHS product identifier Castrol Brake Fluid DOT 4
Product type Liquid.
Product code 466630-TH01
SDS no. 466630

Relevant identified uses of the substance or mixture and uses advised against


Product use Brake fluids.
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

Supplier BP Singapore Pte. Limited (196600436K)
7 Straits View
Marina One East Tower
#26-01, Singapore 018936

Tel: +65-6335 3000

EMERGENCY TELEPHONE NUMBER Carechem: +65 3158 1074 (24/7)

Section 2. Hazards identification

Classification of the substance or mixture  REPRODUCTIVE TOXICITY (Unborn child) - Category 2

GHS label elements

Hazard pictograms



Signal word

 Warning

Hazard statements


 H361 - Suspected of damaging the unborn child.

Precautionary statements

General

P103 - Read label before use.
P102 - Keep out of reach of children.
P101 - If medical advice is needed, have product container or label at hand.

Prevention

 P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing.


Response

 P308 + P313 - IF exposed or concerned: Get medical attention.

Storage

 P405 - Store locked up.

Disposal

 P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not result in classification Defatting to the skin.

Product name Castrol Brake Fluid DOT 4 **Product code** 466630-TH01 **Page:** 1/9

Version 2 **Date of issue** 07/25/2019.

Format Singapore
(Singapore)

Language ENGLISH
(ENGLISH)

Section 2. Hazards identification

Section 3. Composition/information on ingredients

Substance/mixture Mixture
polyethylene glycol Proprietary performance additives.

Ingredient name	%	CAS number
Tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] orthoborate	≥25 - ≤50	30989-05-0
2-[2-(2-butoxyethoxy)ethoxy]ethanol	≥10 - ≤25	143-22-6
2,2'-oxybisethanol	≤10	111-46-6
Di-isopropanolamine	≤10	110-97-4

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Inhalation	In case of inhalation of decomposition products in a fire, symptoms may be delayed. If inhaled, remove to fresh air. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention.
Skin contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Treatment should in general be symptomatic and directed to relieving any effects.
Specific treatments	No specific treatment.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet.

Product name Castrol Brake Fluid DOT 4	Product code 466630-TH01	Page: 2/9	
Version 2	Date of issue 07/25/2019.	Format Singapore	Language ENGLISH
		(Singapore)	(ENGLISH)

Section 5. Firefighting measures

Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	Combustion products may include the following: carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide) nitrogen oxides (NO, NO ₂ etc.)
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	N o action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling. Contact emergency personnel.
For emergency responders	E ntry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".
Environmental precautions	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	S top leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	P ut on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
----------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Product name Castrol Brake Fluid DOT 4	Product code 466630-TH01	Page: 3/9	
Version 2	Date of issue 07/25/2019.	Format Singapore	Language ENGLISH
		(Singapore)	(ENGLISH)

Section 7. Handling and storage

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. DO NOT ADD NITRITES TO THIS FLUID.

Not suitable

Prolonged exposure to elevated temperature

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

This product does not have any assigned OELs.

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety glasses with side shields.

Skin protection

Product name Castrol Brake Fluid DOT 4

Product code 466630-TH01 Page: 4/9

Version 2 Date of issue 07/25/2019.

Format Singapore Language ENGLISH

(Singapore) (ENGLISH)

Section 8. Exposure controls/personal protection

Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Butyl gloves. Neoprene gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Skin protection

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application.

Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

Appearance

Physical state	Liquid.
Colour	Yellow.
Odour	Characteristic.
Odour threshold	Not available.
pH	7.5 to 9
Melting point	<-70°C (<-94°F)
Boiling point	>260°C (>500°F)
Flash point	Closed cup: >125°C (>257°F) [Pensky-Martens.]
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable. Based on - Physical state
Lower and upper explosive (flammable) limits	Lower: 1.5%
Vapour pressure	<0.13 kPa (<1 mm Hg) [20°C (68°F)]
Vapour density	Not available.
Relative density	Not available.
Density	>1000 kg/m ³ (>1 g/cm ³) at 20°C
Solubility	Miscible in water.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Kinematic: 16 mm ² /s (16 cSt) at 20°C

Product name Castrol Brake Fluid DOT 4

Product code 466630-TH01 Page: 5/9

Version 2 Date of issue 07/25/2019.

Format Singapore

Language ENGLISH

(Singapore)

(ENGLISH)

Section 10. Stability and reactivity

Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
Incompatible materials	Reactive or incompatible with the following materials: oxidising materials.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Information on likely routes of exposure Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Eye contact

No known significant effects or critical hazards.

Inhalation

Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Skin contact

Defatting to the skin. May cause skin dryness and irritation.

Ingestion

Diethylene glycol: Ingestion of diethylene glycol can cause metabolic acidosis, kidney damage, central nervous system depression, and convulsions. The estimated human lethal dose is approximately 100 ml (3.4 ounces for an adult).

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact

No specific data.

Inhalation

May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.

Skin contact

Adverse symptoms may include the following:
irritation
dryness
cracking

Ingestion

Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact

Potential risk of transient stinging or redness if accidental eye contact occurs.

Skin contact

Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Ingestion

Ingestion of large quantities may cause nausea and diarrhoea.

Potential chronic health effects

General

May cause damage to organs through prolonged or repeated exposure. (kidney)

Product name Castrol Brake Fluid DOT 4

Product code 466630-TH01 **Page:** 6/9

Version 2 **Date of issue** 07/25/2019.

Format Singapore

Language ENGLISH

(Singapore)

(ENGLISH)

Section 11. Toxicological information

Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	☒ Suspected of damaging the unborn child.
Developmental effects	Birth defects and decreased fetal weight have been observed in laboratory animals fed diethylene glycol in large amounts repeatedly during pregnancy.
Fertility effects	No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
☒ Oral	5050.51 mg/kg

Section 12. Ecological information

Toxicity

Environmental effects	No known significant effects or critical hazards.
------------------------------	---------------------------------------------------

Persistence/degradability

Expected to be biodegradable.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
☒ Di-isopropanolamine	-	-	Readily

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Mobility in soil

Soil/water partition coefficient (K_{oc})	Not available.
Mobility	Spillages may penetrate the soil causing ground water contamination.

Other ecological information	Miscible in water.
-------------------------------------	--------------------

Section 13. Disposal considerations

Disposal methods	☒ The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
-------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Product name Castrol Brake Fluid DOT 4	Product code 466630-TH01	Page: 7/9	
Version 2	Date of issue 07/25/2019.	Format Singapore	Language ENGLISH
		(Singapore)	(ENGLISH)

Section 14. Transport information

	ADR/RID	ADN	IMDG	IATA/ICAO
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

Special precautions for user Not available.

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

No known specific national and/or regional regulations applicable to this product (including its ingredients).

Regulation according to other foreign laws

REACH Status

For the REACH status of this product please consult your company contact, as identified in Section 1.

United States inventory (TSCA 8b)

All components are active or exempted.

Australia inventory (AICS)

All components are listed or exempted.

Canada inventory

At least one component is not listed in DSL but all such components are listed in NDSL.

China inventory (IECSC)

All components are listed or exempted.

Japan inventory (ENCS)

All components are listed or exempted.

Korea inventory (KECI)

At least one component is not listed.

Philippines inventory (PICCS)

All components are listed or exempted.

Taiwan Chemical Substances Inventory (TCSI)

All components are listed or exempted.

Section 16. Other information

History

Date of issue/Date of revision	2019 July 25
Date of previous issue	2018 November 02
Version	2
Prepared by	Product Stewardship

Product name Castrol Brake Fluid DOT 4

Product code 466630-TH01 Page: 8/9

Version 2 Date of issue 07/25/2019.

Format Singapore
(Singapore)

Language ENGLISH
(ENGLISH)

Section 16. Other information

Key to abbreviations

ACGIH = American Conference of Industrial Hygienists
CAS Number = Chemical Abstracts Service Registry Number
GHS = Global Harmonised System
IATA = International Air Transport Association, the organisation
IMDG = International Maritime Organization Rules, rules governing shipment of goods by water.
OEL = Occupational Exposure Limit
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
SDS = Safety Data Sheet
STEL = Short term exposure limit
TWA = Time weighted average
UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods.
Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

✔ Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Castrol Brake Fluid DOT 4

Product code 466630-TH01 **Page:** 9/9

Version 2 **Date of issue** 07/25/2019.

Format Singapore

Language ENGLISH

(Singapore)

(ENGLISH)