



Section 1. Identification

Product name Castrol Elixion 5W-30
SDS # 457028
Code 457028-UX05

Relevant identified uses of the substance or mixture and uses advised against

Product use Engine Oils.
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

Supplier BP Lubricants USA Inc.
1500 Valley Road
Wayne, NJ 07470
Telephone: (973) 633-2200

EMERGENCY HEALTH INFORMATION: 1 (800) 447-8735
Outside the US: +1 703-527-3887 (CHEMTREC)

EMERGENCY SPILL INFORMATION: 1 (800) 424-9300 CHEMTREC (USA)

Section 2. Hazards identification

OSHA/HCS status This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture Not classified.

GHS label elements

Signal word No signal word.

Hazard statements No known significant effects or critical hazards.

Precautionary statements

General Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention Not applicable.

Response Not applicable.

Storage Not applicable.

Disposal Not applicable.

Hazards not otherwise classified Defatting to the skin.
USED ENGINE OILS
Used engine oil may contain hazardous components which have the potential to cause skin cancer.
See Toxicological Information, section 11 of this Safety Data Sheet.

Product name Castrol Elixion 5W-30	Product code 457028-UX05	Page: 1/9
Version 1.01 Date of issue 06/06/2018.	Format US (US)	Language ENGLISH (ENGLISH)

Section 3. Composition/information on ingredients

Substance/mixture Mixture
Synthetic base stock. Proprietary performance additives.

Ingredient name	CAS number	%
Distillates (petroleum), hydrotreated heavy paraffinic Base oil - highly refined	64742-54-7 Varies - See Key to abbreviations	≥25 - ≤50 ≤10
Distillates (petroleum), solvent-dewaxed heavy paraffinic zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	64742-65-0 113706-15-3 / 93819-94-4	≤10 ≤3
Alkyl phenol	74499-35-7 / 121158-58-5	≤0.3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.
Inhalation	If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	No specific treatment.

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet.

Specific hazards arising from the chemical In a fire or if heated, a pressure increase will occur and the container may burst.

Product name Castrol Elixion 5W-30	Product code 457028-UX05	Page: 2/9
Version 1.01 Date of issue 06/06/2018.	Format US (US)	Language ENGLISH (ENGLISH)

Section 5. Fire-fighting measures

Hazardous combustion products

Combustion products may include the following:
phosphorus oxides
metal oxide/oxides
carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)
sulfur oxides (SO, SO₂ etc.)
nitrogen oxides (NO, NO₂ etc.)

Special protective actions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8).

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Not suitable

Prolonged exposure to elevated temperature

Product name Castrol Elixion 5W-30

Product code 457028-UX05

Page: 3/9

Version 1.01 **Date of issue** 06/06/2018.

Format US

Language ENGLISH

(US)

(ENGLISH)

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Distillates (petroleum), hydrotreated heavy paraffinic

ACGIH TLV (United States).

TWA: 5 mg/m³ 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction

OSHA PEL (United States).

TWA: 5 mg/m³ 8 hours. Issued/Revised: 6/1993

Base oil - highly refined

ACGIH TLV (United States).

TWA: 5 mg/m³ 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction

OSHA PEL (United States).

TWA: 5 mg/m³ 8 hours. Issued/Revised: 6/1993

Distillates (petroleum), solvent-dewaxed heavy paraffinic

ACGIH TLV (United States).

TWA: 5 mg/m³ 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction

OSHA PEL (United States).

TWA: 5 mg/m³ 8 hours. Issued/Revised: 6/1993

zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

None.

Alkyl phenol

None.

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing.

Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety glasses with side shields.

Skin protection

Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Product name Castrol Elixion 5W-30

Product code 457028-UX05

Page: 4/9

Version 1.01 **Date of issue** 06/06/2018.

Format US

Language ENGLISH

(US)

(ENGLISH)

Section 8. Exposure controls/personal protection

Body protection

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

Appearance

Physical state	Liquid.
Color	Brown.
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point	Not available.
Boiling point	Not available.
Flash point	Closed cup: 200°C (392°F) [Pensky-Martens.]
Pour point	-42 °C
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable. Based on - Physical state
Lower and upper explosive (flammable) limits	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Density	853 kg/m ³ (0.853 g/cm ³) at 15°C
Solubility	insoluble in water.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Kinematic: 68.4 mm ² /s (68.4 cSt) at 40°C Kinematic: 11.38 mm ² /s (11.38 cSt) at 100°C

Section 10. Stability and reactivity

Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur.

Product name	Castrol Elixion 5W-30	Product code	457028-UX05	Page: 5/9
Version	1.01	Date of issue	06/06/2018.	Format US (US)
				Language ENGLISH (ENGLISH)

Section 10. Stability and reactivity

Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
Incompatible materials	Reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Aspiration hazard

Name	Result
Distillates (petroleum), hydrotreated heavy paraffinic	ASPIRATION HAZARD - Category 1
Distillates (petroleum), solvent-dewaxed heavy paraffinic	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Eye contact	No known significant effects or critical hazards.
Skin contact	No known significant effects or critical hazards.
Inhalation	Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Ingestion	No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	No specific data.
Skin contact	Adverse symptoms may include the following: irritation dryness cracking
Inhalation	No specific data.
Ingestion	No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects	Not available.
Potential delayed effects	Not available.

Long term exposure

Potential immediate effects	Not available.
Potential delayed effects	Not available.

Potential chronic health effects

General	USED ENGINE OILS Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

Product name Castrol Elixion 5W-30	Product code 457028-UX05	Page: 6/9
Version 1.01 Date of issue 06/06/2018.	Format US (US)	Language ENGLISH (ENGLISH)

Section 11. Toxicological information

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

No testing has been performed by the manufacturer.

Persistence and degradability

Partially biodegradable.

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Mobility in soil

Soil/water partition coefficient (K_{oc})

Not available.

Mobility

Spillages may penetrate the soil causing ground water contamination.

Other adverse effects

No known significant effects or critical hazards.

Other ecological information

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	<u>DOT Classification</u>	<u>TDG Classification</u>	<u>IMDG</u>	<u>IATA</u>
<u>UN number</u>	Not regulated.	Not regulated.	Not regulated.	Not regulated.
<u>UN proper shipping name</u>	-	-	-	-
<u>Transport hazard class(es)</u>	-	-	-	-
<u>Packing group</u>	-	-	-	-

Product name Castrol Elixion 5W-30

Product code 457028-UX05

Page: 7/9

Version 1.01 **Date of issue** 06/06/2018.

Format US

Language ENGLISH

(US)

(ENGLISH)

Section 14. Transport information

Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

Special precautions for user Not available.

Transport in bulk according to Annex II of MARPOL and the IBC Code Not available.

Section 15. Regulatory information

U.S. Federal regulations

United States inventory (TSCA 8b) All components are listed or exempted.

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 311/312

Classification Not applicable.

SARA 313

	Product name	CAS number	Concentration
Form R - Reporting requirements	zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis (dithiophosphate)	113706-15-3 / 93819-94-4	1.0797
Supplier notification	zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis (dithiophosphate)	113706-15-3 / 93819-94-4	1.0797

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts The following components are listed: OIL MIST, MINERAL; OIL MIST, MINERAL; OIL MIST, MINERAL

New Jersey The following components are listed: MINERAL OIL (UNTREATED and MILDLY TREATED); MINERAL OIL (UNTREATED and MILDLY TREATED); ZINC compounds; MINERAL OIL (UNTREATED and MILDLY TREATED)

Pennsylvania The following components are listed: ZINC COMPOUNDS

California Prop. 65

WARNING: This product can expose you to chemicals including Benzene, Lead, Cadmium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Arsenic, Nickel, which are known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Other regulations

Australia inventory (AICS) All components are listed or exempted.

Canada inventory All components are listed or exempted.

China inventory (IECSC) At least one component is not listed.

Japan inventory (ENCS) All components are listed or exempted.

Korea inventory (KECI) All components are listed or exempted.

Philippines inventory (PICCS) All components are listed or exempted.

Taiwan Chemical Substances Inventory (TCSI) Not determined.

Product name Castrol Elixion 5W-30	Product code 457028-UX05	Page: 8/9
Version 1.01 Date of issue 06/06/2018.	Format US (US)	Language ENGLISH (ENGLISH)

Section 15. Regulatory information

REACH Status

For the REACH status of this product please consult your company contact, as identified in Section 1.

Section 16. Other information

[National Fire Protection Association \(U.S.A.\)](#)



History

Date of issue/Date of revision	06/06/2018.
Date of previous issue	07/13/2016.
Prepared by	Product Stewardship
Key to abbreviations	ACGIH = American Conference of Industrial Hygienists ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor CAS Number = Chemical Abstracts Service Registry Number GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) OEL = Occupational Exposure Limit SDS = Safety Data Sheet STEL = Short term exposure limit TWA = Time weighted average UN = United Nations UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods. Varies = may contain one or more of the following 101316-69-2, 101316-70-5, 101316-71-6, 101316-72-7, 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64741-97-5, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-64-9, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1, 74869-22-0, 90669-74-2

✔ Indicates information that has changed from previously issued version.

[Notice to reader](#)

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name	Castrol Elixion 5W-30	Product code	457028-UX05	Page:	9/9
Version	1.01	Date of issue	06/06/2018.	Format	US (US)
				Language	ENGLISH (ENGLISH)