

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Product name	Castrol High Temperature Grease
Product code	467200-BE26
SDS #	467200
Product type	Grease

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/ mixture	Grease for industrial applications. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
----------------------------------	--

1.3 Details of the supplier of the safety data sheet

Supplier	Castrol Holdings Europe B.V., d'Arcyweg 76, 3198NA Europoort Rotterdam Castrol Lubricants RO S.R.L: 6-8 Corneliu Coposu Blvd., Unirii View Building, 1st Floor, Office 101, Bucharest +40-31-22.95.406
E-mail address	MSDSadvice@bp.com

1.4 Emergency telephone number

EMERGENCY TELEPHONE NUMBER	Phone number: +40 21 599 2300 (information provided in Romanian and English) Emergency phone number: 021 112 (available 24/7)
-------------------------------	--

Carechem: +44 (0) 1235 239 670 (24/7)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Product definition	Mixture
--------------------	---------

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements

Signal word	No signal word.
Hazard statements	No known significant effects or critical hazards.
<u>Precautionary statements</u>	
Prevention	Not applicable.
Response	Not applicable.
Storage	Not applicable.
Disposal	Not applicable.
Hazardous ingredients	Not applicable.

Supplemental label elements	Safety data sheet available on request.
--------------------------------	---

EU Regulation (EC) No. 1907/2006 (REACH)

Product name	Castrol High Temperature Grease			Product code	467200-BE26	Page: 1/13	
Version	3	Date of issue	29 September 2025	Format	Romania	Language	ENGLISH
Date of previous issue	23 August 2023.			(Romania)			

SECTION 2: Hazards identification

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Not applicable.
Special packaging requirements	
Containers to be fitted with child-resistant fastenings	Not applicable.
Tactile warning of danger	Not applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Product meets the criteria for endocrine disrupting properties according to Regulation (EC) No. 1907/2006.	This substance/mixture does not contain any components that are considered to have endocrine disrupting properties.
Other hazards which do not result in classification	Defatting to the skin. Note: High Pressure Applications Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. See 'Notes to physician' under First-Aid Measures, Section 4 of this Safety Data Sheet.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product definition Mixture
Highly refined base oil (IP 346 DMSO extract < 3%). Thickening agent. Proprietary performance additives.

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Distillates (petroleum), solvent-dewaxed heavy paraffinic	REACH #: 01-2119471299-27 EC: 265-169-7 CAS: 64742-65-0 Index: 649-474-00-6	≥25 - ≤50	Not classified.	-	[2]
Residual oils (petroleum), solvent refined	REACH #: 01-2119488707-21 EC: 265-101-6 CAS: 64742-01-4 Index: 649-459-00-4	≥25 - ≤50	Not classified.	-	[2]
Distillates (petroleum), hydrotreated heavy naphthenic	REACH #: 01-2119467170-45 EC: 265-155-0 CAS: 64742-52-5 Index: 649-465-00-7	≤10	Not classified.	-	[2]
dilithium sebacate	REACH #: 01-2120119384-60 EC: 242-999-8 CAS: 19370-86-6	≤3	Acute Tox. 4, H302	ATE [Oral] = 500 mg/kg	[1]
4,4'-methylene bis (dibutylidithiocarbamate)	REACH #: 01-2119969655-20 EC: 233-593-1 CAS: 10254-57-6	≤3	Aquatic Chronic 4, H413	-	[1]

See Section 16 for the full text of the H statements declared above.

Type

- [1] Substance classified with a health or environmental hazard
[2] Substance with a workplace exposure limit
Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.
Inhalation	If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Potential acute health effects

Inhalation	Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Ingestion	No known significant effects or critical hazards.
Skin contact	Defatting to the skin. May cause skin dryness and irritation.
Eye contact	No known significant effects or critical hazards.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation	Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Note: High Pressure Applications Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimise tissue loss and prevent or limit permanent damage. Note that high pressure may force the product considerable distances along tissue planes.
---------------------------	---

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	In case of fire, use water fog, alcohol resistant foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet. The use of a water jet may cause the fire to spread by splashing the burning product.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	No specific fire or explosion hazard.
Hazardous combustion products	Combustion products may include the following: carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide) metal oxide/oxides nitrogen oxides (NO, NO₂ etc.) sulphur oxides (SO, SO₂, etc.)

5.3 Advice for firefighters

Special precautions for fire-fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.
--	---

Product name Castrol High Temperature Grease

Product code 467200-BE26

Page: 3/13

Version 3 **Date of issue** 29 September 2025

Format Romania

Language ENGLISH

Date of previous issue 23 August 2023.

(Romania)

SECTION 5: Firefighting measures**Special protective equipment for fire-fighters**

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Put on appropriate personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up**Small spill**

Move containers from spill area. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. If emergency personnel are unavailable, contain spilt material. Suction or scoop the spill into appropriate disposal or recycling vessels, then cover spill area with oil absorbent. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

See Section 1 for emergency contact information.
See Section 5 for firefighting measures.
See Section 8 for information on appropriate personal protective equipment.
See Section 12 for environmental precautions.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Protective measures**

Put on appropriate personal protective equipment.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/containers designed for use with this product. Do not store in unlabelled containers.

Not suitable

Prolonged exposure to elevated temperature

7.3 Specific end use(s)**Recommendations**

See section 1.2 and Exposure scenarios in annex, if applicable.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limits**

Product/ingredient name	Exposure limit values
Distillates (petroleum), solvent-dewaxed heavy paraffinic	HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania) [Uleiuri minerale] VLA 8 hours: 5 mg/m ³ . Issued/Revised: 3/2021. Short term 15 minutes: 10 mg/m ³ . Issued/Revised: 3/2021.
Residual oils (petroleum), solvent refined	HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania) [Uleiuri minerale] VLA 8 hours: 5 mg/m ³ . Issued/Revised: 3/2021.

Product name Castrol High Temperature Grease

Product code 467200-BE26

Page: 4/13

Version 3 **Date of issue** 29 September 2025

Format Romania

Language ENGLISH

Date of previous issue 23 August 2023.

(Romania)

SECTION 8: Exposure controls/personal protection

Distillates (petroleum), hydrotreated heavy naphthenic

Short term 15 minutes: 10 mg/m³. Issued/Revised: 3/2021.

HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania) [Uleiuri minerale]

VLA 8 hours: 5 mg/m³. Issued/Revised: 3/2021.

Short term 15 minutes: 10 mg/m³. Issued/Revised: 3/2021.

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Recommended monitoring procedures

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Biological exposure indices

No exposure indices known.

Product/ingredient name

Exposure indices

DNELs/DMELs

Not available.

8.2 Exposure controls

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Eye/face protection

Safety glasses with side shields.

Skin protection

Hand protection

General Information:

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile gloves.

Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type.

Our recommendations on the selection of gloves are as follows:

Product name Castrol High Temperature Grease

Product code 467200-BE26

Page: 5/13

Version 3 **Date of issue** 29 September 2025

Format Romania

Language ENGLISH

Date of previous issue 23 August 2023.

(Romania)

SECTION 8: Exposure controls/personal protection

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained.

If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.

It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

Glove Thickness:

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.

- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

Skin and body

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Refer to standards:

Respiratory protection: EN 529

Gloves: EN 420, EN 374

Eye protection: EN 166

Filtering half-mask: EN 149

Filtering half-mask with valve: EN 405

Half-mask: EN 140 plus filter

Full-face mask: EN 136 plus filter

Particulate filters: EN 143

Gas/combined filters: EN 14387

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Physical state	Grease
Colour	Amber.
Odour	Characteristic.

Product name Castrol High Temperature Grease

Product code 467200-BE26

Page: 6/13

Version 3 **Date of issue** 29 September 2025

Format Romania

Language ENGLISH

Date of previous issue 23 August 2023.

(Romania)

SECTION 9: Physical and chemical properties

Odour threshold	Not available.				
Melting point/freezing point	 Not available.				
Initial boiling point and boiling range	Not available.				
Flammability	Not available.				
Lower and upper explosion limit	Not applicable.				
Flash point	 losed cup: >200°C (>392°F) [Pensky-Martens ASTM D 93]				
Auto-ignition temperature	>300°C (>572°F)				
Decomposition temperature	Not available.				
pH	Not applicable.				
Kinematic viscosity	Not available.				
Solubility	<table><tr><th>Media</th><th>Result</th></tr><tr><td>water</td><td>Not soluble</td></tr></table>	Media	Result	water	Not soluble
Media	Result				
water	Not soluble				
Partition coefficient n-octanol/ water (log value)	Not applicable.				
Vapour pressure	Not available.  0.01 kPa				
Relative vapour density	Not applicable.				
Particle characteristics					
Median particle size	Not available.				
9.2 Other information					
Evaporation rate	Not available.				
Explosive properties	Not available.				
Oxidising properties	Not available.				

SECTION 10: Stability and reactivity

10.1 Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
10.2 Chemical stability	The product is stable.
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
10.4 Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
10.5 Incompatible materials	Reactive or incompatible with the following materials: oxidising materials.
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity	
Product/ingredient name	Result
 4'-methylene bis(dibutylidithiocarbamate)	Rat - Oral - LD50 >5000 mg/kg OECD 401
	Rabbit - Dermal - LD50 >2000 mg/kg OECD 402

Acute toxicity estimates

Product name	Castrol High Temperature Grease	Product code	467200-BE26	Page:	7/13
Version	3	Date of issue	29 September 2025	Format	Romania
Date of previous issue	23 August 2023.			Language	ENGLISH
					(Romania)

SECTION 11: Toxicological information

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Castrol High Temperature Grease dilithium sebacate	21760.9 500	N/A N/A	N/A N/A	N/A N/A	N/A N/A

Skin corrosion/irritation

Product/ingredient name	Result
4,4'-methylene bis(dibutyldithiocarbamate)	Rabbit - Skin - Not irritant OECD 404

Serious eye damage/eye irritation

Product/ingredient name	Result
4,4'-methylene bis(dibutyldithiocarbamate)	Rabbit - Eyes - Not irritant OECD 405

Respiratory corrosion/irritation

Not available.

Respiratory or skin sensitization

Product/ingredient name	Result
4,4'-methylene bis(dibutyldithiocarbamate)	Mouse - skin OECD 429 Result: Not sensitising

Germ cell mutagenicity

Product/ingredient name	Result
4,4'-methylene bis(dibutyldithiocarbamate)	In vitro - Bacteria OECD 471 Result: Negative In vitro - Mammalian-Animal OECD 473 Result: Negative In vitro - Mammalian-Animal OECD 476 Result: Negative

Carcinogenicity

Not available.

Reproductive toxicity

Product/ingredient name	Result
4,4'-methylene bis(dibutyldithiocarbamate)	Rat - Oral OECD 422 Maternal toxicity: Negative Fertility effects: Negative Developmental: Negative

Specific target organ toxicity (single exposure)

Not available.

Product name	Castrol High Temperature Grease	Product code	467200-BE26	Page:	8/13
Version	3	Date of issue	29 September 2025	Format	Romania
Date of previous issue	23 August 2023.			Language	ENGLISH
					(Romania)

SECTION 11: Toxicological information

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

- Inhalation Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Ingestion No known significant effects or critical hazards.
- Skin contact Defatting to the skin. May cause skin dryness and irritation.
- Eye contact No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation No specific data.
- Ingestion No specific data.
- Skin contact Adverse symptoms may include the following:
irritation
dryness
cracking
- Eye contact No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

- Inhalation Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.
- Ingestion Ingestion of large quantities may cause nausea and diarrhoea.
- Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs.

Potential chronic health effects

Not available.

- Conclusion/Summary [Product] Not available.
- General No known significant effects or critical hazards.
- Carcinogenicity No known significant effects or critical hazards.
- Mutagenicity No known significant effects or critical hazards.
- Developmental effects No known significant effects or critical hazards.
- Fertility effects No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

- Conclusion/Summary [Product] This substance/mixture does not contain any components that are considered to have endocrine disrupting properties.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result
4,4'-methylene bis(dibutylidithiocarbamate)	Acute - ErC50
	OECD 201
	Algae
	>0.0325 mg/l [72 hours]
	Acute - EC50
	OECD 202
	Daphnia
	>0.052 mg/l [48 hours]
	Acute - EL50
	OECD 203
	Fish
	>0.06 mg/l [96 hours]
	Chronic - NOEC
	OECD 211

SECTION 12: Ecological information

Daphnia
0.247 mg/l [21 days]

Chronic - NOEC
OECD 201
Algae
0.0325 mg/l [72 hours]

Environmental hazards Not classified as dangerous

12.2 Persistence and degradability

Expected to be biodegradable.

Product/ingredient name	Result
4,4'-methylene bis(dibutyldithiocarbamate)	OECD 301B 21% [28 days] - Not readily

12.3 Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	LogP _{ow}	BCF	Potential
4,4'-methylene bis(dibutyldithiocarbamate)	8.42	10.86	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logK _{oc}	K _{oc}
4,4'-methylene bis(dibutyldithiocarbamate)	3.09	1243.29

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
lithium sebacate	No	No	No	No	No	No	No
4,4'-methylene bis(dibutyldithiocarbamate)	No	No	No	No	No	No	No

Mobility Spillages are unlikely to penetrate the soil.

Conclusion/Summary The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
lithium sebacate	No	N/A	N/A	No	N/A	N/A	N/A
4,4'-methylene bis(dibutyldithiocarbamate)	No	N/A	No	No	No	N/A	No

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
lithium sebacate	No	No	No	No	No	No	No
4,4'-methylene bis(dibutyldithiocarbamate)	No	No	No	No	No	No	No

Conclusion/Summary The product does not meet the criteria to be considered as a PBT or vPvB.

Regulation (EC) No. 1272/2008 [CLP]

12.6 Endocrine disrupting properties

Conclusion/Summary [Product] This substance/mixture does not contain any components that are considered to have endocrine disrupting properties.

Other ecological information This product is unlikely to disperse in water.

12.7 Other adverse effects No known significant effects or critical hazards.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product****Methods of disposal**

Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Hazardous waste

Yes.

European waste catalogue (EWC)

Waste code	Waste designation
12 01 12*	spent waxes and fats

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

Packaging**Methods of disposal**

Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Special precautions

This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

References

Commission 2014/955/EU
Directive 2008/98/EC

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

14.6 Special precautions for user

Not available.

14.7 Maritime transport in bulk according to IMO instruments

Not available.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU Regulation (EC) No. 1907/2006 (REACH)****Annex XIV - List of substances subject to authorisation****Annex XIV**

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

No listed substance

Labelling

Not applicable.

Product name	Castrol High Temperature Grease	Product code	467200-BE26	Page:	11/13
Version	3	Date of issue	29 September 2025	Format	Romania
Date of previous issue	23 August 2023.			Language	ENGLISH
					(Romania)

SECTION 15: Regulatory information

Other regulations	
REACH Status	The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.
United States inventory (TSCA 8b)	All components are active or exempted.
Australia inventory (AIIIC)	All components are listed or exempted.
Canada inventory	All components are listed or exempted.
China inventory (IECSC)	All components are listed or exempted.
Japan inventory (CSCL)	At least one component is not listed.
Korea inventory (KECI)	At least one component is not listed.
Philippines inventory (PICCS)	All components are listed or exempted.
Taiwan Chemical Substances Inventory (TCSI)	All components are listed or exempted.
Explosive precursors	 Not applicable.
Ozone depleting substances (EU 2024/590)	
Not listed.	
Prior Informed Consent (PIC) (649/2012/EU)	
Not listed.	
Persistent Organic Pollutants	
Not listed.	
EU - Water framework directive - Priority substances	
None of the components are listed.	
Seveso Directive	
This product is not controlled under the Seveso Directive.	
15.2 Chemical safety assessment	A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

SECTION 16: Other information

Abbreviations and acronyms	ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor CAS = Chemical Abstracts Service CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] CSA = Chemical Safety Assessment CSR = Chemical Safety Report DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EINECS = European Inventory of Existing Commercial chemical Substances ES = Exposure Scenario EUH statement = CLP-specific Hazard statement EWC = European Waste Catalogue GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) OECD = Organisation for Economic Co-operation and Development PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006] RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail RRN = REACH Registration Number
--	---

Product name	Castrol High Temperature Grease	Product code	467200-BE26	Page:	12/13
Version	3	Date of issue	29 September 2025	Format	Romania
Date of previous issue	23 August 2023.			Language	ENGLISH
					(Romania)

SECTION 16: Other information

SADT = Self-Accelerating Decomposition Temperature
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVCB = Complex hydrocarbon substance
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative
Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4/ RRN 01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN 01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN 01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN 01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN 01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8, 64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 / RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN 01-2119474889-13

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

Full text of abbreviated H statements	 302 H413	Harmful if swallowed. May cause long lasting harmful effects to aquatic life.
Full text of classifications [CLP/GHS]	 cute Tox. 4 Aquatic Chronic 4	ACUTE TOXICITY - Category 4 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4

History

Date of issue/ Date of revision	29/09/2025.
Date of previous issue	23/08/2023.
Prepared by	Product Stewardship

 Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.