SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name **Castrol POWER1 A747**

Product code 469405-BE02

SDS # 469405

Product type Liquid.

Use of the substance/ mixture Lubricant for two-stroke engines.
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

1.3 Details of the supplier of the safety data sheet

Supplier

Castrol Holdings Europe B.V.,
d'Arcyweg 76, 3198NA
Europoort
Rotterdam

Castrol France SAS
Campus Saint Christophe, Bâtiment Galilée 3, 10 Avenue de l'Entreprise, Cergy-Pontoise, Cedex, 95863
+33 (0) 805 638 301

E-mail address MSDSadvice@bp.com

1.4 Emergency telephone number

EMERGENCY TELEPHONE NUMBER

Tél 01 45 42 59 59 : ORFILA
Tél 01 40 05 48 48 - Centre Anti-Poisons de Paris, Hôpital Fernand Widal - 200, Rue de Faubourg Saint-Denis - 75475 Paris Cedex 10
Tél 04 72 11 69 11 - Centre Antipoison et de Toxicovigilance de LYON, Bâtiment A, 4ème étage, 162, avenue Lacassagne, 69424 Lyon Cedex 03
Tél 04 91 75 25 25 - Centre Anti-Poisons de Marseille, Hôpital Salvator, 249, Boulevard Sainte-Marguerite - 13274 Marseille Cedex 9

Tél: 01 30 30 49 99 - Permanence BP France 24/24

Carechem: +44 (0) 1235 239 670 (24/7)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements

No signal word.

Hazard statements No known significant effects or critical hazards.

Prevention Not applicable.

Response Not applicable.

Storage Not applicable.

Disposal Not applicable.

Hazardous ingredients Not applicable.

Supplemental label elements Safety data sheet available on request.

EU Regulation (EC) No. 1907/2006 (REACH)

SECTION 2: Hazards identification

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings Not applicable.

Tactile warning of danger Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Product meets the criteria for endocrine disrupting properties according to Regulation (EC) No. 1907/2006. This substance/mixture does not contain any components that are considered to have endocrine disrupting properties.

Other hazards which do not result in classification Defatting to the skin.
NOTE: Product diluted with petrol must be handled with the same precautions used for petrol. Before mixing, the Safety Data Sheet for petrol should be consulted for any precautionary measures necessary.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product definition Mixture

Synthetic base stock. Vegetable oil. Proprietary performance additives.

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
N-[(1,1,3,3-tetramethylbutyl) phenyl]naphthalen-1-amine	REACH #: 01-2119972293-33 EC: 257-406-8 CAS: 51772-35-1	≤3	Aquatic Chronic 4, H413	-	[1]

See Section 16 for the full text of the H statements declared above.

[1] Substance classified with a health or environmental hazard

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.

Skin contact Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.

Inhalation If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Potential acute health effects

Inhalation Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Ingestion No known significant effects or critical hazards.

SECTION 4: First aid measures

Skin contact Defatting to the skin. May cause skin dryness and irritation.

Eye contact See: Section 11. Toxicological Information - Potential acute health effects: Eye contact

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

Ingestion Ingestion of large quantities may cause nausea and diarrhoea.

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician Treatment should in general be symptomatic and directed to relieving any effects.
In case of inhalation of decomposition products in a fire, symptoms may be delayed.
The exposed person may need to be kept under medical surveillance for 48 hours.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media In case of fire, use water fog, alcohol resistant foam, dry chemical or carbon dioxide extinguisher or spray.

Unsuitable extinguishing media Do not use water jet. The use of a water jet may cause the fire to spread by splashing the burning product.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products Combustion products may include the following:
carbon oxides (CO, CO_2) (carbon monoxide, carbon dioxide)
nitrogen oxides (NO, NO_2 etc.)

5.3 Advice for firefighters

Special precautions for fire-fighters No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Put on appropriate personal protective equipment.

For emergency responders If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Small spill Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

SECTION 6: Accidental release measures

6.4 Reference to other sections

See Section 1 for emergency contact information.
See Section 5 for firefighting measures.
See Section 8 for information on appropriate personal protective equipment.
See Section 12 for environmental precautions.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment. NOTE: Product diluted with petrol must be handled with the same precautions used for petrol. Before mixing, the Safety Data Sheet for petrol should be consulted for any precautionary measures necessary.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/ containers designed for use with this product. Do not store in unlabelled containers.

Not suitable

Prolonged exposure to elevated temperature.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Recommended monitoring procedures

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Biological exposure indices

Product/ingredient name	Exposure indices
No exposure indices known.	

Derived No Effect Level

No DNELs/DMELs available.

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.
All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.
Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

SECTION 8: Exposure controls/personal protection

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.
The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Eye/face protection

Safety glasses with side shields.

Skin protection

Hand protection

General Information:

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile gloves.
Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type.
Our recommendations on the selection of gloves are as follows:

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained.
If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.
It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

Glove Thickness:

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.
Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.

- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

SECTION 8: Exposure controls/personal protection

Skin and body

Use of protective clothing is good industrial practice.
Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Refer to standards:

Respiratory protection: EN 529
Gloves: EN 420, EN 374
Eye protection: EN 166
Filtering half-mask: EN 149
Filtering half-mask with valve: EN 405
Half-mask: EN 140 plus filter
Full-face mask: EN 136 plus filter
Particulate filters: EN 143
Gas/combined filters: EN 14387

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state Liquid.

Colour Amber.

Odour Not available.

Odour threshold Not available.

pH Not applicable.

Melting point/freezing point Not available.

Initial boiling point and boiling range Not available.

Pour point -27 °C

Flash point Closed cup: 202°C (395.6°F) [Pensky-Martens ASTM D 93]

Evaporation rate Not available.

Flammability Not available.

Lower and upper explosion limit Not available.

Vapour pressure

	Vapour Pressure at 20˚C			Vapour pressure at 50˚C	
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa
Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191		
Distillates (petroleum), hydrotreated light paraffinic	<0.07501	<0.01	ASTM D 5191		
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<0.07501	<0.01	ASTM D 5191		

Vapour density Not available.

Not available.

Density and/or Relative density <1000 kg/m³ (<1 g/cm³) at 15°C

Solubility(ies)

Media	Result
water	Not soluble

Partition coefficient n-octanol/water (log value) Not applicable.

Auto-ignition temperature Not available.

SECTION 9: Physical and chemical properties

Decomposition temperature	Not available.
Kinematic viscosity	Kinematic: 178 mm^2/s (178 cSt) at 40°C Kinematic: 17.5 to 22.49 mm^2/s (17.5 to 22.49 cSt) at 100°C
Explosive properties	Not available.
Oxidising properties	Not available.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
10.2 Chemical stability	The product is stable.
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
10.4 Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
10.5 Incompatible materials	Reactive or incompatible with the following materials: oxidising materials.
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result
N-[(1,1,3,3-tetramethylbutyl)phenyl]naphthalen-1-amine	**Rat - Oral - LD50** >2000 mg/kg OECD 423 **Rat - Dermal - LD50** >2000 mg/kg OECD 402

Acute toxicity estimates

N/A

Skin corrosion/irritation

Product/ingredient name	Result
N-[(1,1,3,3-tetramethylbutyl)phenyl]naphthalen-1-amine	**RhE - Skin - Non-irritant to skin.** OECD 439

Serious eye damage/eye irritation

Product/ingredient name	Result
N-[(1,1,3,3-tetramethylbutyl)phenyl]naphthalen-1-amine	**RhCE - Eyes - Non-irritating to the eyes.** OECD 492 **BCOP - Eyes - Non-irritating to the eyes.** OECD 437

Respiratory corrosion/irritation

Not available.

SECTION 11: Toxicological information

Respiratory or skin sensitization

Product/ingredient name	Result
N-[(1,1,3,3-tetramethylbutyl)phenyl]naphthalen-1-amine	**Guinea pig - skin** OECD 406 Result: Not sensitising

Germ cell mutagenicity

Product/ingredient name	Result
N-[(1,1,3,3-tetramethylbutyl)phenyl]naphthalen-1-amine	**In vitro - Bacteria** OECD [Bacterial Reverse Mutation Test] Result: Negative **In vitro - Mammal - species unspecified** OECD [In vitro Mammalian Cell Gene Mutation Test] Result: Negative **In vitro - Mammal - species unspecified** OECD [In vitro Mammalian Chromosomal Aberration Test] Result: Negative

Carcinogenicity

Not available.

Reproductive toxicity

Product/ingredient name	Result
N-[(1,1,3,3-tetramethylbutyl)phenyl]naphthalen-1-amine	**Rat - Oral** OECD 422 Maternal toxicity: Negative Fertility effects: Negative Developmental: Negative

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Inhalation Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Ingestion No known significant effects or critical hazards.

Skin contact Defatting to the skin. May cause skin dryness and irritation.

Eye contact See: Section 11. Toxicological Information - Potential acute health effects: Eye contact

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.

Ingestion No specific data.

Skin contact Adverse symptoms may include the following:
irritation
dryness
cracking

Eye contact No specific data.

SECTION 11: Toxicological information

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.

Potential chronic health effects

Not available.

Conclusion/Summary [Product]	Not available.
General	No known significant effects or critical hazards.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]	This substance/mixture does not contain any components that are considered to have endocrine disrupting properties.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result
N-[(1,1,3,3-tetramethylbutyl)phenyl]naphthalen-1-amine	**Acute - ErC50** OECD 201 Algae >100 mg/l [72 hours] **Acute - EC50** OECD 202 Daphnia >100 mg/l [48 hours] **Acute - LC50** OECD 203 Fish >100 mg/l [96 hours] **Chronic - NOEC** OECD 201 Algae 100 mg/l [72 hours]

Environmental hazards	Not classified as dangerous

12.2 Persistence and degradability

Partially biodegradable.

Product/ingredient name	Result
N-[(1,1,3,3-tetramethylbutyl)phenyl]naphthalen-1-amine	OECD 301B 0% [28 days] - Not readily

12.3 Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	$LogP_{ow}$	BCF	Potential
N-[(1,1,3,3-tetramethylbutyl)phenyl]naphthalen-1-amine	>8	-	High

12.4 Mobility in soil

SECTION 12: Ecological information

Soil/water partition coefficient

Not available.

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
N-[(1,1,3,3-tetramethylbutyl) phenyl]naphthalen-1-amine	No	No	No	No	No	No	No

Mobility Spillages may penetrate the soil causing ground water contamination.

Conclusion/Summary The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	
N-[(1,1,3,3-tetramethylbutyl) phenyl]naphthalen-1-amine	No	N/A	N/A	No	N/A	N/A	N/A

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	
N-[(1,1,3,3-tetramethylbutyl) phenyl]naphthalen-1-amine	No	No	No	No	No	No	No

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] This substance/mixture does not contain any components that are considered to have endocrine disrupting properties.

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

12.7 Other adverse effects No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Hazardous waste Yes.

European waste catalogue (EWC)

Waste code	Waste designation
13 02 08*	other engine, gear and lubricating oils

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

Packaging

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Special precautions This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

References Commission 2014/955/EU
Directive 2008/98/EC

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

14.6 Special precautions for user Not available.

14.7 Maritime transport in bulk according to IMO instruments Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

No listed substance

Labelling Not applicable.

Other regulations

REACH Status The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

United States inventory (TSCA 8b) All components are active or exempted.

Australia inventory (AIIC) All components are listed or exempted.

Canada inventory All components are listed or exempted.

China inventory (IECSC) All components are listed or exempted.

Japan inventory (CSCL) All components are listed or exempted.

Korea inventory (KECI) All components are listed or exempted.

Philippines inventory (PICCS) All components are listed or exempted.

Taiwan Chemical Substances Inventory (TCSI) All components are listed or exempted.

Explosive precursors Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

SECTION 15: Regulatory information

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

SECTION 16: Other information

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SADT = Self-Accelerating Decomposition Temperature
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVCB = Complex hydrocarbon substance
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative
Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4/ RRN 01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN 01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN 01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN 01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN 01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8, 64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 / RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN 01-2119474889-13

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

Full text of classifications [CLP/GHS]

Aquatic Chronic 4	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4

History

SECTION 16: Other information

Date of issue/ Date of revision	09/10/2025.
Date of previous issue	No previous validation.
Prepared by	Product Stewardship

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

SECTION 16: Other information

يتفق ولائحة (المجموعة الأوروبية) رقم 1907/2006 (تشريع تقييم المواد الكيميائية وتسجيلها وإقرارها (REACH))، الملحق 2، بصيغته المعدلة بلائحة (الاتحاد الأوروبي) رقم 2020/878

Castrol

صحيفة بيانات السلامة

القسم 1: تعريف المادة/المستحضر و الشركة/المشروع

1.1 مُعرّف المُنتَج

اسم المنتج	**Castrol POWER1 A747**
كود المنتج	469405-BE02
صحيفة بيانات سلامة المادة رقم #	469405
نوع المنتَج	Liquid.

1.3 بيانات مورّد صحيفة بيانات السلامة

المورّد

Castrol Holdings Europe B.V.,
d'Arcyweg 76, 3198NA
Europoort
Rotterdam

Castrol France SAS
Campus Saint Christophe, Bâtiment Galilée 3, 10 Avenue de l'Entreprise, Cergy-Pontoise, Cedex, 95863
+33 (0) 805 638 301

عنوان البريد الإلكتروني: MSDSadvice@bp.com

1.4 رقم هاتف الطوارئ

رقم هاتف الطوارئ

Tél 01 45 42 59 59 : ORFILA
Tél 01 40 05 48 48 - Centre Anti-Poisons de Paris, Hôpital Fernand Widal - 200, Rue de Faubourg Saint-Denis - 75475 Paris Cedex 10
Tél 04 72 11 69 11 - Centre Antipoison et de Toxicovigilance de LYON, Bâtiment A, 4ème étage, 162, avenue Lacassagne, 69424 Lyon Cedex 03
Tél 04 91 75 25 25 - Centre Anti-Poisons de Marseille, Hôpital Salvator, 249, Boulevard Sainte-Marguerite - 13274 Marseille Cedex 9

Tél: 01 30 30 49 99 - Permanence BP France 24/24

Carechem: +44 (0) 1235 239 670 (24/7)

القسم 2: بيان الأخطار

2.1 تصنيف المادة أو الخليط

تعريف المنتج: خليط

مراجعة الأقسام 11 و12 للوقوف على مزيد من المعلومات المفصلة بشأن الآثار الصحية والأعراض والمخاطر البيئية.

2.2 عناصر الوسم

الوقاية	غير قابل للتطبيق.
الاستجابة	غير قابل للتطبيق.
التخزين	غير قابل للتطبيق.
التخلص من النفاية	غير قابل للتطبيق.
عناصر التوسيم التكميلية	صحيفة بيانات السلامة متاحة عند الطلب.

تنظيم (المجلس الأوروبي) رقم 1907/2006 (تسجيل الكيماويات وتقييمها وترخيصها (REACH

القسم 2: بيان الأخطار

المُلحق السابع عشر؛ قيود على تصنيع وطرح واستخدام مواد وخلائط وحاجيات مُعينة خطرة — غير قابل للتطبيق.

متطلبات التغليف الخاصة

يُراعى أن تُزوَّد العبوات بأنظمة إغلاق منيعة للأطفال — غير قابل للتطبيق.

تحذير لمسي من الخطر — غير قابل للتطبيق.

2.3 الأخطار الأخرى

نتائج مأخوذة من تقييم الـ PBT (البقاء والسمية والتراكم البيولوجي) والـ vPvB (البقاء الشديد والتراكم البيولوجي الشديد) — المنتج لا يُلبي معايير ثبات المواد والتراكمية الأحيائية والسمية PBT أو معايير شدة الثبات وشدة التراكمية الأحيائية وفق لائحة المجلس الأوروبي رقم 1907/2006، الملحق XIII.

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII — This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

الأخطار الأخرى التي لا تؤدي إلى تصنيف — يزيل دهون الجلد.
ملاحظة: المنتج المخفف بالبترول يجب التعامل معه بنفس الاحتياطات التي يتم اتخاذها عند التعامل مع البترول. قبل الخلط، يجب مراجعة نشرة بيانات الأمان للبترول للتعرف على أية تدابير وقائية يجب اتخاذها.

القسم 3: التركيب/معلومات عن المكونات

3.2 خلائط

تعريف المنتج — خليط

مخزون أساسي اصطناعي. الزيوت النباتية. إضافات خاصة للأداء.

اسم المُكوّن/المنتَج	المُعرّفات	%	التصنيف	التركيز المحدد الحدود وعوامل الضرب وتقديرات السمية الحادة	النوع
N-[(1,1,3,3-tetramethylbutyl) phenyl]naphthalen-1-amine	:# REACH 01-2119972293-33 المفوضية الأوروبية: 257-406-8 CAS: 51772-35-1	≤3	Aquatic Chronic 4, H413	-	[1]

انظر القسم 16 لمطالعة نص بيانات الأخطار آنف الذكر كاملاً.

لا يحتوي هذا المنتج على أي مكونات خطرة أعلى من الحدود المسموح بها.

[1] المادة مُصنَّفة على أنها ذات خطر صحي أو بيئي

القسم 4: تدبير الإسعاف الأولي

4.1 وصف إجراءات الإسعاف الأوَّلي

ملامسة العين — في حالة الملامسة، يُراعى دفق الماء فوراً على الأعين لمدة لا تقل عن 15 دقيقة. يجب إبعاد الجفون عن مقلات الأعين لضمان الشطف الكامل. يراعى التحقق من عدم وجود عدسات لاصقة أو إزالتها إن وُجدت. يُراعى الحصول على الرعاية الطبية.

ملامسة الجلد — يراعى غسل البشرة غسلا جيدا بالماء و الصابون أو بأحد منظفات الجلد المعترف بها. أزل الثياب و الأحذية الملوثة. يُراعى غسل الثياب قبل إعادة استخدامها. يراعى تنظيف الحذاء تنظيفا جيدا قبل ارتدائه ثانية. يُراعى الحصول على الرعاية الطبية إذا حدث تهيُّج.

استنشاق — في حالة الإستنشاق، يُراعى نقل المصاب إلى الهواء الطلق. في حالة استنشاق مُخلفات التحلل عند نشوب حريق، قد تظهر الأعراض ظهوراً آجلاً. قد يكون من الضروري أن يظل الشخص المعرَّض تحت الملاحظة الطبية لـ 48 ساعة. يُراعى الحصول على الرعاية الطبية لو ظهرت أعراض.

الابتلاع — لا تحرض على القيء إلا إن طلب أحد أعضاء الطاقم الطبي منك أن تقوم بهذا. يُراعى الحصول على الرعاية الطبية لو ظهرت أعراض.

حماية فريق الإسعافات الأولية — يُحظر القيام بأية إجراء ينطوي على مخاطرة أو بدون تدريب مناسب.

4.2 أهم الأعراض والتأثيرات، الحاد منها والمؤجل

انظر القسم 11 لمزيد من المعلومات عن التأثيرات الصحية والأعراض.

آثار صحية حادة كامنة

استنشاق — التعرض لمنتوجات التحلل قد يشكل خطورة صحية. قد تتأجل بعض التأثيرات الخطيرة عقب التعرض.

الابتلاع — لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

ملامسة الجلد — يزيل دهون الجلد. قد تسبب جفاف الجلد وتهيُّجه.

القسم 4: تدبير الإسعاف الأولي

ملامسة العين انظر: القسم 11 . المعلومات السمية - آثار صحية حادة كامنة: ملامسة العين

التأثيرات المتأخرة والفورية وكذلك التأثيرات المزمنة نتيجة للتعرض القصير والطويل الأمد

استنشاق التعرض الزائد لاستنشاق الجزيئات المتطايرة في الهواء أو الإيروسولات قد يتسبب في تهيج الجهاز التنفسي.

الابتلاع ابتلاع كميات كبيرة يمكن أن يؤدي إلى الغثيان والإسهال.

ملامسة الجلد الملامسة بشكل متكرر أو لفترات طويلة يمكن أن تتسبب في إزالة الدهون من الجلد وتتسبب في تهيجات وتشققات و/أو التهابات جلدية.

ملامسة العين هناك خطورة محتملة من حدوث لسعة عابرة أو احمرار عابر في حالة حدوث ملامسة العين بشكل عرضي.

4.3 دواعي أية رعاية طبية فورية ومُعالجة خاصة مطلوبة

ملاحظات للطبيب يجب أن تتم المعالجة حسب الأعراض بشكل عام ويتم إجراؤها لتخفيف حدة التأثيرات.
في حالة استنشاق مُخلفات التحلل عند نشوب حريق، قد تظهر الأعراض ظهوراً آجلاً.
قد يكون من الضروري أن يظل الشخص المعرَّض تحت الملاحظة الطبية لـ 48 ساعة.

القسم 5: تدابير مكافحة النار

5.1 وسائل الإطفاء

وسائل الإطفاء المناسبة في حالة نشوب حريق، استخدم الاسبراي أو أجهزة الإطفاء بثاني أكسيد الكربون أو رذاذ الماء أو الرغوة المقاومة للكحول أو المادة الكيميائية الجافة.

وسائل الإطفاء غير المناسبة لا تستخدم المياه النفاثة. قد يُسبب استخدام القواطع المائية النفاثة انتشار الحريق نتيجة تطاير المنتج المحترق وتناثره.

5.2 الأخطار الخاصة الناجمة عن المادة أو الخليط

الأخطار الناجمة عن المادة أو الخليط سوف يحدث تزايد في الضغط وقد تنفجر الحاوية في حالة حدوث حريق أو تسخين.

منتجات احتراق خطِرة نواتج الاحتراق قد تشمل ما يلي:
أكاسيد الكربون (CO, CO_2)
أكاسيد النيتروجين (NO, NO_2 إلخ)

5.3 نصائح لمكافحي الحريق

إحتياطات خاصة لمكافحي الحريق يُحظر القيام بأية إجراء ينطوي على مخاطرة أو بدون تدريب مناسب. يراعى عزل المكان على الفور و ذلك بإخلاء الأفراد المتواجدين على مقربة من الحادث في حالة نشوب حريق.

معدات الحماية الشخصية والاحتياطات اللازمة لعمال الإطفاء ينبغي أن يرتدي مكافحو الحرائق التجهيزات الواقية المناسبة و جهاز تنفس مكتفي ذاتياً(SCBA) ذا وحدة كاملة للوجه يعمل في نمط الضغط الموجب. ثياب مكافحي الحريق (بما فيها الخوذات والأحذية والقفازات الواقية) التي تتفق والمعيار الأوروبي EN 469 سوف تكفل مُستوى أساسياً من الحماية من الحوادث الكيماوية.

القسم 6: تدابير مواجهة التسرب العارض

6.1 لاحتياطات الشخصية ومعدات الحماية وإجراءات الطوارئ

للأفراد من خارج فريق الطوارئ يُحظر القيام بأية إجراء ينطوي على مخاطرة أو بدون تدريب مناسب. يراعى إخلاء المناطق المجاورة. يراعى عدم السماح بالدخول لكل من لا يرتدي مهمات الواقية أو من لا حاجة لك بهم من الأفراد. يراعى تجنب ملامسة المادة المنسكبة أو السير عليها. قد تكون الأرضيات زلقة؛ يجب توخي العناية لتجنب السقوط. ارتدي مهمات الواقية الشخصية المُلائمة.

لمسعفي الطوارئ إذا لزم الأمر ارتداء ثياباً خاصة للتعامل مع الانسكاب، يُرجى أخذ ما ورد في القسم 8 من معلومات حول المواد المناسبة وغير المناسبة في الحسبان. راجع كذلك المعلومات الواردة في قسم "للأفراد من خارج فريق الطوارئ".

6.2 الاحتياطات البيئية

تجنب تناثر المادة المنسكبة وجريانها السطحي ووصولها إلى التربة و المجاري المائية والبالوعات ومجاري الصرف. يُراعى إبلاغ السلطات المعنية لو تسبب المنتج في تلوث البيئة (مجاري الصرف، المجاري المائية، التربة أو الهواء).

6.3 طرائق ومواد الاحتواء والتنظيف

انسكاب صغير يُراعى وقف التسرب إن لم ينطو ذلك على مخاطرة. يراعى نقل الأوعية من منطقة الانسكاب. يُراعى امتصاصها بمادة خاملة، ثم إيداعها إحدى الحاويات المُلائمة للتخلص من النفاية. تخلص منها عن طريق أحد مقاولي التخلص من النفايات المرخصين.

انسكاب كبير يُراعى وقف التسرب إن لم ينطو ذلك على مخاطرة. يراعى نقل الأوعية من منطقة الانسكاب. امنع دخولها في بالوعات الصرف، و المجاري المائية، أو البدرومات، أو المناطق المغلقة. يُراعى احتواء الانسكاب وجمعه بمادة ماصةٍ غير قابلة للاحتراق مثل الرمل، أو التراب، أو الفرميكيوليت، أو تراب دياتومي، ثم وضعها في إحدى الحاويات للتخلص منها بما يتفق واللوائح المحلية. تخلص منها عن طريق أحد مقاولي التخلص من النفايات المرخصين.

6.4 مرجع للأقسام الأخرى

انظر القسم 1 لمعرفة بيانات الاتصال في أحوال الطوارئ.
انظر القسم 5 الخاص بإجراءات مكافحة الحريق.
انظر القسم 8 للحصول على معلومات عن التجهيزات الوقائية الشخصية المُلائمة.
انظر القسم 12 للاطلاع على الاحتياطات البيئية.
انظر القسم 13 لمزيد من المعلومات حول مُعالجة النفايات.

القسم 7: المناولة والتخزين

7.1 احتياطات للمناولة المأمونة

احتياطات للمناولة الآمنه

ارتدي مهمات الواقية الشخصية المُلائمة. ملاحظة: المنتج المخفف بالبترول يجب التعامل معه بنفس الاحتياطات التي يتم اتخاذها عند التعامل مع البترول. قبل الخلط، يجب مراجعة نشرة بيانات الأمان للبترول للتعرف على أية تدابير وقائية يجب اتخاذها.

إرشادات حول الصحة المهنية العامة

يحظر تناول الطعام، والشراب، والتدخين في الأماكن التي يجري التعامل فيها مع هذه المادة سواء بالمناولة، التخزين أو المعالجة. يُراعى الإغتسال جيداً بعد مناولتها. اخلع الثياب المُلوَّثة والتجهيزات الوقائية قبل دخول الأماكن المخصصة للطعام. انظر القسم 8 لمزيد من المعلومات حول إجراءات الحفاظ على الصحة.

7.2 متطلبات التخزين الآمنه، بما في ذلك ما يتعلق بحالات عدم توافق المواد

خزن المادة وفقاً لتعليمات السلطات المحلية. يُخزَّن في مكان جاف، وبارد وجيد التهوية، بعيداً عن المواد غير المتوافقة (انظر القسم 10). يُراعى الحفظ بعيدا عن الحرارة وضوء الشمس المباشر. يراعى غلق الوعاء غلقا تاما محكما إلى أن يُعدّ للاستخدام. لابد من إحكام غلق الأوعية التي قد فُتِحت و تركها في وضع قائم و ذلك لتلافي حدوث تسريب. يجب أن يتم التخزين والاستعمال فقط في معدات/حاويات مصممة للاستخدام مع هذا المنتج. يُحظر التخزين في حاويات لا تحمل كتابة توضيحية.

غير ملائمة

التعرض لدرجات الحرارة العالية لفترات طويلة.

القسم 8: ضوابط التعرض/الحماية الشخصية

8.1 تدابير التحكم

حدود التعرض المهني

قيمة حد التعرض غير معروفة.

No exposure limit value known.

No exposure limit value known.

في الوقت الذي قد يُظهر حد التعرض المهني (OEL) مكونات معينة في هذا القسم، فإن مكونات أخرى قد توجد في الغبار أو البخار أو الرذاذ الناجم. لذا، فإن حد تعرض مهني معين قد لا ينطبق على المنتج ككل وإنما يدرج للإرشاد والتوجيه فقط

إجراءات المتابعة الموصى بها

تنبغي الإشارة إلى معايير المُراقبة، من مثل ما يلي: المعيار الأوروبي EN 689 (أجواء موقع العمل - إرشادات تقييم التعرض لعوامل كيماوية بالاستنشاق لمقارنتها بالقيم الحدية واستراتيجية القياس) المعيار الأوروبي EN 14042 (أجواء موقع العمل - دليل اتخاذ وتطبيق إجراءات تقييم التعرض للعوامل البيولوجية والكيماوية) المعيار الأوروبي EN 482 (أجواء موقع العمل - المتطلبات العامة لأداء إجراءات قياس العوامل الكيماوية) سيكون من المطلوب كذلك الرجوع إلى وثائق التوجيه الوطنية الخاصة بطرق تحديد المواد الخطِرة.

مستوى مشتق غير مؤثر

DNELs/DMELs غير مُتاحة.

الـ PNEC = تركّز عدم التأثير المُتوقّع

PNECs

Not available.

8.2 ضوابط التعرض

الضوابط الهندسية المناسبة

احرص على توفير تهوية للعوادم أو الوسائل الهندسية الاخرى للحماية، وذلك للإبقاء على مستويات التركيز المعنية للمواد العالقة بالهواء دون حدود التعرض المقبولة لها على الصعيد المهني.
يجب تقييم جميع الأنشطة المرتبطة بالمواد الكيميائية من حيث مخاطرها على الصحة، وذلك لضمان التحكم في معدلات التعرض بالشكل المناسب. لا يجوز تحديد معدات الوقاية الشخصية إلا بعد تقييم الأشكال الأخرى لإجراءات التحكم (على سبيل المثال عمليات التحكم الهندسية) بالشكل المناسب. يجب أن تتوافق معدات الوقاية الشخصية مع المواصفات المعنية وأن تكون مناسبة للاستخدام، ويجب الحفاظ عليها في حالة جيدة وصيانتها بشكل سليم.
يجب التشاور مع مورد معدات الوقاية الشخصية لطلب المشورة بشأن الاختيار والمواصفات المعنية. لمزيد من المعلومات، اتصل بالهيئة المحلية للمواصفات.
القرار النهائي لاختيار معدات الوقاية يعتمد على تقييم المخاطر. ومن المهم التأكد من ملاءمة جميع عناصر معدات الوقاية الشخصية.

تدابير الحماية الفردية

إجراءات النظافة الشخصية

اغسل اليدين، والذراعين، والوجه غسلاً تاماً بعد مناولة المنتجات الكيميائية، وعند الأكل والتدخين، وفي نهاية فترة العمل. تأكد من وجود محطات غسيل الأعين وأدشاش الطوارئ على مقربة من موقع العمل.

حماية تنفسية

في حالة عدم كفاية التهوية، يُراعى ارتداء تجهيزات تنفسية ملائمة.
يعتمد الاختيار الصحيح لتجهيزات حماية الجهاز التنفسي على المواد الكيميائية التي يتم التعامل معها وظروف العمل والاستخدام وحالة تجهيزات حماية الجهاز التنفسي. يجب وضع تدابير أمان تتناسب مع كل استخدام مقرر. لذلك يجب اختيار تجهيزات حماية الجهاز التنفسي بالتشاور مع المورد / الشركة الصانعة مع مراعاة التقييم الكامل لظروف العمل.

أدوات حماية الوجه/العين

نظارات أمان ذات ساترات جانبية.

حماية للجلد

القسم 8: ضوابط التعرض/الحماية الشخصية

حماية يدوية

معلومات عامة:

ظرًا لتفاوت الظروف الخاصة لبيئات العمل واختلاف ممارسات التعامل مع المواد، فيجب وضع تدابير أمان تتناسب مع كل استخدام مقرر. يعتمد الاختيار الصحيح لقفازات الحماية على المواد الكيميائية التي يتم التعامل معها وظروف العمل والاستخدام. معظم القفازات توفر الحماية لفترة زمنية محدودة فقط قبل وجود التخلص منها واستبدالها (حتى أفضل القفازات المقاومة للمواد الكيميائية تتآكل بفعل التعرض المتكرر للمواد الكيميائية).

يجب اختيار القفازات بالتشاور مع المورد / الشركة الصانعة مع مراعاة التقييم الكامل لظروف العمل.
يُنصح باستخدام: قفازات نيتريل.
الزمن اللازم للاختراق:

تُجمع بيانات زمن الاختراق من مصنعي القفاز تحت ظروف الاختبار المعملية وتمثل المدة أو الفترة المتوقعة التي يؤمن خلالها القفاز حماية من تسرب المادة أو نفاذها. ومن الأهمية بمكان مراعاة طبيعة ظروف العمل الفعلية عند اتباع توصيات زمن الاختراق. ويتعين دائمًا التشاور مع مورد القفازات للوقوف على معلومات تقنية وفنية محدثة بشأن زمن الاختراق لنوع القفاز الموصى به.
فيما يلي توصياتنا بخصوص اختيار القفازاتs:

الملامسة المستمرة:

قفازات بفترة اختراق لا تقل عن 240 دقيقة، أو >480 دقيقة، إذا أمكن الحصول على قفازات مناسبة.
إذا لم تتوفر قفازات مناسبة تضمن الحماية بهذا المستوى، فمن الممكن استخدام قفازات بفترات حماية أقل طالما هناك قواعد مناسبة يتم الالتزام بها لصيانة القفازات واستبدالها.

الحماية من الرذاذ قصيرة الأجل

توصيات فترات الاختراق كما سبق.
يمكن في المعتاد استخدام القفازات ذات فترات الاختراق القصيرة للأعمال التي يتم فيها التعرض للزيوت لفترات قصيرة وعابرة. لذلك، يجب أن تكون هناك قواعد مناسبة يتم الالتزام بها بشكل تام لصيانة القفازات واستبدالها.
سُمك القفاز:

بالنسبة للاستخدامات العامة، فإننا نوصى بقفاز بسُمك يزيد على 0.35 مم.

يجب التأكيد والتشديد أن سُمك القفاز لا يمثل بالضرورة مؤشرًا موثوقا على مقاومة القفاز لمادة كيميائية معينة، ذلك أن كفاءة مقاومة التسرب للقفاز ستكون معتمدة على تركيب المادة المصنعة منها القفاز تحديدًا. لذا فإن اختيار القفاز يجب أن يستند على عوامل ومتطلبات المهمة ومعرفة بأزمان الاختراق.
كذلك قد يتنوع سُمك القفاز بناء على مُصنع القفاز، ونوع القفاز وموديل القفاز. لذا، يجب أخذ بيانات المصنع الفنية بالحسبان وذلك لضمان القفاز الأكثر مناسبة للمهمة.

ملاحظة: اعتمادًا على نوع النشاط قيد الممارسة، فإن القفازات ذات السُمك المختلف قد تكون مطلوبة لمهام مُحددة. على سبيل المثال:

• قد يتطلب الأمر القفازات الرقيقة (بسُمك يبلغ 0.1 مم أو أقل) متى تطلب الأمر درجة من المهارة اليدوية والبراعة. ومع ذلك، فإن مثل هذه القفازات ينتظر منها أن توفر الحماية لفترة قصيرة، وعادة ما تكون للاستخدام مرة واحدة ثم يجري التخلص منها.

• قد تبرز الحاجة لقفازات أكثر سُمكًا (حتى 3 مم أو أكثر) في حالة المخاطر الميكانيكية (وكذلك الكيميائية)؛ أي متى كان هناك احتمال للتآكل أو القشط أو الثقب.

الجلد والجسم

استخدام الملابس الواقية يعتبر من الممارسات الجيدة في المجال الصناعي.
يجب انتقاء التجهيزات الشخصية الواقية للجسم بما يتفق والمهمة التي يجري القيام بها والمخاطر التي تنطوي عليها، كما يجب أن يعتمدها أحد المختصين قبل التعامل مع هذا المنتج.
أفرولات العمل المصنوعة من القطن أو البوليستر/القطن توفر الحماية فقط من التلوث السطحي الخفيف الذي لا يصل إلى الجلد. ويجب غسل أفرولات العمل بصفة منتظمة. عندما تزداد خطورة تعرض الجلد للمواد (على سبيل المثال عند تنظيف المواد المنسكبة أو في حالة وجود خطورة من تناثر الرذاذ)، فيجب ارتداء مريلة مقاومة للمواد الكيميائية و/أو أحذية وسترات غير منفذة للمواد الكيميائية.

يتعين مراجعة المعايير:

حماية تنفسية: EN 529
قفازات: EN 420, EN 374
حماية للعين: EN 166
الترشيح نصف الوجهي: EN 149
الترشيح نصف الوجهي ذي الصمام: EN 405
قناع نصفي: EN 140 مرشح إضافي
قناع وجهي كامل: EN 136 مرشح إضافي
مرشحات الجزئيات: EN 143
مرشحات الغاز/ المشتركة: EN 14387

ضوابط التعرض البيئي

ننصح بفحص الإنبعاثات الصادرة من أجهزة العمل والتهوية، للتأكد من استيفائها لمتطلبات قانون حماية البيئة. في بعض الحالات، قد يكون من الضروري استخدام أجهزة إمتصاص الدُّخان، أو المُرشِّحات أو إجراء تعديلاتٍ هندسية للمُعِدَّات، كي يتسنى تقليل الانبعاثات إلى مستويات مقبولة.

القسم 9: الخصائص الفيزيائية والكيميائية

9.1 معلومات حول الخواص الكيميائية والفيزيائية الأساسية

المظهر

الحالة الفيزيائية	سائل.
اللون	كهرمان.
الرائحة	غير متوفرة.
عتبة الرائحة	غير متوفرة.
الأس الهيدروجيني pH	غير قابل للتطبيق.
نقطة الانصهار/نقطة التجمد	غير متوفرة.
نقطة الغليان الأوّلية ونطاق الغليان	غير متوفرة.
نقطة الإنسكاب	-27 °C
نقطة الوميض	كأس مغلق: 202°C (395.6 ف) [جهاز بنسكي-مارتينز ASTM D 93]
معدل التبخر	غير متوفرة.
Flammability	غير متوفرة.
الحد الأدنى والأقصى للانفجار	غير متوفرة.
الضغط البخاري	غير متوفرة.
الكثافة البخارية	غير متوفرة.
Density and/or Relative density	غير متوفرة.
Density and/or Relative density	1000< كجم/م³ (1< g/cm³) عند 15°C

الذوبانية (نيات)

النتيجة	وسائل الإعلام
غير قابل للذوبان	الماء

Partition coefficient n-octanol/ water (log value)	غير قابل للتطبيق.
درجة حرارة الاشتعال الذاتي	غير متوفرة.
درجة حرارة الانحلال	غير متوفرة.
Kinematic viscosity	كينماتي: 178 mm²/S (178 سنتي ستوك) عند 40°C كينماتي: 17.5 إلى 22.49 mm²/S (17.5 إلى 22.49 سنتي ستوك) عند 100°C
الخواص الانفجارية	غير متوفرة.
خواص مؤكسِدة	غير متوفرة.

9.2 المعلومات الأخرى

ليس هناك مزيد من المعلومات.

القسم 10: الثبات الكيميائي والقابلية للتفاعل

10.1 التفاعلية

غير متاح بيانات اختبار أخرى معينة لهذا المنتج. ارجع إلى الظروف التي يجب تجنبها والمواد غير المتوافقة لمزيد من المعلومات.

10.2 الثبات الكيميائي

المُنتَج ثابت.

10.3 إمكانية التفاعلات الخطرة

لن تحدث تفاعلات خطِرة في ظروف التخزين والاستخدام العادية.
لن تحدث بلمرة خطِرة في ظروف التخزين والاستخدام العادية.

10.4 الظروف التي ينبغي تجنبها

يجب تجنب جميع مصادر الاشتعال الممكنة (شرر أو لهب).

10.5 المواد غير المتوافقة

تتفاعل أو غير متطابقة مع المواد التالية: مواد مؤكسِدة.

10.6 نواتج الانحلال الخطرة

في ظروف التخزين والاستخدام العادية، من غير المنتظر أن تتولّد نواتج تحلل خطِرة.

القسم 11: المعلومات السمومية

11.1 المعلومات المتعلقة بفئات المخاطر على النحو المحدد في لائحة (مجلس الاتحاد الأوروبي) رقم 1272/2008

سمية حادة

Result	Product/ingredient name
Rat - Oral - LD50 >2000 mg/kg OECD 423	N-[(1,1,3,3-tetramethylbutyl)phenyl]naphthalen-1-amine
Rat - Dermal - LD50 >2000 mg/kg OECD 402	

Conclusion/Summary [Product]

تقديرات السمية الحادة

غير متوفرة.

Skin corrosion/irritation

Result	Product/ingredient name
RhE - Skin - Non-irritant to skin. OECD 439	N-[(1,1,3,3-tetramethylbutyl)phenyl]naphthalen-1-amine

Conclusion/Summary [Product] Not available.

Serious eye damage/eye irritation

Result	Product/ingredient name
RhCE - Eyes - Non-irritating to the eyes. OECD 492	N-[(1,1,3,3-tetramethylbutyl)phenyl]naphthalen-1-amine
BCOP - Eyes - Non-irritating to the eyes. OECD 437	

Conclusion/Summary [Product] Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] Not available.

Respiratory or skin sensitization

Result	Product/ingredient name
Guinea pig - skin OECD 406 Result: Not sensitising	N-[(1,1,3,3-tetramethylbutyl)phenyl]naphthalen-1-amine

Skin

Conclusion/Summary [Product] Not available.

Respiratory

Conclusion/Summary [Product] Not available.

Germ cell mutagenicity

Result	Product/ingredient name
In vitro - Bacteria OECD [Bacterial Reverse Mutation Test] Result: Negative	N-[(1,1,3,3-tetramethylbutyl)phenyl]naphthalen-1-amine
In vitro - Mammal - species unspecified OECD [In vitro Mammalian Cell Gene Mutation Test] Result: Negative	

In vitro - Mammal - species unspecified
OECD [In vitro Mammalian Chromosomal Aberration Test]
Result: Negative

Conclusion/Summary [Product] Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] Not available.

Reproductive toxicity

Product/ingredient name	Result
N-[(1,1,3,3-tetramethylbutyl)phenyl]naphthalen-1-amine	**Rat - Oral** OECD 422 Maternal toxicity: Negative Fertility effects: Negative Developmental: Negative

Conclusion/Summary [Product] Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

آثار صحية حادة كامنة

استنشاق التعرض لمنتوجات التحلل قد يشكل خطورة صحية. قد تتأجل بعض التأثيرات الخطيرة عقب التعرض.

الابتلاع لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

ملامسة الجلد يزيل دهون الجلد. قد تسبب جفاف الجلد وتهيُّجه.

ملامسة العين انظر: القسم 11 . المعلومات السمية - آثار صحية حادة كامنة: ملامسة العين

أعراض متعلقة بالخواص السمية والكيميائية والفيزيائية

استنشاق قد يؤدي إلى ضرر في حالة الاستنشاق في حالة التعرض للأبخرة أو الرذاذ أو العوادم الناتجة عن التحلل الحراري للمنتجات.

الابتلاع ليست هناك بيانات معينة.

ملامسة الجلد الأعراض الضائرة قد تشمل ما يلي:
تهيُّج
الجفاف
التشقق

ملامسة العين ليست هناك بيانات معينة.

التأثيرات المتأخرة والفورية وكذلك التأثيرات المزمنة نتيجة للتعرض القصير والطويل الأمد

استنشاق التعرض الزائد لاستنشاق الجزيئات المتطايرة في الهواء أو الإيروسولات قد يتسبب في تهيج الجهاز التنفسي.

الابتلاع ابتلاع كميات كبيرة يمكن أن يؤدي إلى الغثيان والإسهال.

ملامسة الجلد الملامسة بشكل متكرر أو لفترات طويلة يمكن أن تتسبب في إزالة الدهون من الجلد وتتسبب في تهيجات وتشققات و/أو التهابات جلدية.

ملامسة العين هناك خطورة محتملة من حدوث لسعة عابرة أو احمرار عابر في حالة حدوث ملامسة العين بشكل عرضي.

آثار صحية مزمنة كامنة

عامة لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

السرطنة لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

التأثير على الجينات لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

التأثيرات النمائية لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

التأثيرات الخصوبية لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

11.2 المعلومات المتعلقة بالمخاطر الأخرى

القسم 11: المعلومات السمومية

11.2.1 خصائص اضطراب الغدد الصماء

لا تحتوي هذه المادة/هذا المزيج على أي مكونات تعتبر ذات خصائص مسببة لاضطرابات الغدد الصماء.

Remarks - Endocrine dirsupting properties for human health Summary/ Conclusion (All ingredients) غير متوفرة.

11.2.2 المعلومات الأخرى

غير متوفرة.

القسم 12: المعلومات الإيكولوجية

12.1 السمية

Product/ingredient name	Result
N-[(1,1,3,3-tetramethylbutyl)phenyl]naphthalen-1-amine	**Acute - ErC50** OECD 201 Algae >100 mg/l [72 hours] **Acute - EC50** OECD 202 Daphnia >100 mg/l [48 hours] **Acute - LC50** OECD 203 Fish >100 mg/l [96 hours] **Chronic - NOEC** OECD 201 Algae 100 mg/l [72 hours]

الأخطار البيئية غير مُصنَّفة كمادة خطِرة

12.2 الثبات والتحلل

قابلية جزئية على التحلل الحيوي.

Product/ingredient name	Result
N-[(1,1,3,3-tetramethylbutyl)phenyl]naphthalen-1-amine	OECD 301B 0% [28 days] - Not readily

12.3 القدرة على التراكم الأحيائي

لايُتوقع أن يتراكم هذا المنتَج حيوياً في البيئة من خلال السلاسل الغذائية.

اسم المُكوّن/المنتَج	LogPow	BCF	إمكانية
N-phenyl-1,1,3,3-tetramethylbutylnaphthalen-1-amine	>8	-	عالٍ

12.4 القابلية على التحرك عبر التربة

Soil/water partition coefficient

Not available.

Results of PMT and vPvM assessment

vM	vP	vPvM	T	M	P	PMT	Product/ingredient name
No	No	No	No	No	No	No	N-[(1,1,3,3-tetramethylbutyl)phenyl]naphthalen-1-amine

Mobility Spillages may penetrate the soil causing ground water contamination.

Conclusion/Summary The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 نتائج مأخوذة من تقييم الـ PBT (البقاء والسمية والتراكم البيولوجي) والـ vPvB (البقاء الشديد والتراكم البيولوجي الشديد)

المنتج لا يُلبي معايير ثبات المواد والتراكمية الأحيائية والسمية PBT أو معايير شدة الثبات وشدة التراكمية الأحيائية وفق لائحة المجلس الأوروبي رقم 1907/2006، الملحق XIII.

Regulation (EC) No. 1907/2006 [REACH]

القسم 12: المعلومات الإيكولوجية

	vP	vPvB	T	B	P	PBT	Product/ingredient name
N/A	N/A	N/A	No	N/A	N/A	No	N-[(1,1,3,3-tetramethylbutyl) phenyl]naphthalen-1-amine

Regulation (EC) No. 1272/2008 [CLP]

	vP	vPvB	T	B	P	PBT	Product/ingredient name
No	No	No	No	No	No	No	N-[(1,1,3,3-tetramethylbutyl) phenyl]naphthalen-1-amine

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 التأثيرات الضارة الأخرى

Not available.

Conclusion/Summary [Product] This substance/mixture does not contain any components that are considered to have endocrine disrupting properties.

معلومات بيئية أخرى قد تتسبب السوائل المنسكبة في تكوين طبقة على أسطح الماء، وقد تتسبب في ضرر مادي للكائنات الحية. وقد يتم إعاقة نقل الإكسجين أيضًا.

12.7 Other adverse effects No known significant effects or critical hazards.

القسم 13: الاعتبارات المتعلقة بتصريف المواد والتخلص منها

13.1 طرق مُعالجة النفاية

المُنتَج

طرق التخلص السليم من النفاية إذا أمكن، قم بتحضير المنتج لإعادة تدويره. يجب أن يتم التخلص من المواد بمعرفة شخص معتمد / جهة معتمدة للتخلص من النفايات وفقًا للقواعد المحلية.

نفاية خطِرة نعم.

قائمة النفايات الأوروبية (EWC)

كود النفاية	تعيين النفاية
13 02 08*	زيوت أخرى للتزليق وللمحركات والتروس

ومع ذلك فإن الخروج عن الاستخدام المعد والمقصود بداية و/أو وجود أي مواد ملوثة محتملة قد يتطلب من المستخدم النهائي وضع وتعيين كود بديل للتخلص من النفايات.

التغليف

طرق التخلص السليم من النفاية إذا أمكن، قم بتحضير المنتج لإعادة تدويره. يجب أن يتم التخلص من المواد بمعرفة شخص معتمد / جهة معتمدة للتخلص من النفايات وفقًا للقواعد المحلية.

الاحتياطات الخاصة لابد أن يجري التخلص من هذا المنتج وحاويته بطريقة آمنة. قد تظل بعض رواسب المنتج عالقة بالحاويات الفارغة أو قُمصانها. تجنب تناثر المادة المنسكبة وجريانها السطحي ووصولها إلى التربة و المجاري المائية والبالوعات ومجاري الصرف.

المراجع اللجنة EU/2014/955
التوجيه EC/2008/98

القسم 14: المعلومات المتعلقة بالنقل

	ADR/RID	ADN	IMDG	IATA
14.1 الرقم بالأمم المتحدة أو الرقم التعريفي	غير مقننة.	غير مقننة.	غير مقننة.	غير مقننة.
14.2 اسم الشحن الصحيح الخاص بالأمم المتحدة	-	-	-	-
14.3 فئة/فئات مخاطر النقل	-	-	-	-
14.4 مجموعة التعبئة	-	-	-	-
14.5 الأخطار البيئية	لا.	لا.	لا.	لا.
معلومات إضافية	-	-	-	-

القسم 14: المعلومات المتعلقة بالنقل

14.6 احتياطات خاصة للمُستخدم غير متوفرة.

14.7 النقل البحري سائباً بحسب اتفاقيات المنظمة البحرية الدولية (IMO) غير متوفرة.

القسم 15: المعلومات التنظيمية

15.1 تشريع/لوائح السلامة والصحة والبيئة الخاصة بالمادة أو الخليط

تنظيم (المجلس الأوروبي) رقم 1907/2006 (تسجيل الكيماويات وتقييمها وترخيصها (REACH)

المُلحق الرابع عشر؛ قائمة المواد الخاضعة للترخيص

المُلحق الرابع عشر

لم يُدرج أيٌّ من المكونات.

مواد مُقلقة للغاية

None of the components are listed.

لوائح أخرى

الوضع وفق REACH (النظام المتعلق بتسجيل وتقييم وترخيص المواد الكيماوية) تقوم الشركة، كما هو موضح في القسم 1، ببيع هذا المنتَج في الاتحاد الأوروبي وفقًا لمتطلبات هيئة REACH الحالية.

قائمة الولايات المتحدة (8b TSCA) جميع المكونات تحمل الصفة "فعالة" أو الصفة "مستثناة".

مخزون أستراليا (AICS) كافة المُكوّنات مُدرجة بالقائمة أو مُستثناة منها.

قائمة كندا كافة المُكوّنات مُدرجة بالقائمة أو مُستثناة منها.

قائمة الصين (IECSC) كافة المُكوّنات مُدرجة بالقائمة أو مُستثناة منها.

قائمة اليابان (CSCL) كافة المُكوّنات مُدرجة بالقائمة أو مُستثناة منها.

قائمة كوريا (KECI) كافة المُكوّنات مُدرجة بالقائمة أو مُستثناة منها.

قائمة الفلبين (PICCS) كافة المُكوّنات مُدرجة بالقائمة أو مُستثناة منها.

مخزون تايوان من المواد الكيميائية (TCSI) كافة المُكوّنات مُدرجة بالقائمة أو مُستثناة منها.

مواد مستنفدة للأوزون (EU/1005/2009)

لم ترد بالقائمة.

الموافقة المسبقة عن علم (PIC) (EU/649/2012)

لم ترد بالقائمة.

توجيه سيفيسو

هذا المنتج لا يحكمه التوجيه سيفيسو.

اللوائح الوطنية

فرنسا

15.2 تقييم مأمونية الكيماويات

تم إجراء تقييم سلامة كيميائية لواحدة أو أكثر من مواد هذا المزيج. لم يتم إجراء تقييم سلامة كيميائية لهذا المزيج نفسه.

القسم 16: المعلومات الأخرى

الاختصارات

الـ ADN = اللوائح الأوروبية الخاصة بالنقل الدولي للبضائع الخطيرة عبر المجاري المائية الداخلية
الـ ADR = الاتفاقية الأوروبية المتعلقة بنقل البضائع الخطيرة الدولي براً
ATE = تقدير السمية الحادة
الـ BCF = مُعامل التركز الحيوي
CAS = خدمة الملخصات الكيميائية
CLP = تنظيم التصنيف والتوسيم والتعبئة [لائحة (EC) رقم 1272/2008]
الـ CSA = تقييم السلامة الكيماوية
الـ CSR = تقرير السلامة الكيماوية
الـ DMEL = مستوى التأثير الأدنى المُشتَق
الـ DNEL = مستوى عدم التأثير المُشتق
EINECS = القائمة الأوروبية للمواد الكيميائية المتوفرة تجاريا
ES = سيناريو التعرض
بيان EUH = بيان الأخطار الخاصة بتنظيم التصنيف والتوسيم والتعبئة
EWC = فهرس النفاية الأوروبية
GHS = النظام المتوافق عالمياً لتصنيف وتوسيم المواد الكيميائية
الـ IATA = رابطة النقل الجوي الدولي
الـ IBC = حاوية سوائب وسيطة
الـ IMDG = البحرية الدولية للبضائع الخطِرة

القسم 16: المعلومات الأخرى

LogPow = لوغاريتم معامل تجزئة الأوكتانول/الماء
الـ MARPOL = المُعاهدة الدولية لمنع التلوث الناجم عن السفن، 1973 المُعدَّلة بموجب بروتوكول 1978. ("ماربول" = التلوث البحري)
OECD = منظمة التعاون الأقتصادي والتنمية
PBT = باقية وسامة ومتراكمة بيولوجيا
الـ PNEC = تركُز عدم التأثير المُتوقَّع
REACH = التنظيم المتعلق بتسجيل وتقييم وترخيص المواد الكيماوية [نظام (المفوضية الأوروبية) رقم 1907/2006]
RID = التنظيمات الدولية لحمل البضائع الخطرة عبر السكك الحديدية
RRN = رقم التسجيل في التنظيم المتعلق بتسجيل وتقييم وترخيص المواد الكيماوية (REACH)
SADT = درجة حرارة التحلل المتسارع ذاتياً
SVHC = مواد مثيرة لقلق شديد
STOT-RE = السمية الموجهة إلى عضو مستهدف- عند تكرار التعرض
STOT-SE = السمية الموجهة إلى عضو مستهدف - عند التعرض لمرة واحدة
TWA = المتوسط الزمني المرجح
UN = الأمم المتحدة
UVCB = مادة هيدُروكرْبُونية مركبة
الـ VOC = مُركب عضوي مُتطاير
vPvB = شديد البقاء وشديد التراكم البيولوجي
متنوع = قد يحتوي على واحد أو أكثر من المكونات التالية 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / 64741-96-4/ 01-2119487081-40 RRN / 64741-95-3 ,01-2119487067-30 RRN / 64742-44-5 ,01-2119488707-21 RRN / 64742-01-4 ,01-2119483621-38 RRN / 64742-53-6 ,01-2119467170-45 RRN / 64742-52-5 ,64742-45-6 ,01-2119985177-24 RRN / 64742-55-8 ,01-2119484627-25 RRN / 64742-54-7 ,01-2119480375-34 RRN / 64742-57-0 ,01-2119480132-48 RRN / 64742-56-9 ,01-2119487077-29 RRN ,64742-63-8 ,01-2119480472-38 RRN / 64742-62-7 ,64742-58-1 ,01-2119489287-22 RRN / 72623-85-9 ,01-2119487080-42 RRN / 64742-70-7 ,01-2119471299-27 RRN / 64742-65-0 / 72623-87-1 ,01-2119474878-16 RRN / 72623-86-0 ,01-2119555262-43 RRN
01-2119474889-13 RRN

الإجراء المُستخدم لاشتقاق التصنيف بحسب تنظيم (المفوضية الأوروبية) رقم 1272/2008 [النظام المتوائم عالمياً (GHS)/التصنيف والوسم والتعبئة (CLP)]

التصنيف	التبرير
غير مُصنَّفة.	

نص بيانات الأخطار المُختصرة كاملاً	قد يسبب للحياة المائية تأثيرات ضارة طويلة الأمد.	H413
نص التصنيفات كاملاً [التصنيف والوسم والتعبئة (CLP)/ النظام المتوائم عالمياً(GHS)]	الخطورة البيئية المائية (طويلة الأمد) - الفئة 4	Aquatic Chronic 4

السيرة

تاريخ الإصدار/ تاريخ المراجعة	09/10/2025.
تاريخ الإصدار السابق	
من إعداد	Product Stewardship

تشير إلى معلومات تم تغييرها مقارنة بالنسخة التي سبق إصدارها.

ملاحظة للقارىء الكريم

تم اتخاذ جميع الخطوات المتاحة المعقولة لضمان دقة نشرة البيانات هذه والمعلومات المتعلقة بالصحة والأمان والبيئة حسب البيانات الموضحة أدناه. لا يوجد ضمان أو تفويض، صريح أو ضمني، بشأن دقة أو اكتمال البيانات والمعلومات الواردة في نشرة البيانات هذه.

تسري البيانات والنصائح المعطاة في حالة بيع المنتج للتطبيق المذكور أو التطبيقات المذكورة. لا يجوز لك استخدام المنتج في غير التطبيق المذكور أو التطبيقات المذكورة دون طلب المشورة من شركة Group BP.

يجب على المستخدم تقييم هذا المنتج واستخدامه بشكل آمن بما يتوافق مع جميع القوانين والتشريعات المعمول بها. لا تتحمل شركة Group BP أية مسؤولية عن أي ضرر أو إصابة تنتج عن الاستخدام، أو أي استخدام آخر بخلاف استخدام المنتج المذكور للخامة، أو في حالة عدم مراعاة التوصيات، أو المخاطر المتأصلة في طبيعة الخامة. القائمون بشراء المنتج لتوريده إلى طرف ثالث للاستخدام في العمل عليهم اتخاذ جميع الخطوات اللازمة للتأكد من أن أي شخص يستخدم المنتج يكون على دراية بالمعلومات الواردة في هذه النشرة. يجب على أصحاب العمل إبلاغ الموظفين لديهم وغيرهم من الأشخاص المعنيين بالمخاطر الموضحة في هذه النشرة وعن الاحتياطات الواجب اتخاذها. يمكنك الاتصال بشركة Group BP للتأكد من أن هذا المستند على أحدث وضع. ممنوع منعًا باتًا إجراء تغيير على هذا المستند.

يتفق ولائحة (المجموعة الأوروبية) رقم 1907/2006 (تشريع تقييم المواد الكيميائية وتسجيلها وإقرارها (REACH))، الملحق 2، بصيغته المعدلة بلائحة (الاتحاد الأوروبي) رقم 2020/878