

Castrol Transmax Manual FE 75W

## Section 1. Identification

<b>GHS product identifier</b>	Castrol Transmax Manual FE 75W
<b>Product code</b>	469681-DE01
<b>SDS no.</b>	469681
<b>Relevant identified uses of the substance or mixture and uses advised against</b>	
<b>Use of the substance/ mixture</b>	Manual transmission fluid For specific application advice see appropriate Technical Data Sheet or consult our company representative. Manual transmission fluid For specific application advice see appropriate Technical Data Sheet or consult our company representative.
<b>Supplier</b>	BP Taiwan Marketing Limited Level 57-1, TAIPEI 101 Tower, No. 7, Section 5, Xinyi Road, Taipei, 11049, Taiwan, R.O.C.  Tel: +886 70 1011 9900 Carechem: +886 2 8793 3212 (24/7)
<b>EMERGENCY TELEPHONE NUMBER</b>	

## Section 2. Hazards identification

<b>Classification of the substance or mixture</b>	AQUATIC TOXICITY (ACUTE) - Category 3 AQUATIC TOXICITY (CHRONIC) - Category 3
<b>GHS label elements</b>	
<b>Signal word</b>	No signal word.
<b>Hazard statements</b>	H412 - Harmful to aquatic life with long lasting effects.
<b>Precautionary statements</b>	
<b>Prevention</b>	P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand.
<b>Response</b>	P273 - Avoid release to the environment.
<b>Storage</b>	Not applicable.
<b>Disposal</b>	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
<b>Other hazards which do not result in classification</b>	Defatting to the skin.

## Section 3. Composition/information on ingredients

**Substance/mixture** Mixture  
Highly refined base oil (IP 346 DMSO extract < 3%). Synthetic base stock. Proprietary performance additives.

Chinese name	% (w/w)	CAS number	Type
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	≥50 - ≤75	72623-87-1	[1] [2]
Dec-1-ene, homopolymer, hydrogenated	≥10 - ≤25	68037-01-4	[1]
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	≥10 - ≤25	68037-01-4	[1]
Distillates (petroleum), hydrotreated heavy paraffinic	≤3	64742-54-7	[2]
Distillates (petroleum), solvent-dewaxed heavy paraffinic	≤3	64742-65-0	[1] [2]

**Product name** Castrol Transmax Manual FE 75W

**Product code** 469681-DE01

Page: 1/15

**Version** 5.07 **Date of issue** 03/07/2024.

**Format** Taiwan

**Language** ENGLISH

Taiwan

(ENGLISH)

## Section 3. Composition/information on ingredients

Distillates (petroleum), solvent-refined heavy paraffinic	≤3	64741-88-4	[2]
reaction mass of: triphenylthiophosphate and tertiary butylated phenyl derivatives	<1	192268-65-8	[1]
zinc isodecyl phosphorodithioate	≤0.3	25103-54-2	[1]
2,6-di-tert-butylphenol	≤0.3	128-39-2	[1]
物品名稱	% (w/w)	化學文摘社登記號碼(CAS No.)	類型
潤滑油(石油), C20-50, 氫化中性油基	≥50 - ≤75	72623-87-1	[1] [2]
Dec-1-ene, homopolymer, hydrogenated	≥10 - ≤25	68037-01-4	[1]
1-癸烯, 同元聚合物, 氫化 1-癸烯, 低聚合物, 氫化	≥10 - ≤25	68037-01-4	[1]
氫化處理的重質蠟族石油餾分	≤3	64742-54-7	[2]
溶劑脫蠟重質蠟族石油餾分	≤3	64742-65-0	[1] [2]
溶劑精製的重石蠟烴餾份(石油)	≤3	64741-88-4	[2]
以下物質的反應量: 三苯硫磷和叔丁基苯衍生物	<1	192268-65-8	[1]
zinc isodecyl phosphorodithioate	≤0.3	25103-54-2	[1]
2,6-二-三-丁苯酚	≤0.3	128-39-2	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

#### Inhalation

If inhaled, remove to fresh air. Get medical attention if symptoms occur.

#### Ingestion

Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if adverse health effects persist or are severe.

#### Skin contact

Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur. If skin irritation or rash occurs: Get medical advice/attention.

#### Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.

#### Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training.

### Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

### Indication of immediate medical attention and special treatment needed, if necessary

#### Specific treatments

No specific treatment.

#### Notes to physician

Treatment should in general be symptomatic and directed to relieving any effects.

## Section 5. Firefighting measures

### Extinguishing media

**Suitable extinguishing media** Use foam or all-purpose dry chemical to extinguish.

**Unsuitable extinguishing media** Do not use water jet.

**Specific hazards arising from the chemical** Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects.

**Hazardous thermal decomposition products** Combustion products may include the following:  
carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)

**Special protective actions for fire-fighters** No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

**Special protective equipment for fire-fighters** Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## Section 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures** Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

**Environmental precautions** Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### Methods and material for containment and cleaning up

**Small spill** Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

## Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Avoid contact of spilt material and runoff with soil and surface waterways.

**Advice on general occupational hygiene** Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. Contaminated work clothing should not be allowed out of the workplace. See also Section 8 for additional information on hygiene measures.

**Conditions for safe storage, including any incompatibilities** Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

**Not suitable** Prolonged exposure to elevated temperature

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

**TW Ministry of Labor, labor permissible workplace exposure standards, allowable concentration (Taiwan). [Oil mist]**

STEL: 10 mg/m<sup>3</sup> 15 minutes. Issued/

Revised: 1/2005 Form: Mist

TWA: 5 mg/m<sup>3</sup> 8 hours. Issued/Revised:  
1/2005 Form: Mist

Distillates (petroleum), hydrotreated heavy paraffinic

**TW Ministry of Labor, labor permissible workplace exposure standards, allowable concentration (Taiwan). [Oil mist]**

STEL: 10 mg/m<sup>3</sup> 15 minutes. Issued/

Revised: 1/2005 Form: Mist

TWA: 5 mg/m<sup>3</sup> 8 hours. Issued/Revised:  
1/2005 Form: Mist

Distillates (petroleum), solvent-dewaxed heavy paraffinic

**TW Ministry of Labor, labor permissible workplace exposure standards, allowable concentration (Taiwan). [Oil mist]**

STEL: 10 mg/m<sup>3</sup> 15 minutes. Issued/

Revised: 1/2005 Form: Mist

TWA: 5 mg/m<sup>3</sup> 8 hours. Issued/Revised:  
1/2005 Form: Mist

Distillates (petroleum), solvent-refined heavy paraffinic

**TW Ministry of Labor, labor permissible workplace exposure standards, allowable concentration (Taiwan). [Oil mist]**

STEL: 10 mg/m<sup>3</sup> 15 minutes. Issued/

Revised: 1/2005 Form: Mist

TWA: 5 mg/m<sup>3</sup> 8 hours. Issued/Revised:  
1/2005 Form: Mist

#### Biological exposure indices

No exposure indices known.

#### Recommended monitoring procedures

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

#### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

##### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing.

Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

##### Eye protection

Safety glasses with side shields.

##### Skin protection

## Section 8. Exposure controls/personal protection

### Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

### Body protection

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

### Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

<b>Physical state</b>	Liquid.
<b>Colour</b>	Brown.
<b>Odour</b>	Not available.
<b>Odour threshold</b>	Not available.
<b>pH</b>	Not applicable.
<b>Melting point/freezing point</b>	Not available.
<b>Boiling point, initial boiling point, and boiling range</b>	Not available.
<b>Drop Point</b>	Not available.
<b>Flash point</b>	Open cup: >220°C (>428°F) [Cleveland ASTM D 92]
<b>Evaporation rate</b>	Not available.
<b>Flammability</b>	Not available.
<b>Lower and upper explosion limit/flammability limit</b>	Not applicable. Based on - Physical state
<b>Vapour pressure</b>	Not available.

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	<0.07501	<0.01	ASTM D 5191			
Dec-1-ene, homopolymer, hydrogenated	<0.0041	<0.00055	ASTM E 1194-87			
Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191			
Distillates (petroleum),	<0.07501	<0.01	ASTM D 5191			

## Section 9. Physical and chemical properties

solvent-dewaxed heavy paraffinic						
Distillates (petroleum), solvent-refined heavy paraffinic	<0.07501	<0.01	ASTM D 5191			

**Relative vapour density** Not available.  
**Relative density** Not available.  
**Density** <1000 kg/m<sup>3</sup> (<1 g/cm<sup>3</sup>) at 15°C  
**Solubility(ies)**

Media	Result
water	Not soluble

**Partition coefficient: n-octanol/water** Not applicable.

**Auto-ignition temperature**

Ingredient name	°C	°F	Method
Dec-1-ene, homopolymer, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159

**Decomposition temperature** Not available.

**Viscosity** Kinematic: 32.2 mm<sup>2</sup>/s (32.2 cSt) at 40°C  
Kinematic: 6.3 to 6.8 mm<sup>2</sup>/s (6.3 to 6.8 cSt) at 100°C (ASTM D 445)

### Particle characteristics

**Median particle size** Not applicable.

## Section 10. Stability and reactivity

**Reactivity** No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.

**Chemical stability** The product is stable.

**Possibility of hazardous reactions** Under normal conditions of storage and use, hazardous reactions will not occur.  
Under normal conditions of storage and use, hazardous polymerisation will not occur.

**Conditions to avoid** Avoid all possible sources of ignition (spark or flame).

**Incompatible materials** Reactive or incompatible with the following materials: oxidising materials.

**Hazardous decomposition products** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Test	Species	Result	Exposure	Remarks
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours	Based on studies with similar substances.
	LD50 Dermal	Rat	>5000 mg/kg	-	Based on studies with similar substances.
	LD50 Oral	Rat	>5000 mg/kg	-	Based on studies with similar substances.
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	LD50 Dermal	Rat	>2000 mg/kg	-	Based on studies with similar substances.
	LD50 Oral	Rat	>2000 mg/kg	-	-
Distillates (petroleum),	LD50 Dermal	Rabbit	>5000 mg/kg	-	Based on

## Section 11. Toxicological information

hydrotreated heavy paraffinic	LD50 Oral	Rat	>5000 mg/kg	-	studies with similar substances. Based on studies with similar substances.
	LD50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours	Based on studies with similar substances.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours	Based on studies with similar substances.
	LD50 Dermal	Rat	>2000 mg/kg	-	Based on studies with similar substances.
	LD50 Oral	Rat	>5000 mg/kg	-	Based on studies with similar substances.
reaction mass of: triphenylthiophosphate and tertiary butylated phenyl derivatives	LD50 Dermal	Rabbit	>2000 mg/kg	-	-
	LD50 Oral	Rat	>2000 mg/kg	-	-
zinc isodecyl phosphorodithioate	LD50 Dermal	Rat	>5000 mg/kg	-	Based on studies with similar substances.
	LD50 Oral	Rat	3100 mg/kg	-	Based on studies with similar substances.
2,6-di-tert-butylphenol	LD50 Dermal	Rabbit	>5000 mg/kg	-	-
	LD50 Oral	Rat	>5000 mg/kg	-	-

### Irritation/Corrosion

Product/ingredient name	Species	Result	Score	Exposure	Observation	Remarks
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	Rabbit	Eyes - Severe irritant	-	-	-	Based on studies with similar substances.
	Rabbit	Skin - Non-irritant to skin.	-	-	-	Based on studies with similar substances.
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	Rabbit	Eyes - Non-irritating to the eyes.	-	-	-	Based on studies with similar substances.
	Rabbit	Skin - Non-irritant to skin.	-	-	-	-
Distillates (petroleum), hydrotreated heavy paraffinic	Rabbit	Eyes - Non-irritating to the eyes.	-	-	-	Based on studies with similar substances.
	Rabbit	Skin - Mild irritant	-	-	-	Based on studies with similar substances.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Rabbit	Eyes - Non-irritating to the eyes.	-	-	-	Based on studies with similar



## Section 11. Toxicological information

	Rabbit	Skin - Non-irritant to skin.	-	-	-	substances. Based on studies with similar substances.
reaction mass of: triphenylthiophosphate and tertiary butylated phenyl derivatives	Rabbit	Eyes - Non-irritating to the eyes.	-	-	-	-
	Rabbit	Skin - Non-irritant to skin.	-	-	-	-
zinc isodecyl phosphorodithioate	Unspecified	Eyes - Non-irritating to the eyes.	-	-	-	BCOP
	Unspecified	Skin - Non-irritant to skin.	-	-	-	RHE
2,6-di-tert-butylphenol	Rabbit	Eyes - Non-irritating to the eyes.	-	-	-	-
	Rabbit	Skin - Irritant	-	-	-	-

### Sensitisation

Product/ingredient name	Route of exposure	Species	Result	Remarks
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	skin	Guinea pig	Not sensitising	Based on studies with similar substances.
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	skin	Guinea pig	Not sensitising	-
Distillates (petroleum), hydrotreated heavy paraffinic	skin	Guinea pig	Not sensitising	Based on studies with similar substances.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	skin	Guinea pig	Not sensitising	Based on studies with similar substances.
reaction mass of: triphenylthiophosphate and tertiary butylated phenyl derivatives	skin	Guinea pig	Not sensitising	-
zinc isodecyl phosphorodithioate	skin	Guinea pig	Not sensitising	Based on studies with similar substances.
2,6-di-tert-butylphenol	skin	Guinea pig	Not sensitising	-

### Mutagenicity

Product/ingredient name	Test	Experiment	Result	Remarks
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	OECD 473 Mammalian Chromosomal Aberration Test	Experiment: In vitro Subject: Mammal - species unspecified	Positive	Based on studies with similar substances.
	OECD 471 Bacterial Reverse Mutation Test	Experiment: In vitro Subject: Bacteria	Negative	Based on studies with similar substances.
	OECD 476 In vitro Mammalian Cell Gene Mutation Test	Experiment: In vitro	Negative	Based on studies with similar substances.
	OECD 474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo Subject: Mammal -	Negative	Based on studies with similar substances.



## Section 11. Toxicological information

Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	OECD 471 Bacterial Reverse Mutation Test	species unspecified Experiment: In vitro	Negative	Based on studies with similar substances.
	OECD 473 In vitro Mammalian Chromosomal Aberration Test	Subject: Bacteria Experiment: In vitro	Negative	Based on studies with similar substances.
	OECD 474 Mammalian Erythrocyte Micronucleus Test	Subject: Mammal - species unspecified Experiment: In vivo	Negative	Based on studies with similar substances.
Distillates (petroleum), hydrotreated heavy paraffinic	471 Bacterial Reverse Mutation Test	Subject: Bacteria Experiment: In vitro	Negative	Based on studies with similar substances.
	473 In vitro Mammalian Chromosomal Aberration Test	Subject: Bacteria Experiment: In vitro	Negative	Based on studies with similar substances.
	476 In vitro Mammalian Cell Gene Mutation Test	Subject: Mammal - species unspecified Experiment: In vitro	Negative	Based on studies with similar substances.
	474 Mammalian Erythrocyte Micronucleus Test	Subject: Mammal - species unspecified Experiment: In vivo	Negative	Based on studies with similar substances.
	OECD 471 Bacterial Reverse Mutation Test	Subject: Mammal - species unspecified Experiment: In vitro	Negative	Based on studies with similar substances.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	OECD 473 In vitro Mammalian Chromosomal Aberration Test	Subject: Bacteria Experiment: In vitro	Negative	Based on studies with similar substances.
	OECD 476 In vitro Mammalian Cell Gene Mutation Test	Subject: Mammal - species unspecified Experiment: In vitro	Negative	Based on studies with similar substances.
	OECD 474 Mammalian Erythrocyte Micronucleus Test	Subject: Unspecified Experiment: In vivo	Negative	Based on studies with similar substances.
	OECD 471 Bacterial Reverse Mutation Test	Subject: Mammal - species unspecified Experiment: In vitro	Negative	-
reaction mass of: triphenylthiophosphate and tertiary butylated phenyl derivatives	OECD 473 In vitro Mammalian Chromosomal Aberration Test	Subject: Bacteria Experiment: In vitro	Negative	-
	OECD 476 In vitro	Subject: Mammal - species unspecified Experiment: In vitro	Negative	-

## Section 11. Toxicological information

	Mammalian Cell Gene Mutation Test	Subject: Mammal - species unspecified		
zinc isodecyl phosphorodithioate	OECD 471 Bacterial Reverse Mutation Test	Experiment: In vitro	Negative	Based on studies with similar substances.
	OECD 474 Mammalian Erythrocyte Micronucleus Test	Subject: Bacteria Experiment: In vivo	Negative	Based on studies with similar substances.
2,6-di-tert-butylphenol	OECD 471 Bacterial Reverse Mutation Test	Subject: Mammal - species unspecified Experiment: In vitro	Negative	-
	OECD 473 In vitro Mammalian Chromosomal Aberration Test	Subject: Bacteria Experiment: In vitro	Negative	-
		Subject: Mammal - species unspecified		

### Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Result	Exposure
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	Negative	Negative	Negative	Rat	Oral	-
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	Negative	Negative	Negative	Rat	Oral	-
reaction mass of: triphenylthiophosphate and tertiary butylated phenyl derivatives	Negative	Negative	Negative	Rat	Oral	-
zinc isodecyl phosphorodithioate	Negative	Negative	Negative	Rat	Oral	-
2,6-di-tert-butylphenol	Positive	Negative	Equivocal	Rat	Oral	-

### Aspiration hazard

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	ASPIRATION HAZARD - Category 1
Dec-1-ene, homopolymer, hydrogenated	ASPIRATION HAZARD - Category 1
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	ASPIRATION HAZARD - Category 1
Distillates (petroleum), solvent-dewaxed heavy paraffinic	ASPIRATION HAZARD - Category 1

**Information on likely routes of exposure** Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

### Potential acute health effects

<b>Eye contact</b>	No known significant effects or critical hazards.
<b>Inhalation</b>	Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.
<b>Skin contact</b>	Defatting to the skin. May cause skin dryness and irritation.
<b>Ingestion</b>	No known significant effects or critical hazards.
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	
<b>Eye contact</b>	No specific data.
<b>Inhalation</b>	May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
<b>Skin contact</b>	Adverse symptoms may include the following: irritation dryness cracking
<b>Ingestion</b>	No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Product name</b> Castrol Transmax Manual FE 75W	<b>Product code</b> 469681-DE01	Page: 10/15
<b>Version</b> 5.07	<b>Date of issue</b> 03/07/2024.	<b>Format</b> Taiwan
	<b>Taiwan</b>	<b>Language</b> ENGLISH (ENGLISH)

## Section 11. Toxicological information

<b>Eye contact</b>	Potential risk of transient stinging or redness if accidental eye contact occurs.
<b>Inhalation</b>	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
<b>Skin contact</b>	Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/ or dermatitis.
<b>Ingestion</b>	Ingestion of large quantities may cause nausea and diarrhoea.
<b>Potential chronic health effects</b>	
<b>General</b>	No known significant effects or critical hazards.
<b>Carcinogenicity</b>	No known significant effects or critical hazards.
<b>Mutagenicity</b>	No known significant effects or critical hazards.
<b>Teratogenicity</b>	No known significant effects or critical hazards.
<b>Developmental effects</b>	No known significant effects or critical hazards.
<b>Fertility effects</b>	No known significant effects or critical hazards.

## Section 12. Ecological information

**Environmental effects** This material is harmful to aquatic life with long lasting effects.

### Toxicity

Product/ingredient name	Species	Test/Result	Exposure	Effects	Remarks
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	Daphnia	Acute EL50 >10000 mg/l	48 hours	-	Based on studies with similar substances. Based on studies with similar substances. -
	Fish	Acute LL50 >100 mg/l	96 hours	-	
	Algae	Acute NOEL ≥100 mg/l	72 hours	-	
	Daphnia	Chronic NOEL ≥1000 mg/l	21 days	-	
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	Algae	Acute EL50 >1000 mg/l	72 hours	-	Based on studies with similar substances. Based on studies with similar substances. -
	Daphnia	Acute EL50 >1000 mg/l	48 hours	-	
	Fish	Acute LL50 >1000 mg/l	96 hours	-	
	Daphnia	Chronic NOELR 125 mg/l	21 days	-	
Distillates (petroleum), hydrotreated heavy paraffinic	Daphnia	Acute EL50 >10000 mg/l	48 hours	-	Based on studies with similar substances. Based on studies with similar substances. -
	Fish	Acute LL50 >100 mg/l	96 hours	-	
	Algae	Chronic NOEL ≥100 mg/l	72 hours	-	
	Daphnia	Chronic NOEL 10 mg/l	21 days	-	
Distillates (petroleum), solvent-dewaxed	Daphnia	Acute EL50 >1000 mg/l	48 hours	-	Based on studies with

## Section 12. Ecological information

heavy paraffinic						similar substances. Based on studies with similar substances.
	Algae	Acute ErL50 100 mg/l	72 hours	-		Based on studies with similar substances.
	Fish	Acute LL50 >100 mg/l	96 hours	-		Based on studies with similar substances.
	Algae	Chronic NOELR 100 mg/l	72 hours	-		Based on studies with similar substances.
	Daphnia	Chronic NOELR 10 to 1000 mg/l	21 days	-		Based on studies with similar substances.
reaction mass of: triphenylthiophosphate and tertiary butylated phenyl derivatives	Algae	Acute EC50 >100 mg/l	72 hours	-		-
	Daphnia	Acute EC50 >100 mg/l	48 hours	-		-
	Fish	Acute LC50 >100 mg/l	96 hours	-		-
	Algae	Chronic NOEC >100 mg/l	72 hours	-		-
	Daphnia	Chronic NOEC 0.026 mg/l	21 days	-		-
	Fish	Chronic NOEC 0.0044 mg/l	87 days	-		-
zinc isodecyl phosphorodithioate	Daphnia	Acute EC50 0.2 mg/l	48 hours	-		-
	Algae	Acute ErC50 >1.6 mg/l	72 hours	-		-
	Fish	Acute LC50 >0.28 mg/l	96 hours	-		-
2,6-di-tert-butylphenol	Algae	Acute EL50 1.2 mg/l	96 hours	-		-
	Daphnia	Acute EL50 0.45 mg/l	48 hours	-		-
	Fish	Acute LC50 1.4 mg/l	96 hours	-		-
	Algae	Chronic NOEC 0.64 mg/l	96 hours	-		-
	Daphnia	Chronic NOEC 0.035 mg/l	21 days	-		-

### Persistence and degradability

Partially biodegradable.

Product/ingredient name	Test	Result	Remarks
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	OECD 301F	31 % - Inherent - 28 days	Based on studies with similar substances.
Distillates (petroleum), hydrotreated heavy paraffinic	OECD 301F	31 % - Not readily - 28 days	Based on studies with similar substances.
reaction mass of: triphenylthiophosphate and tertiary butylated phenyl derivatives	OECD 301D	0 % - Not readily - 28 days	-
zinc isodecyl phosphorodithioate	OECD 301b	1 % - Not readily - 28 days	Based on studies with similar substances.
2,6-di-tert-butylphenol	OECD 301B	24 % - Not readily - 28 days	-

### Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

## Section 12. Ecological information

### Mobility in soil

Soil/water partition coefficient ( $K_{oc}$ )

Not available.

Mobility

Spillages may penetrate the soil causing ground water contamination.

### Other ecological information

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

## Section 13. Disposal considerations

### Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	IMDG	IATA
UN number	Not regulated.	Not regulated.
UN proper shipping name	-	-
Transport hazard class(es)	-	-
Packing group	-	-
Environmental hazards	No.	No.
Additional information	-	-

Special precautions for user Not available.

## Section 15. Regulatory information

Not applicable.

### TCCSCA List of concerned chemicals

Not applicable.

### OSHA Article 29

None of the components are listed.

### OSHA Article 30

None of the components are listed.

### Montreal Protocol

Ingredient name	Status
Not listed.	

### Stockholm Convention on Persistent Organic Pollutants

Ingredient name	List name	Status
Not listed.		

## Section 15. Regulatory information

### [Rotterdam Convention on Prior Informed Consent \(PIC\)](#)

Ingredient name	Status
Not listed.	

### Regulation according to other foreign laws

<b>REACH Status</b>	The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.
<b>Australia inventory (AIIIC)</b>	All components are listed or exempted.
<b>Canada inventory status</b>	All components are listed or exempted.
<b>China inventory (IECSC)</b>	All components are listed or exempted.
<b>Japan inventory (CSCL)</b>	All components are listed or exempted.
<b>Philippines inventory (PICCS)</b>	All components are listed or exempted.
<b>Korea inventory (KECI)</b>	All components are listed or exempted.
<b>Taiwan Chemical Substances Inventory (TCSI)</b>	All components are listed or exempted.
<b>United States inventory (TSCA 8b)</b>	All components are active or exempted.

## Section 16. Other information

### [Procedure used to derive the classification](#)

Classification	Justification
AQUATIC TOXICITY (ACUTE) - Category 3	Calculation method
AQUATIC TOXICITY (CHRONIC) - Category 3	Calculation method

**References** Not available.

**Organisation that prepared the SDS** BP

### [History](#)

**Date of printing** 7/3/2024

**Date of previous issue** 03/07/2024.

**Version** 5.07

**Prepared by** Product Stewardship

### [Key to abbreviations](#)

ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]  
UN = United Nations  
Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

 **Indicates information that has changed from previously issued version.**

### [Notice to reader](#)

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

**Product name** Castrol Transmax Manual FE 75W

**Product code** 469681-DE01

Page: 14/15

**Version** 5.07 **Date of issue** 03/07/2024.

**Format** Taiwan

**Language** ENGLISH

Taiwan

(ENGLISH)

## Section 16. Other information

The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.