

SAFETY DATA SHEET



Castrol Transmax Axle Long Life 75W-140

Section 1. Chemical product and company identification

GHS product identifier Castrol Transmax Axle Long Life 75W-140
Product code 469697-DE01
SDS no. 469697

Relevant identified uses of the substance or mixture and uses advised against

Product use Gear lubricant
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

Supplier Setra Lubricants LLC
2 Paveletskaya Square, Bld. 1
115054 Moscow, Russia

Tel +7 (495) 961-27-87
Fax +7 (495) 961-27-99

EMERGENCY TELEPHONE NUMBER Carechem: +44 (0) 1235 239 670 (24/7)

Section 2. Hazards identification

Classification of the substance or mixture **H**411 - SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 2
H412 - LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2

GHS label elements

Hazard pictograms



Signal word No signal word.

Hazard statements **H**411 - Toxic to aquatic life with long lasting effects.

Precautionary statements

General P102 - Keep out of reach of children.
P101 - If medical advice is needed, have product container or label at hand.

Prevention P273 - Avoid release to the environment.

Response **P**391 - Collect spillage.

Storage Not applicable.

Disposal P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not result in classification Defatting to the skin.

Product name Castrol Transmax Axle Long Life 75W-140 **Product code** 469697-DE01 **Page:** 1/10
Version 3 **Date of issue** 01/19/2022. **Format** Russia **Language** ENGLISH
Russia **(ENGLISH)**

Section 3. Composition/information on ingredients

Substance/mixture

Mixture

Poly-alpha-olefin. Ester. Proprietary performance additives.

Ingredient name	%	CAS number
<input checked="" type="checkbox"/> -Decene, homopolymer, hydrogenated	≥10 - ≤25	68037-01-4
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	≥10 - ≤25	68037-01-4
tris(methylphenyl)phosphate	≤3	1330-78-5
Amines, C12-14-tert-alkyl	≤0.3	68955-53-3
(Z)-octadec-9-enylamine	≤0.1	112-90-3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Inhalation

If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Ingestion

Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if adverse health effects persist or are severe.

Skin contact

Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.

Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Specific treatments

No specific treatment.

Notes to physician

Treatment should in general be symptomatic and directed to relieving any effects.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media

Use foam or all-purpose dry chemical to extinguish.

Unsuitable extinguishing media

Do not use water jet.

Specific hazards arising from the chemical

Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects.

Hazardous thermal decomposition products

Combustion products may include the following:
phosphorus oxides
carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)
sulphur oxides (SO, SO₂, etc.)

Product name Castrol Transmax Axle Long Life 75W-140

Product code 469697-DE01 **Page:** 2/10

Version 3 **Date of issue** 01/19/2022.

Format Russia

Language ENGLISH

Russia

(ENGLISH)

Section 5. Firefighting measures

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling. Contact emergency personnel.

For emergency responders

Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and material for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Avoid contact of spilt material and runoff with soil and surface waterways.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Product name Castrol Transmax Axle Long Life 75W-140

Product code 469697-DE01 **Page:** 3/10

Version 3 **Date of issue** 01/19/2022.

Format Russia

Language ENGLISH

Russia

(ENGLISH)

Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Not suitable

Prolonged exposure to elevated temperature

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
tris(methylphenyl)phosphate	Ministry of Health and Social Development MAC (Russian Federation). STEL: 0.5 mg/m ³ 15 minutes. Issued/ Revised: 6/2003 Form: Aerosol, o-isomer content <3% STEL: 0.1 mg/m ³ 15 minutes. Issued/ Revised: 6/2003 Form: Aerosol, o-isomer content >3%

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety glasses with side shields.

Skin protection

Product name Castrol Transmax Axle Long Life 75W-140	Product code 469697-DE01	Page: 4/10	
Version 3	Date of issue 01/19/2022.	Format Russia	Language ENGLISH
		Russia	(ENGLISH)

Section 8. Exposure controls/personal protection

Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Body protection

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	Liquid.
Colour	Amber.
Odour	Not available.
Odour threshold	Not available.
pH	Not available.
Melting point	Not available.
Boiling point, initial boiling point, and boiling range	Not available.
Flash point	Open cup: >180°C (>356°F) [Cleveland]
Evaporation rate	Not available.
Flammability	Not applicable. Based on - Physical state
Lower and upper explosion limit/flammability limit	Not available.
Vapour pressure	

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	0	0	ASTM E 1194-87			
Decanoic acid, ester with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol octanoate	0	0				

Product name Castrol Transmax Axle Long Life 75W-140	Product code 469697-DE01	Page: 5/10
Version 3	Date of issue 01/19/2022.	Format Russia
	Russia	Language ENGLISH (ENGLISH)

Section 9. Physical and chemical properties

1-Decene, homopolymer, hydrogenated	0	0	ASTM E 1194-87			
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	0	0	ASTM E 1194-87			
tris(methylphenyl) phosphate	2.1	0.28	EU A.4			

Relative vapour density

Not available.

Relative density

Not available.

Density

<1000 kg/m³ (<1 g/cm³) at 15°C

Solubility

insoluble in water.

Partition coefficient: n-octanol/water

Not applicable.

Auto-ignition temperature

Ingredient name	°C	°F	Method
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159
1-Decene, homopolymer, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159

Decomposition temperature

Not available.

Viscosity

Kinematic: 182 mm²/s (182 cSt) at 40°C

Kinematic: 24.5 to 25.5 mm²/s (24.5 to 25.5 cSt) at 100°C

Particle characteristics

Median particle size

Not applicable.

Section 10. Stability and reactivity

Reactivity

No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.

Chemical stability

The product is stable.

Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.
Under normal conditions of storage and use, hazardous polymerisation will not occur.

Conditions to avoid

Avoid all possible sources of ignition (spark or flame).

Incompatible materials

Reactive or incompatible with the following materials: oxidising materials.

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Product name Castrol Transmax Axle Long Life 75W-140

Product code 469697-DE01 **Page:** 6/10

Version 3 **Date of issue** 01/19/2022.

Format Russia

Language ENGLISH

Russia

(ENGLISH)

Section 11. Toxicological information

Information on toxicological effects

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Amines, C12-14-tert-alkyl	Category 3	-	Respiratory tract irritation
(Z)-octadec-9-enylamine	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
(Z)-octadec-9-enylamine	Category 2	-	-

Aspiration hazard

Name	Result
Decene, homopolymer, hydrogenated	ASPIRATION HAZARD - Category 1
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	ASPIRATION HAZARD - Category 1
(Z)-octadec-9-enylamine	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Eye contact

No known significant effects or critical hazards.

Inhalation

Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.

Skin contact

Defatting to the skin. May cause skin dryness and irritation.

Ingestion

No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact

No specific data.

Inhalation

May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.

Skin contact

Adverse symptoms may include the following:
irritation
dryness
cracking

Ingestion

No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact

Potential risk of transient stinging or redness if accidental eye contact occurs.

Inhalation

Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

Skin contact

Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Ingestion

Ingestion of large quantities may cause nausea and diarrhoea.

Potential chronic health effects

General

No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.

Mutagenicity

No known significant effects or critical hazards.

Product name Castrol Transmax Axle Long Life 75W-140

Product code 469697-DE01 **Page:** 7/10

Version 3 **Date of issue** 01/19/2022.

Format Russia

Language ENGLISH

Russia

(ENGLISH)

Section 11. Toxicological information

Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

Section 12. Ecological information

Environmental effects This material is toxic to aquatic life with long lasting effects.

Persistence and degradability

Not expected to be rapidly degradable.

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Mobility in soil

Mobility Spillages may penetrate the soil causing ground water contamination.

Other ecological information





Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	IMDG	IATA
UN number	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (tris (methylphenyl)phosphate). Marine pollutant (tris(methylphenyl)phosphate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (tris (methylphenyl)phosphate)
Transport hazard class(es)	9  	9  
Packing group	III	III

Product name Castrol Transmax Axle Long Life 75W-140

Product code 469697-DE01 **Page:** 8/10

Version 3 **Date of issue** 01/19/2022.

Format Russia

Language ENGLISH

Russia

(ENGLISH)

Section 14. Transport information

Environmental hazards	Yes.	Yes.
Additional information	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user Not available.

Section 15. Regulatory information

Regulation according to other foreign laws

REACH Status	The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.
United States inventory (TSCA 8b)	All components are active or exempted.
Australia inventory (AIC)	All components are listed or exempted.
Canada inventory	All components are listed or exempted.
China inventory (IECSC)	All components are listed or exempted.
Japan inventory (CSCL)	All components are listed or exempted.
Korea inventory (KECI)	All components are listed or exempted.
Philippines inventory (PICCS)	All components are listed or exempted.
Taiwan Chemical Substances Inventory (TCSI)	All components are listed or exempted.

Section 16. Other information

History

Date of printing	1/19/2022
Date of issue/Date of revision	1/19/2022
Date of previous issue	10/29/2021
Version	3
Prepared by	Product Stewardship

Key to abbreviations

ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
UN = United Nations
Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0,

Product name Castrol Transmax Axle Long Life 75W-140	Product code 469697-DE01	Page: 9/10	
Version 3	Date of issue 01/19/2022.	Format Russia	Language ENGLISH
		Russia	(ENGLISH)

Section 16. Other information

72623-87-1

References

Not available.

✔ Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.