

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name	Techniclean S Extra FF
UFI:	EE52-G0KN-Q00K-3AFW
Product code	465404-FR01
SDS #	465404
Product type	Liquid.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Use of lubricants and greases in open systems-Industrial
Use of lubricants and greases in open systems-Professional
Handling and dilution of metal working fluid concentrates-Industrial

Use of the substance/ mixture	Cleaner. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
--	---

1.3 Details of the supplier of the safety data sheet

Supplier	Lubricants UK Limited, Chertsey Road, Sunbury On Thames, Middlesex, TW16 7BP
E-mail address	+44 (0)345 600 8125 MSDSadvice@bp.com

1.4 Emergency telephone number

EMERGENCY TELEPHONE NUMBER	Carechem: +44 (0) 1235 239 670 (24/7)
---------------------------------------	---------------------------------------

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition	Mixture
<u>Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]</u>	

Skin Irrit. 2, H315
Eye Dam. 1, H318
Aquatic Chronic 3, H412

Additional information CLP: Not classified as hazardous when diluted below 10%.

See Section 16 for the full text of the H statements declared above.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements

UFI:	EE52-G0KN-Q00K-3AFW
Hazard pictograms	



Signal word	Danger
Hazard statements	H315 - Causes skin irritation. H318 - Causes serious eye damage. H412 - Harmful to aquatic life with long lasting effects.

Product name Techniclean S Extra FF	Product code 465404-FR01	Page: 1/26
Version 1.01	Date of issue 13 August 2024	Format United Kingdom (UK) (United Kingdom)
Date of previous issue 21 February 2024.		Language ENGLISH

SECTION 2: Hazards identification

Precautionary statements

Prevention	P280 - Wear protective gloves. Wear eye or face protection. P273 - Avoid release to the environment. P264 - Wash hands thoroughly after handling.
Response	P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.
Storage	Not applicable.
Disposal	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	<input checked="" type="checkbox"/> -aminoethanol
Supplemental label elements	Not applicable.

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Not applicable.
---	-----------------

Special packaging requirements

Containers to be fitted with child-resistant fastenings	Not applicable.
Tactile warning of danger	Not applicable.

2.3 Other hazards

Results of PBT and vPvB assessment	Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	Defatting to the skin. This product contains complex ionic mixtures within the fluid matrix which are an intrinsic part of the product and cannot be separated from the fluid matrix. Toxicology testing has shown the ionic-mixture containing products exhibit skin and eye irritation properties that are notably attenuated when compared to the individual acid and base components.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product definition Mixture
Alkalis and additives in aqueous solution.

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
<input checked="" type="checkbox"/> -aminoethanol	REACH #: 01-2119486455-28 EC: 205-483-3 CAS: 141-43-5 Index: 603-030-00-8	≥10 - ≤17	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Chronic 3, H412	ATE [Oral] = 500 mg/kg ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/l STOT SE 3, H335: C ≥ 5%	[1] [2]
neodecanoic acid	REACH #: 01-2119449554-33 EC: 248-093-9 CAS: 26896-20-8	≤7.1	Acute Tox. 4, H302	ATE [Oral] = 500 mg/kg	[1]
2,2'-(methylimino)diethanol	REACH #: 01-2119488970-24 EC: 203-312-7	≤5	Eye Irrit. 2, H319	-	[1]

Product name Techniclean S Extra FF	Product code 465404-FR01	Page: 2/26
Version 1.01 Date of issue 13 August 2024	Format United Kingdom (UK)	Language ENGLISH
Date of previous issue 21 February 2024.	(United Kingdom)	

SECTION 3: Composition/information on ingredients

undecanedioic acid	CAS: 105-59-9 Index: 603-079-00-5 REACH #: 01-2119983505-29 EC: 217-440-6	≤5	Eye Irrit. 2, H319	-	[1]
dodecanedioic acid	CAS: 1852-04-6 REACH #: 01-2119543732-40 EC: 211-746-3	≤3	Eye Irrit. 2, H319	-	[1]
2-(2-butoxyethoxy)ethanol	CAS: 693-23-2 REACH #: 01-2119475104-44 EC: 203-961-6	≤3	Eye Irrit. 2, H319	-	[1] [2]
3-butoxypropan-2-ol	CAS: 112-34-5 Index: 603-096-00-8 REACH #: 01-2119475527-28 EC: 225-878-4	≤3	Skin Irrit. 2, H315 Eye Irrit. 2, H319	-	[1]
potassium hydroxide	CAS: 5131-66-8 Index: 603-052-00-8 REACH #: 01-2119487136-33 EC: 215-181-3	<1	Met. Corr. 1, H290 Acute Tox. 4, H302 Skin Corr. 1A, H314 Eye Dam. 1, H318	ATE [Oral] = 500 mg/kg Skin Corr. 1A, H314: C ≥ 5% Skin Corr. 1B, H314: 2% ≤ C < 5% Skin Irrit. 2, H315: 0.5% ≤ C < 2% Eye Dam. 1, H318: C ≥ 2% Eye Irrit. 2, H319: 0.5% ≤ C < 2%	[1] [2]
1,2-ethanediamine, N,N,N',N'-tetramethyl-, polymer with 1,1'-oxybis(2-chloroethane)	REACH #: Polymer CAS: 31075-24-8	<0.25	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 500 mg/kg ATE [Inhalation (vapours)] = 11 mg/l M [Acute] = 10 M [Chronic] = 10	[1]
2-butyloctan-1-ol	REACH #: 01-2119978234-31 EC: 223-470-0 CAS: 3913-02-8	≤0.3	Aquatic Acute 1, H400 Aquatic Chronic 2, H411	M [Acute] = 1	[1]

See Section 16 for the full text of the H statements declared above.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Chemical burns must be treated promptly by a physician. Get medical attention immediately.

Skin contact

Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention.

Inhalation

If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.

Ingestion

Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Wash out mouth with water if person is conscious. Get medical attention if symptoms occur.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Product name Techniclean S Extra FF	Product code 465404-FR01	Page: 3/26
Version 1.01	Date of issue 13 August 2024	Format United Kingdom (UK)
Date of previous issue 21 February 2024.	Language ENGLISH	(United Kingdom)

SECTION 4: First aid measures

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Potential acute health effects

Inhalation	May give off gas, vapour or dust that is very irritating or corrosive to the respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure. May cause irritation to eyes, nose and throat due to exposure to vapour, mists or fumes.
Ingestion	Irritating to mouth, throat and stomach.
Skin contact	Causes skin irritation. Defatting to the skin.
Eye contact	Causes serious eye damage.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
---------------------------	---

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	Use foam or all-purpose dry chemical to extinguish.
Unsuitable extinguishing media	Do not use water jet. The use of a water jet may cause the fire to spread by splashing the burning product.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	Combustion products may include the following: carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide) nitrogen oxides (NO, NO ₂ etc.)

5.3 Advice for firefighters

Special precautions for fire-fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. This material is harmful to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Do not breathe vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment.
For emergency responders	Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

Product name Techniclean S Extra FF	Product code 465404-FR01	Page: 4/26
Version 1.01	Date of issue 13 August 2024	Format United Kingdom (UK) (United Kingdom)
Date of previous issue 21 February 2024.		Language ENGLISH

SECTION 6: Accidental release measures

6.2 Environmental precautions	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	See Section 1 for emergency contact information. See Section 5 for firefighting measures. See Section 8 for information on appropriate personal protective equipment. See Section 12 for environmental precautions. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling	
Protective measures	Put on appropriate personal protective equipment. Do not breathe vapour or mist. Do not ingest. Avoid contact of spilt material and runoff with soil and surface waterways. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Empty containers retain product residue and can be hazardous. Use only with adequate ventilation. Do not get in eyes, on skin or on clothing.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	
Not suitable	Store between the following temperatures: 5 to 40°C (41 to 104°F). Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Store locked up. Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/containers designed for use with this product. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. Prolonged exposure to elevated temperature
7.3 Specific end use(s)	
Recommendations	See section 1.2 and Exposure scenarios in annex, if applicable.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters	
Occupational exposure limits	No exposure limit value known.
Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.	
This product contains a preservative that may release trace amounts of formaldehyde during use.	

Product name Techniclean S Extra FF	Product code 465404-FR01	Page: 5/26
Version 1.01	Date of issue 13 August 2024	Format United Kingdom (UK)
Date of previous issue 21 February 2024.		Language ENGLISH
		(United Kingdom)

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived No Effect Level

Product/ingredient name	Type	Exposure	Value	Population	Effects
2,2'-(methylimino)diethanol	DNEL	Long term Inhalation -	7.9 mg/m³	Workers	Systemic
	DNEL	Long term Dermal -	5.6 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal -	0.05 mg/kg bw/day	Workers	Local
	DNEL	Long term Inhalation -	0.4 mg/m³	General population	Systemic
	DNEL	Long term Dermal -	0.67 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal -	0.03 mg/kg bw/day	General population	Local
undecanedioic acid	DNEL	Long term Oral -	0.13 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation -	70 mg/m³	Workers	Systemic
	DNEL	Long term Dermal -	10 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation -	17.4 mg/m³	General population	Systemic
	DNEL	Long term Dermal -	5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral -	5 mg/kg bw/day	General population	Systemic

Predicted No Effect Concentration

Product/ingredient name	Compartment Detail	Value	Method Detail
2,2'-(methylimino)diethanol	Fresh water	0.278 mg/l	-
	Marine water	0.028 mg/l	-
	Sewage Treatment Plant	10 mg/l	-
	Fresh water sediment	2.17 mg/kg dwt	-
	Marine water sediment	0.217 mg/kg dwt	-
undecanedioic acid	Soil	0.27 mg/kg dwt	-
	Fresh water	0.039 mg/l	-
	Marine water	0.004 mg/l	-
	Sewage Treatment Plant	10 mg/l	-
	Fresh water sediment	0.064 mg/kg dwt	-
Marine water sediment	0.006 mg/kg dwt	-	
Soil	0.047 mg/kg dwt	-	

8.2 Exposure controls

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

Product name Techniclean S Extra FF	Product code 465404-FR01	Page: 6/26
Version 1.01	Date of issue 13 August 2024	Format United Kingdom (UK)
Date of previous issue 21 February 2024.	Language ENGLISH	(United Kingdom)

SECTION 8: Exposure controls/personal protection

Use with adequate ventilation.
 In case of insufficient ventilation, wear suitable respiratory equipment.
 Recommended: half-face mask - inorganic gases/vapor filter (Type B) - particulate filter.
 The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.
 Chemical splash goggles.

[Eye/face protection](#)
[Skin protection](#)
[Hand protection](#)

General Information:

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Wear suitable gloves.
 Recommended: Butyl gloves.

Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type.
 Our recommendations on the selection of gloves are as follows:

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained.
 If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.
 It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

Glove Thickness:

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.
 Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

Product name Techniclean S Extra FF	Product code 465404-FR01	Page: 7/26
Version 1.01 Date of issue 13 August 2024	Format United Kingdom (UK)	Language ENGLISH
Date of previous issue 21 February 2024.	(United Kingdom)	

SECTION 8: Exposure controls/personal protection

Skin and body

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Refer to standards:

Respiratory protection: EN 529
 Gloves: EN 420, EN 374
 Eye protection: EN 166
 Filtering half-mask: EN 149
 Filtering half-mask with valve: EN 405
 Half-mask: EN 140 plus filter
 Full-face mask: EN 136 plus filter
 Particulate filters: EN 143
 Gas/combined filters: EN 14387

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Physical state Liquid.
Colour Amber. [Light]
Odour Unfragranced
Odour threshold Not available.
Melting point/freezing point Not available.
Initial boiling point and boiling range Not available.
Flammability Not available.
Lower and upper explosion limit Not available.

Flash point Open cup: >100°C (>212°F) [Water content interferes with flash point determination.]

Auto-ignition temperature

Ingredient name	°C	°F	Method
2,2'-nitrotriethanol	324	615.2	
neodecanoic acid	375	707	ASTM E 659
2,2'-(methylimino)diethanol	280	536	DIN 51794
2-(2-butoxyethoxy)ethanol	210	410	DIN 51794
3-butoxypropan-2-ol	260	500	EU A.15

Decomposition temperature Not available.

pH 9.6 [Conc. (% w/w): 5%]

Kinematic viscosity Kinematic: 4.8 mm²/s (4.8 cSt) at 40°C

Solubility

Media	Result
water	Soluble

Partition coefficient n-octanol/water (log value) Not applicable.

Vapour pressure

SECTION 9: Physical and chemical properties

Ingredient name	Vapour Pressure at 20°C		Vapour pressure at 50°C			
	mm Hg	kPa	Method	mm Hg	kPa	Method
Water	17.5	2.3				
2-aminoethanol	0.4	0.053				
undecanedioic acid	<0.075	<0.01	OECD 104			
2-(2-butoxyethoxy) ethanol	0.022	0.0029				
3-butoxypropan-2-ol	1.05	0.14	OECD 104			

Density and/or Relative density >1000 kg/m³ (>1 g/cm³) at 20°C
Relative vapour density Not available.
Particle characteristics
Median particle size Not applicable.
9.2 Other information
Evaporation rate Not available.
Explosive properties Not available.
Oxidising properties Not available.

SECTION 10: Stability and reactivity

10.1 Reactivity No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
10.2 Chemical stability The product is stable.
10.3 Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions will not occur.
 Under normal conditions of storage and use, hazardous polymerisation will not occur.
10.4 Conditions to avoid High temperatures
10.5 Incompatible materials Reactive or incompatible with the following materials: oxidising materials.
 Slightly reactive or incompatible with the following materials: acids.
10.6 Hazardous decomposition products Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result / Route	Test authority / Number	Species	Dose	Exposure	Remarks
2-aminoethanol	LC50 Inhalation Vapour	- -	Rat	1487 mg/m ³	6 hours	-
	LD50 Dermal	OECD 402	Rat	2504 mg/kg	-	-
	LD50 Oral	OECD 401	Rat	1089 mg/kg	-	-
2,2'-(methylimino) diethanol	LD50 Dermal	OECD 402	Rabbit	>5000 mg/kg	-	-
	LD50 Oral	OECD 401	Rat	4680 mg/kg	-	-
undecanedioic acid	LD50 Dermal	- -	Rabbit	>6000 mg/kg	-	Based on studies with similar substances.
	LD50 Oral	- -	Rat	>5000 mg/kg	-	Based on studies with

Product name Techniclean S Extra FF	Product code 465404-FR01	Page: 9/26
Version 1.01	Date of issue 13 August 2024	Format United Kingdom (UK) (United Kingdom)
Date of previous issue 21 February 2024.		Language ENGLISH

SECTION 11: Toxicological information

1,2-ethanediamine, N,N,N',N'-tetramethyl-, polymer with 1,1'-oxybis(2-chloroethane)	LC50	-	-	Rat	2.9 mg/l	4 hours	-	similar substances.
	Inhalation Vapour							
	LD50 Dermal	OECD	402	Rabbit	>2000 mg/kg	-	-	
	LD50 Oral	OECD	401	Rat	1951 mg/kg	-	-	

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Techniclean S Extra FF	2855.7	8778.2	N/A	87.8	N/A
2-aminoethanol	500	1100	N/A	11	N/A
neodecanoic acid	500	N/A	N/A	N/A	N/A
potassium hydroxide	500	N/A	N/A	N/A	N/A
1,2-ethanediamine, N,N,N',N'-tetramethyl-, polymer with 1,1'-oxybis(2-chloroethane)	500	N/A	N/A	11	N/A

Irritation/Corrosion

Product/ingredient name	Test authority / Test number	Species	Route / Result	Test concentration	Remarks
2-aminoethanol	OECD -	Rabbit	Eyes - Corrosive	-	-
	OECD 404	Rabbit	Skin - Corrosive	-	-
2,2'-(methylimino) diethanol	OECD 405	Rabbit	Eyes - Irritant	-	-
	OECD 404	Rabbit	Skin - Not irritant	-	-
undecanedioic acid	OECD 405	Rabbit	Eyes - Irritant	-	Based on studies with similar substances.
	OECD 404	Rabbit	Skin - Not irritant	-	Based on studies with similar substances.
1,2-ethanediamine, N,N,N',N'-tetramethyl-, polymer with 1,1'-oxybis(2-chloroethane)	-	Unspecified	Eyes - Moderate irritant	-	-
	-	Unspecified	Skin - Slightly irritating to the skin.	-	-

Sensitiser

Product/ingredient name	Route	Test authority / Test number	Species	Result	Remarks
2-aminoethanol	skin	OECD 406	Guinea pig	Not sensitising	-
2,2'-(methylimino) diethanol	skin	OECD 406	Guinea pig	Not sensitising	-
undecanedioic acid	skin	OECD 406	Guinea pig	Not sensitising	Based on studies with similar substances.
1,2-ethanediamine, N,N,N',N'-tetramethyl-, polymer with 1,1'-oxybis(2-chloroethane)	skin	-	Unspecified	Not sensitising	-

GERM CELL MUTAGENICITY

Product name Techniclean S Extra FF	Product code 465404-FR01	Page: 10/26
Version 1.01	Date of issue 13 August 2024	Format United Kingdom (UK) (United Kingdom)
Date of previous issue 21 February 2024.		Language ENGLISH

SECTION 11: Toxicological information

Product/ingredient name	Test authority / Test number	Cell	Type	Result	Remarks
2-aminoethanol	OECD 471	-	Experiment: In vitro Subject: Bacteria	Negative	-
	OECD 473	-	Experiment: In vitro Subject: Mammalian-Animal	Negative	-
	OECD 476	-	Experiment: In vitro Subject: Mammalian-Animal	Negative	-
2,2'-(methylimino) diethanol	471 Bacterial Reverse Mutation Test	-	Experiment: In vitro Subject: Bacteria	Negative	-
	473 In vitro Mammalian Chromosomal Aberration Test	-	Experiment: In vitro Subject: Mammal - species unspecified	Negative	-
	476 In vitro Mammalian Cell Gene Mutation Test	-	Experiment: In vitro Subject: Mammal - species unspecified	Negative	-
	474 Mammalian Erythrocyte Micronucleus Test	-	Experiment: In vivo Subject: Mammal - species unspecified	Negative	-
undecanedioic acid	471 Bacterial Reverse Mutation Test	-	Experiment: In vitro Subject: Bacteria	Negative	Based on studies with similar substances.
	-	-	Experiment: In vitro Subject: Mammal - species unspecified	Negative	Based on studies with similar substances.
	-	-	Experiment: In vivo Subject: Mammal - species unspecified	Negative	Based on studies with similar substances.

Carcinogenicity

Not available.

Reproductive toxicity

Product/ingredient name	Test authority / Test number	Species	Route	Exposure	Developmental	Maternal toxicity	Fertility	Remarks
2-aminoethanol	OECD 416	Rat	Oral	-	Negative	Negative	Negative	Based on studies with similar substances.
2,2'-(methylimino) diethanol	OECD 416	Rat	Oral	-	Negative	Negative	Negative	-

Aspiration hazard

Product/ingredient name	Result
Not available.	

Conclusion/Summary

Not classified. Based on available data, the classification criteria are not met.

Conclusion/Summary

Not available.

Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Product name Techniclean S Extra FF	Product code 465404-FR01	Page: 11/26
Version 1.01	Date of issue 13 August 2024	Format United Kingdom (UK) (United Kingdom)
Date of previous issue 21 February 2024.		Language ENGLISH

SECTION 11: Toxicological information

- Inhalation** May give off gas, vapour or dust that is very irritating or corrosive to the respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure. May cause irritation to eyes, nose and throat due to exposure to vapour, mists or fumes.
- Ingestion** Irritating to mouth, throat and stomach.
- Skin contact** Causes skin irritation. Defatting to the skin.
- Eye contact** Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation** No specific data.
- Ingestion** Adverse symptoms may include the following:
stomach pains
- Skin contact** Adverse symptoms may include the following:
pain or irritation
redness
dryness
cracking
blistering may occur
- Eye contact** Adverse symptoms may include the following:
pain
watering
redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

- Inhalation** Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
- Ingestion** Ingestion of large quantities may cause nausea and diarrhoea.
- Skin contact** Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
- Eye contact** Potential risk of transient stinging or redness if accidental eye contact occurs.

Potential chronic health effects

- General** No known significant effects or critical hazards.
- Carcinogenicity** No known significant effects or critical hazards.
- Mutagenicity** No known significant effects or critical hazards.
- Developmental effects** No known significant effects or critical hazards.
- Fertility effects** No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Test authority / Test number	Species	Type / Result	Exposure	Effects	Remarks
2-aminoethanol	OECD 202	Daphnia	Acute EC50 27.04 mg/l	48 hours	-	-
	OECD 201	Algae	Acute ErC50 2.8 mg/l	72 hours	-	-
	OECD 203	Fish	Acute LC50 >100 mg/l	96 hours	-	-
	-	Algae	Chronic ECr10 0.7 mg/l	72 hours	-	-
	OECD 211	Daphnia	Chronic NOEC 0.85 mg/l	21 days	-	-
	OECD 210	Fish	Chronic NOEC 1.24 mg/l	41 days	-	-
2,2'-(methylimino) diethanol	DIN 38412, part 9	Algae	Acute EC50 >100 mg/l	72 hours	-	-
	OECD 202	Daphnia	Acute EC50 >100 mg/l	48 hours	-	-
	DIN 38412, part 8	Micro-organism	Acute EC50 >100 mg/l	17 hours	-	-

Product name Techniclean S Extra FF	Product code 465404-FR01	Page: 12/26
Version 1.01	Date of issue 13 August 2024	Format United Kingdom (UK) (United Kingdom)
Date of previous issue 21 February 2024.		Language ENGLISH

SECTION 12: Ecological information

	DIN	38412, part 15	Fish	Acute LC50 >1000 mg/l	96 hours	-	-
	DIN	38412, part 9	Algae	Chronic NOEC 6.25 mg/l	72 hours	-	-
undecanedioic acid	ISO	8192	Micro-organism	Acute EC20 >1000 mg/l	3 hours	-	-
	OECD	202	Daphnia	Acute EC50 >100 mg/l	48 hours	-	-
	ISO	10253	Algae	Acute EL50 38.7 mg/l	72 hours	-	-
	OECD	203	Fish	Acute LC50 >100 mg/l	96 hours	-	-
	ISO	10253	Algae	Chronic NOEC 3 mg/l	72 hours	-	-
1,2-ethanediamine, N,N, N',N'-tetramethyl-, polymer with 1,1'-oxybis (2-chloroethane)	-	-	Daphnia	Acute EC50 0.37 mg/l	48 hours	-	-
	-	-	Fish	Acute LC50 0.047 mg/l	96 hours	-	-
	-	-	Algae	Acute NOEC 0.0019 mg/l	120 hours	-	-
	-	-	Daphnia	Acute NOEC 0.08 mg/l	48 hours	-	-
	-	-	Fish	Acute NOEL 0.037 mg/l	96 hours	-	-

Environmental hazards Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Expected to be biodegradable.

Product/ingredient name	Test authority / Test number	Result - Exposure	Remarks
2-aminoethanol	OECD 301A	>90 % - Readily - 21 days	-
2,2'-(methylimino)diethanol	OECD 301A	>90 % - Readily - 18 days	-
undecanedioic acid	OECD 301D	71 % - Readily - 28 days	-

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-butoxypropan-2-ol	-	-	Readily

12.3 Bioaccumulative potential

Not available.

Product/ingredient name	LogP _{ow}	BCF	Potential
2-aminoethanol	-2.3	-	Low
neodecanoic acid	2.1	-	Low
2,2'-(methylimino)diethanol	-1.08	0.9 to 9	Low
undecanedioic acid	2.8	-	Low
dodecanedioic acid	3.2	-	Low
2-(2-butoxyethoxy)ethanol	1	-	Low
3-butoxypropan-2-ol	1.2	-	Low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) Not available.

Mobility Liquid. Soluble in water.

Product name Techniclean S Extra FF	Product code 465404-FR01	Page: 13/26
Version 1.01	Date of issue 13 August 2024	Format United Kingdom (UK)
Date of previous issue 21 February 2024.	(United Kingdom)	Language ENGLISH

SECTION 12: Ecological information

12.5 Results of PBT and vPvB assessment

Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.

12.6 Endocrine disrupting properties Not available.

12.7 Other adverse effects No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Hazardous waste Yes.

European waste catalogue (EWC)

Waste code	Waste designation
12 03 01*	aqueous washing liquids

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

Packaging

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Waste code	European waste catalogue (EWC)
15 01 10*	packaging containing residues of or contaminated by hazardous substances

Special precautions This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Empty containers represent a fire hazard as they may contain flammable product residues and vapour. Never weld, solder or braze empty containers. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

References Commission 2014/955/EU
Directive 2008/98/EC

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

14.6 Special precautions for user Not available.

Product name Techniclean S Extra FF	Product code 465404-FR01	Page: 14/26
Version 1.01	Date of issue 13 August 2024	Format United Kingdom (UK)
Date of previous issue 21 February 2024.	Language ENGLISH	(United Kingdom)

SECTION 14: Transport information

14.7 Maritime transport in bulk according to IMO instruments Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
<input checked="" type="checkbox"/> Techniclean S Extra FF	95-100	3
2-(2-butoxyethoxy)ethanol	1-5	55 [Consumer paint]

Labelling Not applicable.

Other regulations

REACH Status

The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

United States inventory (TSCA 8b)

All components are active or exempted.

Australia inventory (AIC)

All components are listed or exempted.

Canada inventory

All components are listed or exempted.

China inventory (IECSC)

All components are listed or exempted.

Japan inventory (CSCL)

All components are listed or exempted.

Korea inventory (KECI)

All components are listed or exempted.

Philippines inventory (PICCS)

At least one component is not listed.

Taiwan Chemical Substances Inventory (TCSI)

All components are listed or exempted.

Explosive precursors Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

EU - Water framework directive - Priority substances

None of the components are listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

Product name Techniclean S Extra FF

Product code 465404-FR01

Page: 15/26

Version 1.01 **Date of issue** 13 August 2024

Format United Kingdom (UK)

Language ENGLISH

Date of previous issue 21 February 2024.

(United Kingdom)

SECTION 16: Other information

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 CAS = Chemical Abstracts Service
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 CSA = Chemical Safety Assessment
 CSR = Chemical Safety Report
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EINECS = European Inventory of Existing Commercial chemical Substances
 ES = Exposure Scenario
 EUH statement = CLP-specific Hazard statement
 EWC = European Waste Catalogue
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 OECD = Organisation for Economic Co-operation and Development
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
 RRN = REACH Registration Number
 SADT = Self-Accelerating Decomposition Temperature
 SVHC = Substances of Very High Concern
 STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
 STOT-SE = Specific Target Organ Toxicity - Single Exposure
 TWA = Time weighted average
 UN = United Nations
 UVCB = Complex hydrocarbon substance
 VOC = Volatile Organic Compound
 vPvB = Very Persistent and Very Bioaccumulative
 Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4/ RRN 01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN 01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN 01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN 01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN 01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8, 64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 / RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN 01-2119474889-13

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412	Expert judgment Calculation method Calculation method

Full text of abbreviated H statements	
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Product name Techniclean S Extra FF	Product code 465404-FR01	Page: 16/26
Version 1.01	Date of issue 13 August 2024	Format United Kingdom (UK)
Date of previous issue 21 February 2024.	Language ENGLISH	(United Kingdom)

SECTION 16: Other information

Full text of classifications [CLP/GHS]	Acute Tox. 4	ACUTE TOXICITY - Category 4
	Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
	Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
	Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
	Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
	Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
	Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
	Met. Corr. 1	CORROSIVE TO METALS - Category 1
	Skin Corr. 1A	SKIN CORROSION/IRRITATION - Category 1A
	Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
	Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
	STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

History

Date of issue/ Date of revision	13/08/2024.
Date of previous issue	21/02/2024.
Prepared by	Product Stewardship

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Techniclean S Extra FF	Product code 465404-FR01	Page: 17/26
Version 1.01	Date of issue 13 August 2024	Format United Kingdom (UK) (United Kingdom)
Date of previous issue 21 February 2024.		Language ENGLISH

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition	Mixture
Code	465404-FR01
Product name	Techniclean S Extra FF

Section 1: Title

Short title of the exposure scenario	Use of lubricants and greases in open systems - Industrial
List of use descriptors	<p>Identified use name: Use of lubricants and greases in open systems-Industrial</p> <p>Process Category: PROC01, PROC02, PROC07, PROC08b, PROC09, PROC10, PROC13</p> <p>Sector of end use: SU03</p> <p>Subsequent service life relevant for that use: No.</p> <p>Environmental Release Category: ERC04</p> <p>Specific Environmental Release Category: ATIEL-ATC SPERC 4.Ci.v1</p>

Processes and activities covered by the exposure scenario	Covers use of lubricants and greases in open systems, including application of lubricant to work pieces or equipment by dipping, brushing or spraying (without exposure to heat), e.g. mould releases, corrosion protection, slideways. Includes associated product storage, material transfers, sampling and maintenance activities.
--	---

Section 2 Operational conditions and risk management measures

Section 2.1 Control of worker exposure

Product characteristics:

Physical state:	Liquid, vapour pressure < 0.5 kPa
Concentration of substance in product:	Covers use of substance/product up to 100 % (unless stated differently)
Frequency and duration of use:	Covers daily exposures up to 8 hours
Other conditions affecting workers exposure:	Assumes use at not more than 20°C above ambient temperature. Assumes a good basic standard of occupational hygiene is implemented

Contributing scenarios: Operational conditions and risk management measures

The following information provides minimum risk management measures for the contributing scenarios identified within this lubricant use group. However, more detailed information on control measures e.g. specific glove types may be documented in Section 8 of the main body of this safety data sheet.

Please review Section 8 in conjunction with the information on this Generic Exposure Scenario.

General measures applicable to all activities:

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying.

Use suitable eye protection. Avoid direct eye contact with product also via contamination on hands.

Material transfers Manual:

Avoid carrying out activities involving exposure for more than 1 hour per day.

Material transfers Automated process with (semi) closed systems:

Ensure material transfers are under containment or extract ventilation.

Roller, spreader, flow application:

Provide extract ventilation to points where emissions occur.

Spraying:

Carry out in a vented booth or extracted enclosure.

Treatment by dipping and pouring:

Techniclean S Extra FF	Use of lubricants and greases in open systems - Industrial
-------------------------------	---

Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

Equipment cleaning and maintenance:

Drain down system prior to equipment break-in or maintenance. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training. Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Storage:

Store substance within a closed system.

Section 2.2: Control of environmental exposure

Product characteristics:	Applicability domain: product in which the risk determining substance has the following hazard profile: LogKow: Vapour pressure: PNEC Freshwater aquatic range (mg/L):
Amounts used:	
EU tonnage of risk determining substance per year:	3.81E+01 Tonnes/year
Frequency and duration of use:	
Emission days	300
Environment factors not influenced by risk management:	
Local freshwater dilution factor	10
Local marine water dilution factor	100
Other conditions affecting environmental exposure:	Negligible wastewater emissions as process operates without water contact.
Release fraction to air (after typical onsite RMMs)	5.00E-05
Release fraction to soil from process (after typical onsite RMMs)	0
Release fraction to wastewater from process (after typical onsite RMMs and before sewage treatment plan)	No data available yet
Technical conditions and measures at process level (source) to prevent release:	Common practices vary across sites thus conservative process release estimates used.
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:	Prevent discharge of undissolved substance to or recover from onsite wastewater. User sites are assumed to be provided with oil/water separators and waste water to be discharged via a sewage treatment plant
Organisational measures to prevent/limit release from site:	Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.
Conditions and measures related to sewage treatment plant:	
Estimated substance removal from wastewater via on-site sewage treatment	No data available yet
Assumed domestic sewage treatment plant flow rate (m³/d)	2.00E+3
Maximum allowable site tonnage (M_{Safe}) based on release following total wastewater treatment removal	No data available yet
Maximum allowable site tonnage (M_{Safe}) based on release following total wastewater treatment removal as product:	No data available yet
Conditions and measures related to external treatment of waste for disposal:	External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste:	External recovery and recycling of waste should comply with applicable local and/or national regulations.

Section 3: Exposure estimation and reference to its source

Exposure estimation and reference to its source - Environment

Exposure assessment (environment): Used ECETOC TRA model (May 2010 release).

Exposure estimation and reference to its source - Workers

Exposure assessment (human): The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 4: Guidance to check compliance with the exposure scenario

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.ATIEL.org/REACH_GES

Health

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Annex to the extended Safety Data Sheet (eSDS)

Professional

Identification of the substance or mixture

Product definition	Mixture
Code	465404-FR01
Product name	Techniclean S Extra FF

Section 1: Title

Short title of the exposure scenario	Use of lubricants and greases in open systems - Professional
List of use descriptors	<p>Identified use name: Use of lubricants and greases in open systems-Professional</p> <p>Process Category: PROC01, PROC02, PROC08a, PROC10, PROC11, PROC13</p> <p>Sector of end use: SU22</p> <p>Subsequent service life relevant for that use: No.</p> <p>Environmental Release Category: ERC08a, ERC08d</p> <p>Specific Environmental Release Category: ATIEL-ATC SPERC 8.Cp.v1</p>

Processes and activities covered by the exposure scenario	Covers use of lubricants and greases in open systems, including application of lubricant to work pieces or equipment by dipping, brushing or spraying (without exposure to heat), e.g. mould releases, corrosion protection, slideways. Includes associated product storage, material transfers, sampling and maintenance activities.
Assessment Method	See Section 3

Section 2 Operational conditions and risk management measures

Section 2.1 Control of worker exposure

Physical state:	Liquid, vapour pressure < 0.5 kPa
Amounts used:	Covers use of substance/product up to 100 % (unless stated differently)
Frequency and duration of use:	Covers daily exposures up to 8 hours
Other conditions affecting workers exposure:	Assumes use at not more than 20°C above ambient temperature. Assumes a good basic standard of occupational hygiene is implemented

Contributing scenarios: Operational conditions and risk management measures

General measures applicable to all activities:

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop.

Use suitable eye protection. Avoid direct eye contact with product also via contamination on hands.

Material transfers

Manual: Avoid carrying out activities involving exposure for more than 1 hour per day.

Roller, spreader, flow application: Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Avoid carrying out activities involving exposure for more than 4 hours per day. Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

Spraying: Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Avoid carrying out activities involving exposure for more than 1 hour per day. Wear a respirator conforming to EN140 with type A/P2 filter or better. Wear suitable coveralls to prevent exposure to the skin. Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

Treatment by dipping and pouring: Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.

Equipment cleaning and maintenance:

Drain down system prior to equipment break-in or maintenance. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Avoid carrying out activities involving exposure for more than 4 hours per day. Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Storage:

Techniclean S Extra FF

Use of lubricants and greases in open systems - Professional

Store substance within a closed system.

Section 2.2: Control of environmental exposure

Product characteristics:	Applicability domain: product in which the risk determining substance has the following hazard profile: LogKow: Vapour pressure: PNEC Freshwater aquatic range (mg/L):
Amounts used:	2.24E+01 Tonnes/year
Frequency and duration of use:	
Emission days	365
Environment factors not influenced by risk management:	
Local freshwater dilution factor	10
Local marine water dilution factor	100
Other conditions affecting environmental exposure:	Negligible wastewater emissions as process operates without water contact.
Release fraction to air (after typical onsite RMMs)	1.00E-04
Release fraction to soil from process (after typical onsite RMMs)	1E-03
Release fraction to wastewater from process (after typical onsite RMMs and before sewage treatment plan)	No data available yet
Technical conditions and measures at process level (source) to prevent release:	Common practices vary across sites thus conservative process release estimates used.
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:	Prevent discharge of undissolved substance to or recover from onsite wastewater.
Organisational measures to prevent/limit release from site:	Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.
Conditions and measures related to sewage treatment plant:	
Estimated substance removal from wastewater via on-site sewage treatment	No data available yet
Maximum allowable site tonnage (M_{safe}) based on release following total wastewater treatment removal	No data available yet
Conditions and measures related to external treatment of waste for disposal:	External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste:	External recovery and recycling of waste should comply with applicable local and/or national regulations.

Section 3: Exposure estimation and reference to its source

Exposure estimation and reference to its source - Environment

Exposure assessment (environment): Used ECETOC TRA model (May 2010 release).

Exposure estimation and reference to its source - Workers

Exposure assessment (human): The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 4: Guidance to check compliance with the exposure scenario

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.ATIEL.org/REACH_GES

Health

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition	Mixture
Code	465404-FR01
Product name	Techniclean S Extra FF

Section 1: Title

Short title of the exposure scenario	Handling and dilution of metal working fluid concentrates - Industrial
List of use descriptors	<p>Identified use name: Handling and dilution of metal working fluid concentrates-Industrial</p> <p>Process Category: PROC01, PROC02, PROC08b, PROC05</p> <p>Sector of end use: SU03</p> <p>Subsequent service life relevant for that use: No.</p> <p>Environmental Release Category: ERC02</p> <p>Specific Environmental Release Category: ATIEL-ATC SPERC 2.Ei.v1</p>

Processes and activities covered by the exposure scenario	Handling and dilution of metal working fluid concentrates. Includes associated product storage, material transfers, sampling and maintenance activities.
--	--

Section 2 Operational conditions and risk management measures

Section 2.1 Control of worker exposure

Product characteristics:

Physical state:	Liquid, vapour pressure < 0.5 kPa
Concentration of substance in product:	Covers use of substance/product up to 100 % (unless stated differently)
Frequency and duration of use:	Covers daily exposures up to 8 hours
Other conditions affecting workers exposure:	Assumes use at not more than 20°C above ambient temperature. Assumes a good basic standard of occupational hygiene is implemented

Contributing scenarios: Operational conditions and risk management measures

General measures applicable to all activities:
Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Use suitable eye protection. Avoid direct eye contact with product also via contamination on hands.

Filling of equipment from drums or containers:
Avoid carrying out activities involving exposure for more than 4 hours per day.

Process sampling:
Avoid carrying out activities involving exposure for more than 4 hours per day.

Equipment cleaning and maintenance:
Drain down system prior to equipment break-in or maintenance. Avoid carrying out activities involving exposure for more than 4 hours per day. Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Storage:
Store substance within a closed system.

Section 2.2: Control of environmental exposure

Amounts used:	3.02E+02 Tonnes/year
EU tonnage of risk determining substance per year:	3.02E+02 Tonnes/year
Frequency and duration of use:	
Emission days	300
Environment factors not influenced by risk management:	
Local freshwater dilution factor	10
Local marine water dilution factor	100
Other conditions affecting environmental exposure:	Water-based (oil in water emulsion) or straight oil (contains no water) process
Release fraction to air (after typical onsite RMMs)	5.00E-05
Release fraction to soil from process (after typical onsite RMMs)	0
Release fraction to wastewater from process (after typical onsite RMMs and before sewage treatment plan)	No data available
Technical conditions and measures at process level (source) to prevent release:	Common practices vary across sites thus conservative process release estimates used.
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:	Prevent discharge of undissolved substance to or recover from onsite wastewater. User sites are assumed to be provided with oil/water separators and waste water to be discharged via a sewage treatment plant
Organisational measures to prevent/limit release from site:	Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.
Conditions and measures related to sewage treatment plant:	
Estimated substance removal from wastewater via on-site sewage treatment	No data available
Assumed domestic sewage treatment plant flow rate (m³/d)	2.00E+3
Maximum allowable site tonnage (M_{Safe}) based on release following total wastewater treatment removal as product:	No data available
Conditions and measures related to external treatment of waste for disposal:	External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste:	External recovery and recycling of waste should comply with applicable local and/or national regulations.

Section 3: Exposure estimation and reference to its source

Exposure estimation and reference to its source - Environment

Exposure assessment (environment): Used ECETOC TRA model (May 2010 release).

Exposure estimation and reference to its source - Workers

Exposure assessment (human): The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 4: Guidance to check compliance with the exposure scenario

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.ATIEL.org/REACH_GES

Health

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.