

1. Product and company identification

Product name	Castrol Transmax ATF Dex/Merc Multivehicle
Product code	469842-JP03
SDS #	469842
Original preparation date	24/11/2020
Supplier	BP Castrol K.K. 1-11-2, Osaki, Shinagawaku, Tokyo, 141-0032 East Tower 20F, Gate City Osaki Telephone : 03-5719-7860 (days & hours of operation : Monday - Friday, 09:00 - 17:00) Carechem: +81 50 5057 7850 (Operation time: 24 hrs)
EMERGENCY TELEPHONE NUMBER	Carechem: +81 50 5057 7850 (Operation time: 24 hrs)

Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Automatic transmission fluid For specific application advice see appropriate Technical Data Sheet or consult our company representative.
-----------------	---

Uses advised against

Use advised against: Consult with experts for use other than relevant identified use

2. Hazards identification

GHS Classification	HAZARDOUS TO THE AQUATIC ENVIRONMENT - ACUTE HAZARD - Category 3
<u>GHS label elements</u>	
Signal word	No signal word.
Hazard statements	H402 - Harmful to aquatic life.
Precautionary statements	
General	P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand.
Prevention	P273 - Avoid release to the environment.
Response	Not applicable.
Storage	Not applicable.
Disposal	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	Defatting to the skin.

Product name	Castrol Transmax ATF Dex/Merc Multivehicle	Product code	469842-JP03	Page: 1/17
Version	3.07	Date of issue	2026 January 9	Format Japan
		Date of previous issue	2025 December 17.	Language
		Original preparation date	11/24/2020	ENGLISH (ENGLISH)
			Build 6.2 (Japan)	

3. Composition/information on ingredients

Substance/mixture

Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Ingredient name	%	CAS number	Official Gazette notice reference number	
			CSCL	ISHL
Distillates (petroleum), hydrotreated heavy paraffinic	≥50 - ≤75	CAS: 64742-54-7	(9)-1692	Not available.
Distillates (petroleum), hydrotreated heavy paraffinic	≥25 - ≤50	CAS: 64742-54-7	Not available.	Not available.
Distillates (petroleum), hydrotreated light paraffinic	≤3.0	CAS: 64742-55-8	Not available.	Not available.
Bis (2-hydroxyethyl) tallow alkylamine	≤0.10	CAS: 61791-44-4	7-60	Not available.
2-(heptadecenyl)-4,5-dihydro-1H-imidazole-1-ethanol	≤0.10	CAS: 27136-73-8	5-3496; 5-425	Not available.
2-(2-heptadec-8-enyl-2-imidazolin-1-yl) ethanol	≤0.10	CAS: 95-38-5	5-3496; 5-425	Not available.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Applicability to local regulations are determined with consideration of reactions of constituents included in the formulation. Please see section 15 for regulatory information.

4. First aid measures

Description of necessary first aid measures

Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.

Inhalation

If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.

Skin contact

Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur. If skin irritation or rash occurs: Get medical advice/attention.

Ingestion

Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if adverse health effects persist or are severe.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training.

Product name	Castrol Transmax ATF Dex/Merc Multivehicle	Product code	469842-JP03	Page: 2/17	
Version	3.07	Date of issue	2026 January 9	Format Japan	Language ENGLISH
		Date of previous issue	2025 December 17.	Build 6.2 (Japan)	(ENGLISH)
	Original preparation date	11/24/2020			

4. First aid measures

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	No specific treatment.

5. Firefighting measures

Extinguishing media

Suitable	Use foam or all-purpose dry chemical to extinguish.
Not suitable	Do not use water jet.
Specific hazards arising from the chemical	Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life.
Hazardous thermal decomposition products	Combustion products may include the following: carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide) nitrogen oxides (NO, NO ₂ etc.)
Special protective actions for fire-fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.
Special protective equipment for fire-fighters	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.
For emergency responders	Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".
Environmental precautions	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and material for containment and cleaning up

Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

Product name	Castrol Transmax ATF Dex/Merc Multivehicle	Product code	469842-JP03	Page: 3/17	
Version	3.07	Date of issue	2026 January 9	Format Japan	Language ENGLISH
		Date of previous issue	2025 December 17.	Build 6.2 (Japan)	(ENGLISH)
	Original preparation date	11/24/2020			

6. Accidental release measures

In the case of spillage at sea approved dispersants may be used where authorised by the appropriate government/regulatory authorities.

7. Handling and storage

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Avoid contact of spilt material and runoff with soil and surface waterways.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. Contaminated work clothing should not be allowed out of the workplace. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Not suitable

Avoid all possible sources of ignition (spark or flame).

8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy paraffinic	Japan Society for Occupational Health (Japan) [Mineral oils] Carc 1. Japan Society for Occupational Health (Japan) [Soots] Carc 1. Japan Society for Occupational Health (Japan) [Oil mist, mineral] OEL-M 8 hours: 3 mg/m ³ . Form: Mist. Issued/Revised: 5/2010.
Distillates (petroleum), hydrotreated heavy paraffinic	Japan Society for Occupational Health (Japan) [Mineral oils] Carc 1. Japan Society for Occupational Health (Japan) [Soots] Carc 1. Japan Society for Occupational Health (Japan) [Oil mist, mineral] OEL-M 8 hours: 3 mg/m ³ . Form: Mist. Issued/Revised: 5/2010.
Distillates (petroleum), hydrotreated light paraffinic	Japan Society for Occupational Health (Japan) [Mineral oils] Carc 1. Japan Society for Occupational Health (Japan) [Soots] Carc 1. Japan Society for Occupational Health (Japan) [Oil mist, mineral]

Product name	Castrol Transmax ATF Dex/Merc Multivehicle	Product code	469842-JP03	Page: 4/17		
Version	3.07	Date of issue	2026 January 9	Format Japan	Language ENGLISH	
		Date of previous issue	2025 December 17.	Build 6.2	(JAPAN)	(ENGLISH)
		Original preparation date	11/24/2020			

8. Exposure controls/personal protection

OEL-M 8 hours: 3 mg/m³. Form: Mist.
Issued/Revised: 5/2010.

Recommended monitoring procedures

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Biological exposure indices

No exposure indices known.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Eye protection

Safety glasses with side shields.

Product name	Castrol Transmax ATF Dex/Merc Multivehicle	Product code	469842-JP03	Page: 5/17	
Version	3.07	Date of issue	2026 January 9	Format Japan	Language ENGLISH
		Date of previous issue	2025 December 17.	Build 6.2 (Japan)	(ENGLISH)
		Original preparation date	11/24/2020		

8. Exposure controls/personal protection

Skin protection

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state

Liquid.

Colour

Red. [Light]

Odour

Mild

pH

Not applicable.

Melting point/freezing point

Not available.

Softening point

Not available.

Boiling point or initial boiling point and boiling range

Not available.

Flash point

Closed cup: >170°C (>338°F) [Pensky-Martens]
Open cup: >200°C (>392°F) [Cleveland]

Fire point

Not available.

Evaporation rate

Not available.

Flammability

Not available.

Lower and upper explosive (flammable) limits

Not available.

Vapour pressure

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191			
Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191			
Distillates (petroleum), hydrotreated light paraffinic	<0.07501	<0.01	ASTM D 5191			

Relative vapour density

Not available.

Relative Density

Not available.

Density

<1 g/cm³ [15°C (59°F)]

Auto-ignition temperature

Not available.

Product name Castrol Transmax ATF Dex/Merc Multivehicle

Product code 469842-JP03

Page: 6/17

Version 3.07 **Date of issue** 2026 January 9

Format Japan

Language ENGLISH

Date of previous issue 2025 December 17.

Build 6.2 (Japan)

(ENGLISH)

Original preparation date 11/24/2020

9. Physical and chemical properties

Ingredient name	°C	°F	Method
Not listed.			

Decomposition temperature	Not available.
Lower and upper explosion limit/flammability limit	Not available.
Critical temperature	Not available.
Oxidising properties	Not available.
Viscosity	Kinematic: 35 mm ² /s (35 cSt) at 40°C Kinematic: 7 to 8 mm ² /s (7 to 8 cSt) at 100°C
Drop Point	Not available.
Density	<1000 kg/m ³ (<1 g/cm ³) at 15°C
Solubility(ies)	

Media	Result
water	Not soluble

Solubility at room temperature (g/l)	Not available.
Partition coefficient (LogKow)	Not applicable.
Remarks	Not available.

Particle characteristics

Median particle size	Not applicable.
----------------------	-----------------

10. Stability and reactivity

Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
Incompatible materials	Reactive or incompatible with the following materials: oxidising materials.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Acute toxicity

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Result

Rat - Oral - LD50

>5000 mg/kg

OECD 401

Rabbit - Dermal - LD50

>5000 mg/kg

OECD 402

Rat - Inhalation - LC50 Dusts and mists

>5 mg/l [4 hours]

OECD 403

Distillates (petroleum), hydrotreated heavy

Rat - Oral - LD50

Product name	Castrol Transmax ATF Dex/Merc Multivehicle	Product code	469842-JP03	Page: 7/17	
Version	3.07	Date of issue	2026 January 9	Format Japan	Language ENGLISH
		Date of previous issue	2025 December 17.	Build 6.2 (Japan)	(ENGLISH)
	Original preparation date	11/24/2020			

11. Toxicological information

paraffinic	>5000 mg/kg OECD 401 Rabbit - Dermal - LD50 >5000 mg/kg OECD 402 Rat - Inhalation - LC50 Dusts and mists >5 mg/l [4 hours] OECD 403
Distillates (petroleum), hydrotreated light paraffinic	Rat - Oral - LD50 >5000 mg/kg OECD 401 Rabbit - Dermal - LD50 >5000 mg/kg OECD 402 Rat - Inhalation - LC50 Dusts and mists >5.53 mg/l [4 hours] OECD 403
Bis (2-hydroxyethyl) tallow alkylamine	Rat - Oral - LD50 1350 mg/kg OECD 401
2-(heptadecenyl)-4,5-dihydro-1H-imidazole-1-ethanol	Rat - Oral - LD50 500 to 5000 mg/kg
2-(2-heptadec-8-enyl-2-imidazolin-1-yl) ethanol	Rat - Oral - LD50 1265 mg/kg OECD 401

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Castrol Transmax ATF Dex/Merc Multivehicle	206558.7	N/A	N/A	N/A	N/A
Bis (2-hydroxyethyl) tallow alkylamine	500	N/A	N/A	N/A	N/A
2-(heptadecenyl)-4,5-dihydro-1H-imidazole-1-ethanol	500	N/A	N/A	N/A	N/A
2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	500	N/A	N/A	N/A	N/A

Ingredient name

2-(2-heptadec-8-enyl-2-imidazolin-1-yl) ethanol

Conclusion/Summary

Acute Dermal toxicity not conducted as corrosive to skin

Skin corrosion/irritation

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), hydrotreated light paraffinic

Bis (2-hydroxyethyl) tallow alkylamine

2-(2-heptadec-8-enyl-2-imidazolin-1-yl) ethanol

Result

Rabbit - Skin - Mild irritant

OECD 404

Rabbit - Skin - Mild irritant

OECD 404

Rabbit - Skin - Non-irritant to skin.

Rabbit - Skin - Corrosive

OECD 404

Rabbit - Skin - Visible necrosis

OECD 404

Product name	Castrol Transmax ATF Dex/Merc Multivehicle	Product code	469842-JP03	Page: 8/17
Version	3.07	Date of issue	2026 January 9	Format Japan
		Date of previous issue	2025 December 17.	Language ENGLISH
		Original preparation date	11/24/2020	(ENGLISH)
			Build 6.2 (Japan)	

11. Toxicological information

[Serious eye damage/eye irritation](#)

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), hydrotreated light paraffinic

2-(2-heptadec-8-enyl-2-imidazolin-1-yl) ethanol

Result

Rabbit - Eyes - Non-irritating to the eyes.
OECD 405

Rabbit - Eyes - Non-irritating to the eyes.
OECD 405

Rabbit - Eyes - Non-irritating to the eyes.
OECD 405

Rabbit - Eyes - Visible necrosis
OECD 405

[Respiratory corrosion/irritation](#)

Not available.

[Respiratory or skin sensitization](#)

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), hydrotreated light paraffinic

Bis (2-hydroxyethyl) tallow alkylamine

2-(2-heptadec-8-enyl-2-imidazolin-1-yl) ethanol

Result

Guinea pig - skin
OECD 406
Result: Not sensitising

Guinea pig - skin
OECD 406
Result: Not sensitising

Guinea pig - skin
OECD 406
Result: Not sensitising

Guinea pig - skin
OECD 406
Result: Not sensitising

Guinea pig - skin
OECD 406
Result: Not sensitising

[Germ cell mutagenicity](#)

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Result

In vitro - Bacteria
Bacterial Reverse Mutation Test
Result: Negative

In vitro - Mammal - species unspecified
In vitro Mammalian Chromosomal Aberration Test
Result: Negative

In vivo - Mammal - species unspecified
Mammalian Erythrocyte Micronucleus Test
Result: Negative

Product name	Castrol Transmax ATF Dex/Merc Multivehicle	Product code	469842-JP03	Page: 9/17
Version	3.07	Date of issue	2026 January 9	Format Japan
		Date of previous issue	2025 December 17.	Language ENGLISH
		Original preparation date	11/24/2020	(ENGLISH)

11. Toxicological information

Distillates (petroleum), hydrotreated heavy paraffinic

In vitro - Mammal - species unspecified
In vitro Mammalian Cell Gene Mutation Test
Result: Negative

In vitro - Bacteria
Bacterial Reverse Mutation Test
Result: Negative

In vitro - Mammal - species unspecified
In vitro Mammalian Chromosomal Aberration Test
Result: Negative

In vivo - Mammal - species unspecified
Mammalian Erythrocyte Micronucleus Test
Result: Negative

In vitro - Mammal - species unspecified
In vitro Mammalian Cell Gene Mutation Test
Result: Negative

Distillates (petroleum), hydrotreated light paraffinic

In vitro - Bacteria
OECD [Bacterial Reverse Mutation Test]
Result: Negative

In vitro - Mammal - species unspecified
OECD [In vitro Mammalian Chromosomal Aberration Test]
Result: Negative

Bis (2-hydroxyethyl) tallow alkylamine

In vitro - Bacteria
OECD [Bacterial Reverse Mutation Test]
Result: Negative

In vitro - Mammal - species unspecified
OECD [In vitro Mammalian Cell Gene Mutation Test]
Result: Negative

In vitro - Mammalian-Human
OECD [In vitro Mammalian Chromosomal Aberration Test]
Result: Negative

2-(2-heptadec-8-enyl-2-imidazolin-1-yl) ethanol

In vitro - Bacteria
Bacterial Reverse Mutation Test
Result: Negative

In vitro - Mammal - species unspecified
In vitro Mammalian Chromosomal Aberration Test
Result: Negative

[Carcinogenicity](#)

[Product/ingredient name](#)

[Result](#)

Distillates (petroleum), hydrotreated heavy paraffinic

Mouse - Dermal - Unspecified
OECD 451
Result: Negative

Distillates (petroleum), hydrotreated heavy paraffinic

Mouse - Dermal - Unspecified
OECD 451
Result: Negative

[Reproductive toxicity](#)

[Product/ingredient name](#)

[Result](#)

Product name	Castrol Transmax ATF Dex/Merc Multivehicle	Product code	469842-JP03	Page: 10/17
Version	3.07	Date of issue	2026 January 9	Format Japan
		Date of previous issue	2025 December 17.	Language ENGLISH
		Original preparation date	11/24/2020	(ENGLISH)
			Build 6.2 (Japan)	

11. Toxicological information

Distillates (petroleum), hydrotreated heavy paraffinic

Rat - Oral
OECD 421
Maternal toxicity: Negative
Fertility effects: Negative
Developmental: Negative

Distillates (petroleum), hydrotreated heavy paraffinic

Rat - Oral
OECD 421
Maternal toxicity: Negative
Fertility effects: Negative
Developmental: Negative

Distillates (petroleum), hydrotreated light paraffinic

Rat - Oral
OECD 421
Maternal toxicity: Negative
Fertility effects: Negative
Developmental: Negative

Bis (2-hydroxyethyl) tallow alkylamine

Rat - Oral
OECD 422
Maternal toxicity: Positive
Fertility effects: Equivocal
Developmental: Equivocal

2-(2-heptadec-8-enyl-2-imidazolin-1-yl) ethanol

Rat - Oral
OECD 422
Maternal toxicity: Positive
Fertility effects: Negative
Developmental: Negative

[Specific target organ toxicity \(single exposure\)](#)

Not available.

[Specific target organ toxicity \(repeated exposure\)](#)

[Product/ingredient name](#)

2-(heptadecenyl)-4,5-dihydro-1H-imidazole-1-ethanol
2-(2-heptadec-8-enyl-2-imidazolin-1-yl) ethanol

[Result](#)

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE (digestive system, thymus) (oral) - Category 2
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE (digestive system, thymus) (oral) - Category 2

[Aspiration hazard](#)

[Product/ingredient name](#)

Distillates (petroleum), hydrotreated heavy paraffinic
Distillates (petroleum), hydrotreated light paraffinic

[Result](#)

ASPIRATION HAZARD - Category 1
ASPIRATION HAZARD - Category 1

[Information on likely routes of exposure](#)

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

[Potential acute health effects](#)

[Eye contact](#)

No known significant effects or critical hazards.

[Inhalation](#)

Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Product name	Castrol Transmax ATF Dex/Merc Multivehicle	Product code	469842-JP03	Page: 11/17	
Version	3.07	Date of issue	2026 January 9	Format Japan	Language ENGLISH
		Date of previous issue	2025 December 17.	Build 6.2 (Japan)	(ENGLISH)
	Original preparation date	11/24/2020			

11. Toxicological information

Skin contact	Defatting to the skin. May cause skin dryness and irritation.
Ingestion	No known significant effects or critical hazards.
<u>Symptoms related to the physical, chemical and toxicological characteristics</u>	
Eye contact	No specific data.
Inhalation	May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
Skin contact	Adverse symptoms may include the following: irritation dryness cracking
Ingestion	No specific data.
<u>Delayed and immediate effects as well as chronic effects from short and long-term exposure</u>	
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
<u>Potential chronic health effects</u>	
General	No known significant effects or critical hazards.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

12. Ecological information

Environmental effects This material is harmful to aquatic life.

Ecotoxicity

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Result

Acute - EL50

OECD 201
Algae
>100 mg/l [72 hours]

Acute - EL50

OECD 202
Daphnia
>10000 mg/l [48 hours]

Acute - LL50

OECD 203
Fish
>100 mg/l [96 hours]

Chronic - NOEL

OECD 201
Algae
≥100 mg/l [72 hours]

Chronic - NOEL

OECD 211
Daphnia
10 mg/l [21 days]

Product name	Castrol Transmax ATF Dex/Merc Multivehicle	Product code	469842-JP03	Page: 12/17	
Version	3.07	Date of issue	2026 January 9	Format Japan	Language ENGLISH
		Date of previous issue	2025 December 17.	Build 6.2 (Japan)	(ENGLISH)
		Original preparation date	11/24/2020		

12. Ecological information

Distillates (petroleum), hydrotreated heavy paraffinic

Acute - EL50

OECD 201

Algae

>100 mg/l [72 hours]

Acute - EL50

OECD 202

Daphnia

>10000 mg/l [48 hours]

Acute - LL50

OECD 203

Fish

>100 mg/l [96 hours]

Chronic - NOEL

OECD 201

Algae

≥100 mg/l [72 hours]

Chronic - NOEL

OECD 211

Daphnia

10 mg/l [21 days]

Distillates (petroleum), hydrotreated light paraffinic

Acute - EL50

OECD 201

Algae

>100 mg/l [72 hours]

Acute - EL50

OECD 202

Daphnia

>10000 mg/l [48 hours]

Acute - LL50

OECD 203

Fish

>100 mg/l [96 hours]

Chronic - NOEL

OECD 201

Algae

≥100 mg/l [72 hours]

Chronic - NOEL

OECD 211

Daphnia

10 mg/l [21 days]

Bis (2-hydroxyethyl) tallow alkylamine

Acute - EC50

OECD 201

Algae

0.0538 mg/l [72 hours]

Acute - EC50

OECD 202

Daphnia

0.043 mg/l [48 hours]

Acute - LC50

OECD 203

Fish

0.1 mg/l [96 hours]

Chronic - EC10

Product name	Castrol Transmax ATF Dex/Merc Multivehicle	Product code	469842-JP03	Page: 13/17	
Version	3.07	Date of issue	2026 January 9	Format Japan	Language ENGLISH
		Date of previous issue	2025 December 17.	Build 6.2 (Japan)	(ENGLISH)
		Original preparation date	11/24/2020		

12. Ecological information

	OECD 201 Algae 0.0156 mg/l [72 hours] Chronic - EC10
2-(heptadecenyl)-4,5-dihydro-1H-imidazole-1-ethanol	OECD 211 Daphnia 0.0107 mg/l [21 days] EC50 Fish 0.01 to 0.1 mg/l [96 hours] Acute - ErC50
2-(2-heptadec-8-enyl-2-imidazolin-1-yl) ethanol	OECD 201 Algae 0.03 mg/l [72 hours] Acute - EC50 OECD 202 Daphnia 0.163 mg/l [48 hours] Acute - LL50 OECD 203 Fish 0.3 mg/l [96 hours] Chronic - ErC10 OECD 201 Algae 0.014 mg/l [72 hours]

Persistence and degradability Not expected to be rapidly degradable.

Product/ingredient name	Result
Distillates (petroleum), hydrotreated heavy paraffinic	OECD 301F 31% [28 days] - Not readily
Distillates (petroleum), hydrotreated heavy paraffinic	OECD 301F 31% [28 days] - Not readily
Distillates (petroleum), hydrotreated light paraffinic	OECD 301F 31% [28 days] - Not readily
Bis (2-hydroxyethyl) tallow alkylamine	OECD 301D 61 to 65% [28 days] - Readily
2-(2-heptadec-8-enyl-2-imidazolin-1-yl) ethanol	OECD 301B 1% [28 days] - Not readily

Bioaccumulative potential

Bioaccumulative potential This product is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	LogP _{ow}	BCF	Potential
Bis (2-hydroxyethyl) tallow alkylamine	3.6	-	Low
2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	>7	-	High

Mobility Spillages may penetrate the soil causing ground water contamination.

Product name	Castrol Transmax ATF Dex/Merc Multivehicle	Product code	469842-JP03	Page: 14/17
Version	3.07	Date of issue	2026 January 9	Format Japan
		Date of previous issue	2025 December 17.	Language ENGLISH
		Original preparation date	11/24/2020	(ENGLISH)
			Build 6.2 (Japan)	

12. Ecological information

Hazardous to the ozone layer

Not applicable.

Other ecological information

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

	IMDG	IATA
UN number	Not regulated.	Not regulated.
UN proper shipping name	-	-
Transport hazard class(es)	-	-
Packing group	-	-
Environmental hazards	No.	No.
Additional information	-	-

Special precautions for user

Not available.

[Transport in bulk according to IMO instruments](#)

Not available.

15. Regulatory information

[Fire Service Law](#)

Category	Substance name/Type	Danger category	Signal word	Designated quantity
Category IV	Class IV petroleum	III	Flammable - Keep Fire Away	6000 L

[Industrial Safety and Health Act](#)

Product name	Castrol Transmax ATF Dex/Merc Multivehicle	Product code	469842-JP03	Page: 15/17	
Version	3.07	Date of issue	2026 January 9	Format Japan	Language ENGLISH
	Date of previous issue	2025 December 17.	Build 6.2	(Japan)	(ENGLISH)
	Original preparation date	11/24/2020			

15. Regulatory information

Special Organic Solvents, etc. Not applicable.

Substances requiring labelling

Ingredient name	Name on list	CAS no.	Conc.	Status
-	Mineral oil	-	90 - 100	Listed

*Chemicals damaging skin/eye and Skin-absorbable harmful substances based on Article 594-2 are disclosed in the above table.

Chemicals requiring notification

Ingredient name	Name on list	CAS no.	Conc.	Status
-	Mineral oil	-	90 - 100	Listed

Carcinogens based on Article 577-2 of the Ordinance on ISH

Ingredient name	%	Status	Reference number
None of the components are listed.			

Carcinogens based on Paragraph 3, Article 28 of the Law

Ingredient name	%	Status	Reference number
None of the components are listed.			

Pollutant Release and Transfer Registers (PRTR)

None of the components are listed.

Other regulations

Australia inventory (AIC)	All components are listed or exempted.
Canada inventory	All components are listed or exempted.
China inventory (IECSC)	All components are listed or exempted.
Japan inventory (CSCL)	All components are listed or exempted.
Korea inventory (KECI)	All components are listed or exempted.
Philippines inventory (PICCS)	Not determined.
Taiwan Chemical Substances Inventory (TCSI)	All components are listed or exempted.
United States inventory (TSCA 8b)	Not determined.
REACH Status	For the REACH status of this product please consult your company contact, as identified in Section 1.

16. Other information

History

Date of issue/Date of revision	2026 January 9.
Date of previous issue	2025 December 17.
Prepared by	Product Stewardship

Product name	Castrol Transmax ATF Dex/Merc Multivehicle	Product code	469842-JP03	Page: 16/17	
Version	3.07	Date of issue	2026 January 9	Format Japan	Language ENGLISH
		Date of previous issue	2025 December 17.	Build 6.2 (Japan)	(ENGLISH)
		Original preparation date	11/24/2020		

16. Other information

The Japan key to abbreviations is as follows:

GHS = Global Harmonized System
CAS Number = Chemical Abstracts Service Registry Number
ISHL = Industrial Safety and Health Law
OSHL = Occupational Safety and Health Law
PRTR = Law Concerning Reporting of the Release into the Environment of Specific Chemical Substances and Promoting Improvements in Their Management
ENCS = Existing and New Chemical Substances
METI = Ministry of Economy, Trade and Industry
OEL = Occupational Exposure Limit
JSOH = Japan Society for Occupational Health
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
TWA = Time weighted average
STEL = Short term exposure limit
IMDG = International Maritime Organization Rules, rules governing shipment of goods by water.
IATA = International Air Transport Association, the organization
UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods.
Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

[Procedure used to derive the classification](#)

Classification	Justification
HAZARDOUS TO THE AQUATIC ENVIRONMENT - ACUTE HAZARD - Category 3	Calculation method

 Indicates information that has changed from previously issued version.

[Notice to reader](#)

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name	Castrol Transmax ATF Dex/Merc Multivehicle	Product code	469842-JP03	Page: 17/17	
Version	3.07	Date of issue	2026 January 9	Format Japan	Language ENGLISH
		Date of previous issue	2025 December 17.	Build 6.2 (Japan)	(ENGLISH)
		Original preparation date	11/24/2020		