

# SAFETY DATA SHEET



Castrol High Temperature Grease

## Section 1. Identification

**GHS product identifier** Castrol High Temperature Grease

**SDS #** 467200

**Product code** 467200-BE26

### Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Grease for industrial applications.  
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

**Uses advised against** Consult with experts for use other than relevant identified use.

**Supplier's details** CASTROL BRASIL LTDA.  
Avenida das Américas no. 3.434, bloco 07,  
salas 301 a 308, Barra da Tijuca,  
Rio de Janeiro/RJ, CEP 22.640-102.  
Brasil

**EMERGENCY SPILL INFORMATION:** +55 0800 7040 720 (24h)

**e-mail address of person responsible for this SDS** MSDSadvice@bp.com

## Section 2. Hazards identification

**Classification of the substance or mixture** ☒ Not classified as hazardous according to ABNT NBR 14725

### GHS label elements

**Signal word** No signal word.

**Hazard statements** No known significant effects or critical hazards.

### Precautionary statements

**Prevention** Not applicable.

**Response** Not applicable.

**Storage** Not applicable.

**Disposal** Not applicable.

**Other hazards which do not result in classification** None known.

**Product name** Castrol High Temperature Grease

**Product code** 467200-BE26 **Page:** 1/12

**Version** 3 **Date of issue** 29/09/2025.

**Format Brazil**  
(Brazil)

**Language ENGLISH**  
(ENGLISH)

## Section 3. Composition/information on ingredients

### Substance/mixture

Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Thickening agent. Proprietary performance additives.

Ingredient name	%	Identifiers	Classification
Distillates (petroleum), solvent-dewaxed heavy paraffinic	≥25 - ≤50	CAS: 64742-65-0	Not classified as hazardous according to ABNT NBR 14725
Residual oils (petroleum), solvent refined	≥25 - ≤50	CAS: 64742-01-4	Not classified as hazardous according to ABNT NBR 14725
Distillates (petroleum), hydrotreated heavy naphthenic	≤10	CAS: 64742-52-5	Not classified as hazardous according to ABNT NBR 14725
dilithium sebacate	≤3	CAS: 19370-86-6	ACUTE TOXICITY (oral) - Category 4
4,4'-methylene bis (dibutylthiocarbamate)	≤3	CAS: 10254-57-6	AQUATIC HAZARD (LONG-TERM) - Category 4

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

#### Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.

#### Inhalation

If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.

#### Skin contact

Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur. If skin irritation or rash occurs: Get medical advice/attention.

#### Ingestion

Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

##### Eye contact

No known significant effects or critical hazards.

##### Inhalation

Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

##### Skin contact

Defatting to the skin. May cause skin dryness and irritation.

##### Ingestion

No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

##### Eye contact

No specific data.

##### Inhalation

No specific data.

##### Skin contact

Adverse symptoms may include the following:  
irritation  
dryness  
cracking

##### Ingestion

No specific data.

## Section 4. First aid measures

### Indication of immediate medical attention and special treatment needed, if necessary

#### Notes to physician

Treatment should in general be symptomatic and directed to relieving any effects. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Note: High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discolored and extremely painful with extensive subcutaneous necrosis.

Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimize tissue loss and prevent or limit permanent damage. Note that high pressure may force the product considerable distances along tissue planes.

#### Specific treatments

No specific treatment.

#### Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

#### Suitable extinguishing media

In case of fire, use water fog, alcohol resistant foam, dry chemical or carbon dioxide extinguisher or spray.

#### Unsuitable extinguishing media

Do not use water jet.

#### Specific hazards arising from the chemical

No specific fire or explosion hazard.

#### Hazardous thermal decomposition products

Combustion products may include the following:  
metal oxide/oxides  
carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)  
sulfur oxides (SO, SO<sub>2</sub> etc.)  
nitrogen oxides (NO, NO<sub>2</sub> etc.)

#### Special protective actions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

#### Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

#### For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

**Product name** Castrol High Temperature Grease

**Product code** 467200-BE26 **Page:** 3/12

**Version** 3 **Date of issue** 29/09/2025.

**Format** Brazil  
(Brazil)

**Language** ENGLISH  
(ENGLISH)

## Section 6. Accidental release measures

### Small spill

Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

### Large spill

Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. If emergency personnel are unavailable, contain spilled material. Suction or scoop the spill into appropriate disposal or recycling vessels, then cover spill area with oil absorbent. Dispose of via a licensed waste disposal contractor.

## Section 7. Handling and storage

### Precautions for safe handling

#### Protective measures

Put on appropriate personal protective equipment (see Section 8).

#### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. Contaminated work clothing should not be allowed out of the workplace. See also Section 8 for additional information on hygiene measures.

#### Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

#### Not suitable

Prolonged exposure to elevated temperature

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<b>ACGIH TLV (United States) [Mineral Oil, pure, highly and severely refined] A4.</b> TWA 8 hours: 5 mg/m <sup>3</sup> . Form: Inhalable fraction. Issued/Revised: 11/2009.
Residual oils (petroleum), solvent refined	<b>ACGIH TLV (United States) [Mineral Oil, pure, highly and severely refined] A4.</b> TWA 8 hours: 5 mg/m <sup>3</sup> . Form: Inhalable fraction. Issued/Revised: 11/2009.
Distillates (petroleum), hydrotreated heavy naphthenic	<b>ACGIH TLV (United States) [Mineral Oil, pure, highly and severely refined] A4.</b> TWA 8 hours: 5 mg/m <sup>3</sup> . Form: Inhalable fraction. Issued/Revised: 11/2009.

#### Biological exposure indices

No exposure indices known.

## Section 8. Exposure controls/personal protection

### Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

#### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

☑ Safety glasses with side shields.

#### Skin protection

##### Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacture and with a full assessment of the working conditions.

##### Skin protection

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

##### Respiratory protection

☑ In case of insufficient ventilation, wear suitable respiratory equipment.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacture and with a full assessment of the working conditions.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

Physical state	Solid. [Grease]
Color	Amber.
Odor	Characteristic.
Odor threshold	Not available.
pH	Not applicable.
Melting point/freezing point	<input checked="" type="checkbox"/> Not available.
Boiling point or initial boiling point and boiling range	Not available.
Flash point	<input checked="" type="checkbox"/> Closed cup: >200°C (>392°F) [Pensky-Martens ASTM D 93]
Evaporation rate	Not available.
Flammability	Not available.
Lower and upper explosion limit/flammability limit	Not applicable.
Vapor pressure	Not available. <0.01 kPa
Relative vapor density	Not applicable.
Relative density	Not available.
Solubility(ies)	

Media	Result
water	Not soluble

Solubility in water	Not available.
Partition coefficient: n-octanol/water	Not applicable.
Auto-ignition temperature	>300°C (>572°F)
Decomposition temperature	Not available.
Particle characteristics	
Median particle size	Not available.
Shape	

## Section 10. Stability and reactivity

Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur.
Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
Incompatible materials	Reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Product name	Castrol High Temperature Grease	Product code	467200-BE26	Page:	6/12
Version	3	Date of issue	29/09/2025.	Format	Brazil
				(Brazil)	Language ENGLISH
					(ENGLISH)

# Section 11. Toxicological information

## Information on toxicological effects

### Acute toxicity

#### Product/ingredient name

Distillates (petroleum), solvent-dewaxed heavy paraffinic

4,4'-methylene bis(dibutyldithiocarbamate)

#### Result

##### Rat - Oral - LD50

>5000 mg/kg  
OECD 401

##### Rat - Dermal - LD50

>2000 mg/kg  
OECD 402

##### Rat - Inhalation - LC50 Dusts and mists

>5.53 mg/l [4 hours]  
OECD 403

##### Rat - Oral - LD50

>5000 mg/kg  
OECD 401

##### Rabbit - Dermal - LD50

>2000 mg/kg  
OECD 402

### Skin corrosion/irritation

#### Product/ingredient name

Distillates (petroleum), solvent-dewaxed heavy paraffinic  
4,4'-methylene bis(dibutyldithiocarbamate)

#### Result

Rabbit - Skin - Non-irritant to skin.

##### Rabbit - Skin - Not irritant

OECD 404

### Serious eye damage/eye irritation

#### Product/ingredient name

Distillates (petroleum), solvent-dewaxed heavy paraffinic  
4,4'-methylene bis(dibutyldithiocarbamate)

#### Result

Rabbit - Eyes - Non-irritating to the eyes.

OECD 405

##### Rabbit - Eyes - Not irritant

OECD 405

### Respiratory or skin sensitization

#### Product/ingredient name

Distillates (petroleum), solvent-dewaxed heavy paraffinic

4,4'-methylene bis(dibutyldithiocarbamate)

#### Result

##### Guinea pig - skin

OECD 406

Result: Not sensitizing

##### Mouse - skin

OECD 429

Result: Not sensitizing

Product/ingredient name	Hazard class	Category
Not available.		

### Germ cell mutagenicity

#### Product/ingredient name

Distillates (petroleum), solvent-dewaxed heavy paraffinic

4,4'-methylene bis(dibutyldithiocarbamate)

#### Result

##### In vitro - Bacteria

OECD [Bacterial Reverse Mutation Test]

Result: Negative

##### In vitro - Mammal - species unspecified

OECD [In vitro Mammalian Chromosomal Aberration Test]

Result: Negative

##### In vitro - Bacteria

OECD 471

Result: Negative

##### In vitro - Mammalian-Animal

Product name Castrol High Temperature Grease

Version 3 Date of issue 29/09/2025.

Product code 467200-BE26 Page: 7/12

Format Brazil

(Brazil)

Language ENGLISH

(ENGLISH)



## Section 11. Toxicological information

OECD 473  
Result: Negative  
**In vitro - Mammalian-Animal**  
OECD 476  
Result: Negative

### Carcinogenicity

#### Product/ingredient name

Distillates (petroleum), solvent-dewaxed heavy paraffinic

#### Result

**Mouse - Dermal - Unspecified**  
OECD 451  
Result: Negative

Product/ingredient name	Category	Route of exposure
Not available.		

### Classification

Not available.

### Reproductive toxicity

#### Product/ingredient name

Distillates (petroleum), solvent-dewaxed heavy paraffinic

#### Result

**Rat - Oral**  
OECD 421  
Maternal toxicity: Negative  
Fertility effects: Negative  
Developmental: Negative

4,4'-methylene bis(dibutyldithiocarbamate)

**Rat - Oral**  
OECD 422  
Maternal toxicity: Negative  
Fertility effects: Negative  
Developmental: Negative

Product/ingredient name	Hazard class	Category	Route of exposure	Effects
Not available.				

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

### Information on the likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

### Potential acute health effects

#### Eye contact

No known significant effects or critical hazards.

#### Inhalation

Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

#### Skin contact

Defatting to the skin. May cause skin dryness and irritation.

#### Ingestion

No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

#### Eye contact

No specific data.

#### Inhalation

No specific data.



## Section 11. Toxicological information

### Skin contact

Adverse symptoms may include the following:  
irritation  
dryness  
cracking

### Ingestion

No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Eye contact

Potential risk of transient stinging or redness if accidental eye contact occurs.

#### Skin contact

Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

#### Ingestion

Ingestion of large quantities may cause nausea and diarrhea.

#### Short term exposure

##### Potential immediate effects

Not available.

##### Potential delayed effects

Not available.

#### Long term exposure

##### Potential immediate effects

Not available.

##### Potential delayed effects

Not available.

### Potential chronic health effects

#### General

No known significant effects or critical hazards.

#### Carcinogenicity

No known significant effects or critical hazards.

#### Mutagenicity

No known significant effects or critical hazards.

#### Developmental effects

No known significant effects or critical hazards.

#### Fertility effects

No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Oral	21760.87 mg/kg

## Section 12. Ecological information

### Toxicity

#### Product/ingredient name

Distillates (petroleum), solvent-dewaxed heavy paraffinic

#### Result

##### Acute - EL50

OECD 201

Algae

>100 mg/l [72 hours]

##### Acute - EL50

OECD 202

Daphnia

>10000 mg/l [48 hours]

##### Acute - LL50

OECD 203

Fish

>100 mg/l [96 hours]

##### Chronic - NOEL

OECD 201

Algae

≥100 mg/l [72 hours]

##### Chronic - NOEL

OECD 211

Product name Castrol High Temperature Grease

Product code 467200-BE26 Page: 9/12

Version 3 Date of issue 29/09/2025.

Format Brazil  
(Brazil)

Language ENGLISH  
(ENGLISH)

## Section 12. Ecological information

4,4'-methylene bis(dibutyldithiocarbamate)	Daphnia
	10 mg/l [21 days]
	<b>Acute - ErC50</b>
	OECD 201
	Algae
	>0.0325 mg/l [72 hours]
	<b>Acute - EC50</b>
	OECD 202
	Daphnia
	>0.052 mg/l [48 hours]
	<b>Acute - EL50</b>
	OECD 203
	Fish
	>0.06 mg/l [96 hours]
	<b>Chronic - NOEC</b>
	OECD 211
	Daphnia
	0.247 mg/l [21 days]
	<b>Chronic - NOEC</b>
	OECD 201
	Algae
	0.0325 mg/l [72 hours]

### Persistence/degradability

No testing has been performed by the manufacturer.

#### **Product/ingredient name**

Distillates (petroleum), solvent-dewaxed  
heavy paraffinic  
4,4'-methylene bis(dibutyldithiocarbamate)

#### **Result**

OECD 301F  
31% [28 days] - Not readily  
OECD 301B  
21% [28 days] - Not readily

### Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
4,4'-methylene bis (dibutyldithiocarbamate)	8.42	10.86	Low

### Mobility in soil

#### **Soil/Water partition coefficient**

Not available.

#### **Mobility**

Spillages are unlikely to penetrate the soil.

### Other ecological information

This product is unlikely to disperse in water.

## Section 13. Disposal considerations

### **Disposal methods**

The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	Brazil (ANTT)	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Special precautions for user Not available.

Transport in bulk according to IMO instruments Not available.

## Section 15. Regulatory information

This safety data sheet was prepared in accordance with the Brazilian Standard (ABNT NBR 14725)

### Montreal Protocol

Not listed.

### Stockholm Convention on Persistent Organic Pollutants

Not listed.

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### Inventory list

#### Australia inventory (AIIIC)

All components are listed or exempted.

#### Canada inventory

All components are listed or exempted.

#### China inventory (IECSC)

All components are listed or exempted.

#### REACH Status

The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

#### Japan inventory (CSCL)

At least one component is not listed.

#### Korea inventory (KECI)

At least one component is not listed.

#### Philippines inventory (PICCS)

All components are listed or exempted.

#### Taiwan Chemical Substances Inventory (TCSI)

All components are listed or exempted.

#### United States inventory (TSCA 8b)

All components are active or exempted.

Product name Castrol High Temperature Grease

Product code 467200-BE26 Page: 11/12

Version 3 Date of issue 29/09/2025.

Format Brazil  
(Brazil)

Language ENGLISH  
(ENGLISH)

## Section 16. Other information

### History

Date of printing	29/09/2025.
Date of issue/Date of revision	29/09/2025.
Date of previous issue	08/04/2024.
Version	3
Prepared by	Product Stewardship
Key to abbreviations	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods IMO = International Maritime Organization LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

### Procedure used to derive the classification

Not classified as hazardous according to ABNT NBR 14725

**References** Not available.

Indicates information that has changed from previously issued version.

### Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below.

The data and advice given apply when the product is sold and applied for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from us.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken.