

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name	Castrol Transmax Universal 75W-90
Product code	469688-DE04
SDS #	469688
Product type	Liquid.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/ mixture	Gear oils For specific application advice see appropriate Technical Data Sheet or consult our company representative.
----------------------------------	--

1.3 Details of the supplier of the safety data sheet

Supplier	Castrol Holdings Europe B.V., d'Arcyweg 76, 3198NA Europoort Rotterdam Castrol Hellas MAE 26A, IOANNOU APOSTOLOPOULOU, Chalandri, 15231 Greece +30 210 6887 777
E-mail address	MSDSadvice@bp.com

1.4 Emergency telephone number

EMERGENCY TELEPHONE NUMBER	Carechem: +44 (0) 1235 239 670 (24/7)
-------------------------------	---------------------------------------

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition	Mixture
<u>Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]</u>	
Aquatic Chronic 2, H411 PBT, EUH440	

See Section 16 for the full text of the H statements declared above.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements

Hazard pictograms



Signal word	Danger
Hazard statements	H411 - Toxic to aquatic life with long lasting effects. EUH440 - Accumulates in the environment and living organisms including in humans.

Precautionary statements

General	P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand.
Prevention	P201 - Obtain special instructions before use. P273 - Avoid release to the environment.
Response	P391 - Collect spillage.
Storage	Not applicable.
Disposal	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Product name		Castrol Transmax Universal 75W-90		Product code		469688-DE04		Page: 1/20							
Version		8		Date of issue		23 January 2026		Format		Greece		Language		ENGLISH	
Date of previous issue		20 February 2025.								(Greece)					

SECTION 2: Hazards identification

Hazardous ingredients	Not applicable.
Supplemental label elements	Contains Polysulfides, di-tert-Bu and Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl. May produce an allergic reaction.
EU Regulation (EC) No. 1907/2006 (REACH)	
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Not applicable.
Special packaging requirements	
Containers to be fitted with child-resistant fastenings	Not applicable.
Tactile warning of danger	Not applicable.

2.3 Other hazards	
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	This mixture contains substances that are assessed to be a PBT or a vPvB, refer to Section 3.2.
Product meets the criteria for endocrine disrupting properties according to Regulation (EC) No. 1907/2006.	This substance/mixture does not contain any components that are considered to have endocrine disrupting properties.
Other hazards which do not result in classification	Defatting to the skin.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product definition		Mixture			
Highly refined base oil (IP 346 DMSO extract < 3%). Synthetic base stock. Proprietary performance additives.					
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Distillates (petroleum), hydrotreated heavy paraffinic	REACH #: 01-2119484627-25 EC: 265-157-1 CAS: 64742-54-7 Index: 649-467-00-8	≥25 - ≤50	Not classified.	-	[2]
Polysulfides, di-tert-Bu	REACH #: 01-2119540515-43 EC: 273-103-3 CAS: 68937-96-2	≤5	Skin Sens. 1B, H317 Aquatic Chronic 3, H412	Skin Sens. 1, H317: C ≥ 46%	[1]
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	REACH #: 01-2119493620-38 EC: 931-384-6 CAS: -	≤3	Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 2, H411	ATE [Oral] = 500 mg/kg Eye Irrit. 2, H319: C ≥ 50% Skin Sens. 1, H317: C ≥ 9.39%	[1]
Distillates (petroleum), hydrotreated heavy paraffinic	REACH #: 01-2119484627-25 EC: 265-157-1 CAS: 64742-54-7 Index: 649-467-00-8	≤3	Asp. Tox. 1, H304	-	[1] [2]
Distillates (petroleum), solvent-dewaxed heavy paraffinic	REACH #: 01-2119471299-27 EC: 265-169-7 CAS: 64742-65-0 Index: 649-474-00-6	≤3	Asp. Tox. 1, H304	-	[1] [2]
Distillates (petroleum), hydrotreated light paraffinic	REACH #: 01-2119487077-29 EC: 265-158-7	≤3	Asp. Tox. 1, H304	-	[1] [2]

Product name	Castrol Transmax Universal 75W-90	Product code	469688-DE04	Page:	2/20
Version	8	Date of issue	23 January 2026	Format	Greece
Date of previous issue	20 February 2025.			Language	ENGLISH
					(Greece)

SECTION 3: Composition/information on ingredients

Distillates (petroleum), solvent-dewaxed light paraffinic	CAS: 64742-55-8 Index: 649-468-00-3 REACH #: 01-2119480132-48 EC: 265-159-2	≤3	Asp. Tox. 1, H304	-	[1] [2]
	CAS: 64742-56-9 Index: 649-469-00-9 REACH #: 01-2119979545-21 EC: 209-909-9 CAS: 597-82-0				
O,O,O-triphenyl phosphorothioate	CAS: 64742-55-8 Index: 649-468-00-3 REACH #: 01-2119480132-48 EC: 265-159-2	≤1	Aquatic Chronic 1, H410 PBT, EUH440	M [Chronic] = 10	[1] [3]

See Section 16 for the full text of the H statements declared above.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures**4.1 Description of first aid measures****Eye contact**

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.

Skin contact

Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.

Inhalation

If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Ingestion

Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if symptoms occur.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Potential acute health effects**Inhalation**

Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.

Ingestion

No known significant effects or critical hazards.

Skin contact

Defatting to the skin. May cause skin dryness and irritation.

Eye contact

See: Section 11. Toxicological Information - Potential acute health effects: Eye contact

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Inhalation**

Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

Ingestion

Ingestion of large quantities may cause nausea and diarrhoea.

Skin contact

Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

Eye contact

Potential risk of transient stinging or redness if accidental eye contact occurs.

4.3 Indication of any immediate medical attention and special treatment needed**Notes to physician**

Treatment should in general be symptomatic and directed to relieving any effects.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Use foam or all-purpose dry chemical to extinguish.

Unsuitable extinguishing media

Do not use water jet. The use of a water jet may cause the fire to spread by splashing the burning product.

5.2 Special hazards arising from the substance or mixture**Hazards from the substance or mixture**

In a fire or if heated, a pressure increase will occur and the container may burst.

Product name Castrol Transmax Universal 75W-90

Product code 469688-DE04

Page: 3/20

Version 8 **Date of issue** 23 January 2026

Format Greece

Language ENGLISH

Date of previous issue 20 February 2025.

(Greece)

SECTION 5: Firefighting measures

Hazardous combustion products

Combustion products may include the following:
carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

5.3 Advice for firefighters

Special precautions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. This material is toxic to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment.

For emergency responders

Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

See Section 1 for emergency contact information.
See Section 5 for firefighting measures.
See Section 8 for information on appropriate personal protective equipment.
See Section 12 for environmental precautions.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid contact of spilt material and runoff with soil and surface waterways. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/containers designed for use with this product. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Not suitable

Prolonged exposure to elevated temperature.

Product name Castrol Transmax Universal 75W-90

Product code 469688-DE04

Page: 4/20

Version 8 **Date of issue** 23 January 2026

Format Greece

Language ENGLISH

Date of previous issue 20 February 2025.

(Greece)

SECTION 7: Handling and storage

7.3 Specific end use(s)

Recommendations See section 1.2 and Exposure scenarios in annex, if applicable.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Distillates (petroleum), hydrotreated heavy paraffinic	Presidential Decree 307/1986: Occupational exposure limit values (Greece) [ορυκτέλαιο] TWA 8 hours: 5 mg/m³. Form: mist. Issued/Revised: 5/1999. Presidential Decree 307/1986: Occupational exposure limit values (Greece) [εργασίες που συνεπάγονται δερματική έκθεση σε ορυκτέλαιο που έχουν χρησιμοποιηθεί προηγουμένως σε κινητήρες εσωτερικής καύσης για τη λίπανση και την ψύξη των κινητών μερών εντός του κινητήρα] Absorbed through skin.
Distillates (petroleum), hydrotreated heavy paraffinic	Presidential Decree 307/1986: Occupational exposure limit values (Greece) [ορυκτέλαιο] TWA 8 hours: 5 mg/m³. Form: mist. Issued/Revised: 5/1999. Presidential Decree 307/1986: Occupational exposure limit values (Greece) [εργασίες που συνεπάγονται δερματική έκθεση σε ορυκτέλαιο που έχουν χρησιμοποιηθεί προηγουμένως σε κινητήρες εσωτερικής καύσης για τη λίπανση και την ψύξη των κινητών μερών εντός του κινητήρα] Absorbed through skin.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Presidential Decree 307/1986: Occupational exposure limit values (Greece) [ορυκτέλαιο] TWA 8 hours: 5 mg/m³. Form: mist. Issued/Revised: 5/1999. Presidential Decree 307/1986: Occupational exposure limit values (Greece) [εργασίες που συνεπάγονται δερματική έκθεση σε ορυκτέλαιο που έχουν χρησιμοποιηθεί προηγουμένως σε κινητήρες εσωτερικής καύσης για τη λίπανση και την ψύξη των κινητών μερών εντός του κινητήρα] Absorbed through skin.
Distillates (petroleum), hydrotreated light paraffinic	Presidential Decree 307/1986: Occupational exposure limit values (Greece) [ορυκτέλαιο] TWA 8 hours: 5 mg/m³. Form: mist. Issued/Revised: 5/1999. Presidential Decree 307/1986: Occupational exposure limit values (Greece) [εργασίες που συνεπάγονται δερματική έκθεση σε ορυκτέλαιο που έχουν χρησιμοποιηθεί προηγουμένως σε κινητήρες εσωτερικής καύσης για τη λίπανση και την ψύξη των κινητών μερών εντός του κινητήρα] Absorbed through skin.
Distillates (petroleum), solvent-dewaxed light paraffinic	Presidential Decree 307/1986: Occupational exposure limit values (Greece) [ορυκτέλαιο] TWA 8 hours: 5 mg/m³. Form: mist. Issued/Revised: 5/1999. Presidential Decree 307/1986: Occupational exposure limit values (Greece) [εργασίες που συνεπάγονται δερματική έκθεση σε ορυκτέλαιο που έχουν χρησιμοποιηθεί προηγουμένως σε κινητήρες εσωτερικής καύσης για τη λίπανση και την ψύξη των κινητών μερών εντός του κινητήρα] Absorbed through skin.

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Recommended monitoring procedures Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Biological exposure indices

Product/ingredient name	Exposure indices
No exposure indices known.	
DNELs/DMELs	
Not available.	

SECTION 8: Exposure controls/personal protection

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.
All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.
Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.
The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Eye/face protection

Safety glasses with side shields.

Skin protection

Hand protection

General Information:

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile gloves.

Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type.
Our recommendations on the selection of gloves are as follows:

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained.

If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.

It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

Glove Thickness:

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove

Product name	Castrol Transmax Universal 75W-90	Product code	469688-DE04	Page:	6/20
Version	8	Date of issue	23 January 2026	Format	Greece
Date of previous issue	20 February 2025.			Language	ENGLISH
					(Greece)

SECTION 8: Exposure controls/personal protection

resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

Skin and body	Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
Refer to standards:	Respiratory protection: EN 529 Gloves: EN 420, EN 374 Eye protection: EN 166 Filtering half-mask: EN 149 Filtering half-mask with valve: EN 405 Half-mask: EN 140 plus filter Full-face mask: EN 136 plus filter Particulate filters: EN 143 Gas/combined filters: EN 14387
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Physical state	Liquid.								
Colour	Amber.								
Odour	Not available.								
Odour threshold	Not available.								
Melting point/freezing point	Not available.								
Initial boiling point and boiling range	Not available.								
Flammability	Not available.								
Lower and upper explosion limit	Not available.								
Flash point	Open cup: >180°C (>356°F) [Cleveland]								
Auto-ignition temperature	<table><tr><th>Ingredient name</th><th>°C</th><th>°F</th><th>Method</th></tr><tr><td>Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated</td><td>343 to 369</td><td>649.4 to 696.2</td><td>ASTM D 2159</td></tr></table>	Ingredient name	°C	°F	Method	Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159
Ingredient name	°C	°F	Method						
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159						
Decomposition temperature	Not available.								
pH	Not applicable.								
Kinematic viscosity	Kinematic: 108.1 mm²/s (108.1 cSt) at 40°C Kinematic: 14.3 to 15.3 mm²/s (14.3 to 15.3 cSt) at 100°C								
Solubility									

Product name		Castrol Transmax Universal 75W-90		Product code		469688-DE04		Page: 7/20							
Version		8		Date of issue		23 January 2026		Format		Greece		Language		ENGLISH	
Date of previous issue						20 February 2025.									

SECTION 9: Physical and chemical properties

	Media	Result																																														
	water	Not soluble																																														
Partition coefficient n-octanol/ water (log value)	Not applicable.																																															
Vapour pressure	<table><tr><th rowspan="2">Ingredient name</th><th colspan="2">Vapour Pressure at 20°C</th><th colspan="2">Vapour pressure at 50°C</th></tr><tr><th>mm Hg</th><th>kPa</th><th>Method</th><th>mm Hg</th><th>kPa</th><th>Method</th></tr><tr><td>Distillates (petroleum), hydrotreated heavy paraffinic</td><td><0.07501</td><td><0.01</td><td>ASTM D 5191</td><td></td><td></td><td></td></tr><tr><td>Polysulfides, di-tert-Bu</td><td>0.12</td><td>0.016</td><td>OECD 104</td><td></td><td></td><td></td></tr><tr><td>Distillates (petroleum), hydrotreated heavy paraffinic</td><td><0.07501</td><td><0.01</td><td>ASTM D 5191</td><td></td><td></td><td></td></tr><tr><td>Distillates (petroleum), solvent-dewaxed heavy paraffinic</td><td><0.07501</td><td><0.01</td><td>ASTM D 5191</td><td></td><td></td><td></td></tr><tr><td>Distillates (petroleum), hydrotreated light paraffinic</td><td><0.07501</td><td><0.01</td><td>ASTM D 5191</td><td></td><td></td><td></td></tr></table>		Ingredient name	Vapour Pressure at 20°C		Vapour pressure at 50°C		mm Hg	kPa	Method	mm Hg	kPa	Method	Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191				Polysulfides, di-tert-Bu	0.12	0.016	OECD 104				Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191				Distillates (petroleum), solvent-dewaxed heavy paraffinic	<0.07501	<0.01	ASTM D 5191				Distillates (petroleum), hydrotreated light paraffinic	<0.07501	<0.01	ASTM D 5191			
Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C																																												
	mm Hg	kPa	Method	mm Hg	kPa	Method																																										
Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191																																													
Polysulfides, di-tert-Bu	0.12	0.016	OECD 104																																													
Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191																																													
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<0.07501	<0.01	ASTM D 5191																																													
Distillates (petroleum), hydrotreated light paraffinic	<0.07501	<0.01	ASTM D 5191																																													
Density and/or Relative density	<1000 kg/m³ (<1 g/cm³) at 15°C																																															
Relative vapour density	Not available.																																															
Particle characteristics																																																
Median particle size	Not applicable.																																															
9.2 Other information																																																
Evaporation rate	Not available.																																															
Explosive properties	Not available.																																															
Oxidising properties	Not available.																																															
Pour point	-45 °C																																															

SECTION 10: Stability and reactivity

10.1 Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
10.2 Chemical stability	The product is stable.
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
10.4 Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
10.5 Incompatible materials	Reactive or incompatible with the following materials: oxidising materials.
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	Rat - Oral - LD50 2000 mg/kg OECD 401
Distillates (petroleum), hydrotreated heavy paraffinic	Rat - Oral - LD50 >5000 mg/kg OECD 401
	Rabbit - Dermal - LD50 >5000 mg/kg

Product name	Castrol Transmax Universal 75W-90	Product code	469688-DE04	Page:	8/20
Version	8	Date of issue	23 January 2026	Format	Greece
Date of previous issue	20 February 2025.			Language	ENGLISH
					(Greece)

SECTION 11: Toxicological information

	OECD 402
	Rat - Inhalation - LC50 Dusts and mists >5 mg/l [4 hours] OECD 403
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Rat - Oral - LD50 >5000 mg/kg OECD 401
	Rat - Dermal - LD50 >2000 mg/kg OECD 402
	Rat - Inhalation - LC50 Dusts and mists >5.53 mg/l [4 hours] OECD 403
Distillates (petroleum), hydrotreated light paraffinic	Rat - Oral - LD50 >5000 mg/kg OECD 401
	Rabbit - Dermal - LD50 >5000 mg/kg OECD 402
	Rat - Inhalation - LC50 Dusts and mists >5.53 mg/l [4 hours] OECD 403
Distillates (petroleum), solvent-dewaxed light paraffinic	Rat - Oral - LD50 >5000 mg/kg OECD 401
	Rabbit - Dermal - LD50 >5000 mg/kg OECD 402
	Rat - Inhalation - LC50 Dusts and mists >2.18 mg/l [4 hours] OECD 403

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Castrol Transmax Universal 75W-90 Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	26720.2 500	N/A N/A	N/A N/A	N/A N/A	N/A N/A

Skin corrosion/irritation

Product/ingredient name	Result
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	Rabbit - Skin - Non-irritant to skin. OECD 404
Distillates (petroleum), hydrotreated heavy paraffinic	Rabbit - Skin - Mild irritant OECD 404
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Rabbit - Skin - Non-irritant to skin.
Distillates (petroleum), hydrotreated light paraffinic	Rabbit - Skin - Non-irritant to skin.

Rabbit - Skin - Non-irritant to skin.

Product/ingredient name

Result

Rabbit - Eyes - Irritant
FHSA 16CFR1500

Rabbit - Eyes - Non-irritating to the eyes.
OECD 405

Rabbit - Eyes - Non-irritating to the eyes.
OECD 405

Rabbit - Eyes - Non-irritating to the eyes.
OECD 405

Rabbit - Eyes - Non-irritating to the eyes.
OECD 405

Not available.

Product/ingredient name

Result

Mouse - skin

OECD 429

Result: Sensitising

Guinea pig - skin

OECD 406

Result: Not sensitising

Guinea pig - skin

OECD 406

Result: Not sensitising

Guinea pig - skin

OFCD 406

Result: Not sensitising

Guinea pig - skin

OFCD 406

Result: Not sensitising

Product/ingredient name

Result

In vitro - Bacteria

OECD 471

Result: Negative

In vitro - Mammal - species unspecified

OECD 476

Result: Negative

In vitro - Unspecified - Somatic

OECD 474

Result: Negative

SECTION 11: Toxicological information

Distillates (petroleum), hydrotreated heavy paraffinic	In vitro - Bacteria Bacterial Reverse Mutation Test <u>Result:</u> Negative In vitro - Mammal - species unspecified In vitro Mammalian Chromosomal Aberration Test <u>Result:</u> Negative In vivo - Mammal - species unspecified Mammalian Erythrocyte Micronucleus Test <u>Result:</u> Negative In vitro - Mammal - species unspecified In vitro Mammalian Cell Gene Mutation Test <u>Result:</u> Negative
Distillates (petroleum), solvent-dewaxed heavy paraffinic	In vitro - Bacteria OECD [Bacterial Reverse Mutation Test] <u>Result:</u> Negative In vitro - Mammal - species unspecified OECD [In vitro Mammalian Chromosomal Aberration Test] <u>Result:</u> Negative
Distillates (petroleum), hydrotreated light paraffinic	In vitro - Bacteria OECD [Bacterial Reverse Mutation Test] <u>Result:</u> Negative In vitro - Mammal - species unspecified OECD [In vitro Mammalian Chromosomal Aberration Test] <u>Result:</u> Negative
Distillates (petroleum), solvent-dewaxed light paraffinic	In vitro - Bacteria OECD [Bacterial Reverse Mutation Test] <u>Result:</u> Negative In vitro - Mammal - species unspecified In vitro Mammalian Chromosomal Aberration Test <u>Result:</u> Negative

Carcinogenicity

Product/ingredient name Distillates (petroleum), hydrotreated heavy paraffinic	Result Mouse - Dermal - Unspecified OECD 451 <u>Result:</u> Negative
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Mouse - Dermal - Unspecified OECD 451 <u>Result:</u> Negative

Reproductive toxicity

Product/ingredient name Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	Result Rat - Oral OECD 421 <u>Maternal toxicity:</u> Positive <u>Fertility effects:</u> Negative <u>Developmental:</u> Negative
Distillates (petroleum), hydrotreated heavy paraffinic	Rat - Oral OECD 421 <u>Maternal toxicity:</u> Negative <u>Fertility effects:</u> Negative <u>Developmental:</u> Negative
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Rat - Oral OECD 421 <u>Maternal toxicity:</u> Negative <u>Fertility effects:</u> Negative

SECTION 11: Toxicological informationDevelopmental: Negative

Distillates (petroleum), hydrotreated light paraffinic

Rat - Oral
OECD 421
Maternal toxicity: Negative
Fertility effects: Negative
Developmental: Negative

Distillates (petroleum), solvent-dewaxed light paraffinic

Rat - Oral
OECD 421
Maternal toxicity: Negative
Fertility effects: Negative
Developmental: NegativeSpecific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard**Product/ingredient name****Result**

Distillates (petroleum), hydrotreated heavy paraffinic

ASPIRATION HAZARD - Category 1

Distillates (petroleum), solvent-dewaxed heavy paraffinic

ASPIRATION HAZARD - Category 1

Distillates (petroleum), hydrotreated light paraffinic

ASPIRATION HAZARD - Category 1

Distillates (petroleum), solvent-dewaxed light paraffinic

ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects**Inhalation**

Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.

Ingestion

No known significant effects or critical hazards.

Skin contact

Defatting to the skin. May cause skin dryness and irritation.

Eye contact

No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics**Inhalation**

May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.

Ingestion

No specific data.

Skin contactAdverse symptoms may include the following:
irritation
dryness
cracking**Eye contact**

No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Inhalation**

Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

Ingestion

Ingestion of large quantities may cause nausea and diarrhoea.

Skin contact

Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

Eye contact

Potential risk of transient stinging or redness if accidental eye contact occurs.

Potential chronic health effects

Not available.

Conclusion/Summary [Product]

Not available.

General

No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.

Mutagenicity

No known significant effects or critical hazards.

Developmental effects

No known significant effects or critical hazards.

Fertility effects

No known significant effects or critical hazards.

Product name Castrol Transmax Universal 75W-90**Product code** 469688-DE04**Page:** 12/20**Version** 8**Date of issue** 23 January 2026**Format** Greece**Language** ENGLISH**Date of previous issue** 20 February 2025.**(Greece)**

SECTION 11: Toxicological information

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Conclusion/Summary [Product]

This substance/mixture does not contain any components that are considered to have endocrine disrupting properties.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	Acute - ErC50 OECD 201 Algae 6.4 mg/l [96 hours]
	Chronic - NOEC OECD 201 Algae 1.7 mg/l [96 hours]
	Acute - EC50 OECD 202 Daphnia 91.4 mg/l [48 hours]
	Chronic - EC50 OECD 211 Daphnia 0.66 mg/l [21 days]
	Chronic - NOEC OECD 211 Daphnia 0.12 mg/l [21 days]
	Acute - LC50 OECD 203 Fish 24 mg/l [96 hours]
	Acute - EL50 OECD 201 Algae >100 mg/l [72 hours]
	Acute - EL50 OECD 202 Daphnia >10000 mg/l [48 hours]
	Acute - LL50 OECD 203 Fish >100 mg/l [96 hours]
	Chronic - NOEL OECD 201 Algae ≥100 mg/l [72 hours]
Distillates (petroleum), hydrotreated heavy paraffinic	Chronic - NOEL OECD 211 Daphnia 10 mg/l [21 days]
	Acute - EL50 OECD 201 Algae >100 mg/l [72 hours]

SECTION 12: Ecological information

	Acute - EL50 OECD 202 Daphnia >10000 mg/l [48 hours] Acute - LL50 OECD 203 Fish >100 mg/l [96 hours] Chronic - NOEL OECD 201 Algae ≥100 mg/l [72 hours] Chronic - NOEL OECD 211 Daphnia 10 mg/l [21 days]
Distillates (petroleum), hydrotreated light paraffinic	Acute - EL50 OECD 201 Algae >100 mg/l [72 hours] Acute - EL50 OECD 202 Daphnia >10000 mg/l [48 hours] Acute - LL50 OECD 203 Fish >100 mg/l [96 hours] Chronic - NOEL OECD 201 Algae ≥100 mg/l [72 hours] Chronic - NOEL OECD 211 Daphnia 10 mg/l [21 days]
Distillates (petroleum), solvent-dewaxed light paraffinic	Acute - EL50 OECD 201 Algae >100 mg/l [72 hours] Acute - EL50 OECD 202 Daphnia >10000 mg/l [48 hours] Acute - LL50 OECD 203 Fish >100 mg/l [96 hours] Chronic - NOEL OECD 201 Algae ≥100 mg/l [72 hours] Chronic - NOEL OECD 211 Daphnia 10 mg/l [21 days]
Environmental hazards	Toxic to aquatic life with long lasting effects.

SECTION 12: Ecological information**12.2 Persistence and degradability**

Not expected to be rapidly degradable.

Product/ingredient name**Result**

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl

OECD 301B
7.4% [28 days] - Not readily

Distillates (petroleum), hydrotreated heavy paraffinic

OECD 301F
31% [28 days] - Not readily

Distillates (petroleum), solvent-dewaxed heavy paraffinic

OECD 301F
31% [28 days] - Not readily

Distillates (petroleum), hydrotreated light paraffinic

OECD 301F
31% [28 days] - Not readily

Distillates (petroleum), solvent-dewaxed light paraffinic

OECD 301F
31% [28 days] - Not readily**12.3 Bioaccumulative potential**

This product is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	LogP _{ow}	BCF	Potential
Polysulfides, di-tert-Bu	5.6	-	High

12.4 Mobility in soil**Soil/water partition coefficient**

Product/ingredient name	logK _{oc}	K _{oc}
O,O,O-triphenyl phosphorothioate	4.7	49128.4

Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Polysulfides, di-tert-Bu	No	No	No	No	No	No	No
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	No	No	No	No	No	No	No
Distillates (petroleum), hydrotreated heavy paraffinic	No	No	No	No	No	No	No
Distillates (petroleum), solvent-dewaxed heavy paraffinic	No	No	No	No	No	No	No
Distillates (petroleum), hydrotreated light paraffinic	No	No	No	No	No	No	No
Distillates (petroleum), solvent-dewaxed light paraffinic	No	No	No	No	No	No	No
O,O,O-triphenyl phosphorothioate	No	Yes	No	Yes	No	No	No

Mobility

Spillages may penetrate the soil causing ground water contamination.

Conclusion/Summary

The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment**Regulation (EC) No. 1907/2006 [REACH]**

SECTION 12: Ecological information

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Polysulfides, di-tert-Bu	No	N/A	N/A	No	N/A	N/A	N/A
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	No	N/A	N/A	No	N/A	N/A	N/A
Distillates (petroleum), hydrotreated heavy paraffinic	No	N/A	N/A	No	N/A	N/A	N/A
Distillates (petroleum), solvent-dewaxed heavy paraffinic	No	N/A	N/A	No	N/A	N/A	N/A
Distillates (petroleum), hydrotreated light paraffinic	No	N/A	N/A	No	N/A	N/A	N/A
Distillates (petroleum), solvent-dewaxed light paraffinic	No	N/A	N/A	No	N/A	N/A	N/A
O,O,O-triphenyl phosphorothioate	Yes	Yes	Yes	Yes	N/A	N/A	N/A

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Polysulfides, di-tert-Bu	No	No	No	No	No	No	No
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	No	No	No	No	No	No	No
Distillates (petroleum), hydrotreated heavy paraffinic	No	No	No	No	No	No	No
Distillates (petroleum), solvent-dewaxed heavy paraffinic	No	No	No	No	No	No	No
Distillates (petroleum), hydrotreated light paraffinic	No	No	No	No	No	No	No
Distillates (petroleum), solvent-dewaxed light paraffinic	No	No	No	No	No	No	No
O,O,O-triphenyl phosphorothioate	Yes	Yes	Yes	Yes	No	No	No

Conclusion/Summary

Accumulates in the environment and living organisms including in humans.

Regulation (EC) No. 1272/2008 [CLP]**12.6 Endocrine disrupting properties****Conclusion/Summary [Product]**

This substance/mixture does not contain any components that are considered to have endocrine disrupting properties.

Other ecological information

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product****Methods of disposal**

Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Hazardous waste

Yes.

European waste catalogue (EWC)**Product name** Castrol Transmax Universal 75W-90**Product code** 469688-DE04**Page:** 16/20**Version** 8 **Date of issue** 23 January 2026**Format** Greece**Language** ENGLISH**Date of previous issue** 20 February 2025.**(Greece)**

SECTION 13: Disposal considerations	
Waste code	Waste designation
13 02 08*	other engine, gear and lubricating oils
However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.	
Packaging	
Methods of disposal	Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Empty containers represent a fire hazard as they may contain flammable product residues and vapour. Never weld, solder or braze empty containers. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
References	Commission 2014/955/EU Directive 2008/98/EC

SECTION 14: Transport information				
	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (O,O, O-triphenyl phosphorothioate)	Environmentally hazardous substance, liquid, n.o.s. (O,O,O-triphenyl phosphorothioate)	Environmentally hazardous substance, liquid, n.o.s.. Marine pollutant (O,O,O-triphenyl phosphorothioate)	Environmentally hazardous substance, liquid, n.o.s. (O,O,O-triphenyl phosphorothioate)
14.3 Transport hazard class(es)	9  	9  	9  	9  
14.4 Packing group	III	III	III	-
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.
Additional information	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Hazard identification number 90 Tunnel code -	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Emergency schedules F-A, S-F	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

14.6 Special precautions for user Not available.

ADR/RID Classification code: M6

ADN Classification code: M6

14.7 Maritime transport in bulk according to IMO instruments Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

Ingredient name	Intrinsic property	Status	Reference number	Date of revision
O,O,O-triphenyl phosphorothioate	PBT	Candidate	D(2024) 7663-DC	1/21/2025

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
Castrol Transmax Universal 75W-90	95-100	3

Labelling Not applicable.

Other regulations

REACH Status The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

United States inventory (TSCA 8b) All components are active or exempted.

Australia inventory (AIC) All components are listed or exempted.

Canada inventory At least one component is not listed in DSL but all such components are listed in NDSL.

China inventory (IECSC) All components are listed or exempted.

Japan inventory (CSCL) All components are listed or exempted.

Korea inventory (KECI) All components are listed or exempted.

Philippines inventory (PICCS) At least one component is not listed.

Taiwan Chemical Substances Inventory (TCSI) All components are listed or exempted.

Explosive precursors Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

EU - Water framework directive - Priority substances

None of the components are listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category
E2

15.2 Chemical safety assessment A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

SECTION 16: Other information**Abbreviations and acronyms**

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 CAS = Chemical Abstracts Service
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 CSA = Chemical Safety Assessment
 CSR = Chemical Safety Report
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EINECS = European Inventory of Existing Commercial chemical Substances
 ES = Exposure Scenario
 EUH statement = CLP-specific Hazard statement
 EWC = European Waste Catalogue
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 OECD = Organisation for Economic Co-operation and Development
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
 RRN = REACH Registration Number
 SADT = Self-Accelerating Decomposition Temperature
 SVHC = Substances of Very High Concern
 STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
 STOT-SE = Specific Target Organ Toxicity - Single Exposure
 TWA = Time weighted average
 UN = United Nations
 UVCB = Complex hydrocarbon substance
 VOC = Volatile Organic Compound
 vPvB = Very Persistent and Very Bioaccumulative
 Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4 / RRN 01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN 01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN 01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN 01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN 01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8, 64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 / RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN 01-2119474889-13

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aquatic Chronic 2, H411 PBT, EUH440	Calculation method On basis of test data

Full text of abbreviated H statements

H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.
 EUH440 Accumulates in the environment and living organisms including in humans.

Product name Castrol Transmax Universal 75W-90**Product code** 469688-DE04**Page:** 19/20**Version** 8 **Date of issue** 23 January 2026**Format** Greece**Language** ENGLISH**Date of previous issue** 20 February 2025.**(Greece)**

SECTION 16: Other information

Full text of classifications [CLP/GHS]	Acute Tox. 4	ACUTE TOXICITY - Category 4
	Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
	Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
	Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
	Asp. Tox. 1	ASPIRATION HAZARD - Category 1
	Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
	PBT	PERSISTENT, BIOACCUMULATIVE AND TOXIC
	Skin Sens. 1B	SKIN SENSITISATION - Category 1B

History

Date of issue/ Date of revision	23/01/2026.
Date of previous issue	20/02/2025.
Prepared by	Product Stewardship

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name	Castrol Transmax Universal 75W-90	Product code	469688-DE04	Page:	20/20
Version	8	Date of issue	23 January 2026	Format	Greece
Date of previous issue	20 February 2025.			Language	ENGLISH
			(Greece)		