SAFETY DATA SHEET



Castrol High Temperature Grease

Section 1. Identification

GHS product identifier Castrol High Temperature Grease

Product code 467200-SG01 SDS # 467200

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/ Grease for industrial applications.

mixture For specific application advice see appropriate Technical Data Sheet or consult our

company representative.

Supplier BP Taiwan Marketing Limited

Level 57-1, TAIPEI 101 Tower, No. 7, Section 5, Xinyi Road, Taipei, 11049, Taiwan,

R.O.C.

Tel: +886 70 1011 9900

EMERGENCY TELEPHONE

Carechem: +886 2 8793 3212 (24/7)

NUMBER

Section 2. Hazards identification

Classification of the substance or mixture

Not classified.

GHS label elements

Signal word No signal word.

Hazard statements No known significant effects or critical hazards.

Precautionary statements

PreventionNot applicable.ResponseNot applicable.StorageNot applicable.DisposalNot applicable.

Other hazards which do not

result in classification

Defatting to the skin.

Note: High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure

constitute a major medical emergency.

See 'Notes to physician' under First-Aid Measures, Section 4 of this Safety Data

Sheet

Section 3. Composition/information on ingredients

Substance/mixture

Version 5.01

Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Thickening agent. Proprietary performance additives.

Chinese name	% (w/w)	CAS number	Type
Distillates (petroleum), solvent-dewaxed heavy paraffinic	≥25 - ≤50	CAS: 64742-65-0	[2]
Residual oils (petroleum), solvent refined	≥25 - ≤50	CAS: 64742-01-4	[2]
Distillates (petroleum), hydrotreated heavy naphthenic	≤10	CAS: 64742-52-5	[2]
dilithium sebacate	≤3	CAS: 19370-86-6	[1]
4,4'-methylene bis(dibutyldithiocarbamate)	≤3	CAS: 10254-57-6	[1]
化學品名稱	% (w/w)	化學文摘社登記號碼(CAS No.)	類型

Product name Castrol High Temperature Grease

Date of issue 29/09/2025.

Product code 46720

467200-SG01

Page: 1/10

Format Taiwan

Language ENGLISH

Taiwan

in (ENGLISH)

Section 3. Composition/information on ingredients

				1
溶劑脫蠟重質蠟族石油餾分	≥25 - ≤50	化學文摘社: 64742-65-0	[2]	_
溶劑精製石油殘留油	≥25 - ≤50	化學文摘社: 64742-01-4	[2]	
經過氫化處理的重質環烷烴石油餾分	≤10	化學文摘社: 64742-52-5	[2]	
dilithium sebacate	≤3	化學文摘社: 19370-86-6	[1]	
4,4'-methylene bis(dibutyldithiocarbamate)	≤3	化學文摘社: 10254-57-6	[1]	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Inhalation If inhaled, remove to fresh air. In case of inhalation of decomposition products in a

fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. Get medical

attention if symptoms occur.

Skin contact Wash skin thoroughly with soap and water or use recognised skin cleanser.

Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur. If skin

irritation or rash occurs: Get medical advice/attention.

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for

and remove any contact lenses. Get medical attention.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Specific treatments No specific treatment.

Notes to physician Treatment should in general be symptomatic and directed to relieving any effects.

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Note: High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discoloured and extremely painful with extensive subcutaneous necrosis.

Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimise tissue loss and prevent or limit permanent damage. Note that high pressure may force the

product considerable distances along tissue planes.

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing

media

In case of fire, use water fog, alcohol resistant foam, dry chemical or carbon dioxide extinguisher or spray.

Unsuitable extinguishing

media

Do not use water jet.

Specific hazards arising from the chemical

No specific fire or explosion hazard.

Product nameCastrol High Temperature GreaseProduct code467200-SG01Page: 2/10Version 5.01Date of issue 29/09/2025.Format TaiwanLanguage ENGLISHTaiwan(ENGLISH)

Section 5. Firefighting measures

Hazardous thermal decomposition products

Combustion products may include the following:

metal oxide/oxides

carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

sulphur oxides (SO, SO₂, etc.) nitrogen oxides (NO, NO₂ etc.)

Special protective actions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if

there is a fire.

Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Small spill

Move containers from spill area. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. If emergency personnel are unavailable, contain spilt material. Suction or scoop the spill into appropriate disposal or recycling vessels, then cover spill area with oil absorbent. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Advice on general occupational hygiene

Put on appropriate personal protective equipment (see Section 8).

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. Contaminated work clothing should not be allowed out of the workplace. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Not suitable Prolonged exposure to elevated temperature

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), solvent-dewaxed heavy paraffinic	TW Minstry of Labor, labor permissible workplace exposure standards, allowable concentration (Taiwan) [Oil mist] STEL 15 minutes: 10 mg/m³. Form: Mist. Issued/Revised: 1/2005. TWA 8 hours: 5 mg/m³. Form: Mist. Issued/Revised: 1/2005.
Residual oils (petroleum), solvent refined	TW Minstry of Labor, labor permissible workplace exposure standards, allowable

Product nameCastrol High Temperature GreaseProduct code467200-SG01Page: 3/10Version 5.01Date of issue 29/09/2025.Format TaiwanLanguage ENGLISHTaiwan(ENGLISH)

Section 8. Exposure controls/personal protection

concentration (Taiwan) [Oil mist]

STEL 15 minutes: 10 mg/m³. Form: Mist.

Issued/Revised: 1/2005.

TWA 8 hours: 5 mg/m³. Form: Mist. Issued/

Revised: 1/2005.

TW Minstry of Labor, labor permissible workplace exposure standards, allowable concentration (Taiwan) [Oil mist]

STEL 15 minutes: 10 mg/m³. Form: Mist.

Issued/Revised: 1/2005.

TWA 8 hours: 5 mg/m³. Form: Mist. Issued/

Revised: 1/2005.

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures

ng

Distillates (petroleum), hydrotreated heavy naphthenic

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye protection Skin protection

Hand protection

Safety glasses with side shields.

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Body protection

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Product name Castrol High Temperature Grease

Version 5.01 Date of issue 29/09/2025.

Product code 467200-SG01

Taiwan

Page: 4/10

Format Taiwan

Language ENGLISH (ENGLISH)

Section 8. Exposure controls/personal protection

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state Grease Colour Amber. Odour Characteristic. Not available. **Odour threshold** pН Not applicable. Melting point/freezing point Not available. **Boiling point or initial** Not available.

boiling point and boiling

range

Drop Point Not available.

Closed cup: >200°C (>392°F) [Pensky-Martens ASTM D 93] Flash point

Evaporation rate Not available. **Flammability** Not available. Lower and upper explosion Not applicable.

limit/flammability limit

Vapour pressure

Not available.

Not applicable.

	Vapou	Vapour Pressure at 20°C			Vapour pressure at 50°	
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method

Relative vapour density

Relative density

Density

Not available.

Solubility(ies)

Media	Result
water	Not soluble

Partition coefficient: n-

octanol/water

Not applicable.

>300°C (>572°F) **Auto-ignition temperature** Not available. **Decomposition temperature Viscosity** Not available.

Particle characteristics

Median particle size Not available.

Section 10. Stability and reactivity

Reactivity No specific test data available for this product. Refer to Conditions to avoid and

Incompatible materials for additional information.

The product is stable. Chemical stability

Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.

Conditions to avoid Avoid all possible sources of ignition (spark or flame).

Incompatible materials Reactive or incompatible with the following materials: oxidising materials.

Hazardous decomposition Under normal conditions of storage and use, hazardous decomposition products products should not be produced.

467200-SG01 **Product name** Castrol High Temperature Grease Product code Page: 5/10 Language ENGLISH Date of issue 29/09/2025. **Format Taiwan** Version 5.01 (ENGLISH) **Taiwan**

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name

Distillates (petroleum), solvent-dewaxed

heavy paraffinic

Result

Rat - Oral - LD50 >5000 mg/kg OECD 401

Rat - Dermal - LD50 >2000 mg/kg **OECD 402**

Rat - Inhalation - LC50 Dusts and mists

>5.53 mg/l [4 hours] **OECD 403** Rat - Oral - LD50

4,4'-methylene bis(dibutyldithiocarbamate)

>5000 mg/kg **OECD 401**

Rabbit - Dermal - LD50

>2000 mg/kg **OECD 402**

Skin corrosion/irritation

Product/ingredient name

Distillates (petroleum), solvent-dewaxed heavy paraffinic

4,4'-methylene bis(dibutyldithiocarbamate)

Rabbit - Skin - Non-irritant to skin.

Rabbit - Skin - Not irritant

OECD 404

Serious eye damage/eye irritation

Product/ingredient name

Distillates (petroleum), solvent-dewaxed

heavy paraffinic

4,4'-methylene bis(dibutyldithiocarbamate)

Result

Rabbit - Eyes - Non-irritating to the eyes.

OECD 405

Rabbit - Eyes - Not irritant

OECD 405

Respiratory corrosion/irritation

Not available.

Respiratory or skin sensitization

Product/ingredient name

Distillates (petroleum), solvent-dewaxed heavy paraffinic

4,4'-methylene bis(dibutyldithiocarbamate)

Result

Guinea pig - skin **OECD 406**

Result: Not sensitising

Mouse - skin **OECD 429**

Result: Not sensitising

Germ cell mutagenicity

Product/ingredient name

Distillates (petroleum), solvent-dewaxed

heavy paraffinic

Version 5.01

Result

In vitro - Bacteria

OECD [Bacterial Reverse Mutation Test]

Result: Negative

In vitro - Mammal - species unspecified

OECD [In vitro Mammalian Chromosomal Aberration Test]

Result: Negative In vitro - Bacteria

OECD 471

Product name Castrol High Temperature Grease

4,4'-methylene bis(dibutyldithiocarbamate)

467200-SG01 Product code

Page: 6/10

Format Taiwan

Language ENGLISH (ENGLISH)

Date of issue 29/09/2025.

Taiwan

Section 11. Toxicological information

Result: Negative

In vitro - Mammalian-Animal

OECD 473 Result: Negative

In vitro - Mammalian-Animal

OECD 476 Result: Negative

Carcinogenicity

Product/ingredient name Result

Distillates (petroleum), solvent-dewaxed Mouse - Dermal - Unspecified

heavy paraffinic OECD 451
Result: Negative

Information on likely routes

of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact No known significant effects or critical hazards.

Inhalation Exposure to decomposition products may cause a health hazard. Serious effects

may be delayed following exposure.

Skin contact Defatting to the skin. May cause skin dryness and irritation.

Ingestion No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact No specific data.

Inhalation No specific data.

Skin contact Adverse symptoms may include the following:

irritation dryness cracking

Ingestion No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs.

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/

or dermatitis.

Ingestion Ingestion of large quantities may cause nausea and diarrhoea.

Potential chronic health effects

General

No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	21760.87 mg/kg

Section 12. Ecological information

Environmental effects No known significant effects or critical hazards.

Product/ingredient name Result

Product nameCastrol High Temperature GreaseProduct code467200-SG01Page: 7/10Version 5.01Date of issue 29/09/2025.Format TaiwanLanguage ENGLISHTaiwan(ENGLISH)

Section 12. Ecological information

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Acute - EL50 OECD 201 Algae

>100 mg/l [72 hours]
Acute - EL50
OECD 202
Daphnia

>10000 mg/l [48 hours]

Acute - LL50 OECD 203 Fish

>100 mg/l [96 hours] Chronic - NOEL OECD 201 Algae

≥100 mg/l [72 hours]
Chronic - NOEL
OECD 211
Daphnia
10 mg/l [21 days]

4,4'-methylene bis(dibutyldithiocarbamate)

Acute - ErC50 OECD 201 Algae

>0.0325 mg/l [72 hours]

Acute - EC50 OECD 202 Daphnia

>0.052 mg/l [48 hours]

Acute - EL50 OECD 203 Fish

>0.06 mg/l [96 hours] Chronic - NOEC OECD 211 Daphnia

0.247 mg/l [21 days] Chronic - NOEC OECD 201

Algae

0.0325 mg/l [72 hours]

Persistence and degradability

Expected to be biodegradable.

Product/ingredient name

Distillates (petroleum), solvent-dewaxed heavy paraffinic

4,4'-methylene bis(dibutyldithiocarbamate)

Result

OECD 301F

31% [28 days] - Not readily

OECD 301B

21% [28 days] - Not readily

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	LogPow	BCF	Potential
4,4'-methylene bis (dibutyldithiocarbamate)	8.42	10.86	Low

Mobility in soil

Soil/water partition coefficient

Not available.

Mobility Spillages are unlikely to penetrate the soil.

Product nameCastrol High Temperature GreaseProduct code467200-SG01Page: 8/10Version 5.01Date of issue 29/09/2025.Format TaiwanLanguage ENGLISHTaiwan(ENGLISH)

Section 12. Ecological information

Other ecological information

This product is unlikely to disperse in water.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	IMDG	IATA
UN number	Not regulated.	Not regulated.
UN proper shipping name	-	-
Transport hazard class(es)	-	-
Packing group	-	-
Environmental hazards	No.	No.
Additional information	-	-

Special precautions for user Not available.

Section 15. Regulatory information

TCCSCA List of concerned chemicals

Not applicable.

OSHA Article 29 None of the components are listed.
OSHA Article 30 None of the components are listed.

Montreal Protocol

Ingredient name	Status
Not listed.	

Stockholm Convention on Persistent Organic Pollutants

Ingredient name	List name	Status
Not listed.		

Rotterdam Convention on Prior Informed Consent (PIC)

Ingredient name	Status
Not listed.	

Regulation according to other foreign laws

REACH Status For the REACH status of this product please consult your company contact, as identified in

Section 1.

Australia inventory (AIIC) All components are listed or exempted.

Product nameCastrol High Temperature GreaseProduct code467200-SG01Page: 9/10Version 5.01Date of issue 29/09/2025.Format TaiwanLanguage ENGLISHTaiwan(ENGLISH)

Section 15. Regulatory information

Canada inventory status
China inventory (IECSC)

Japan inventory (CSCL)

Philippines inventory
(PICCS)

All components are listed or exempted.

At least one component is not listed.

All components are listed or exempted.

Korea inventory (KECI) At least one component is not listed.

Taiwan Chemical All components are listed or exempted.

Substances Inventory

(TCSI)
United States inventory
All components are active or exempted.

(TSCA 8b)

Section 16. Other information

Procedure used to derive the classification

Classification	Justification
Not classified.	

References Not available.

Organisation that prepared

the SDS History

Date of printing9/29/2025Date of previous issue29/09/2025.

Version 5.01

Prepared by Product Stewardship

Key to abbreviations

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

Regulation (EC) No. 1907/2006]

UN = United Nations

Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0,

72623-87-1

▼ Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Castrol High Temperature GreaseProduct code467200-SG01Page: 10/10Version 5.01Date of issue 29/09/2025.Format TaiwanLanguage ENGLISHTaiwan(ENGLISH)