SAFETY DATA SHEET



Castrol Transmax Axle 85W-140

Section 1. Identification

GHS product identifier Castrol Transmax Axle 85W-140

Product code 469574-IN01 SDS # 469574

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/ Gear lubricant

mixture For specific application advice see appropriate Technical Data Sheet or consult our

company representative.

Manufacturer

Supplier Castrol India Limited

Technopolis Knowledge Park Mahakali Caves Road

Andheri (East), MUMBAI 400 093

Maharashtra, India

Contact: +91 22 66984100

EMERGENCY TELEPHONE Toll free: 000800 100 7479 (for use in India only - 24/7)

NUMBER Carechem Singapore: +65 3158 1198 (24/7)

Section 2. Hazards identification

GHS Classification SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 2

LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3

GHS label elements

Signal word No signal word.

Hazard statements H401 - Toxic to aquatic life.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

General P102 - Keep out of reach of children.

P101 - If medical advice is needed, have product container or label at hand.

Prevention P273 - Avoid release to the environment.

Response Not applicable.

Storage Not applicable.

Disposal P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Other hazards which do not

result in classification

Defatting to the skin.

Section 3. Composition/information on ingredients

Substance/mixture

Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Ingredient name	%	CAS number
Residual oils (petroleum), solvent-dewaxed	≥25 - ≤50	CAS: 64742-62-7
Residual oils (petroleum), hydrotreated	≥25 - ≤50	CAS: 64742-57-0
Distillates (petroleum), hydrotreated heavy paraffinic	≤10	CAS: 64742-54-7
Polysulfides, di-tert-Bu	≤3	CAS: 68937-96-2
Amines, C12-14-tert-alkyl	≤0.3	CAS: 68955-53-3
(Z)-octadec-9-enylamine	≤0.3	CAS: 112-90-3

Product name Castrol Transmax Axle 85W-140

Version 2.01 Date of issue 30/09/2025.

Product code 4 Format GHS - India

469574-IN01 Page: 1/11

Build 6.1.1 (GHS -India)

Language ENGLISH (ENGLISH)

Section 3. Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eye contact

Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for

and remove any contact lenses. Get medical attention.

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Skin contact Wash skin thoroughly with soap and water or use recognised skin cleanser.

> Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur. If skin

irritation or rash occurs: Get medical advice/attention.

Do not induce vomiting unless directed to do so by medical personnel. Never give Ingestion

> anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if adverse

health effects persist or are severe.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Specific treatments No specific treatment.

Notes to physician Treatment should in general be symptomatic and directed to relieving any effects.

Section 5. Firefighting measures

Extinguishing media

Suitable Use foam or all-purpose dry chemical to extinguish.

Not suitable Do not use water jet.

Specific hazards arising from the chemical

Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life.

This material is harmful to aquatic life with long lasting effects.

Hazardous thermal decomposition products Combustion products may include the following:

Special precautions for fire-

carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if

there is a fire.

Special protective

(SCBA) and full turnout gear.

equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

For emergency responders

Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and material for containment and cleaning up

Product name Castrol Transmax Axle 85W-140 Product code 469574-IN01 Page: 2/11 Language ENGLISH Date of issue 30/09/2025. Format GHS - India Version 2.01 (ENGLISH) Build 6.1.1 (GHS -India)

Section 6. Accidental release measures

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Avoid contact of spilt material and runoff with soil and surface waterways.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. Contaminated work clothing should not be allowed out of the workplace. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Not suitable

Prolonged exposure to elevated temperature

Ensure product is stored in covered area away from direct sunlight, heat, rain and water exposure.



Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Residual oils (petroleum), solvent-dewaxed	Directorate General Factory Advice Service & Labour Institutes, Factories Act (India, 4/2001) [oil mist mineral] STEL 15 minutes: 10 mg/m³. Form: mist. TWA 8 hours: 5 mg/m³. Form: mist.
Residual oils (petroleum), hydrotreated	Directorate General Factory Advice Service & Labour Institutes, Factories Act (India, 4/2001) [oil mist mineral] STEL 15 minutes: 10 mg/m³. Form: mist. TWA 8 hours: 5 mg/m³. Form: mist.
Distillates (petroleum), hydrotreated heavy paraffinic	Directorate General Factory Advice Service & Labour Institutes, Factories Act (India, 4/2001) [oil mist mineral] STEL 15 minutes: 10 mg/m³. Form: mist. TWA 8 hours: 5 mg/m³. Form: mist.

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Biological exposure indices

Product name Castrol Transmax Axle 85W-140Product code469574-IN01Page: 3/11Version 2.01Date of issue 30/09/2025.Format GHS - IndiaLanguage ENGLISHBuild 6.1.1(GHS -India)(ENGLISH)

Section 8. Exposure controls/personal protection

Ingredient name	Exposure indices
No exposure indices known.	

Recommended monitoring procedures

Appropriate engineering controls

Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye protection Skin protection

Hand protection

Safety glasses with side shields.

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Skin protection

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Product name Castrol Transmax Axle 85W-140

Version 2.01 Date of issue 30/09/2025.

Product code Format GHS - India 469574-IN01

Language ENGLISH (ENGLISH)

Page: 4/11

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state Liquid.

Colour Amber. [Light] Odour Not available. **Odour threshold** Not available. Ha Not applicable. Melting point/freezing point Not available. **Boiling point or initial** Not available.

boiling point and boiling

range

Not available. **Drop Point Pour point** -21 °C

Closed cup: 177°C (350.6°F) [Pensky-Martens ASTM D 93] Flash point

Evaporation rate Not available. **Flammability** Not available.

Flammability Not applicable. Based on - Physical state

Lower and upper explosion limit/flammability limit

Vapour pressure

Not available.

	Vapour Pressure at 20°C		/apour Pressure at 20°C Vapour pressure a		ure at 50°C	
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
Sesidual oils (petroleum), solvent- dewaxed	<0.07501	<0.01	ASTM D 5191			
Residual oils (petroleum), hydrotreated	<0.07501	<0.01	ASTM D 5191			
Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191			
Polysulfides, di-tert-Bu	0.12	0.016	OECD 104			

Relative vapour density Not available. Relative density Not available.

Density <1000 kg/m³ (<1 g/cm³) at 15°C

Solubility(ies)

Media	Result
water	Not soluble

Partition coefficient: n-

octanol/water

Not applicable.

Auto-ignition temperature Decomposition temperature

Not available.

Not available.

Viscosity Kinematic: 360.8 mm²/s (360.8 cSt) at 40°C Kinematic: 25 to 28 mm²/s (25 to 28 cSt) at 100°C

Particle characteristics

Median particle size Not applicable.

Section 10. Stability and reactivity

No specific test data available for this product. Refer to Conditions to avoid and Reactivity

Incompatible materials for additional information.

Chemical stability The product is stable.

Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous polymerisation will not occur.

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid Avoid all possible sources of ignition (spark or flame).

Incompatible materials Reactive or incompatible with the following materials: oxidising materials.

469574-IN01 Product name Castrol Transmax Axle 85W-140 Product code Page: 5/11 Language ENGLISH Version 2.01 Date of issue 30/09/2025. Format GHS - India (GHS -India) (ENGLISH) Build 6.1.1

Section 10. Stability and reactivity

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name

vistillates (petroleum), hydrotreated heavy paraffinic

Result

Rat - Oral - LD50 >5000 mg/kg **OECD 401**

Rabbit - Dermal - LD50

>5000 mg/kg **OECD 402**

Rat - Inhalation - LC50 Dusts and mists

>5 mg/l [4 hours] **OECD 403**

Amines, C12-14-tert-alkyl Rat - Oral - LD50 612 mg/kg

OECD 401

Rat - Dermal - LD50

251 mg/kg **OECD 402**

Rat - Inhalation - LC50 Vapour

1.19 mg/l [4 hours] **OECD 403** Rat - Oral - LD50 1689 ma/ka **OECD 401**

(Z)-octadec-9-enylamine

Skin corrosion/irritation

Product/ingredient name

vistillates (petroleum), hydrotreated heavy paraffinic

Amines, C12-14-tert-alkyl (Z)-octadec-9-enylamine

Result

Rabbit - Skin - Mild irritant

OECD 404

Rabbit - Skin - Visible necrosis Rabbit - Skin - Visible necrosis

OECD 404

Serious eye damage/eye irritation

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Amines, C12-14-tert-alkyl (Z)-octadec-9-enylamine

Result

Rabbit - Eyes - Non-irritating to the eyes.

OECD 405

Rabbit - Eyes - Visible necrosis Rabbit - Eyes - Severe irritant

OECD 405

Respiratory corrosion/irritation

Not available.

Respiratory or skin sensitization

Product/ingredient name

vistillates (petroleum), hydrotreated heavy paraffinic

Amines, C12-14-tert-alkyl

Result

Build 6.1.1

Guinea pig - skin **OECD 406**

Result: Not sensitising Guinea pig - skin **OECD 406** Result: Sensitising

Product name Castrol Transmax Axle 85W-140 Version 2.01 Date of issue 30/09/2025.

Product code Format GHS - India

469574-IN01

Page: 6/11

Language ENGLISH (GHS -India) (ENGLISH)

Section 11. Toxicological information

Germ cell mutagenicity

Product/ingredient name

Amines, C12-14-tert-alkyl

(Z)-octadec-9-enylamine

istillates (petroleum), hydrotreated heavy paraffinic

Result

In vitro - Bacteria

Bacterial Reverse Mutation Test

Result: Negative

In vitro - Mammal - species unspecified
In vitro Mammalian Chromosomal Aberration Test

Result: Negative

In vivo - Mammal - species unspecified Mammalian Erythrocyte Micronucleus Test

Result: Negative

In vitro - Mammal - species unspecified In vitro Mammalian Cell Gene Mutation Test

Result: Negative In vitro - Bacteria

Bacterial Reverse Mutation Test

Result: Negative

In vitro - Mammal - species unspecified In vitro Mammalian Cell Gene Mutation Test

Result: Negative

In vivo - Mammal - species unspecified Mammalian Erythrocyte Micronucleus Test

Result: Negative In vitro - Bacteria OECD 471

Result: Negative
In vitro - Unspecified

OECD 473
Result: Negative

In vitro - Mammal - species unspecified

OECD 476
Result: Negative

Carcinogenicity

Product/ingredient name

vistillates (petroleum), hydrotreated heavy paraffinic

Result

Mouse - Dermal - Unspecified

OECD 451
Result: Negative

Reproductive toxicity

Product/ingredient name

stillates (petroleum), hydrotreated heavy paraffinic

Amines, C12-14-tert-alkyl

(Z)-octadec-9-enylamine

Result

Rat - Oral OECD 421

<u>Maternal toxicity</u>: Negative <u>Fertility effects</u>: Negative <u>Developmental</u>: Negative

Rat - Oral OECD 415

Maternal toxicity: Negative Fertility effects: Negative Developmental: Negative

Rat - Oral

OECD 421

Maternal toxicity: Positive Fertility effects: Negative Developmental: Negative

Product nameCastrol Transmax Axle 85W-140Product code469574-IN01Page: 7/11Version 2.01Date of issue 30/09/2025.Format GHS - IndiaLanguage ENGLISHBuild 6.1.1(GHS -India)(ENGLISH)

Section 11. Toxicological information

Specific target organ toxicity (single exposure)

Product/ingredient name Result

✓)-octadec-9-enylamine SPECIFIC TARGET ORGAN TOXICITY - SINGLE

EXPOSURE (Respiratory tract irritation) - Category 3

Specific target organ toxicity (repeated exposure)

Product/ingredient name Result

☑)-octadec-9-enylamine SPECIFIC TARGET ORGAN TOXICITY - REPEATED

EXPOSURE - Category 2

Aspiration hazard

Product/ingredient name Result

(Z)-octadec-9-enylamine ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact No known significant effects or critical hazards.

Inhalation Vapour inhalation under ambient conditions is not normally a problem due to low

vapour pressure.

Skin contact Defatting to the skin. May cause skin dryness and irritation.

Ingestion No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact No specific data.

Inhalation May be harmful by inhalation if exposure to vapour, mists or fumes resulting from

thermal decomposition products occurs.

Skin contact Adverse symptoms may include the following:

irritation dryness cracking

Ingestion No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs.

Inhalation Overexposure to the inhalation of airborne droplets or aerosols may cause irritation

of the respiratory tract.

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/

or dermatitis.

Ingestion Ingestion of large quantities may cause nausea and diarrhoea.

Potential chronic health effects

GeneralNo known significant effects or critical hazards.CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

Section 12. Ecological information

Environmental effects This material is toxic to aquatic life. This material is harmful to aquatic life with long

Result

lasting effects.

Product/ingredient name

stillates (petroleum), hydrotreated heavy

Acute - EL50

paraffinic OECD 2

OECD 201 Algae

>100 mg/l [72 hours] **Acute - EL50**

Acute - EL50 OECD 202 Daphnia

Product nameCastrol Transmax Axle 85W-140Product code469574-IN01Page: 8/11Version 2.01Date of issue 30/09/2025.Format GHS - IndiaLanguage ENGLISH

Build 6.1.1 (GHS -India) (ENGLISH)

Section 12. Ecological information

>10000 mg/l [48 hours]

Acute - LL50 OECD 203 Fish

>100 mg/l [96 hours] Chronic - NOEL

OECD 201 Algae

≥100 mg/l [72 hours]

Chronic - NOEL
OECD 211
Daphnia
10 mg/l [21 days]

10 mg/l [21 days]
Acute - ErC50

OECD 201 Algae

0.44 mg/l [72 hours]

Acute - EC50 OECD 202 Daphnia

2.5 mg/l [48 hours] **Acute - LC50**

OECD 203 Fish

1.3 mg/l [96 hours]

Acute - EC50 OECD 209 Micro-organism 63.5 mg/l [3 hours] Chronic - NOEC

OECD 201 Algae

0.05 mg/l [72 hours] **Acute - ErC50**

OECD 201 Algae

0.04 mg/l [96 hours]
Chronic - NOEC

OECD 201 Algae

0.01 mg/l [96 hours]
Chronic - NOEC

OECD 211 Daphnia

0.013 mg/l [21 days] **Acute - LC50**

EPA OPPTS 850.1085

Fish

0.06 mg/l [96 hours]

Persistence and degradability

Expected to be biodegradable.

Amines, C12-14-tert-alkyl

(Z)-octadec-9-enylamine

Product/ingredient name

stillates (petroleum), hydrotreated heavy paraffinic

Amines, C12-14-tert-alkyl

(Z)-octadec-9-enylamine

Result

OECD 301F

31% [28 days] - Not readily

OECD 301D

21.8% [28 days] - Not readily

OECD 301B

66% [28 days] - Readily

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Product name Castrol Transmax Axle 85W-140

Version 2.01

Date of issue 30/09/2025.

Build 6.1.1

Product code 469574-IN01

Page: 9/11

Language ENGLISH

Build 6.1.1

(GHS -India)

(ENGLISH)

Section 12. Ecological information

Product/ingredient name	LogPow	BCF	Potential
Polysulfides, di-tert-Bu	5.6	-	High
, -	2.9	-	Low
(Z)-octadec-9-enylamine	4.33	-	High

Mobility

Spillages may penetrate the soil causing ground water contamination.

Other adverse effects

No known significant effects or critical hazards.

Other ecological information

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	IMDG	IATA
UN number	Not regulated.	Not regulated.
UN proper shipping name	-	-
Transport hazard class(es)	-	-
Packing group	-	-
Environmental hazards	No.	No.
Additional information	-	-

Special precautions for user

Not available.

Transport in bulk according to IMO instruments

Not available.

Section 15. Regulatory information

Regulation according to other foreign laws

REACH Status For the REACH status of this product please consult your company contact, as identified in

Section 1.

Australia inventory (AIIC) All components are listed or exempted. Canada inventory status All components are listed or exempted. China inventory (IECSC) All components are listed or exempted. Japan inventory (CSCL) All components are listed or exempted. All components are listed or exempted. Korea inventory (KECI) Philippines inventory All components are listed or exempted.

(PICCS)

All components are listed or exempted.

Taiwan Chemical Substances Inventory

(TCSI)

Product name Castrol Transmax Axle 85W-140 469574-IN01 Page: 10/11 Product code Language ENGLISH Version 2.01 Date of issue 30/09/2025. Format GHS - India (ENGLISH) Build 6.1.1 (GHS -India)

Section 15. Regulatory information

United States inventory (TSCA 8b)

All components are active or exempted.

Section 16. Other information

History

Date of issue/Date of

revision

30/09/2025.

Date of previous issue

05/03/2025.

Prepared by

Product Stewardship

Key to abbreviations

ACGIH = American Conference of Industrial Hygienists CAS Number = Chemical Abstracts Service Registry Number

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

OEL = Occupational Exposure Limit

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

Regulation (EC) No. 1907/2006]

SDS = Safety Data Sheet STEL = Short term exposure limit TWA = Time weighted average

UN Number = United Nations Number, a four digit number assigned by the United

Nations Committee of Experts on the Transport of Dangerous Goods. Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

▼ Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Castrol Transmax Axle 85W-140Product code469574-IN01Page: 11/11Version 2.01Date of issue 30/09/2025.Format GHS - IndiaLanguage ENGLISHBuild 6.1.1(GHS -India)(ENGLISH)