

Castrol Vecton Long Drain 10W-40 E7

Safety Data Sheet according to GB/T 16483-2008 and GB/T 17519-2013

Section 1. Identification

GHS product identifier	Castrol Vecton Long Drain 10W-40 E7
Product code	468510-MY01
SDS #	468510
<u>Relevant identified uses of the substance or mixture and uses advised against</u>	
Use of the substance/ mixture	Engine Oils. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
Supplier	Castrol (Shanghai) Management Co., Ltd. 3F, Building 5, No. 255 of Guiqiao Road, Shanghai P.R.C. 201206 Tel:+86 21 38605888
EMERGENCY TELEPHONE NUMBER	+86 (0)532 8388 9090

Section 2. Hazards identification

Classification of the substance or mixture	<input checked="" type="checkbox"/> SKIN CORROSION/IRRITATION - Category 3
<u>GHS label elements</u>	
Signal word	Warning
Hazard statements	<input checked="" type="checkbox"/> H316 - Causes mild skin irritation.
<u>Precautionary statements</u>	
Prevention	<input checked="" type="checkbox"/> Not applicable.
Response	P332 + P313 - If skin irritation occurs: Get medical attention.
Storage	Not applicable.
Disposal	<input checked="" type="checkbox"/> Not applicable.
Other hazards which do not result in classification	Defatting to the skin. USED ENGINE OILS Used engine oil may contain hazardous components which have the potential to cause skin cancer. See Toxicological Information, section 11 of this Safety Data Sheet.

Section 3. Composition/information on ingredients

Substance/mixture	Mixture
Chemically modified base oil Proprietary performance additives.	

Ingredient name	%	CAS number
<input checked="" type="checkbox"/> Distillates (petroleum), hydrotreated heavy paraffinic	≥10 - ≤25	CAS: 64742-54-7
Distillates (petroleum), solvent-dewaxed light paraffinic	≤3	CAS: 64742-56-9
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isoctyl) esters, zinc salts	<2.5	CAS: 113706-15-3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Product name	Castrol Vecton Long Drain 10W-40 E7	Product code	468510-MY01	Page: 1/12
Version 4	Date of issue 10/23/2025	Format China	Language ENGLISH	
		China	(ENGLISH)	

Section 3. Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Inhalation	If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.
Skin contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur. If skin irritation or rash occurs: Get medical advice/attention.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if adverse health effects persist or are severe.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	No specific treatment.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media	 In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet.
Specific hazards arising from the chemical	 In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	 Combustion products may include the following: carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide) nitrogen oxides (NO, NO ₂ etc.)
Special protective actions for fire-fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.
Special protective equipment for fire-fighters	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.
------------------------------------	---

Product name Castrol Vecton Long Drain 10W-40 E7

Product code 468510-MY01 **Page:** 2/12

Version 4 **Date of issue** 10/23/2025

Format China

Language ENGLISH

China

(ENGLISH)

Section 6. Accidental release measures

For emergency responders Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

Environmental precautions Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Small spill Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. Contaminated work clothing should not be allowed out of the workplace. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Not suitable Prolonged exposure to elevated temperature

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
None.	

Biological exposure indices

No exposure indices known.

Product name Castrol Vecton Long Drain 10W-40 E7

Product code 468510-MY01 **Page:** 3/12

Version 4 **Date of issue** 10/23/2025

Format China

Language ENGLISH

China

(ENGLISH)

Section 8. Exposure controls/personal protection

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety glasses with side shields.

Skin protection

Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Skin protection

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	Liquid.
Colour	Brown. [Dark]
Odour	Not available.
Odour threshold	Not available.
pH	Not applicable.
Melting point/freezing point	Not available.
Boiling point or initial boiling point and boiling range	Not available.
Drop Point	Not available.
Flash point	☑ Closed cup: 212°C (413.6°F) [Pensky-Martens ASTM D 93]
Evaporation rate	Not available.
Flammability	Not available.
Lower and upper explosion limit/flammability limit	Not available.
Vapour pressure	

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
☑ Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191			
Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191			
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<0.07501	<0.01	ASTM D 5191			
Polybutene (Isobutylene/butene copolymer)	5.10043	0.68		13.05111	1.7	
Distillates (petroleum), solvent-dewaxed light paraffinic	<0.07501	<0.01	ASTM D 5191			

Relative vapour density	Not available.
Relative density	Not available.
Density	<1000 kg/m ³ (<1 g/cm ³) at 15°C
Solubility(ies)	

Media	Result
water	Not soluble

Partition coefficient: n-octanol/water	Not applicable.
--	-----------------

Auto-ignition temperature			
Ingredient name	°C	°F	Method
☑ Polybutene (Isobutylene/butene copolymer)	215	419	EU A.15

Decomposition temperature	Not available.
---------------------------	----------------

Viscosity	☑ Kinematic: 84.03 mm ² /s (84.03 cSt) at 40°C Kinematic: 12.84 mm ² /s (12.84 cSt) at 100°C
-----------	---

Particle characteristics

Product name	Castrol Vecton Long Drain 10W-40 E7	Product code	468510-MY01	Page:	5/12
Version	4	Date of issue	10/23/2025	Format	China
			China	Language	ENGLISH (ENGLISH)

Section 9. Physical and chemical properties

Median particle size Not applicable.

Section 10. Stability and reactivity

Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
Incompatible materials	Reactive or incompatible with the following materials: oxidising materials.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Result

Rat - Oral - LD50

>5000 mg/kg
OECD 401

Rabbit - Dermal - LD50

>5000 mg/kg
OECD 402

Rat - Inhalation - LC50 Dusts and mists

>5 mg/l [4 hours]
OECD 403

Distillates (petroleum), solvent-dewaxed light paraffinic

Rat - Oral - LD50

>5000 mg/kg
OECD 401

Rabbit - Dermal - LD50

>5000 mg/kg
OECD 402

Rat - Inhalation - LC50 Dusts and mists

>2.18 mg/l [4 hours]
OECD 403

Skin corrosion/irritation

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Result

Rabbit - Skin - Mild irritant

OECD 404

Distillates (petroleum), solvent-dewaxed light paraffinic

Rabbit - Skin - Non-irritant to skin.

Serious eye damage/eye irritation

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Result

Rabbit - Eyes - Non-irritating to the eyes.

OECD 405

Distillates (petroleum), solvent-dewaxed light paraffinic

Rabbit - Eyes - Non-irritating to the eyes.

OECD 405

Product name Castrol Vecton Long Drain 10W-40 E7

Product code 468510-MY01 **Page:** 6/12

Version 4 **Date of issue** 10/23/2025

Format China

Language ENGLISH

China

(ENGLISH)

Section 11. Toxicological information

Respiratory corrosion/irritation

Not available.

Respiratory or skin sensitization

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), solvent-dewaxed light paraffinic

Result

Guinea pig - skin

OECD 406

Result: Not sensitising

Guinea pig - skin

OECD 406

Result: Not sensitising

Germ Cell Mutagenicity

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), solvent-dewaxed light paraffinic

Result

In vitro - Bacteria

Bacterial Reverse Mutation Test

Result: Negative

In vitro - Mammal - species unspecified

In vitro Mammalian Chromosomal Aberration Test

Result: Negative

In vivo - Mammal - species unspecified

Mammalian Erythrocyte Micronucleus Test

Result: Negative

In vitro - Mammal - species unspecified

In vitro Mammalian Cell Gene Mutation Test

Result: Negative

In vitro - Bacteria

OECD [Bacterial Reverse Mutation Test]

Result: Negative

In vitro - Mammal - species unspecified

In vitro Mammalian Chromosomal Aberration Test

Result: Negative

Carcinogenicity

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Result

Mouse - Dermal - Unspecified

OECD 451

Result: Negative

Reproductive toxicity

Product/ingredient name

Result

Section 11. Toxicological information

Distillates (petroleum), hydrotreated heavy paraffinic

Rat - Oral
OECD 421
Maternal toxicity: Negative
Fertility effects: Negative
Developmental: Negative

Distillates (petroleum), solvent-dewaxed light paraffinic

Rat - Oral
OECD 421
Maternal toxicity: Negative
Fertility effects: Negative
Developmental: Negative

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Product/ingredient name

Result

Distillates (petroleum), hydrotreated heavy paraffinic

ASPIRATION HAZARD - Category 1

Distillates (petroleum), solvent-dewaxed light paraffinic

ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact

No known significant effects or critical hazards.

Inhalation

Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Skin contact

Causes mild skin irritation. Defatting to the skin.

Ingestion

Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact

Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation

No specific data.

Skin contact

Adverse symptoms may include the following:
irritation
redness
dryness
cracking

Ingestion

No specific data.

Short term exposure

Potential immediate effects

Not available.

Potential delayed effects

Not available.

Section 11. Toxicological information

Long term exposure

Potential immediate effects Not available.

Potential delayed effects Not available.

Potential chronic health effects

General

USED ENGINE OILS

Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.

Carcinogenicity

No known significant effects or critical hazards.

Mutagenicity

No known significant effects or critical hazards.

Developmental effects

No known significant effects or critical hazards.

Fertility effects

No known significant effects or critical hazards.

Section 12. Ecological information

Toxicity

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Result

Acute - EL50

OECD 201

Algae

>100 mg/l [72 hours]

Acute - EL50

OECD 202

Daphnia

>10000 mg/l [48 hours]

Acute - LL50

OECD 203

Fish

>100 mg/l [96 hours]

Chronic - NOEL

OECD 201

Algae

≥100 mg/l [72 hours]

Chronic - NOEL

OECD 211

Daphnia

10 mg/l [21 days]

Acute - EL50

OECD 201

Algae

>100 mg/l [72 hours]

Acute - EL50

OECD 202

Daphnia

>10000 mg/l [48 hours]

Acute - LL50

OECD 203

Fish

>100 mg/l [96 hours]

Chronic - NOEL

OECD 201

Algae

≥100 mg/l [72 hours]

Distillates (petroleum), solvent-dewaxed light paraffinic

Product name Castrol Vecton Long Drain 10W-40 E7

Product code 468510-MY01 **Page:** 9/12

Version 4 **Date of issue** 10/23/2025

Format China

Language ENGLISH

China

(ENGLISH)

Section 12. Ecological information

Chronic - NOEL

OECD 211
Daphnia
10 mg/l [21 days]

Environmental effects No known significant effects or critical hazards.

Persistence/degradability

Partially biodegradable.

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), solvent-dewaxed light paraffinic

Result

OECD 301F
31% [28 days] - Not readily

OECD 301F
31% [28 days] - Not readily

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Mobility in soil

Soil/water partition coefficient

Not available.

Mobility

Spillages may penetrate the soil causing ground water contamination.

Other adverse effects

No known significant effects or critical hazards.

Other ecological information

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	China GB12268	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-

Product name Castrol Vecton Long Drain 10W-40 E7

Product code 468510-MY01 **Page:** 10/12

Version 4 **Date of issue** 10/23/2025

Format China

Language ENGLISH

China

(ENGLISH)

Section 14. Transport information

Packing group	-	-	-
Environmental hazards	No.	No.	No.
Additional information	-	-	-

Special precautions for user Not available.

Matters needing attention for transportation Ensure that any additional local government transport conditions are met

Section 15. Regulatory information

List of Goods banned for Importing

None of the components are listed.

Drug Precursors Requiring an Import/Export License

None of the components are listed.

Catalogue and classification of drug precursor chemicals

None of the components are listed.

List of Explosive Precursors

None of the components are listed.

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

Safety, health and environmental regulations specific for the product No known specific national and/or regional regulations applicable to this product (including its ingredients).

Regulation according to other foreign laws

REACH Status

For the REACH status of this product please consult your company contact, as identified in Section 1.

Australia inventory (AIC)

All components are listed or exempted.

Canada inventory

All components are listed or exempted.

China inventory (IECSC)

All components are listed or exempted.

Japan inventory (CSCL)

All components are listed or exempted.

Korea inventory (KECI)

All components are listed or exempted.

Philippines inventory (PICCS)

All components are listed or exempted.

Taiwan Chemical Substances Inventory (TCSI)

All components are listed or exempted.

United States inventory (TSCA 8b)

All components are active or exempted.

Product name Castrol Vecton Long Drain 10W-40 E7

Product code 468510-MY01 **Page:** 11/12

Version 4 **Date of issue** 10/23/2025

Format China

Language ENGLISH

China

(ENGLISH)

Section 16. Other information

History

Date of printing	10/23/2025
Date of issue/Date of revision	10/23/2025
Date of previous issue	9/19/2025
Version	4
Prepared by	Product Stewardship
Key to abbreviations	ACGIH = American Conference of Industrial Hygienists CAS Number = Chemical Abstracts Service Registry Number GHS = Global Harmonised System IATA = International Air Transport Association, the organisation IMDG = International Maritime Organization Rules, rules governing shipment of goods by water. OEL = Occupational Exposure Limit REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006] SDS = Safety Data Sheet STEL = Short term exposure limit TWA = Time weighted average UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods. Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1
References	Not available.

✔ Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Date of issue/Date of revision	: 10/23/2025	Date of previous issue	: 9/19/2025	Version	: 4	12/12
---------------------------------------	--------------	-------------------------------	-------------	----------------	-----	-------

Product name	Castrol Vecton Long Drain 10W-40 E7	Product code	468510-MY01	Page:	12/12		
Version	4	Date of issue	10/23/2025	Format	China	Language	ENGLISH
				China		(ENGLISH)	