

## 1. Product and company identification

|  |  |
|--|--|
| Product name   | Castrol Transmax Axle Long Life 75W-90   |
| Product code   | 469698-DE01  |
| SDS no.  | 469698   |
| Original preparation date  | 24-Feb-2021  |
| Supplier   | BP Castrol K.K.<br>1-11-2, Osaki, Shinagawaku, Tokyo, 141-0032<br>East Tower 20F, Gate City Osaki<br>Telephone : 03-5719-7860 (days & hours of operation : Monday - Friday, 09:00 - 17:00)<br>Facsimile : 03-5435-2256 |
| EMERGENCY TELEPHONE NUMBER   | Carechem: 3 4578 9341 (Operation time: 24/7)<br>(from overseas ; +81 3 4578 9341)  |
| <u>Relevant identified uses of the substance or mixture and uses advised against</u> |  |
| Use of the substance/<br>mixture   | Automotive gear lubricant<br>For specific application advice see appropriate Technical Data Sheet or consult our company representative.   |

## 2. Hazards identification

|   |   |
|---|---|
| GHS Classification                                  | Not classified.                                   |
| <u>GHS label elements</u>                           |   |
| Signal word   | No signal word.                                   |
| Hazard statements                                   | No known significant effects or critical hazards. |
| <u>Precautionary statements</u>                     |   |
| Prevention  | Not applicable.                                   |
| Response  | Not applicable.                                   |
| Storage   | Not applicable.                                   |
| Disposal  | Not applicable.                                   |
| Other hazards which do not result in classification | None known.                                       |

## 3. Composition/information on ingredients

|  |         |
|--|---------|
| Substance/mixture  | Mixture |
| Synthetic base stock. Proprietary performance additives. |         |

|                     |  |                               |                     |                          |
|---------------------|--|-------------------------------|---------------------|--------------------------|
| <b>Product name</b> | Castrol Transmax Axle Long Life 75W-90 | <b>Product code</b>           | 469698-DE01         | Page: 1/10               |
| <b>Version</b>      | 1.01                                   | <b>Date of issue</b>          | 2021 April 1        | <b>Format Japan</b>      |
|                     |  | <b>Date of previous issue</b> | 2021 February 25.   | <b>Language</b>          |
|                     |  |                               | Build 6.0.7 (Japan) | <b>ENGLISH (ENGLISH)</b> |

### 3. Composition/information on ingredients

| Ingredient name   | %    | CAS number  |
|---|------|-------------|
| Polysulfides, di-tert-Bu                                  | ≤5.0 | 68937-96-2  |
| Phosphoric acid esters, amine salt                        | ≤1.9 | Proprietary |
| Distillates (petroleum), hydrotreated heavy paraffinic    | ≤3.0 | 64742-54-7  |
| Distillates (petroleum), hydrotreated light paraffinic    | ≤3.0 | 64742-55-8  |
| Distillates (petroleum), solvent-dewaxed light paraffinic | ≤3.0 | 64742-56-9  |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | ≤3.0 | 64742-65-0  |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### 4. First aid measures

#### Description of necessary first aid measures

|                     |   |
|---------------------|---|
| <b>Eye contact</b>  | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention. |
| <b>Inhalation</b>   | If inhaled, remove to fresh air. Get medical attention if symptoms occur.   |
| <b>Skin contact</b> | Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.       |
| <b>Ingestion</b>    | Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.  |

#### Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

#### Indication of immediate medical attention and special treatment needed, if necessary

|                                   |  |
|-----------------------------------|--|
| <b>Protection of first-aiders</b> | No action shall be taken involving any personal risk or without suitable training. |
| <b>Notes to physician</b>         | Treatment should in general be symptomatic and directed to relieving any effects.  |
| <b>Specific treatments</b>        | No specific treatment.   |

### 5. Firefighting measures

#### Extinguishing media

|   |   |
|---|---|
| <b>Suitable</b>                                       | In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.  |
| <b>Not suitable</b>                                   | Do not use water jet.   |
| <b>Specific hazards arising from the chemical</b>     | In a fire or if heated, a pressure increase will occur and the container may burst.   |
| <b>Hazardous thermal decomposition products</b>       | Combustion products may include the following:<br>carbon oxides (CO, CO <sub>2</sub> ) (carbon monoxide, carbon dioxide)  |
| <b>Special protective actions for fire-fighters</b>   | No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. |
| <b>Special protective equipment for fire-fighters</b> | Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.  |

|                     |  |                               |                     |                         |
|---------------------|--|-------------------------------|---------------------|-------------------------|
| <b>Product name</b> | Castrol Transmax Axle Long Life 75W-90 | <b>Product code</b>           | 469698-DE01         | Page: 2/10              |
| <b>Version</b>      | 1.01                                   | <b>Date of issue</b>          | 2021 April 1        | <b>Format</b> Japan     |
|                     |  | <b>Date of previous issue</b> | 2021 February 25.   | <b>Language</b> ENGLISH |
|                     |  |                               | Build 6.0.7 (Japan) | <b>(ENGLISH)</b>        |

## 6. Accidental release measures

### [Personal precautions, protective equipment and emergency procedures](#)

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

[Environmental precautions](#)

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### [Methods and material for containment and cleaning up](#)

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

In the case of spillage at sea approved dispersants may be used where authorised by the appropriate government/regulatory authorities.

## 7. Handling and storage

[Protective measures](#)

Put on appropriate personal protective equipment (see Section 8).

[Advice on general occupational hygiene](#)

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

[Conditions for safe storage](#)

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Not suitable

Prolonged exposure to elevated temperature.

## 8. Exposure controls/personal protection

[Control parameters](#)

[Occupational exposure limits](#)

|                     |  |                               |                     |                                   |
|---------------------|--|-------------------------------|---------------------|-----------------------------------|
| <b>Product name</b> | Castrol Transmax Axle Long Life 75W-90 | <b>Product code</b>           | 469698-DE01         | Page: 3/10                        |
| <b>Version</b>      | 1.01                                   | <b>Date of issue</b>          | 2021 April 1        | <b>Format</b> Japan               |
|                     |  | <b>Date of previous issue</b> | 2021 February 25.   | <b>Language</b> ENGLISH (ENGLISH) |
|                     |  |                               | Build 6.0.7 (Japan) |                                   |

## 8. Exposure controls/personal protection

| Ingredient name   | Exposure limits  |
|---|--|
| Distillates (petroleum), hydrotreated heavy paraffinic    | <b>Japan Society for Occupational Health (Japan).</b><br>OEL-M: 3 mg/m <sup>3</sup> 8 hours. Issued/Revised: 1/1977 Form: Mist |
| Distillates (petroleum), hydrotreated light paraffinic    | <b>Japan Society for Occupational Health (Japan).</b><br>OEL-M: 3 mg/m <sup>3</sup> 8 hours. Issued/Revised: 1/1977 Form: Mist |
| Distillates (petroleum), solvent-dewaxed light paraffinic | <b>Japan Society for Occupational Health (Japan).</b><br>OEL-M: 3 mg/m <sup>3</sup> 8 hours. Issued/Revised: 1/1977 Form: Mist |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | <b>Japan Society for Occupational Health (Japan).</b><br>OEL-M: 3 mg/m <sup>3</sup> 8 hours. Issued/Revised: 1/1977 Form: Mist |

### Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

#### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

|                     |  |                               |                   |                     |
|---------------------|--|-------------------------------|-------------------|---------------------|
| <b>Product name</b> | Castrol Transmax Axle Long Life 75W-90 | <b>Product code</b>           | 469698-DE01       | Page: 4/10          |
| <b>Version</b>      | 1.01                                   | <b>Date of issue</b>          | 2021 April 1      | <b>Format Japan</b> |
|                     |  | <b>Date of previous issue</b> | 2021 February 25. | Build 6.0.7         |
|                     |  |                               | <b>(Japan)</b>    | <b>Language</b>     |
|                     |  |                               |                   | <b>ENGLISH</b>      |
|                     |  |                               |                   | <b>(ENGLISH)</b>    |

## 8. Exposure controls/personal protection

|                        |  |
|------------------------|--|
| Respiratory protection | In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.   |
| Hand protection        | Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions. |
| Eye protection         | Safety glasses with side shields.  |
| Skin protection        | Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.  |
| Other skin protection  | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.  |

## 9. Physical and chemical properties

|  |  |
|--|--|
| <a href="#">Appearance</a>                   |  |
| Physical state                               | Liquid.                                |
| Colour                                       | Amber.                                 |
| Odour  | Not available.                         |
| pH   | Not applicable.                        |
| Melting point / range                        | Not available.                         |
| Boiling point / range                        | Not available.                         |
| Flash point                                  | Open cup: >205°C (>401°F) [Cleveland.] |
| Fire point                                   | Not available.                         |
| Evaporation rate                             | Not available.                         |
| Lower and upper explosive (flammable) limits | Not available.                         |
| Vapour pressure                              | Not available.                         |
| Vapour density                               | Not available.                         |
| Relative Density                             | Not available.                         |
| Auto-ignition temperature                    | Not available.                         |
| Explosion limits                             | Not available.                         |
| Volatility                                   | Not available.                         |
| Critical temperature                         | Not available.                         |
| Oxidising properties                         | Not available.                         |

|                     |  |                      |                     |                                   |
|---------------------|--|----------------------|---------------------|-----------------------------------|
| <b>Product name</b> | Castrol Transmax Axle Long Life 75W-90 | <b>Product code</b>  | 469698-DE01         | Page: 5/10                        |
| <b>Version</b>      | 1.01                                   | <b>Date of issue</b> | 2021 April 1        | <b>Format</b> Japan               |
|                     | <b>Date of previous issue</b>          | 2021 February 25.    | Build 6.0.7 (Japan) | <b>Language</b> ENGLISH (ENGLISH) |

## 9. Physical and chemical properties

|                                      |   |
|--------------------------------------|---|
| Viscosity                            | Kinematic: 101 mm <sup>2</sup> /s (101 cSt) at 40°C<br>Kinematic: 14.8 to 15.8 mm <sup>2</sup> /s (14.8 to 15.8 cSt) at 100°C |
| Drop Point                           | Not available.  |
| Density                              | <1000 kg/m <sup>3</sup> (<1 g/cm <sup>3</sup> ) at 15°C   |
| Solubility                           | insoluble in water.   |
| Solubility at room temperature (g/l) | Not available.  |
| Dispersibility properties            | Not available.  |
| Partition coefficient (LogKow)       | Not available.  |
| Remarks                              | Not available.  |

## 10. Stability and reactivity

|                                    |   |
|------------------------------------|---|
| Reactivity                         | No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.                                   |
| Chemical stability                 | The product is stable.  |
| Possibility of hazardous reactions | Under normal conditions of storage and use, hazardous reactions will not occur.<br>Under normal conditions of storage and use, hazardous polymerisation will not occur. |
| Conditions to avoid                | Avoid all possible sources of ignition (spark or flame).  |
| Incompatible materials             | Reactive or incompatible with the following materials: oxidising materials.   |
| Hazardous decomposition products   | Under normal conditions of storage and use, hazardous decomposition products should not be produced.  |

## 11. Toxicological information

### Aspiration hazard

| Name  | Result                         |
|---|--------------------------------|
| Distillates (petroleum), hydrotreated heavy paraffinic    | ASPIRATION HAZARD - Category 1 |
| Distillates (petroleum), hydrotreated light paraffinic    | ASPIRATION HAZARD - Category 1 |
| Distillates (petroleum), solvent-dewaxed light paraffinic | ASPIRATION HAZARD - Category 1 |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | ASPIRATION HAZARD - Category 1 |

Information on likely routes of exposure Routes of entry anticipated: Dermal, Inhalation.

### Potential acute health effects

|              |  |
|--------------|--|
| Eye contact  | No known significant effects or critical hazards.  |
| Inhalation   | Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure. |
| Skin contact | Defatting to the skin. May cause skin dryness and irritation.                                    |
| Ingestion    | No known significant effects or critical hazards.  |

### Symptoms related to the physical, chemical and toxicological characteristics

|              |  |
|--------------|--|
| Eye contact  | No specific data.  |
| Inhalation   | May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs. |
| Skin contact | Adverse symptoms may include the following:<br>irritation<br>dryness<br>cracking   |
| Ingestion    | No specific data.  |

|                     |  |                               |                   |                     |                 |                  |
|---------------------|--|-------------------------------|-------------------|---------------------|-----------------|------------------|
| <b>Product name</b> | Castrol Transmax Axle Long Life 75W-90 | <b>Product code</b>           | 469698-DE01       | Page: 6/10          |                 |                  |
| <b>Version</b>      | 1.01                                   | <b>Date of issue</b>          | 2021 April 1      | <b>Format Japan</b> | <b>Language</b> | <b>ENGLISH</b>   |
|                     |  | <b>Date of previous issue</b> | 2021 February 25. | Build 6.0.7 (Japan) |                 | <b>(ENGLISH)</b> |

## 11. Toxicological information

### [Delayed and immediate effects as well as chronic effects from short and long-term exposure](#)

|              |  |
|--------------|--|
| Eye contact  | Potential risk of transient stinging or redness if accidental eye contact occurs.                              |
| Inhalation   | Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract. |
| Skin contact | Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.           |
| Ingestion    | Ingestion of large quantities may cause nausea and diarrhoea.  |

### [Potential chronic health effects](#)

|                       |   |
|-----------------------|---|
| General               | No known significant effects or critical hazards. |
| Carcinogenicity       | No known significant effects or critical hazards. |
| Mutagenicity          | No known significant effects or critical hazards. |
| Teratogenicity        | No known significant effects or critical hazards. |
| Developmental effects | No known significant effects or critical hazards. |
| Fertility effects     | No known significant effects or critical hazards. |

### [Numerical measures of toxicity](#)

#### [Acute toxicity estimates](#)

| Route | ATE value     |
|-------|---------------|
| Oral  | 30992.7 mg/kg |

## 12. Ecological information

|                               |  |
|-------------------------------|--|
| Environmental effects         | No known significant effects or critical hazards.  |
| Persistence and degradability | Not expected to be rapidly degradable.   |
| Bioaccumulative potential     | This product is not expected to bioaccumulate through food chains in the environment.                                  |
| Mobility                      | Spillages may penetrate the soil causing ground water contamination.   |
| Other ecological information  | Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired. |

## 13. Disposal considerations

|                  |  |
|------------------|--|
| Disposal methods | The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. |
|------------------|--|

|                     |  |                      |                     |                                   |
|---------------------|--|----------------------|---------------------|-----------------------------------|
| <b>Product name</b> | Castrol Transmax Axle Long Life 75W-90 | <b>Product code</b>  | 469698-DE01         | Page: 7/10                        |
| <b>Version</b>      | 1.01                                   | <b>Date of issue</b> | 2021 April 1        | <b>Format</b> Japan               |
|                     | <b>Date of previous issue</b>          | 2021 February 25.    | Build 6.0.7 (Japan) | <b>Language</b> ENGLISH (ENGLISH) |

## 14. Transport information

|                            | IMDG           | IATA           |
|----------------------------|----------------|----------------|
| UN number                  | Not regulated. | Not regulated. |
| UN proper shipping name    | -              | -              |
| Transport hazard class(es) | -              | -              |
| Packing group              | -              | -              |
| Environmental hazards      | No.            | No.            |
| Additional information     | -              | -              |

Special precautions for user Not available.

[Transport in bulk according to IMO instruments](#)

Not available.

## 15. Regulatory information

[Fire Service Law](#)

| Category    | Substance name/Type | Danger category | Signal word                | Designated quantity |
|-------------|---------------------|-----------------|----------------------------|---------------------|
| Category IV | Class IV petroleum  | III             | Flammable - Keep Fire Away | 6000 L              |

[ISHL](#)

[Label requirements](#)

| Ingredient name   | Name on list | CAS no.    | Conc. | Status | Reference number |
|---|--------------|------------|-------|--------|------------------|
| Distillates (petroleum), hydrotreated heavy paraffinic    | Mineral oil  | 64742-54-7 | ≤3.0  | Listed | 168              |
| Distillates (petroleum), hydrotreated light paraffinic    | Mineral oil  | 64742-55-8 | ≤3.0  | Listed | 168              |
| Distillates (petroleum), solvent-dewaxed light paraffinic | Mineral oil  | 64742-56-9 | ≤3.0  | Listed | 168              |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | Mineral oil  | 64742-65-0 | ≤3.0  | Listed | 168              |

[Chemicals requiring notification](#)

|                     |  |                      |                     |                                   |
|---------------------|--|----------------------|---------------------|-----------------------------------|
| <b>Product name</b> | Castrol Transmax Axle Long Life 75W-90 | <b>Product code</b>  | 469698-DE01         | Page: 8/10                        |
| <b>Version</b>      | 1.01                                   | <b>Date of issue</b> | 2021 April 1        | <b>Format</b> Japan               |
|                     | <b>Date of previous issue</b>          | 2021 February 25.    | Build 6.0.7 (Japan) | <b>Language</b> ENGLISH (ENGLISH) |



## 15. Regulatory information

| Ingredient name   | Name on list | CAS no.    | Conc. | Status | Reference number |
|---|--------------|------------|-------|--------|------------------|
| Distillates (petroleum), hydrotreated heavy paraffinic    | Mineral oil  | 64742-54-7 | ≤3.0  | Listed | 168              |
| Distillates (petroleum), hydrotreated light paraffinic    | Mineral oil  | 64742-55-8 | ≤3.0  | Listed | 168              |
| Distillates (petroleum), solvent-dewaxed light paraffinic | Mineral oil  | 64742-56-9 | ≤3.0  | Listed | 168              |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | Mineral oil  | 64742-65-0 | ≤3.0  | Listed | 168              |

### Pollutant Release and Transfer Registers (PRTR)

Not applicable.

This SDS is updated according to amended PRTR Law.

### Other regulations

|   |   |
|---|---|
| <a href="#">Australia inventory (AICS)</a>                  | All components are listed or exempted.  |
| <a href="#">Canada inventory</a>                            | All components are listed or exempted.  |
| <a href="#">China inventory (IECSC)</a>                     | All components are listed or exempted.  |
| <a href="#">Japan inventory (ENCS)</a>                      | All components are listed or exempted.  |
| <a href="#">Korea inventory (KECI)</a>                      | All components are listed or exempted.  |
| <a href="#">Philippines inventory (PICCS)</a>               | All components are listed or exempted.  |
| <a href="#">Taiwan Chemical Substances Inventory (TCSI)</a> | All components are listed or exempted.  |
| <a href="#">United States inventory (TSCA 8b)</a>           | All components are active or exempted.  |
| <a href="#">REACH Status</a>                                | The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH. |

## 16. Other information

### History

|  |                     |
|--|---------------------|
| <a href="#">Date of issue/Date of revision</a> | 2021 April 1.       |
| <a href="#">Date of previous issue</a>         | 2021 February 25.   |
| <a href="#">Prepared by</a>                    | Product Stewardship |

The Japan key to abbreviations is as follows:

GHS = Global Harmonized System  
CAS Number = Chemical Abstracts Service Registry Number  
ISHL = Industrial Safety and Health Law  
OSHL = Occupational Safety and Health Law  
PRTR = Law Concerning Reporting of the Release into the Environment of Specific Chemical Substances and Promoting Improvements in Their Management  
ENCS = Existing and New Chemical Substances  
METI = Ministry of Economy, Trade and Industry  
OEL = Occupational Exposure Limit  
JSOH = Japan Society for Occupational Health  
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]  
TWA = Time weighted average

|                     |  |                      |                     |                                   |
|---------------------|--|----------------------|---------------------|-----------------------------------|
| <b>Product name</b> | Castrol Transmax Axle Long Life 75W-90 | <b>Product code</b>  | 469698-DE01         | Page: 9/10                        |
| <b>Version</b>      | 1.01                                   | <b>Date of issue</b> | 2021 April 1        | <b>Format</b> Japan               |
|                     | <b>Date of previous issue</b>          | 2021 February 25.    | Build 6.0.7 (Japan) | <b>Language</b> ENGLISH (ENGLISH) |

## 16. Other information

STEL = Short term exposure limit

IMDG = International Maritime Organization Rules, rules governing shipment of goods by water.

IATA = International Air Transport Association, the organization

UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods.

Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

### [Procedure used to derive the classification](#)

| Classification  | Justification |
|-----------------|---------------|
| Not classified. |               |

 **Indicates information that has changed from previously issued version.**

### [Notice to reader](#)

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

|                     |  |                               |                     |                         |
|---------------------|--|-------------------------------|---------------------|-------------------------|
| <b>Product name</b> | Castrol Transmax Axle Long Life 75W-90 | <b>Product code</b>           | 469698-DE01         | Page: 10/10             |
| <b>Version</b>      | 1.01                                   | <b>Date of issue</b>          | 2021 April 1        | <b>Format</b> Japan     |
|                     |  | <b>Date of previous issue</b> | 2021 February 25.   | <b>Language</b> ENGLISH |
|                     |  |                               | Build 6.0.7 (Japan) | <b>(ENGLISH)</b>        |