

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name	Castrol Transmax Axle EPX 85W-90
Product code	469696-DE04
SDS #	469696
Product type	Liquid.

1.2 Relevant identified uses of the substance or mixture and uses advised against

PW: Widespread use by professional workers PC24: Lubricants, greases, release products
C: Consumer use PC24: Lubricants, greases, release products

**Use of the substance/
mixture** Automotive gear lubricant
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

1.3 Details of the supplier of the safety data sheet

Supplier	Castrol Holdings Europe B.V., d'Arcyweg 76, 3198NA Europoort Rotterdam
	Castrol CEE sp z.o.o, Ul. Grzybowska 62, 00 844 Warszawa
	+48 (0)800 121 4817
E-mail address	MSDSadvice@bp.com

1.4 Emergency telephone number

EMERGENCY TELEPHONE NUMBER	112 Carechem: +44 (0) 1235 239 670 (24/7)
Slovakia Poison Center	NTIC (Národní toxikologické centrum) +421 2 54 77 41 66 (24 hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements

Signal word	No signal word.
Hazard statements	No known significant effects or critical hazards.
Precautionary statements	
Prevention	Not applicable.
Response	Not applicable.
Storage	Not applicable.
Disposal	Not applicable.
Hazardous ingredients	Not applicable.
Supplemental label elements	<input checked="" type="checkbox"/> Contains Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl. May produce an allergic reaction. Safety data sheet available on request.

EU Regulation (EC) No. 1907/2006 (REACH)

Product name Castrol Transmax Axle EPX 85W-90	Product code 469696-DE04	Page: 1/13
Version 4	Date of issue 28 March 2025	Format Slovakia
Date of previous issue 23 August 2023.		Language ENGLISH
		(Slovakia)

SECTION 2: Hazards identification

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings Not applicable.

Tactile warning of danger Not applicable.

2.3 Other hazards

Results of PBT and vPvB assessment Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification Defatting to the skin.

Experimental data on one or more of the components has been used to determine all or part of the hazard classification of this product.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product definition Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Distillates (petroleum), solvent-dewaxed heavy paraffinic	REACH #: 01-2119471299-27 EC: 265-169-7 CAS: 64742-65-0 Index: 649-474-00-6	≥25 - ≤50	Not classified.	-	[2]
Residual oils (petroleum), solvent-dewaxed	REACH #: 01-2119480472-38 EC: 265-166-0 CAS: 64742-62-7 Index: 649-471-00-X	≥10 - ≤25	Not classified.	-	[2]
Residual oils (petroleum), hydrotreated	REACH #: 01-2119489287-22 EC: 265-160-8 CAS: 64742-57-0 Index: 649-470-00-4	≥10 - ≤25	Not classified.	-	[2]
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	REACH #: 01-2119493620-38 EC: 931-384-6 CAS: -	≤3	Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 2, H411	ATE [Oral] = 500 mg/kg Eye Irrit. 2, H319: C ≥ 50% Skin Sens. 1B, H317: C ≥ 9.39%	[1]

See Section 16 for the full text of the H statements declared above.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

Product name Castrol Transmax Axle EPX 85W-90

Product code 469696-DE04

Page: 2/13

Version 4 **Date of issue** 28 March 2025

Format Slovakia

Language ENGLISH

Date of previous issue 23 August 2023.

(Slovakia)

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Potential acute health effects

Inhalation	Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.
Ingestion	No known significant effects or critical hazards.
Skin contact	Defatting to the skin. May cause skin dryness and irritation. Product not classified for sensitisation. Based on data available for this or related materials.
Eye contact	Not classified as an eye irritant. Based on data available for this or related materials.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects.
---------------------------	---

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet. The use of a water jet may cause the fire to spread by splashing the burning product.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	<input checked="" type="checkbox"/> Combustion products may include the following: carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide)

5.3 Advice for firefighters

Special precautions for fire-fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Put on appropriate personal protective equipment.
------------------------------------	--

Product name Castrol Transmax Axle EPX 85W-90	Product code 469696-DE04	Page: 3/13
Version 4	Date of issue 28 March 2025	Format Slovakia
Date of previous issue 23 August 2023.		Language ENGLISH
	(Slovakia)	

SECTION 6: Accidental release measures

For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	See Section 1 for emergency contact information. See Section 5 for firefighting measures. See Section 8 for information on appropriate personal protective equipment. See Section 12 for environmental precautions. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling	
Protective measures	Put on appropriate personal protective equipment.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/containers designed for use with this product. Do not store in unlabelled containers.
Not suitable	Prolonged exposure to elevated temperature
7.3 Specific end use(s)	
Recommendations	See section 1.2 and Exposure scenarios in annex, if applicable.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
☑ Distillates (petroleum), solvent-dewaxed heavy paraffinic	Government regulation SR c. 355/2006 (Slovakia). [oleje minerálne] TWA: 1 mg/m ³ , (Mineral oils) 8 hours. Issued/Revised: 6/2024 Form: liquid aerosol, fumes TWA: 5 ppm, (Mineral oils) 8 hours. Issued/Revised: 6/2024 Form: liquid aerosol, fumes STEL: 3 mg/m ³ , (Mineral oils) 15 minutes. Issued/Revised: 6/2024 Form: liquid aerosol, fumes STEL: 15 ppm, (Mineral oils) 15 minutes. Issued/Revised: 6/2024 Form: liquid aerosol, fumes
Residual oils (petroleum), solvent-dewaxed	Government regulation SR c. 355/2006 (Slovakia). [oleje minerálne] TWA: 1 mg/m ³ , (Mineral oils) 8 hours. Issued/Revised: 6/2024 Form: liquid aerosol, fumes TWA: 5 ppm, (Mineral oils) 8 hours. Issued/Revised: 6/2024 Form: liquid aerosol, fumes STEL: 3 mg/m ³ , (Mineral oils) 15 minutes. Issued/Revised: 6/2024 Form: liquid aerosol, fumes STEL: 15 ppm, (Mineral oils) 15 minutes. Issued/Revised: 6/2024 Form: liquid aerosol, fumes

Product name Castrol Transmax Axle EPX 85W-90	Product code 469696-DE04	Page: 4/13
Version 4	Date of issue 28 March 2025	Format Slovakia
Date of previous issue 23 August 2023.		Language ENGLISH
	(Slovakia)	

SECTION 8: Exposure controls/personal protection

Residual oils (petroleum), hydrotreated

Government regulation SR c. 355/2006 (Slovakia). [oleje minerálne]

TWA: 1 mg/m³, (Mineral oils) 8 hours. Issued/Revised: 6/2024 Form: liquid aerosol, fumes

TWA: 5 ppm, (Mineral oils) 8 hours. Issued/Revised: 6/2024 Form: liquid aerosol, fumes

STEL: 3 mg/m³, (Mineral oils) 15 minutes. Issued/Revised: 6/2024 Form: liquid aerosol, fumes

STEL: 15 ppm, (Mineral oils) 15 minutes. Issued/Revised: 6/2024 Form: liquid aerosol, fumes

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Recommended monitoring procedures

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Biological exposure indices

Product/ingredient name

Exposure indices

No exposure indices known.

Derived No Effect Level

No DNELs/DMELs available.

Predicted No Effect Concentration

No PNECs available

8.2 Exposure controls

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Eye/face protection

Safety glasses with side shields.

Skin protection

Hand protection

General Information:

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile gloves.

Product name Castrol Transmax Axle EPX 85W-90	Product code 469696-DE04	Page: 5/13
Version 4	Date of issue 28 March 2025	Format Slovakia
Date of previous issue 23 August 2023.		Language ENGLISH
	(Slovakia)	

SECTION 8: Exposure controls/personal protection

Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained.

If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.

It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

Glove Thickness:

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.

- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

Skin and body

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Refer to standards:

Respiratory protection: EN 529
Gloves: EN 420, EN 374
Eye protection: EN 166
Filtering half-mask: EN 149
Filtering half-mask with valve: EN 405
Half-mask: EN 140 plus filter
Full-face mask: EN 136 plus filter
Particulate filters: EN 143
Gas/combined filters: EN 14387

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Physical state	Liquid.
Colour	Amber.
Odour	Not available.
Odour threshold	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flammability	Not available.
Lower and upper explosion limit	Not available.
Flash point	Open cup: >180°C (>356°F) [Cleveland]
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
pH	Not applicable.
Kinematic viscosity	Kinematic: 188.7 mm ² /s (188.7 cSt) at 40°C Kinematic: 16.5 to 18 mm ² /s (16.5 to 18 cSt) at 100°C

Solubility

Media	Result
water	Not soluble

Partition coefficient n-octanol/water (log value) Not applicable.

Vapour pressure  0.01 kPa

Density and/or Relative density <1000 kg/m³ (<1 g/cm³) at 15°C

Relative vapour density Not available.

Particle characteristics

Median particle size Not applicable.

9.2 Other information

Evaporation rate Not available.

Explosive properties Not available.

Oxidising properties Not available.

Pour point -30 °C

SECTION 10: Stability and reactivity

10.1 Reactivity No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.

10.2 Chemical stability The product is stable.

10.3 Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions will not occur.
Under normal conditions of storage and use, hazardous polymerisation will not occur.

10.4 Conditions to avoid Avoid all possible sources of ignition (spark or flame).

10.5 Incompatible materials Reactive or incompatible with the following materials: oxidising materials.

10.6 Hazardous decomposition products Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result / Route	Test authority / Number	Species	Dose	Exposure	Remarks
Amines, C12-14-alkyl, reaction products with hexanol, phosphorus oxide (P2O5), phosphorus sulphide (P2S5) and propylene oxide	LD50 Oral	OECD 401	Rat	2000 mg/kg	-	-

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Castrol Transmax Axle EPX 85W-90 Amines, C12-14-alkyl, reaction products with hexanol, phosphorus oxide (P2O5), phosphorus sulphide (P2S5) and propylene oxide	38703.7500	N/A	N/A	N/A	N/A

Irritation/Corrosion

Product/ingredient name	Test authority / Test number	Species	Route / Result	Test concentration	Remarks
Amines, C12-14-alkyl, reaction products with hexanol, phosphorus oxide (P2O5), phosphorus sulphide (P2S5) and propylene oxide	FHSA 16CFR1500	Rabbit	Eyes - Irritant	-	<50% Non-irritating to the eyes.
	OECD 404	Rabbit	Skin - Non-irritant to skin.	-	-

Sensitiser

Product/ingredient name	Route	Test authority / Test number	Species	Result	Remarks
Amines, C12-14-alkyl, reaction products with hexanol, phosphorus oxide (P2O5), phosphorus sulphide (P2S5) and propylene oxide	skin	OECD 429	Mouse	Sensitising	<9.39% Non-sensitiser to skin.

GERM CELL MUTAGENICITY

Product/ingredient name	Test authority / Test number	Cell	Type	Result	Remarks
Amines, C12-14-alkyl, reaction products with hexanol, phosphorus oxide (P2O5), phosphorus sulphide (P2S5) and propylene oxide	OECD 471	-	Experiment: In vitro	Negative	-
	OECD 476	-	Experiment: In vitro	Negative	-
	OECD 474	Cell: Somatic	Experiment: In vitro	Negative	-

Carcinogenicity

Not available.

Product name Castrol Transmax Axle EPX 85W-90	Product code 469696-DE04	Page: 8/13
Version 4	Date of issue 28 March 2025	Format Slovakia
Date of previous issue 23 August 2023.		Language ENGLISH
	(Slovakia)	

SECTION 11: Toxicological information

Reproductive toxicity

Product/ ingredient name	Test authority / Test number	Species	Route	Exposure	Developmental	Maternal toxicity	Fertility	Remarks
Amines, C12-14-alkyl, reaction products with hexanol, phosphorus oxide (P2O5), phosphorus sulphide (P2S5) and propylene oxide	OECD 421	Rat	Oral	-	Negative	Positive	Negative	-

Aspiration hazard

Product/ingredient name	Result
Not available.	

Conclusion/Summary

Not classified. Based on available data, the classification criteria are not met.

Conclusion/Summary

Not available.

Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Inhalation

Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.

Ingestion

No known significant effects or critical hazards.

Skin contact

Defatting to the skin. May cause skin dryness and irritation. Product not classified for sensitisation. Based on data available for this or related materials.

Eye contact

Not classified as an eye irritant. Based on data available for this or related materials.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation

May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.

Ingestion

No specific data.

Skin contact

Adverse symptoms may include the following:
irritation
dryness
cracking

Eye contact

No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation

Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

Ingestion

Ingestion of large quantities may cause nausea and diarrhoea.

Skin contact

Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

Eye contact

Potential risk of transient stinging or redness if accidental eye contact occurs.

Potential chronic health effects

General

No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.

Mutagenicity

No known significant effects or critical hazards.

Developmental effects

No known significant effects or critical hazards.

Fertility effects

No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

Product name Castrol Transmax Axle EPX 85W-90	Product code 469696-DE04	Page: 9/13
Version 4	Date of issue 28 March 2025	Format Slovakia
Date of previous issue 23 August 2023.		Language ENGLISH
	(Slovakia)	

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Test authority / Test number	Species	Type / Result	Exposure	Effects	Remarks
Amines, C12-14-alkyl, reaction products with hexanol, phosphorus oxide (P2O5), phosphorus sulphide (P2S5) and propylene oxide	OECD 202	Daphnia	Acute EC50 91.4 mg/l	48 hours	-	-
	OECD 201	Algae	Acute ErC50 6.4 mg/l	96 hours	-	-
	OECD 203	Fish	Acute LC50 24 mg/l	96 hours	-	-
	OECD 211	Daphnia	Chronic EC50 0.66 mg/l	21 days	-	-
	OECD 201	Algae	Chronic NOEC 1.7 mg/l	96 hours	-	-
	OECD 211	Daphnia	Chronic NOEC 0.12 mg/l	21 days	-	-

Environmental hazards

Not classified as dangerous

Product not classified for environmental effects. Based on data available for this or related materials.

12.2 Persistence and degradability

Expected to be biodegradable.

Product/ingredient name	Test authority / Test number	Result - Exposure	Remarks
Amines, C12-14-alkyl, reaction products with hexanol, phosphorus oxide (P2O5), phosphorus sulphide (P2S5) and propylene oxide	OECD 301B	7.4 % - Not readily - 28 days	-

12.3 Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc})

Not available.

Mobility

Spillages may penetrate the soil causing ground water contamination.

12.5 Results of PBT and vPvB assessment

Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.

12.6 Endocrine disrupting properties

Not available.

Other ecological information

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Hazardous waste

Yes.

European waste catalogue (EWC)

Product name Castrol Transmax Axle EPX 85W-90	Product code 469696-DE04	Page: 10/13
Version 4	Date of issue 28 March 2025	Format Slovakia
Date of previous issue 23 August 2023.		Language ENGLISH
	(Slovakia)	

SECTION 13: Disposal considerations

Waste code	Waste designation
13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

Packaging

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Special precautions

This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

References

Commission 2014/955/EU
Directive 2008/98/EC

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

14.6 Special precautions for user Not available.

14.7 Maritime transport in bulk according to IMO instruments Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
benzene	<0.0001	5 72
toluene	<0.0001	48

Labelling Not applicable.

Other regulations

REACH Status

The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

Product name Castrol Transmax Axle EPX 85W-90	Product code 469696-DE04	Page: 11/13
Version 4	Date of issue 28 March 2025	Format Slovakia
Date of previous issue 23 August 2023.		Language ENGLISH
		(Slovakia)

SECTION 15: Regulatory information

United States inventory (TSCA 8b)	All components are active or exempted.
Australia inventory (AIC)	All components are listed or exempted.
Canada inventory	All components are listed or exempted.
China inventory (IECSC)	All components are listed or exempted.
Japan inventory (CSCL)	All components are listed or exempted.
Korea inventory (KECI)	All components are listed or exempted.
Philippines inventory (PICCS)	At least one component is not listed.
Taiwan Chemical Substances Inventory (TCSI)	All components are listed or exempted.

[Explosive precursors](#) Not applicable.

[Ozone depleting substances \(1005/2009/EU\)](#)

Not listed.

[Prior Informed Consent \(PIC\) \(649/2012/EU\)](#)

Not listed.

[Persistent Organic Pollutants](#)

Not listed.

[EU - Water framework directive - Priority substances](#)

None of the components are listed.

[Seveso Directive](#)

This product is not controlled under the Seveso Directive.

[15.2 Chemical safety assessment](#)

A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

SECTION 16: Other information

Abbreviations and acronyms	<p>ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway</p> <p>ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road</p> <p>ATE = Acute Toxicity Estimate</p> <p>BCF = Bioconcentration Factor</p> <p>CAS = Chemical Abstracts Service</p> <p>CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]</p> <p>CSA = Chemical Safety Assessment</p> <p>CSR = Chemical Safety Report</p> <p>DMEL = Derived Minimal Effect Level</p> <p>DNEL = Derived No Effect Level</p> <p>EINECS = European Inventory of Existing Commercial chemical Substances</p> <p>ES = Exposure Scenario</p> <p>EUH statement = CLP-specific Hazard statement</p> <p>EWC = European Waste Catalogue</p> <p>GHS = Globally Harmonized System of Classification and Labelling of Chemicals</p> <p>IATA = International Air Transport Association</p> <p>IBC = Intermediate Bulk Container</p> <p>IMDG = International Maritime Dangerous Goods</p> <p>LogPow = logarithm of the octanol/water partition coefficient</p> <p>MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)</p> <p>OECD = Organisation for Economic Co-operation and Development</p> <p>PBT = Persistent, Bioaccumulative and Toxic</p> <p>PNEC = Predicted No Effect Concentration</p> <p>REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]</p> <p>RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail</p> <p>RRN = REACH Registration Number</p> <p>SADT = Self-Accelerating Decomposition Temperature</p> <p>SVHC = Substances of Very High Concern</p> <p>STOT-RE = Specific Target Organ Toxicity - Repeated Exposure</p> <p>STOT-SE = Specific Target Organ Toxicity - Single Exposure</p>
--	--

Product name Castrol Transmax Axle EPX 85W-90

Product code 469696-DE04

Page: 12/13

Version 4 **Date of issue** 28 March 2025

Format Slovakia

Language ENGLISH

Date of previous issue 23 August 2023.

(Slovakia)

SECTION 16: Other information

TWA = Time weighted average
 UN = United Nations
 UVCB = Complex hydrocarbon substance
 VOC = Volatile Organic Compound
 vPvB = Very Persistent and Very Bioaccumulative
 Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4/ RRN 01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN 01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN 01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN 01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN 01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8, 64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 / RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN 01-2119474889-13

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

Full text of abbreviated H statements

<input checked="" type="checkbox"/> H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

<input checked="" type="checkbox"/> Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Sens. 1B	SKIN SENSITISATION - Category 1B

History

Date of issue/ Date of revision	28/03/2025.
Date of previous issue	23/08/2023.
Prepared by	Product Stewardship

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.