

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Product name	Castrol Transmax ATF Z
Product code	469682-DE01
SDS #	469682
Product type	Liquid.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/ mixture	Transmission fluid For specific application advice see appropriate Technical Data Sheet or consult our company representative.
----------------------------------	---

1.3 Details of the supplier of the safety data sheet

Supplier	Castrol Holdings Europe B.V., d'Arcyweg 76, 3198NA Europoort Rotterdam Castrol Denmark A/S Kampmannsgade 2 1604 København Denmark +45 70 80 70 54
E-mail address	MSDSadvice@bp.com

1.4 Emergency telephone number

EMERGENCY TELEPHONE NUMBER	Carechem: +44 (0) 1235 239 670 (24/7)
-------------------------------	---------------------------------------

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Product definition	Mixture
--------------------	---------

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements

Signal word	No signal word.
Hazard statements	No known significant effects or critical hazards.
<u>Precautionary statements</u>	
Prevention	Not applicable.
Response	Not applicable.
Storage	Not applicable.
Disposal	Not applicable.
Hazardous ingredients	Not applicable.

Supplemental label elements	Safety data sheet available on request.
--------------------------------	---

EU Regulation (EC) No. 1907/2006 (REACH)

Product name	Castrol Transmax ATF Z	Product code	469682-DE01	Page:	1/15		
Version	8	Date of issue	10 July 2025	Format	Estonia	Language	ENGLISH
Date of previous issue	3 July 2024.			(Estonia)			

SECTION 2: Hazards identification

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Not applicable.
Special packaging requirements	
Containers to be fitted with child-resistant fastenings	Not applicable.
Tactile warning of danger	Not applicable.
2.3 Other hazards	
Results of PBT and vPvB assessment	Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	Defatting to the skin.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product definition Mixture
Synthetic base stock. Proprietary performance additives.

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Decene, homopolymer, hydrogenated	REACH #: 01-2119486452-34 EC: 500-183-1 CAS: 68037-01-4	≥25 - ≤50	Asp. Tox. 1, H304	-	[1]
Dec-1-ene, trimers, hydrogenated	REACH #: 01-2119486452-34 EC: 500-393-3 CAS: 157707-86-3	≥25 - ≤50	Asp. Tox. 1, H304	-	[1]
Dec-1-ene, trimers, hydrogenated	REACH #: 01-2119493949-12 EC: 500-393-3 CAS: 157707-86-3	≥25 - ≤50	Asp. Tox. 1, H304	-	[1]
1-Propene, polymer with ethene	CAS: 9010-79-1	≤10	Not classified.	-	[2]
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	REACH #: 01-2119491299-23 EC: 270-128-1 CAS: 68411-46-1	≤1	Repr. 2, H361f	-	[1]

See Section 16 for the full text of the H statements declared above.

Type
[1] Substance classified with a health or environmental hazard
[2] Substance with a workplace exposure limit
Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.
Inhalation	If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.

Product name	Castrol Transmax ATF Z	Product code	469682-DE01	Page:	2/15
Version	8	Date of issue	10 July 2025	Format	Estonia
Date of previous issue	3 July 2024.			Language	ENGLISH
					(Estonia)

SECTION 4: First aid measures

Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Potential acute health effects

Inhalation	Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Ingestion	No known significant effects or critical hazards.
Skin contact	Defatting to the skin. May cause skin dryness and irritation.
Eye contact	No known significant effects or critical hazards.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
---------------------------	---

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet. The use of a water jet may cause the fire to spread by splashing the burning product.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	Combustion products may include the following: carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide) nitrogen oxides (NO, NO ₂ etc.)

5.3 Advice for firefighters

Special precautions for fire-fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Put on appropriate personal protective equipment.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Product name Castrol Transmax ATF Z

Product code 469682-DE01

Page: 3/15

Version 8 **Date of issue** 10 July 2025

Format Estonia

Language ENGLISH

Date of previous issue 3 July 2024.

(Estonia)

SECTION 6: Accidental release measures

6.3 Methods and material for containment and cleaning up

Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

See Section 1 for emergency contact information.
See Section 5 for firefighting measures.
See Section 8 for information on appropriate personal protective equipment.
See Section 12 for environmental precautions.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Not suitable	Prolonged exposure to elevated temperature
--------------	--

7.3 Specific end use(s)

Recommendations	See section 1.2 and Exposure scenarios in annex, if applicable.
-----------------	---

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
1-Propene, polymer with ethene	Occupational exposure limits, Regulation No. 293 (Estonia). [plastmassitölm] TWA: 3 mg/m³ 8 hours. Issued/Revised: 8/2018 Form: Total dust
Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.	
Recommended monitoring procedures	Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Biological exposure indices

Product/ingredient name	Exposure indices
No exposure indices known.	

Derived No Effect Level

No DNELs/DMELs available.

Predicted No Effect Concentration

No PNECs available

8.2 Exposure controls

Product name		Castrol Transmax ATF Z		Product code		469682-DE01		Page: 4/15							
Version		8		Date of issue		10 July 2025		Format		Estonia		Language		ENGLISH	
Date of previous issue		3 July 2024.								(Estonia)					

SECTION 8: Exposure controls/personal protection

Appropriate engineering controls	Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.
Eye/face protection	Safety glasses with side shields.
Skin protection	
Hand protection	General Information: Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures). Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions. Recommended: Nitrile gloves. Breakthrough time: Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows: Continuous contact: Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained. If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to. Short-term / splash protection: Recommended breakthrough times as above. It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed. Glove Thickness: For general applications, we recommend gloves with a thickness typically greater than 0.35 mm. It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

SECTION 8: Exposure controls/personal protection

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

Skin and body	Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
Refer to standards:	Respiratory protection: EN 529 Gloves: EN 420, EN 374 Eye protection: EN 166 Filtering half-mask: EN 149 Filtering half-mask with valve: EN 405 Half-mask: EN 140 plus filter Full-face mask: EN 136 plus filter Particulate filters: EN 143 Gas/combined filters: EN 14387
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Physical state	Liquid.																
Colour	Brown.																
Odour	Not available.																
Odour threshold	Not available.																
Melting point/freezing point	Not available.																
Initial boiling point and boiling range	Not available.																
Flammability	Not available.																
Lower and upper explosion limit	Not available.																
Flash point	Open cup: >220°C (>428°F) [Cleveland]																
Auto-ignition temperature	<table><tr><th>Ingredient name</th><th>°C</th><th>°F</th><th>Method</th></tr><tr><td>Decene, homopolymer, hydrogenated</td><td>343 to 369</td><td>649.4 to 696.2</td><td>ASTM D 2159</td></tr><tr><td>Dec-1-ene, homopolymer, hydrogenated</td><td>343 to 369</td><td>649.4 to 696.2</td><td>ASTM D 2159</td></tr><tr><td>Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated</td><td>343 to 369</td><td>649.4 to 696.2</td><td>ASTM D 2159</td></tr></table>	Ingredient name	°C	°F	Method	 Decene, homopolymer, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159	Dec-1-ene, homopolymer, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159	Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159
Ingredient name	°C	°F	Method														
 Decene, homopolymer, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159														
Dec-1-ene, homopolymer, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159														
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159														
Decomposition temperature	Not available.																
pH	Not applicable.																
Kinematic viscosity	Kinematic: 37.8 mm²/s (37.8 cSt) at 40°C Kinematic: 7.5 mm²/s (7.5 cSt) at 100°C																
Solubility																	

SECTION 9: Physical and chemical properties

	Media	Result																																																				
	water	Not soluble																																																				
Partition coefficient n-octanol/ water (log value)	Not applicable.																																																					
Vapour pressure	<table><tr><th rowspan="2">Ingredient name</th><th colspan="3">Vapour Pressure at 20°C</th><th colspan="3">Vapour pressure at 50°C</th></tr><tr><th>mm Hg</th><th>kPa</th><th>Method</th><th>mm Hg</th><th>kPa</th><th>Method</th></tr><tr><td>Decene, homopolymer, hydrogenated</td><td><0.0041</td><td><0.00055</td><td>ASTM E 1194-87</td><td></td><td></td><td></td></tr><tr><td>Dec-1-ene, homopolymer, hydrogenated</td><td><0.0041</td><td><0.00055</td><td>ASTM E 1194-87</td><td></td><td></td><td></td></tr><tr><td>Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated</td><td><0.0041</td><td><0.00055</td><td>ASTM E 1194-87</td><td></td><td></td><td></td></tr><tr><td>diisodecyl azelate</td><td>0</td><td>0</td><td></td><td></td><td></td><td></td></tr><tr><td>Distillates (petroleum), hydrotreated heavy paraffinic</td><td><0.07501</td><td><0.01</td><td>ASTM D 5191</td><td></td><td></td><td></td></tr></table>						Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C			mm Hg	kPa	Method	mm Hg	kPa	Method	Decene, homopolymer, hydrogenated	<0.0041	<0.00055	ASTM E 1194-87				Dec-1-ene, homopolymer, hydrogenated	<0.0041	<0.00055	ASTM E 1194-87				Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	<0.0041	<0.00055	ASTM E 1194-87				diisodecyl azelate	0	0					Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191			
Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C																																																		
	mm Hg	kPa	Method	mm Hg	kPa	Method																																																
Decene, homopolymer, hydrogenated	<0.0041	<0.00055	ASTM E 1194-87																																																			
Dec-1-ene, homopolymer, hydrogenated	<0.0041	<0.00055	ASTM E 1194-87																																																			
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	<0.0041	<0.00055	ASTM E 1194-87																																																			
diisodecyl azelate	0	0																																																				
Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191																																																			
Density and/or Relative density	<1000 kg/m³ (<1 g/cm³) at 15°C																																																					
Relative vapour density	Not available.																																																					
Particle characteristics																																																						
Median particle size	Not applicable.																																																					
9.2 Other information																																																						
Evaporation rate	Not available.																																																					
Explosive properties	Not available.																																																					
Oxidising properties	Not available.																																																					
Pour point	-66 °C																																																					

SECTION 10: Stability and reactivity

10.1 Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
10.2 Chemical stability	The product is stable.
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
10.4 Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
10.5 Incompatible materials	Reactive or incompatible with the following materials: oxidising materials.
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result / Route	Test authority / Number	Species	Dose	Exposure	Remarks
Decene, homopolymer, hydrogenated	LD50 Dermal	OECD 402	Rat	>2000 mg/kg	-	Based on studies with similar substances.
	LD50 Oral	OECD 423	Rat	>5000 mg/kg	-	Based on studies with similar

Product name	Castrol Transmax ATF Z	Product code	469682-DE01	Page:	7/15
Version	8	Date of issue	10 July 2025	Format	Estonia
Date of previous issue	3 July 2024.			Language	ENGLISH
			(Estonia)		

SECTION 11: Toxicological information

								substances.
Dec-1-ene, homopolymer, hydrogenated	LD50 Inhalation Dusts and mists	OECD	403	Rat	>5.2 mg/l	4 hours	-	
	LD50 Dermal	OECD	402	Rat	>2000 mg/kg	-		Based on studies with similar substances.
	LD50 Oral	OECD	423	Rat	>5000 mg/kg	-		Based on studies with similar substances.
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	LD50 Inhalation Dusts and mists	OECD	403	Rat	>5.2 mg/l	4 hours	-	
	LD50 Dermal	OECD	402	Rat	>2000 mg/kg	-		Based on studies with similar substances.
	LD50 Oral	OECD	423	Rat	>5000 mg/kg	-		Based on studies with similar substances.
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	LD50 Inhalation Dusts and mists	OECD	403	Rat	>5.2 mg/l	4 hours	-	
	LC50 Dermal	OECD	402	Rat	>2000 mg/kg	-		-
	LC50 Oral	OECD	401	Rat	>5000 mg/kg	-		-

Acute toxicity estimates

Not available.

Irritation/Corrosion

Product/ingredient name	Test authority / Test number		Species	Route / Result	Test concentration	Remarks
Decene, homopolymer, hydrogenated	OECD	405	Rabbit	Eyes - Non-irritating to the eyes.	-	-
	OECD	404	Rabbit	Skin - Non-irritant to skin.	-	-
Dec-1-ene, homopolymer, hydrogenated	OECD	405	Rabbit	Eyes - Non-irritating to the eyes.	-	-
	OECD	404	Rabbit	Skin - Non-irritant to skin.	-	-
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	OECD	405	Rabbit	Eyes - Non-irritating to the eyes.	-	Based on studies with similar substances.
	OECD	404	Rabbit	Skin - Non-irritant to skin.	-	-
Benzenamine, N-phenyl-,	OECD	405	Rabbit	Eyes - Not irritant	-	-

SECTION 11: Toxicological information

reaction products with
2,4,4-trimethylpentene

OECD	404	Rabbit	Skin - Slightly irritating to the skin.	-	-
------	-----	--------	---	---	---

Sensitiser

Product/ingredient name	Route	Test authority / Test number		Species	Result	Remarks
Decene, homopolymer, hydrogenated	skin	OECD	406	Guinea pig	Not sensitising	-
Dec-1-ene, homopolymer, hydrogenated	skin	OECD	406	Guinea pig	Not sensitising	-
Dec-1-ene, homopolymer, hydrogenated Dec- 1-ene, oligomers, hydrogenated	skin	OECD	406	Guinea pig	Not sensitising	-
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	skin	OECD	406	Guinea pig	Not sensitising	-

GERM CELL MUTAGENICITY

Product/ingredient name	Test authority / Test number	Cell		Type	Result	Remarks
Decene, homopolymer, hydrogenated	OECD 471 Bacterial Reverse Mutation Test	-	Experiment: In vitro	Subject: Bacteria	Negative	-
	OECD 473 In vitro Mammalian Chromosomal Aberration Test	-	Experiment: In vitro	Subject: Mammal - species unspecified	Negative	Based on studies with similar substances.
	OECD 474 Mammalian Erythrocyte Micronucleus Test	-	Experiment: In vivo	Subject: Mammal - species unspecified	Negative	Based on studies with similar substances.
Dec-1-ene, homopolymer, hydrogenated	OECD 471 Bacterial Reverse Mutation Test	-	Experiment: In vitro	Subject: Bacteria	Negative	-
	OECD 473 In vitro Mammalian Chromosomal Aberration Test	-	Experiment: In vitro	Subject: Mammal - species unspecified	Negative	Based on studies with similar substances.
	OECD 474 Mammalian Erythrocyte Micronucleus Test	-	Experiment: In vivo	Subject: Mammal - species unspecified	Negative	Based on studies with similar substances.
Dec-1-ene, homopolymer, hydrogenated Dec- 1-ene, oligomers, hydrogenated	OECD 471 Bacterial Reverse Mutation Test	-	Experiment: In vitro	Subject: Bacteria	Negative	Based on studies with similar substances.
	OECD 473 In vitro Mammalian Chromosomal Aberration Test	-	Experiment: In vitro	Subject: Mammal - species unspecified	Negative	Based on studies with similar substances.

SECTION 11: Toxicological information

	OECD 474 Mammalian Erythrocyte Micronucleus Test	-	Experiment: In vivo	Subject: Mammal - species unspecified	Negative	Based on studies with similar substances.
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	OECD 471	-	Experiment: In vitro	Subject: Bacteria	Negative	-
	OECD 487	-	Experiment: In vitro	Subject: Mammalian- Animal	Negative	-
	OECD 476	-	Experiment: In vitro	Subject: Mammalian- Animal	Negative	-

Carcinogenicity

Not available.

Reproductive toxicity

Product/ ingredient name	Test authority / Test number	Species	Route	Exposure	Developmental	Maternal toxicity	Fertility	Remarks
Decene, homopolymer, hydrogenated	OECD 415	Rat	Oral	-	Negative	Negative	Negative	-
Dec-1-ene, homopolymer, hydrogenated	OECD 415	Rat	Oral	-	Negative	Negative	Negative	-
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	OECD 415	Rat	Oral	-	Negative	Negative	Negative	-
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	OECD 443	Rat	Oral	-	Negative	Negative	Positive	-

Aspiration hazard

Product/ingredient name	Result
Decene, homopolymer, hydrogenated	ASPIRATION HAZARD - Category 1
Dec-1-ene, homopolymer, hydrogenated	ASPIRATION HAZARD - Category 1
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	ASPIRATION HAZARD - Category 1

Conclusion/Summary

Conclusion/Summary

Information on likely routes of exposure

Potential acute health effects

Inhalation

Ingestion

Skin contact

Eye contact

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation

Ingestion

Not classified. Based on available data, the classification criteria are not met.

Not available.

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

No known significant effects or critical hazards.

Defatting to the skin. May cause skin dryness and irritation.

No known significant effects or critical hazards.

May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.

No specific data.

SECTION 11: Toxicological information

Skin contact	Adverse symptoms may include the following: irritation dryness cracking
Eye contact	No specific data.
Delayed and immediate effects as well as chronic effects from short and long-term exposure	
Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.
Potential chronic health effects	
General	No known significant effects or critical hazards.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Test authority / Test number	Species	Type / Result	Exposure	Effects	Remarks
Decene, homopolymer, hydrogenated	Equivalent to OECD	201	Algae	Acute EL50 >1000 mg/l	72 hours	-
	OECD	202	Daphnia	Acute EL50 >1000 mg/l	48 hours	-
	OECD	203	Fish	Acute LL50 >1000 mg/l	96 hours	-
	OECD	211	Daphnia	Chronic NOELR 125 mg/l	21 days	-
Dec-1-ene, homopolymer, hydrogenated	Equivalent to OECD	201	Algae	Acute EL50 >1000 mg/l	72 hours	-
	OECD	202	Daphnia	Acute EL50 >1000 mg/l	48 hours	-
	OECD	203	Fish	Acute LL50 >1000 mg/l	96 hours	-
	OECD	211	Daphnia	Chronic NOELR 125 mg/l	21 days	-
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	OECD	201	Algae	Acute EL50 >1000 mg/l	72 hours	-
	OECD	202	Daphnia	Acute EL50 >1000 mg/l	48 hours	-
	OECD	203	Fish	Acute LL50 >1000 mg/l	96 hours	-
	OECD	211	Daphnia	Chronic NOELR 125 mg/l	21 days	-
Benzenamine, N-phenyl-,	OECD	202	Daphnia	Acute EC50 51 mg/l	48 hours	-

SECTION 12: Ecological information

reaction products with 2,4,4-trimethylpentene								
	OECD	201	Algae	Acute ErC50 >100 mg/l	72 hours	-	-	
	OECD	203	Fish	Acute LC50 >100 mg/l	96 hours	-	-	
	OECD	211	Daphnia	Chronic EC10 1.69 mg/l	21 days	-	-	
	OECD	201	Algae	Chronic NOEC ≥10 mg/l	72 hours	-	-	

Environmental hazards Not classified as dangerous

12.2 Persistence and degradability

Expected to be biodegradable.

Product/ingredient name	Test authority / Test number	Result - Exposure	Remarks
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	OECD 301B	1 % - 28 days	-

12.3 Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	LogP _{ow}	BCF	Potential
Dec-1-ene, homopolymer, hydrogenated	>10	-	High
Dec-1-ene, trimers, hydrogenated	>6.5	-	High
Dec-1-ene, trimers, hydrogenated	>10	-	High
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	5.1	-	High

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) Not available.

Mobility Spillages may penetrate the soil causing ground water contamination.

12.5 Results of PBT and vPvB assessment

Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.

12.6 Endocrine disrupting properties Not available.

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

12.7 Other adverse effects No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Hazardous waste Yes.

European waste catalogue (EWC)

Waste code	Waste designation
13 02 06*	synthetic engine, gear and lubricating oils

Product name	Castrol Transmax ATF Z	Product code	469682-DE01	Page:	12/15
Version	8	Date of issue	10 July 2025	Format	Estonia
Date of previous issue	3 July 2024.			Language	ENGLISH
					(Estonia)

SECTION 13: Disposal considerations

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.	
Packaging	
Methods of disposal	Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.
Special precautions	This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
References	Commission 2014/955/EU Directive 2008/98/EC

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

14.6 Special precautions for user Not available.

14.7 Maritime transport in bulk according to IMO instruments Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)
Annex XIV - List of substances subject to authorisation

Annex XIV
None of the components are listed.
Substances of very high concern
None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles
No listed substance

Labelling	Not applicable.
Other regulations	
REACH Status	The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.
United States inventory (TSCA 8b)	All components are active or exempted.
Australia inventory (AIIIC)	All components are listed or exempted.
Canada inventory	All components are listed or exempted.
China inventory (IECSC)	All components are listed or exempted.
Japan inventory (CSCL)	At least one component is not listed.

Product name	Castrol Transmax ATF Z	Product code	469682-DE01	Page:	13/15
Version	8	Date of issue	10 July 2025	Format	Estonia
				Language	ENGLISH
Date of previous issue	3 July 2024.				(Estonia)

SECTION 15: Regulatory information

Korea inventory (KECI)	All components are listed or exempted.
Philippines inventory (PICCS)	All components are listed or exempted.
Taiwan Chemical Substances Inventory (TCSI)	All components are listed or exempted.
Explosive precursors	Not applicable.

[Ozone depleting substances \(1005/2009/EU\)](#)

Not listed.

[Prior Informed Consent \(PIC\) \(649/2012/EU\)](#)

Not listed.

[Persistent Organic Pollutants](#)

Not listed.

[EU - Water framework directive - Priority substances](#)

None of the components are listed.

[Seveso Directive](#)

This product is not controlled under the Seveso Directive.

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

SECTION 16: Other information**Abbreviations and acronyms**

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 CAS = Chemical Abstracts Service
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 CSA = Chemical Safety Assessment
 CSR = Chemical Safety Report
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EINECS = European Inventory of Existing Commercial chemical Substances
 ES = Exposure Scenario
 EUH statement = CLP-specific Hazard statement
 EWC = European Waste Catalogue
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 OECD = Organisation for Economic Co-operation and Development
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
 RRN = REACH Registration Number
 SADT = Self-Accelerating Decomposition Temperature
 SVHC = Substances of Very High Concern
 STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
 STOT-SE = Specific Target Organ Toxicity - Single Exposure
 TWA = Time weighted average
 UN = United Nations
 UVCB = Complex hydrocarbon substance
 VOC = Volatile Organic Compound
 vPvB = Very Persistent and Very Bioaccumulative
 Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4/ RRN 01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN

Product name Castrol Transmax ATF Z**Product code** 469682-DE01**Page:** 14/15**Version** 8 **Date of issue** 10 July 2025**Format** Estonia**Language** ENGLISH**Date of previous issue** 3 July 2024.**(Estonia)**

SECTION 16: Other information

01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN 01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN 01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN 01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8, 64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 / RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN 01-2119474889-13

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	
Full text of abbreviated H statements	H304 H361f May be fatal if swallowed and enters airways. Suspected of damaging fertility.
Full text of classifications [CLP/GHS]	Asp. Tox. 1 Repr. 2 ASPIRATION HAZARD - Category 1 REPRODUCTIVE TOXICITY - Category 2

History

Date of issue/ Date of revision	10/07/2025.
Date of previous issue	03/07/2024.
Prepared by	Product Stewardship

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.