

SAFETY DATA SHEET**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Product name Castrol Transmax Manual 90
Product code 469621-AE02
SDS no. 469621
Product type Liquid.

**Use of the substance/
mixture** Manual transmission fluid
 For specific application advice see appropriate Technical Data Sheet or consult our company representative.

1.3 Details of the supplier of the safety data sheet

Supplier BP Eastern Mediterranean Ltd
 41-49 Agiou Nicolaou Street, Office 27
 Nimeli Court
 Engomi
 2408
 Nicosia
 Cyprus

Contact Tel: 00357 22 362 300 / 311
 Fax: 00357 22 658 848

E-mail address MSDSadvice@bp.com

1.4 Emergency telephone number

**EMERGENCY
TELEPHONE NUMBER** Carechem: +44 (0) 1235 239 670 (24/7)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Product definition Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements

Signal word No signal word.
Hazard statements No known significant effects or critical hazards.

Precautionary statements

Prevention Not applicable.
Response Not applicable.
Storage Not applicable.
Disposal Not applicable.

**Supplemental label
elements** Contains Amines, C10-14-tert-alkyl. May produce an allergic reaction. Safety data sheet available on request.

EU Regulation (EC) No. 1907/2006 (REACH)

**Annex XVII - Restrictions
on the manufacture,
placing on the market
and use of certain
dangerous substances,
mixtures and articles** Not applicable.

Product name Castrol Transmax Manual 90
Version 1 **Date of issue** 11 May 2020

Product code 469621-AE02 **Page:** 1/19
Format Africa
 Northern
 (Africa Northern) **Language** ENGLISH

SECTION 2: Hazards identification

Special packaging requirements

Containers to be fitted with child-resistant fastenings	Not applicable.
Tactile warning of danger	Not applicable.

2.3 Other hazards

Results of PBT and vPvB assessment	Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	Defatting to the skin.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product definition	Mixture
Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.	
This product does not contain any hazardous ingredients at or above regulated thresholds.	

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Potential acute health effects

Inhalation	Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.
Ingestion	No known significant effects or critical hazards.
Skin contact	Defatting to the skin. May cause skin dryness and irritation.
Eye contact	No known significant effects or critical hazards.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects.
--------------------	---

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.

Unsuitable extinguishing media

Do not use water jet. The use of a water jet may cause the fire to spread by splashing the burning product.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products

Combustion products may include the following:
carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

5.3 Advice for firefighters

Special precautions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Floors may be slippery; use care to avoid falling. Put on appropriate personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

See Section 1 for emergency contact information.
See Section 5 for firefighting measures.
See Section 8 for information on appropriate personal protective equipment.
See Section 12 for environmental precautions.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/containers designed for use with this product. Do not store in unlabelled containers.

SECTION 7: Handling and storage

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived No Effect Level

No DNELs/DMELs available.

Predicted No Effect Concentration

No PNECs available

8.2 Exposure controls

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Eye/face protection

Safety glasses with side shields.

Skin protection

Hand protection

General Information:

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile gloves.

Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It

Product name Castrol Transmax Manual 90

Product code 469621-AE02

Page: 4/19

Version 1 **Date of issue** 11 May 2020

Format Africa
Northern
(Africa Northern)

Language ENGLISH

SECTION 8: Exposure controls/personal protection

is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained.

If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.

It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

Glove Thickness:

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

Skin and body

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Refer to standards:

Respiratory protection: EN 529
Gloves: EN 420, EN 374
Eye protection: EN 166
Filtering half-mask: EN 149
Filtering half-mask with valve: EN 405
Half-mask: EN 140 plus filter
Full-face mask: EN 136 plus filter
Particulate filters: EN 143
Gas/combined filters: EN 14387

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	Liquid.
Colour	Amber. [Dark]
Odour	Not available.
Odour threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Pour point	-12 °C
Flash point	Open cup: >180°C (>356°F) [Cleveland.]
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	Not available.
Density	<1000 kg/m ³ (<1 g/cm ³) at 15°C
Solubility(ies)	insoluble in water.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Kinematic: 177.5 mm ² /s (177.5 cSt) at 40°C Kinematic: 16 to 18 mm ² /s (16 to 18 cSt) at 100°C
Explosive properties	Not available.
Oxidising properties	Not available.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
10.2 Chemical stability	The product is stable.
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
10.4 Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
10.5 Incompatible materials	Reactive or incompatible with the following materials: oxidising materials.
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity estimates

Not available.

Information on likely routes of exposure

Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Product name Castrol Transmax Manual 90
Version 1 Date of issue 11 May 2020

Product code 469621-AE02 Page: 6/19
Format Africa Northern (Africa Northern) Language ENGLISH

SECTION 11: Toxicological information

Inhalation	Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.
Ingestion	No known significant effects or critical hazards.
Skin contact	Defatting to the skin. May cause skin dryness and irritation.
Eye contact	No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation	May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
Ingestion	No specific data.
Skin contact	Adverse symptoms may include the following: irritation dryness cracking
Eye contact	No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.

Potential chronic health effects

General	No known significant effects or critical hazards.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

SECTION 12: Ecological information

12.1 Toxicity

Environmental hazards	Not classified as dangerous
------------------------------	-----------------------------

12.2 Persistence and degradability

Expected to be biodegradable.

12.3 Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc})	Not available.
Mobility	Spillages may penetrate the soil causing ground water contamination.

12.5 Results of PBT and vPvB assessment

Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.

12.6 Other adverse effects

Other ecological information	Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.
-------------------------------------	--

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal	Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.
Hazardous waste	Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

Packaging

Product name Castrol Transmax Manual 90	Product code 469621-AE02	Page: 7/19
Version 1	Date of issue 11 May 2020	Format Africa Northern (Africa Northern)
		Language ENGLISH

SECTION 13: Disposal considerations

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Special precautions This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

References Commission 2014/955/EU
Directive 2008/98/EC

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

14.6 Special precautions for user Not available.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)
[Annex XIV - List of substances subject to authorisation](#)
[Annex XIV](#)

None of the components are listed.

[Substances of very high concern](#)

None of the components are listed.

[Other regulations](#)

REACH Status For the REACH status of this product please consult your company contact, as identified in Section 1.

United States inventory (TSCA 8b) Not determined.

Australia inventory (AICS) All components are listed or exempted.

Canada inventory All components are listed or exempted.

China inventory (IECSC) All components are listed or exempted.

Japan inventory (ENCS) All components are listed or exempted.

Korea inventory (KECI) All components are listed or exempted.

Philippines inventory (PICCS) All components are listed or exempted.

Taiwan Chemical Substances Inventory (TCSI) All components are listed or exempted.

[Ozone depleting substances \(1005/2009/EU\)](#)

Not listed.

SECTION 15: Regulatory information

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

SECTION 16: Other information

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 CAS = Chemical Abstracts Service
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 CSA = Chemical Safety Assessment
 CSR = Chemical Safety Report
 DMEL = Derived Minimal Effect Level
 DNEL = Derived No Effect Level
 EINECS = European Inventory of Existing Commercial chemical Substances
 ES = Exposure Scenario
 EUH statement = CLP-specific Hazard statement
 EWC = European Waste Catalogue
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 OECD = Organisation for Economic Co-operation and Development
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
 RRN = REACH Registration Number
 SADT = Self-Accelerating Decomposition Temperature
 SVHC = Substances of Very High Concern
 STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
 STOT-SE = Specific Target Organ Toxicity - Single Exposure
 TWA = Time weighted average
 UN = United Nations
 UVCB = Complex hydrocarbon substance
 VOC = Volatile Organic Compound
 vPvB = Very Persistent and Very Bioaccumulative
 Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4 / RRN 01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN 01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN 01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN 01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN 01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8, 64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 / RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN 01-2119474889-13

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

Full text of abbreviated H statements Not applicable.

Full text of classifications [CLP/GHS] Not applicable.

Product name Castrol Transmax Manual 90	Product code 469621-AE02	Page: 9/19
Version 1	Date of issue 11 May 2020	Format Africa Northern (Africa Northern)
		Language ENGLISH

SECTION 16: Other information**History**

Date of issue/ Date of revision	11/05/2020.
Date of previous issue	No previous validation.
Prepared by	Product Stewardship

✔ Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

يتفق ولانحة (المجموعة الأوروبية) رقم 1907/2006 (تشریح تقييم المواد الكيميائية وتسجيلها وإقرارها ((REACH)), الملحق 2، بصيغته المعدلة بلانحة (الاتحاد الأوروبي) رقم 2015/830

**صحيفة بيانات السلامة****القسم 1: تعريف المادة/المستحضر و الشركة/المشروع****1.1 مُعرّف المنتج****Castrol Transmax Manual 90**

469621-AE02

469621

اسم المنتج

كود المنتج

صحيفة بيانات سلامة المادة رقم #

نوع المنتج

Liquid.

1.3 بيانات مورّد صحيفة بيانات السلامة

المورّد

BP Eastern Mediterranean Ltd
41-49 Agiou Nicolaou Street, Office 27
Nimeli Court
Engomi
2408
Nicosia
Cyprus

Contact Tel: 00357 22 362 300 / 311

Fax: 00357 22 658 848

MSDSadvice@bp.com

عنوان البريد الإلكتروني

1.4 رقم هاتف الطوارئ

Carechem: +44 (0) 1235 239 670 (24/7)

رقم هاتف الطوارئ

Product name Castrol Transmax Manual 90**Product code** 469621-AE02**Page:** 10/19**Version** 1 **Date of issue** 11 May 2020**Format** Africa
Northern
(Africa Northern)**Language** ENGLISH

القسم 2: بيان الأخطار

2.1 تصنيف المادة أو الخليط

تعريف المنتج خليط

التصنيف وفقاً للتنظيم (الاتحاد الأوروبي) رقم [CLP/GHS] 1272/2008 غير مُصنّف.

مراجعة الأقسام 11 و 12 للوقوف على مزيد من المعلومات المفصلة بشأن الآثار الصحية والأعراض والمخاطر البيئية.

2.2 عناصر الوسم

كلمة التنبيه بدون كلمة تنبيه

عبارات المخاطر لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

عبارات التحذير

الوقاية غير قابل للتطبيق.

الاستجابة غير قابل للتطبيق.

التخزين غير قابل للتطبيق.

التخلص من النفايات غير قابل للتطبيق.

عناصر التوسيم التكميلية تحتوي C10-14-tert-alkyl, Amines. قد يُحدث تفاعل تحسسي. صحيحة بيانات السلامة متاحة عند الطلب.

تنظيم (المجلس الأوروبي) رقم 1907/2006 (تسجيل الكيماويات وتقييمها وترخيصها REACH)

المُلحق السابع عشر؛ قيود على تصنيع غير قابل للتطبيق.

وطرح واستخدام مواد وخطوط

وحاجيات مُعينة خطرة

متطلبات التغليف الخاصة

يُراعى أن تُزوّد العبوات بأنظمة إغلاق غير قابل للتطبيق.

منبوعة للأطفال

تحذير لمسي من الخطر غير قابل للتطبيق.

2.3 الأخطار الأخرى

المنتج لا يُبلى معايير ثبات المواد والتراكمية الأحيائية والسمية PBT أو معايير شدة الثبات وشدة التراكمية الأحيائية وفق لائحة المجلس الأوروبي رقم 1907/2006، الملحق XIII.

نتائج مأخوذة من تقييم الـ PBT (البقاء والسمية والتراكم البيولوجي) والـ vPvB (البقاء الشديد والتراكم البيولوجي الشديد)
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

الأخطار الأخرى التي لا تؤدي إلى تصنيف يزيل دهون الجلد.

القسم 3: التركيب/معلومات عن المكونات

3.2 خلانط

تعريف المنتج خليط

زيت أساسي عالي النقاوة (خلاصة IP 346 DMSO > 3%). إضافات خاصة للأداء.

النوع	تنظيم (المفوضية الأوروبية) رقم 1272/2008 [التصنيف والتوسيم والتعبئة (CLP)]	%	المُعرّفات	اسم المُكوّن/المنتج
-------	--	---	------------	---------------------

لا يحتوي هذا المنتج على أي مكونات خطرة أعلى من الحدود المسموح بها.

القسم 4: تدبير الإسعاف الأولي

4.1 وصف إجراءات الإسعاف الأولي

ملامسة العين في حالة الملامسة، يُراعى دفق الماء فوراً على العين لمدة لا تقل عن 15 دقيقة. يجب إبعاد الجفون عن مقصات العين لضمان الشطف الكامل. يُراعى التحقق من عدم وجود عدسات لاصقة أو إزالتها إن وجدت. يُراعى الحصول على الرعاية الطبية.

ملامسة الجلد

يراعى غسل البشرة غسلاً جيداً بالماء و الصابون أو بأحد منظفات الجلد المعترف بها. أزل الثياب والأحذية الملوثة. يُراعى غسل الثياب قبل إعادة استخدامها. يُراعى تنظيف الحذاء تنظيفاً جيداً قبل ارتدائه ثانية. يُراعى الحصول على الرعاية الطبية إذا حدث تهيج.

استنشاق

في حالة الاستنشاق، يُراعى نقل المصاب إلى الهواء الطلق. يُراعى الحصول على الرعاية الطبية لو ظهرت أعراض.

Product name Castrol Transmax Manual 90

Product code 469621-AE02

Page: 11/19

Version 1 Date of issue 11 May 2020

Format Africa Northern

Language ENGLISH

(Africa Northern)

القسم 4: تدبير الإسعاف الأولي

الابتلاع
لا تحرض على القيء إلا إن طلب أحد أعضاء الطاقم الطبي منك أن تقوم بهذا. يُراعى الحصول على الرعاية الطبية لو ظهرت أعراض.
حماية فريق الإسعافات الأولية
يُحظر القيام بأية إجراء ينطوي على مخاطرة أو بدون تدريب مناسب.

4.2 أهم الأعراض والتأثيرات، الحاد منها والمؤجل

انظر القسم 11 لمزيد من المعلومات عن التأثيرات السمية والأعراض.

آثار صحية حادة كامنة

استنشاق
استنشاق الأبخرة في الظروف المحيطة لا يمثل مشكلة في المعتاد، وذلك لانخفاض ضغط الأبخرة.
الابتلاع
لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.
لاملامسة الجلد
يزيل دهون الجلد. قد تسبب جفاف الجلد وتهيجه.
لاملامسة العين
لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

التأثيرات المتأخرة والفورية وكذلك التأثيرات المزمنة نتيجة للتعرض القصير والطويل الأمد

استنشاق
التعرض الزائد لاستنشاق الجزيئات المتطايرة في الهواء أو الإيروسولات قد يتسبب في تهيج الجهاز التنفسي.
الابتلاع
ابتلاع كميات كبيرة يمكن أن يؤدي إلى الغثيان والإسهال.
لاملامسة الجلد
اللاملامسة بشكل متكرر أو لفترات طويلة يمكن أن تتسبب في إزالة الدهون من الجلد وتتسبب في تهيجات وتشققات و/أو التهابات جلدية.
لاملامسة العين
هناك خطورة محتملة من حدوث لسعة عابرة أو احمرار عابر في حالة حدوث ملامسة العين بشكل عرضي.

4.3 دواعي أية رعاية طبية فورية ومعالجة خاصة مطلوبة

ملاحظات للطبيب
يجب أن تتم المعالجة حسب الأعراض بشكل عام ويتم إجراؤها لتخفيف حدة التأثيرات.

القسم 5: تدابير مكافحة النار**5.1 وسائل الإطفاء**

وسائل الإطفاء المناسبة
في حالة نشوب حريق، استخدم الرغوة والمواد الكيميائية الجافة أو مطفأة حريق أو بخاخة بها ثاني أكسيد الكربون.

وسائل الإطفاء غير المناسبة

لا تستخدم المياه النفاثة. قد يسبب استخدام القواطع المائية النفاثة انتشار الحريق نتيجة تطاير المنتج المحترق وتناثره.

5.2 الأخطار الخاصة الناجمة عن المادة أو الخليط

الأخطار الناجمة عن المادة أو الخليط
سوف يحدث تزايد في الضغط وقد تنفجر الحاوية في حالة حدوث حريق أو تسخين.

منتجات احتراق خطيرة

نواتج الاحتراق قد تشمل ما يلي:
أكاسيد الكربون (CO₂, CO)

5.3 نصائح لمكافحة الحريق**إحتياطات خاصة لمكافحة الحريق**

يُحظر القيام بأية إجراء ينطوي على مخاطرة أو بدون تدريب مناسب. يراعى عزل المكان على الفور وذلك بإخلاء الأفراد المتواجدين على مقربة من الحادث في حالة نشوب حريق.

معدات الحماية الشخصية والإحتياطات

اللائمة لعمال الإطفاء
ينبغي أن يرتدي مكافح الحرائق التجهيزات الواقية المناسبة وجهاز تنفس مكتفي ذاتياً (SCBA) ذا وحدة كاملة للوجه يعمل في نمط الضغط الموجب. ثياب مكافحة الحريق (بما فيها الخوذات والأحذية والقفازات الواقية) التي تتفق والمعيار الأوروبي 469 EN سوف تكفل مستوى أساسياً من الحماية من الحوادث الكيميائية.

القسم 6: تدابير مواجهة التسرب العارض**6.1 لإحتياطات الشخصية ومعدات الحماية وإجراءات الطوارئ****للأفراد من خارج فريق الطوارئ**

يُحظر القيام بأية إجراء ينطوي على مخاطرة أو بدون تدريب مناسب. يراعى إخلاء المناطق المجاورة. يراعى عدم السماح بالدخول لكل من لا يرتدي الثياب الواقية أو من لا حاجة لك بهم من الأفراد. يراعى تجنب ملامسة المادة المنسكبة أو السير عليها. قد تكون الأرضيات زلقة؛ يجب توخي العناية لتجنب السقوط. ارتدي التجهيزات الواقية الشخصية الملائمة.
لمسعي الطوارئ
إذا لزم الأمر ارتداء ثياباً خاصة للتعامل مع الانسكاب، يُرجى أخذ ما ورد في القسم 8 من معلومات حول المواد المناسبة وغير المناسبة في الحسبان. راجع كذلك المعلومات الواردة في قسم "للأفراد من خارج فريق الطوارئ".

6.2 الإحتياطات البيئية

تجنب تناثر المادة المنسكبة وجريانها السطحي ووصولها إلى التربة و المجاري المائية والبالوعات ومجاري الصرف. يُراعى إبلاغ السلطات المعنية لو تسبب المنتج في تلوث البيئة (مجري الصرف، المجاري المائية، التربة أو الهواء).

6.3 طرائق ومواد الاحتواء والتنظيف**انسكاب صغير**

يُراعى وقف التسرب إن لم ينطو ذلك على مخاطرة. يراعى نقل الأوعية من منطقة الانسكاب. يُراعى امتصاصها بمادة خاملة، ثم إيداعها إحدى الحاويات الملائمة للتخلص من النفايات. تخلص منها عن طريق أحد مقاولي التخلص من النفايات المرخصين.

القسم 6: تدابير مواجهة التسرب العارض

انسكاب كبير

يُراعى وقف التسرب إن لم ينطو ذلك على مخاطرة. يراعى نقل الأوعية من منطقة الانسكاب. يمنع دخولها في البوعات الصرف، و المجاري المائية، أو البدرومات، أو المناطق المحصورة. يُراعى احتواء الانسكاب وجمعه بمادة ماصة غير قابلة للاحتراق مثل الرمل، أو التراب، أو الفر ميكبوليت، أو تراب دياتومي، ثم وضعها في إحدى الحاويات للتخلص منها بما يتفق واللوائح المحلية. تخلص منها عن طريق أحد مقاولي التخلص من النفايات المرخصين.

6.4 مرجع للأقسام الأخرى

انظر القسم 1 لمعرفة بيانات الاتصال في أحوال الطوارئ.
انظر القسم 5 الخاص بإجراءات مكافحة الحريق.
انظر القسم 8 للحصول على معلومات عن التجهيزات الوقائية الشخصية الملائمة.
انظر القسم 12 للاطلاع على الاحتياطات البيئية.
انظر القسم 13 لمزيد من المعلومات حول معالجة النفايات.

القسم 7: المناولة والتخزين**7.1 احتياطات للمناولة الآمنة****إجراءات للحماية****إرشادات حول الصحة المهنية العامة**

ارتدي التجهيزات الوقائية الشخصية الملائمة.

يحظر تناول الطعام، والشراب، والتدخين في الأماكن التي يجري التعامل فيها مع هذه المادة سواء بالمناولة، التخزين أو المعالجة. يُراعى الإغتسال جيداً بعد مناولتها. اخلع الثياب الملوثة والتجهيزات الوقائية قبل دخول الأماكن المخصصة للطعام. انظر القسم 8 لمزيد من المعلومات حول إجراءات الحفاظ على الصحة.

7.2 متطلبات التخزين الآمن، بما في ذلك ما يتعلق بحالات عدم توافق المواد

خزن المادة وفقاً لتعليمات السلطات المحلية. يُخزّن في مكان جاف، وبارد وجيد التهوية، بعيداً عن المواد غير المتوافقة (انظر القسم 10). يُراعى الحفظ بعيداً عن الحرارة وضوء الشمس المباشر. يراعى غلق الوعاء غلقاً تاماً محكماً إلى أن يُعدّ للاستخدام. لا بد من إحكام غلق الأوعية التي قد قُتحت و تركها في وضع قائم وذلك لتلافي حدوث تسريب. يجب أن يتم التخزين والاستعمال فقط في معدات/حاويات مصممة للاستخدام مع هذا المنتج. يُحظر التخزين في حاويات لا تحمل كتابة توضيحية.

القسم 8: ضوابط التعرض/الحماية الشخصية**8.1 بارامترات التحكم****حدود التعرض المهني**

قيمة حد التعرض غير معروفة.

في الوقت الذي قد يُظهر حد التعرض المهني (OEL) مكونات معينة في هذا القسم، فإن مكونات أخرى قد توجد في الغبار أو البخار أو الرذاذ الناجم. لذا، فإن حد تعرض مهني معين قد لا ينطبق على المنتج ككل وإنما يدرج للإرشاد والتوجيه فقط.

إجراءات المتابعة الموصى بها

إن كان هذا المنتج يحتوي على مكونات لها حدود تعرض، قد يكون من المطلوب إجراء متابعة حيوية أو متابعة الأشخاص أو مكان العمل كي يتسنى تحديد مدى فاعلية التهوية، أو إجراءات التحكم الأخرى و/أو مدى ضرورة استخدام الأجهزة التنفسية الوقائية. تنبغي الإشارة إلى معايير المراقبة، من مثل ما يلي: المعيار الأوروبي EN 689 (أجواء موقع العمل - إرشادات تقييم التعرض لعوامل كيميائية بالاستنشاق لمقارنتها بالقيم الحدية واستراتيجية القياس) المعيار الأوروبي EN 14042 (أجواء موقع العمل - دليل اتخاذ وتطبيق إجراءات تقييم التعرض للعوامل البيولوجية والكيميائية) المعيار الأوروبي EN 482 (أجواء موقع العمل - المتطلبات العامة لأداء إجراءات قياس العوامل الكيميائية) سيكون من المطلوب كذلك الرجوع إلى وثائق التوجيه الوطنية الخاصة بطرق تحديد المواد الخطرة.

مستوى مشتق غير مؤثر

DNELs/DMELs غير متاحة.

الـ PNEC = تركيز عدم التأثير المتوقع

PNECs غير متاحة.

8.2 ضوابط التعرض**الضوابط الهندسية المناسبة**

احرص على توفير تهوية للعوادم أو الوسائل الهندسية الأخرى للحماية، وذلك للإبقاء على مستويات التركيز المعنية للمواد العالقة بالهواء دون حدود التعرض المقبولة لها على الصعيد المهني.

يجب تقييم جميع الأنشطة المرتبطة بالمواد الكيميائية من حيث مخاطرها على الصحة، وذلك لضمان التحكم في معدلات التعرض بالشكل المناسب. لا يجوز فحص معدات الوقاية الشخصية إلا بعد تقييم الأشكال الأخرى لإجراءات التحكم (على سبيل المثال عمليات التحكم الهندسية) بالشكل المناسب. يجب أن تتوافق معدات الوقاية الشخصية مع المواصفات المعنية وأن تكون مناسبة للاستخدام، ويجب الحفاظ عليها في حالة جيدة وصيانتها بشكل سليم.

يجب التشاور مع مورد معدات الوقاية الشخصية لطلب المشورة بشأن الاختيار والمواصفات المعنية. لمزيد من المعلومات، اتصل بالهيئة المحلية للمواصفات.

القرار النهائي لاختيار معدات الوقاية يعتمد على تقييم المخاطر. ومن المهم التأكد من ملاءمة جميع عناصر معدات الوقاية الشخصية.

تدابير الحماية الفردية**إجراءات النظافة الشخصية**

اغسل اليدين، والذراعين، والوجه غسلاً تاماً بعد مناولة المنتجات الكيميائية، وعند الأكل والتدخين، وفي نهاية فترة العمل. تأكد من وجود محطات غسيل الأعين وأدشاش الأمان على مقربة من موقع العمل.

حماية تنفسية

في حالة عدم كفاية التهوية، يُراعى ارتداء تجهيزات تنفسية ملائمة. يعتمد الاختيار الصحيح لتجهيزات حماية الجهاز التنفسي على المواد الكيميائية التي يتم التعامل معها وظروف العمل والاستخدام وحالة تجهيزات حماية الجهاز التنفسي. يجب وضع تدابير أمان تتناسب مع كل استخدام مقرر. لذلك يجب اختيار تجهيزات حماية الجهاز التنفسي بالتشاور مع المورد / الشركة الصانعة مع مراعاة التقييم الكامل لظروف العمل.

نظرات أمان ذات سترات جانبية.

أدوات حماية الوجه/العين

Product name Castrol Transmax Manual 90

Product code 469621-AE02

Page: 13/19

Version 1 Date of issue 11 May 2020

Format Africa Northern (Africa Northern)

Language ENGLISH

ظراً لتفاوت الظروف الخاصة لبيئات العمل واختلاف ممارسات التعامل مع المواد، فيجب وضع تدابير أمان تتناسب مع كل استخدام مقرر. يعتمد الاختيار الصحيح للقذازات الحماية على المواد الكيميائية التي يتم التعامل معها وظروف العمل والاستخدام. معظم القذازات توفر الحماية لفترة زمنية محدودة فقط قبل وجود التخلص منها واستبدالها (حتى أفضل القذازات المقاومة للمواد الكيميائية تتآكل بفعل التعرض المتكرر للمواد الكيميائية).

يجب اختيار القذازات بالتشاور مع المورد / الشركة الصانعة مع مراعاة التقييم الكامل لظروف العمل. يُنصح باستخدام: قذازات نيتريل. الزمن اللازم للاختراق:

تُجمع بيانات زمن الاختراق من مصنعي القذاز تحت ظروف الاختبار المعملية وتمثل المدة أو الفترة المتوقعة التي يؤمن خلالها القذاز حماية من تسرب المادة أو نفاذها. ومن الأهمية بمكان مراعاة طبيعة ظروف العمل الفعلية عند اتباع توصيات زمن الاختراق. ويتعين دائماً التشاور مع مورد القذازات للوقوف على معلومات تقنية وفنية محدثة بشأن زمن الاختراق لنوع القذاز الموصى به. فيما يلي توصياتنا بخصوص اختيار القذازات:

الملاسة المستمرة:

قذازات بفترة اختراق لا تقل عن 240 دقيقة، أو <480 دقيقة، إذا أمكن الحصول على قذازات مناسبة. إذا لم تتوفر قذازات مناسبة تضمن الحماية بهذا المستوى، فمن الممكن استخدام قذازات بفترة حماية أقل طالما هناك قواعد مناسبة يتم الالتزام بها لصيانة القذازات واستبدالها.

الحماية من الرذاذ قصيرة الأجل

توصيات فترات الاختراق كما سبق. يمكن في المعتاد استخدام القذازات ذات فترات الاختراق القصيرة للأعمال التي يتم فيها التعرض للزيوت لفترات قصيرة وعابرة. لذلك، يجب أن تكون هناك قواعد مناسبة يتم الالتزام بها بشكل تام لصيانة القذازات واستبدالها.

سُمك القذاز:

بالنسبة للاستخدامات العامة، فإننا نوصي بقذاز بسُمك يزيد على 0.35 مم.

يجب التأكيد والتشديد أن سُمك القذاز لا يمثل بالضرورة مؤشراً موثقاً على مقاومة القذاز لمادة كيميائية معينة، ذلك أن كفاءة مقاومة التسرب للقذاز ستكون معتمدة على تركيب المادة المصنعة منها القذاز تحديداً. لذا فإن اختيار القذاز يجب أن يستند على عوامل ومتطلبات المهمة ومعرفة بأزمان الاختراق. كذلك قد يتنوع سُمك القذاز بناء على مُصنِع القذاز، ونوع القذاز وموديل القذاز. لذا، يجب أخذ بيانات المصنِع الفنية بالحسبان وذلك لضمان القذاز الأكثر مناسبة للمهمة.

ملاحظة: اعتماداً على نوع النشاط قيد الممارسة، فإن القذازات ذات السُمك المختلف قد تكون مطلوبة لمهام مُحددة. على سبيل المثال:

- قد يتطلب الأمر القذازات الرقيقة (بسُمك يبلغ 0.1 مم أو أقل) متى تطلب الأمر درجة من المهارة اليدوية والبراعة. ومع ذلك، فإن مثل هذه القذازات ينتظر منها أن توفر الحماية لفترة قصيرة، وعادة ما تكون للاستخدام مرة واحدة ثم يجري التخلص منها.
- قد تبرز الحاجة لقذازات أكثر سُمكاً (حتى 3 مم أو أكثر) في حالة المخاطر الميكانيكية (وكذلك الكيميائية)؛ أي متى كان هناك احتمال للتآكل أو القشط أو الثقب.

الجلد والجسم

استخدام الملابس الواقية يعتبر من الممارسات الجيدة في المجال الصناعي. يجب انتقاء التجهيزات الشخصية الواقية للجسم بما يتفق والمهمة التي يجري القيام بها والمخاطر التي تنطوي عليها، كما يجب أن يعتمد عليها أحد المختصين قبل التعامل مع هذا المنتج. بدلات العمل المصنوعة من القطن أو البوليستر/القطن توفر الحماية فقط من التلوث السطحي الخفيف الذي لا يصل إلى الجلد. ويجب غسل بدلات العمل بصفة منتظمة. عندما تزداد خطورة تعرض الجلد للمواد (على سبيل المثال عند تنظيف المواد المنسكبة أو في حالة وجود خطورة من تآثر الرذاذ)، فيجب ارتداء إزارات مقاومة للمواد الكيميائية و/أو أحذية وسترات غير منفذة للمواد الكيميائية.

يتعين مراجعة المعايير:

حماية تنفسية: EN 529

قذازات: EN 420, EN 374

حماية لليدين: EN 166

الترشيح نصف الوجهي: EN 149

الترشيح نصف الوجهي ذي الصمام: EN 405

قناع نصفى: EN 140 مرشح إضافي

قناع وجهي كامل: EN 136 مرشح إضافي

مرشحات الجزئيات: EN 143

مرشحات الغاز/ المشتركة: EN 14387

نصح بفحص الإنبعاثات الصادرة من أجهزة العمل والتهوية، للتأكد من استيفائها لمتطلبات قانون حماية البيئة. في بعض الحالات، قد يكون من الضروري استخدام أجهزة غسل الأبخار، أو المرشحات أو إجراء تعديلات هندسية للمعدات، كي يتسنى تقليل الإنبعاثات إلى مستويات مقبولة.

ضوابط التعرض البيئي

القسم 9: الخصائص الفيزيائية والكيميائية

9.1 معلومات حول الخصائص الكيميائية والفيزيائية الأساسية

المظهر

الحالة الفيزيائية

سائل.

اللون

كهرمان. [داكن]

الرائحة

غير متوفرة.

عتبة الرائحة

غير متوفرة.

الأس الهيدروجيني pH

غير متوفرة.

نقطة الانصهار/نقطة التجمد

غير متوفرة.

نقطة الغليان الأولية ونطاق الغليان

غير متوفرة.

نقطة الانسكاب

-12 °C

نقطة الوميض

جهاز الكأس المفتوحة: <180 °C (<356 ف) [جهاز كليفلاند].

معدل التبخر

غير متوفرة.

القابلية للاشتعال (مادة صلبة، غاز)

غير متوفرة.

الحدود العليا/الدنيا لقابلية الاشتعال أو الانفجار

غير متوفرة.

الضغط البخاري

غير متوفرة.

الكثافة البخارية

غير متوفرة.

الكثافة النسبية

غير متوفرة.

الكثافة

>1000 كجم/م³ (1 >g/cm³) عند 15 °C

الذوبانية (نيات)

غير ذوب في الماء.

معامل تقرييق الأوكتانول/الماء

غير متوفرة.

درجة حرارة الاشتعال الذاتي

غير متوفرة.

درجة حرارة الانحلال

غير متوفرة.

اللزوجة

كينماتي: 177.5 /S²mm (177.5 سنتي ستوك) عند 40 °C
كينماتي: 16 إلى 18 /S²mm (16 إلى 18 سنتي ستوك) عند 100 °C

الخصائص الانفجارية

غير متوفرة.

خواص مؤكسدة

غير متوفرة.

9.2 المعلومات الأخرى

ليس هناك مزيد من المعلومات.

القسم 10: الثبات الكيميائي والقابلية للتفاعل

10.1 التفاعلية

لا تتاح بيانات اختبار أخرى معينة لهذا المنتج. ارجع إلى الظروف التي يجب تجنبها والمواد غير المتوافقة لمزيد من المعلومات.

10.2 الثبات الكيميائي

المنتج ثابت.

10.3 إمكانية التفاعلات الخطرة

لن تحدث تفاعلات خطرة في ظروف التخزين والاستخدام العادية.
لن تحدث بلمرة خطرة في ظروف التخزين والاستخدام العادية.

10.4 الظروف التي ينبغي تجنبها

يجب تجنب جميع مصادر الاشتعال الممكنة (شرر أو لهب).

10.5 المواد غير المتوافقة

تتفاعل أو غير متطابقة مع المواد التالية: مواد مؤكسدة.

10.6 نواتج الانحلال الخطرة

في ظروف التخزين والاستخدام العادية، من غير المنتظر أن تتولد نواتج تحلل خطرة.

القسم 11: المعلومات السمية**11.1 معلومات حول الآثار السمية****تقديرات السمية الحادة**

N/A

معلومات عن سبب التعرض المرجحة

سبب الدخول المُرتقبة: جلدي، استنشاق.

آثار صحية حادة كامنة

استنشاق

استنشاق الأبخرة في الظروف المحيطة لا يمثل مشكلة في المعتاد، وذلك لانخفاض ضغط الأبخرة.

الابتلاع

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

ملامسة الجلد

يزيل دهون الجلد. قد تسبب جفاف الجلد وتهيجه.

ملامسة العين

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

أعراض متعلقة بالخواص السمية والكيميائية والفيزيائية

استنشاق

قد يؤدي إلى ضرر في حالة الاستنشاق في حالة التعرض للأبخرة أو الرذاذ أو العوادم الناتجة عن التحلل الحراري للمنتجات.

الابتلاع

ليست هناك بيانات معينة.

ملامسة الجلد

الأعراض الضائرة قد تشمل ما يلي:

تهيج

الجفاف

التشقق

ملامسة العين

ليست هناك بيانات معينة.

التأثيرات المتأخرة والفورية وكذلك التأثيرات المزمنة نتيجة للتعرض القصير والطويل الأمد

استنشاق

التعرض الزائد لاستنشاق الجزيئات المتطايرة في الهواء أو الإيروسولات قد يتسبب في تهيج الجهاز التنفسي.

الابتلاع

ابتلاع كميات كبيرة يمكن أن يؤدي إلى الغثيان والإسهال.

ملامسة الجلد

الملامسة بشكل متكرر أو لفترات طويلة يمكن أن تتسبب في إزالة الدهون من الجلد وتسبب في تهيجات وتشققات و/أو التهابات جلدية.

ملامسة العين

هناك خطورة محتملة من حدوث لسعة عابرة أو احمرار عابر في حالة حدوث ملامسة العين بشكل عرضي.

آثار صحية مزمنة كامنة

عامة

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

السرطنة

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

التأثير على الجينات

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

التأثيرات النمائية

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

التأثيرات الخصوبة

لا توجد تأثيرات شديدة أو مخاطر حرجة معروفة.

القسم 12: المعلومات الإيكولوجية**12.1 السمية**

غير مُصنَّفة كمادة خطرة

الأخطار البيئية

12.2 الثبات والتحلل

يُتوقع أن يكون قابلاً للتحلل الحيوي.

12.3 القدرة على التراكم الأحيائي

لا يُتوقع أن يتراكم هذا المنتج حيوياً في البيئة من خلال السلاسل الغذائية.

12.4 القابلية على التحرك عبر التربة

مُعامل تقاسم التربة/الماء (Koc) غير متوفرة.

التحررية

المواد المنسكبة يمكن أن تتوغل في التربة وتتسبب في تلوث المياه الجوفية.

12.5 نتائج مأخوذة من تقييم الـ PBT (البقاء والسمية والتراكم البيولوجي) والـ vPvB (البقاء الشديد والتراكم البيولوجي الشديد)

المنتج لا يُلبى معايير ثبات المواد والتراكمية الأحيائية والسمية PBT أو معايير شدة الثبات وشدة التراكمية الأحيائية وفق لائحة المجلس الأوروبي رقم 1907/2006، الملحق XIII.

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 التأثيرات الضارة الأخرى

معلومات بيئية أخرى

قد تتسبب السوائل المنسكبة في تكوين طبقة على أسطح الماء، وقد تتسبب في ضرر مادي للكائنات الحية. وقد يتم إعاقة نقل الأكسجين أيضاً.

القسم 13: الاعتبارات المتعلقة بتصريف المواد والتخلص منها

13.1 طرق معالجة النفايات

المنتج

إذا أمكن، قم بتحضير المنتج لإعادة تدويره. يجب أن يتم التخلص من المواد بمعرفة شخص معتمد / جهة معتمدة للتخلص من النفايات وفقاً للقواعد المحلية.

طرق التخلص السليم من النفايات

على حد علم المورد حالياً، لا يُعتبر هذا المنتج نفاية خطيرة، وفقاً لتعريف توجيه الاتحاد الأوروبي EC/2008/98.

نفاية خطيرة

التصريف

إذا أمكن، قم بتحضير المنتج لإعادة تدويره. يجب أن يتم التخلص من المواد بمعرفة شخص معتمد / جهة معتمدة للتخلص من النفايات وفقاً للقواعد المحلية.

طرق التخلص السليم من النفايات

لا بد أن يجري التخلص من هذا المنتج وحاويته بطريقة آمنة. قد تظل بعض رواسب المنتج عالقة بالحاويات الفارغة أو قمصانها. تجنب تآثر المادة المنسكية وجريانها السطحي ووصولها إلى التربة و المجاري المائية والبالوعات ومجاري الصرف.

الاحتياطات الخاصة

اللجنة EU/2014/955
التوجيه EC/2008/98

المراجع

القسم 14: المعلومات المتعلقة بالنقل

IATA	IMDG	ADN	ADR/RID	
غير مقننة.	غير مقننة.	غير مقننة.	غير مقننة.	14.1 رقم الأمم المتحدة
-	-	-	-	14.2 اسم الشحن الصحيح الخاص بالأمم المتحدة
-	-	-	-	14.3 فئة/فئات مخاطر النقل
-	-	-	-	14.4 مجموعة التعبئة
لا.	لا.	لا.	لا.	14.5 الأخطار البيئية
-	-	-	-	معلومات إضافية

14.6 احتياطات خاصة للمستخدم غير متوفرة.

14.7 النقل سانبا بحسب الملحق الثاني من اتفاقية ماريبول MARPOL (بشأن منع التلوث الناجم عن السفن) وكود حاوية السوانب الوسيطة (IBC)

القسم 15: المعلومات التنظيمية

15.1 تشريع/لوائح السلامة والصحة والبيئة الخاصة بالمادة أو الخليط

تنظيم (المجلس الأوروبي) رقم 1907/2006 (تسجيل الكيماويات وتقييمها وترخيصها REACH)

الملحق الرابع عشر؛ قائمة المواد الخاضعة للترخيص

الملحق الرابع عشر

لم يُدرج أي من المكونات.

مواد مُقلقة للغاية

لم يُدرج أي من المكونات.

لوائح أخرى

الوضع وفق REACH (النظام

المتعلق بتسجيل وتقييم وترخيص

المواد الكيماوية)

قائمة الولايات المتحدة (8b TSCA)

مخزون أستراليا (AICS)

قائمة كندا

قائمة الصين (IECSC)

قائمة اليابان (ENCS)

قائمة كوريا (KECI)

للتعرف على حالة REACH لهذا المنتج، يرجى التواصل مع جهة الاتصال في شركتك، كما هو محدد في القسم 1.

لم تُحدّد.

كافة المُكوّنات مُدرجة بالقائمة أو مُستثناة منها.

كافة المُكوّنات مُدرجة بالقائمة أو مُستثناة منها.

كافة المُكوّنات مُدرجة بالقائمة أو مُستثناة منها.

كافة المُكوّنات مُدرجة بالقائمة أو مُستثناة منها.

كافة المُكوّنات مُدرجة بالقائمة أو مُستثناة منها.

القسم 15: المعلومات التنظيمية

قائمة الغلبين (PICCS) كافة المُكوّنات مُدرجة بالقائمة أو مُستثناة منها.

مخزون تاويان من المواد الكيميائية (TCSI) كافة المُكوّنات مُدرجة بالقائمة أو مُستثناة منها.

مواد مستفدة للأوزون (EU/1005/2009)

لم ترد بالقائمة.

الموافقة المسبقة عن علم (PIC) (EU/649/2012)

لم ترد بالقائمة.

توجيه سيفيسو

هذا المنتج لا يحكمه التوجيه سيفيسو.

اللوائح الوطنية

فرنسا

15.2 تقييم مأمونية الكيماويات

تم إجراء تقييم سلامة كيميائية لواحدة أو أكثر من مواد هذا المزيج. لم يتم إجراء تقييم سلامة كيميائية لهذا المزيج نفسه.

القسم 16: المعلومات الأخرى

الاختصارات

الـ ADN = اللوائح الأوروبية الخاصة بالنقل الدولي للبضائع الخطيرة عبر المجاري المائية الداخلية

الـ ADR = الاتفاقية الأوروبية المتعلقة بنقل البضائع الخطيرة الدولي برأ

ATE = تقدير السمية الحادة

الـ BCF = مُعامل التركيز الحيوي

CAS = خدمة الملخصات الكيميائية

CLP = تنظيم التصنيف والتوسيم والتعبئة [لائحة (EC) رقم 1272/2008]

الـ CSA = تقييم السلامة الكيماوية

الـ CSR = تقرير السلامة الكيماوية

الـ DMEL = مستوى التأثير الأدنى المُشتق

الـ DNEL = مستوى عدم التأثير المُشتق

EINECS = القائمة الأوروبية للمواد الكيميائية المتوفرة تجارياً

ES = سيناريو التعرض

EUH = بيان الأخطار الخاصة بتنظيم التصنيف والتوسيم والتعبئة

EWC = فهرس النفايات الأوروبية

GHS = النظام المتوافق عالمياً لتصنيف وتوسيم المواد الكيميائية

الـ IATA = رابطة النقل الجوي الدولي

الـ IBC = حاوية سوانب وسيطة

الـ IMDG = البحرية الدولية للبضائع الخطيرة

LogPow = لوغاريتم معامل تجزئة الأوكتانول/الماء

الـ MARPOL = المعاهدة الدولية لمنع التلوث الناجم عن السفن، 1973 المُعدّلة بموجب بروتوكول 1978. ("ماربول" = التلوث البحري)

OECD = منظمة التعاون الاقتصادي والتنمية

PBT = باقية وسامة ومتركمة بيولوجياً

الـ PNEC = تركّز عدم التأثير المُتوقع

REACH = التنظيم المتعلق بتسجيل وتقييم وترخيص المواد الكيماوية [نظام (المفوضية الأوروبية) رقم 1907/2006]

RID = التنظيمات الدولية لحمل البضائع الخطيرة عبر السكك الحديدية

RRN = رقم التسجيل في التنظيم المتعلق بتسجيل وتقييم وترخيص المواد الكيماوية (REACH)

SADT = درجة حرارة التحلل المتسارع ذاتياً

SVHC = مواد مثيرة لقلق شديد

STOT-RE = السمية الموجهة إلى عضو مستهدف - عند تكرار التعرض

STOT-SE = السمية الموجهة إلى عضو مستهدف - عند التعرض لمرة واحدة

TWA = المتوسط الزمني المرجح

UN = الأمم المتحدة

UVCB = مادة هينزوكربونونية مركبة

الـ VOC = مُركب عضوي مُتطاير

vPvB = شديد البقاء وشديد التراكم البيولوجي

متنوع = قد يحتوي على واحد أو أكثر من المكونات التالية 4-64741-88 / RRN 23-06-64741-89-5 / 01-2119488706-23

/64741-96-4, 01-2119487081-40 RRN / 64741-95-3, 01-2119487067-30 RRN

/ 64742-44-5, 01-2119488707-21 RRN / 64742-01-4, 01-2119483621-38 RRN

/ 64742-53-6, 01-2119467170-45 RRN / 64742-52-5, 64742-45-6, 01-2119985177-24 RRN

/ 64742-55-8, 01-2119484627-25 RRN / 64742-54-7, 01-2119480375-34 RRN

/ 64742-57-0, 01-2119480132-48 RRN / 64742-56-9, 01-2119487077-29 RRN

,64742-63-8, 01-2119480472-38 RRN / 64742-62-7, 64742-58-1, 01-2119489287-22 RRN

/ 72623-85-9, 01-2119487080-42 RRN / 64742-70-7, 01-2119471299-27 RRN / 64742-65-0

/ 72623-87-1, 01-2119474878-16 RRN / 72623-86-0, 01-2119555262-43 RRN

01-2119474889-13 RRN

الإجراء المُستخدم لاشتقاق التصنيف بحسب تنظيم (المفوضية الأوروبية) رقم 1272/2008 [النظام المتوائم عالمياً (GHS)/التصنيف والوسم والتعبئة (CLP)]

Product name Castrol Transmax Manual 90

Product code 469621-AE02

Page: 18/19

Version 1 Date of issue 11 May 2020

Format Africa Northern (Africa Northern)

Language ENGLISH

القسم 16: المعلومات الأخرى

التصنيف	التبرير
غير مُصنّفة.	

نص بيانات الأخطار المُختصرة كاملاً غير قابل للتطبيق.

نص التصنيفات كاملاً [التصنيف والوسم والتعبئة (CLP)] النظام المتوائم عالمياً (GHS) السيرة

تاريخ الإصدار/ تاريخ المراجعة 11/05/2020.

تاريخ الإصدار السابق

من إعداد Product Stewardship

تشير إلى معلومات تم تغييرها مقارنة بالنسخة التي سبق إصدارها.

ملاحظة للقارئ الكريم

تم اتخاذ جميع الخطوات المتاحة المعقولة لضمان دقة نشرة البيانات هذه والمعلومات المتعلقة بالصحة والأمان والبيئة حسب البيانات الموضحة أدناه. لا يوجد ضمان أو تفويض، صريح أو ضمني، بشأن دقة أو اكتمال البيانات والمعلومات الواردة في نشرة البيانات هذه.

تسري البيانات والنصائح المعطاة في حالة بيع المنتج للتطبيق المذكور أو التطبيقات المذكورة. لا يجوز لك استخدام المنتج في غير التطبيق المذكور أو التطبيقات المذكورة دون طلب المشورة من شركة Group BP.

يجب على المستخدم تقييم هذا المنتج واستخدامه بشكل آمن بما يتوافق مع جميع القوانين والتشريعات المعمول بها. لا تتحمل شركة Group BP أية مسؤولية عن أي ضرر أو إصابة تنتج عن الاستخدام، أو أي استخدام آخر بخلاف استخدام المنتج المذكور للخامة، أو في حالة عدم مراعاة التوصيات، أو المخاطر المتأصلة في طبيعة الخامة. القائمون بشراء المنتج لتوريده إلى طرف ثالث للاستخدام في العمل عليهم اتخاذ جميع الخطوات اللازمة للتأكد من أن أي شخص يستخدم المنتج يكون على دراية بالمعلومات الواردة في هذه النشرة. يجب على أصحاب العمل إبلاغ الموظفين لديهم وغيرهم من الأشخاص المعنيين بالمخاطر الموضحة في هذه النشرة وعن الاحتياطات الواجب اتخاذها. يمكنك الاتصال بشركة Group BP للتأكد من أن هذا المستند على أحدث وضع. ممنوع منعاً باتاً إجراء تغيير على هذا المستند.

يتفق ولانحة (المجموعة الأوروبية) رقم 1907/2006 (تشريع تقييم المواد الكيميائية وتسجيلها وإقرارها (REACH))، الملحق 2، بصيغته المعدلة بلانحة (الاتحاد الأوروبي) رقم 2015/830

اسم المنتج	تاريخ الإصدار	الشكل (شمال أفريقيا)	شمال أفريقيا	كود المنتج	الصفحة: 19/19
Castrol Transmax Manual 90	11 مايو 2020			469621-AE02	اللغة العربية