

SAFETY DATA SHEET



Castrol Transmax ATF DX III Multivehicle

Section 1. Chemical product and company identification

GHS product identifier Castrol Transmax ATF DX III Multivehicle

Product code 469689-TR01

SDS # 469689

Relevant identified uses of the substance or mixture and uses advised against

Product use Automatic transmission fluid For specific application advice see appropriate Technical Data Sheet or consult our company representative.

Supplier Castrol Madeni Yağlar Ticaret A.Ş
İçerenköy Mah. Değirmen Yolu Cad. Mengerler Blok No: 28/1 İç Kapı No: 12
Ataşehir/İstanbul

EMERGENCY TELEPHONE NUMBER CASTROL DIRECT 0212 473 77 37
Carechem: +44 (0) 1235 239 670 (24/7)
Ministry of Health National Poison Information Centre: 114 (24 hours)

Section 2. Hazards identification

Classification of the substance or mixture Not classified.

GHS label elements

Signal word No signal word.

Hazard statements No known significant effects or critical hazards.

Precautionary statements

Prevention Not applicable.

Response Not applicable.

Storage Not applicable.

Disposal Not applicable.

Other hazards which do not result in classification Defatting to the skin.

Section 3. Composition/information on ingredients

Substance/mixture Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Ingredient name	%	Identifiers	Classification	Type
Distillates (petroleum), hydrotreated heavy paraffinic	≥50 - ≤75	CAS: 64742-54-7 EC: 265-157-1	Not classified.	[2]
Distillates (petroleum), hydrotreated heavy paraffinic	≥25 - ≤50	CAS: 64742-54-7 EC: 265-157-1	ASPIRATION HAZARD - Category 1	[1]
2-Propenoic acid, 2-methyl-, butyl ester,	≤3	CAS: 176487-46-0	ACUTE TOXICITY (oral) - Category 5	[1]

Product name Castrol Transmax ATF DX III Multivehicle

Product code 469689-TR01 **Page:** 1/16

Version 3.03 **Date of issue** 10/07/2025.

Format Uzbekistan

Language ENGLISH

Uzbekistan

(ENGLISH)

Section 3. Composition/information on ingredients

polymer with N-[3-(dimethylamino)propyl]-2-methyl-2-propenamide, dodecyl 2-methyl-2-propenoate, eicosyl 2-methyl-2-propenoate, hexadecyl 2-methyl-2-propenoate and octadecyl 2-methyl-2-propenoate	≤3	CAS: 64742-55-8 EC: 265-158-7	ASPIRATION HAZARD - Category 1	[1]
Distillates (petroleum), hydrotreated light paraffinic	≤3	CAS: 64742-65-0 EC: 265-169-7	ASPIRATION HAZARD - Category 1	[1]
Distillates (petroleum), solvent-dewaxed heavy paraffinic	≤3	CAS: 64742-65-0 EC: 265-169-7	ASPIRATION HAZARD - Category 1	[1]
Bis (2-hydroxyethyl) tallow alkylamine	<0.25	CAS: 61791-44-4 EC: 620-540-6	ACUTE TOXICITY (oral) - Category 4 SKIN CORROSION/IRRITATION - Category 1C SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1	[1]
3-(isodecyloxy) propylamine	<0.1	CAS: 30113-45-2 EC: 939-485-7	ACUTE TOXICITY (oral) - Category 4 SKIN CORROSION/IRRITATION - Category 1B SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Component in composition greater than or equal to 10%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Inhalation

In case of inhalation of decomposition products in a fire, symptoms may be delayed. If inhaled, remove to fresh air. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.

Ingestion

Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Skin contact

Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.

Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Product name Castrol Transmax ATF DX III Multivehicle

Product code 469689-TR01

Page: 2/16

Version 3.03 **Date of issue** 10/07/2025.

Format Uzbekistan

Language ENGLISH

Uzbekistan

(ENGLISH)

Section 4. First aid measures

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Specific treatments	No specific treatment.
Notes to physician	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Treatment should in general be symptomatic and directed to relieving any effects.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet.

Specific hazards arising from the chemical In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products Combustion products may include the following:
carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)
nitrogen oxides (NO, NO₂ etc.)

Special protective actions for fire-fighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Advice on general occupational hygiene

Put on appropriate personal protective equipment (see Section 8).

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. Contaminated work clothing should not be allowed out of the workplace. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Not suitable

Prolonged exposure to elevated temperature

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None.

Biological exposure indices

No exposure indices known.

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety glasses with side shields.

Skin protection

Section 8. Exposure controls/personal protection

Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Body protection

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state

Liquid.

Colour

Red. [Light]

Odour

Not available.

Odour threshold

Not available.

pH

Not applicable.

Melting point

Not available.

Boiling point or initial boiling point and boiling range

Not available.

Flash point

Open cup: >170°C (>338°F) [Cleveland ASTM D 92]

Evaporation rate

Not available.

Flammability

Not available.

Lower and upper explosion limit/flammability limit

Not available.

Vapour pressure

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191			
Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191			
Distillates (petroleum), hydrotreated light	<0.07501	<0.01	ASTM D 5191			

Product name Castrol Transmax ATF DX III Multivehicle

Product code 469689-TR01 **Page:** 5/16

Version 3.03 **Date of issue** 10/07/2025.

Format Uzbekistan

Language ENGLISH

Uzbekistan

(ENGLISH)

Section 9. Physical and chemical properties

	paraffinic					
	Distillates (petroleum), solvent-dewaxed heavy paraffinic	<0.07501	<0.01	ASTM D 5191		

Relative vapour density

Not available.

Relative density

Not available.

Density

<1000 kg/m³ (<1 g/cm³) at 15°C

Solubility(ies)

Media	Result
water	Not soluble

Partition coefficient: n-octanol/water

Not applicable.

Auto-ignition temperature

Not available.

Decomposition temperature

Not available.

Viscosity

Kinematic: 35 mm²/s (35 cSt) at 40°C
Kinematic: 6.8 to 8 mm²/s (6.8 to 8 cSt) at 100°C

Particle characteristics

Median particle size

Not applicable.

Section 10. Stability and reactivity

Reactivity

No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.

Chemical stability

The product is stable.

Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.
Under normal conditions of storage and use, hazardous polymerisation will not occur.

Conditions to avoid

Avoid all possible sources of ignition (spark or flame).

Incompatible materials

Reactive or incompatible with the following materials: oxidising materials.

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Result

Rat - Oral - LD50

>5000 mg/kg
OECD 401

Rabbit - Dermal - LD50

>5000 mg/kg
OECD 402

Rat - Inhalation - LC50 Dusts and mists

>5 mg/l [4 hours]
OECD 403

Distillates (petroleum), hydrotreated heavy paraffinic

Rat - Oral - LD50

>5000 mg/kg
OECD 401

Product name Castrol Transmax ATF DX III Multivehicle

Product code 469689-TR01 **Page: 6/16**

Version 3.03 **Date of issue** 10/07/2025.

Format Uzbekistan

Language ENGLISH

Uzbekistan

(ENGLISH)

Section 11. Toxicological information

Distillates (petroleum), hydrotreated light paraffinic

Rabbit - Dermal - LD50

>5000 mg/kg

OECD 402

Rat - Inhalation - LC50 Dusts and mists

>5 mg/l [4 hours]

OECD 403

Rat - Oral - LD50

>5000 mg/kg

OECD 401

Rabbit - Dermal - LD50

>5000 mg/kg

OECD 402

Rat - Inhalation - LC50 Dusts and mists

>5.53 mg/l [4 hours]

OECD 403

Rat - Oral - LD50

>5000 mg/kg

OECD 401

Rat - Dermal - LD50

>2000 mg/kg

OECD 402

Rat - Inhalation - LC50 Dusts and mists

>5.53 mg/l [4 hours]

OECD 403

Rat - Oral - LD50

1350 mg/kg

OECD 401

Rat - Oral - LC50

500 to 2000 mg/kg

OECD 401

Rabbit - Dermal - LC50

>2000 mg/kg

OECD 402

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Bis (2-hydroxyethyl) tallow alkylamine

3-(isodecyloxy)propylamine

Skin corrosion/irritation

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), hydrotreated light paraffinic

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Bis (2-hydroxyethyl) tallow alkylamine

3-(isodecyloxy)propylamine

Result

Rabbit - Skin - Mild irritant

OECD 404

Rabbit - Skin - Mild irritant

OECD 404

Rabbit - Skin - Non-irritant to skin.

Rabbit - Skin - Non-irritant to skin.

Rabbit - Skin - Corrosive

OECD 404

Rabbit - Skin - Corrosive

OECD 404

Serious eye damage/eye irritation

Product/ingredient name

Result

Section 11. Toxicological information

Distillates (petroleum), hydrotreated heavy paraffinic
Distillates (petroleum), hydrotreated heavy paraffinic
Distillates (petroleum), hydrotreated light paraffinic
Distillates (petroleum), solvent-dewaxed heavy paraffinic
3-(isodecyloxy)propylamine

Rabbit - Eyes - Non-irritating to the eyes.
OECD 405
Rabbit - Eyes - Non-irritating to the eyes.
OECD 405
Rabbit - Eyes - Non-irritating to the eyes.
OECD 405
Rabbit - Eyes - Non-irritating to the eyes.
OECD 405
BCOP - Eyes - Severe irritant
OECD 437

Respiratory corrosion/irritation

Not available.

Respiratory or skin sensitization

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), hydrotreated light paraffinic

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Bis (2-hydroxyethyl) tallow alkylamine

Result

Guinea pig - skin
OECD 406
Result: Not sensitising
Guinea pig - skin
OECD 406
Result: Not sensitising
Guinea pig - skin
OECD 406
Result: Not sensitising
Guinea pig - skin
OECD 406
Result: Not sensitising
Guinea pig - skin
OECD 406
Result: Not sensitising

Germ cell mutagenicity

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), hydrotreated heavy paraffinic

Result

In vitro - Bacteria
Bacterial Reverse Mutation Test
Result: Negative
In vitro - Mammal - species unspecified
In vitro Mammalian Chromosomal Aberration Test
Result: Negative
In vivo - Mammal - species unspecified
Mammalian Erythrocyte Micronucleus Test
Result: Negative
In vitro - Mammal - species unspecified
In vitro Mammalian Cell Gene Mutation Test
Result: Negative
In vitro - Bacteria
Bacterial Reverse Mutation Test
Result: Negative
In vitro - Mammal - species unspecified
In vitro Mammalian Chromosomal Aberration Test
Result: Negative

Section 11. Toxicological information

Distillates (petroleum), hydrotreated light paraffinic

In vivo - Mammal - species unspecified

Mammalian Erythrocyte Micronucleus Test

Result: Negative

In vitro - Mammal - species unspecified

In vitro Mammalian Cell Gene Mutation Test

Result: Negative

In vitro - Bacteria

OECD [Bacterial Reverse Mutation Test]

Result: Negative

In vitro - Mammal - species unspecified

OECD [In vitro Mammalian Chromosomal Aberration Test]

Result: Negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic

In vitro - Bacteria

OECD [Bacterial Reverse Mutation Test]

Result: Negative

In vitro - Mammal - species unspecified

OECD [In vitro Mammalian Chromosomal Aberration Test]

Result: Negative

Bis (2-hydroxyethyl) tallow alkylamine

In vitro - Bacteria

OECD [Bacterial Reverse Mutation Test]

Result: Negative

In vitro - Mammal - species unspecified

OECD [In vitro Mammalian Cell Gene Mutation Test]

Result: Negative

In vitro - Mammalian-Human

OECD [In vitro Mammalian Chromosomal Aberration Test]

Result: Negative

3-(isodecyloxy)propylamine

In vitro - Bacteria

OECD 471

Result: Negative

In vivo - Mammal - species unspecified

OECD 474

Result: Negative

Carcinogenicity

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Result

Mouse - Dermal - Unspecified

OECD 451

Result: Negative

Distillates (petroleum), hydrotreated heavy paraffinic

Mouse - Dermal - Unspecified

OECD 451

Result: Negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Mouse - Dermal - Unspecified

OECD 451

Result: Negative

Reproductive toxicity

Product/ingredient name

Result

Section 11. Toxicological information

Distillates (petroleum), hydrotreated heavy paraffinic

Rat - Oral
OECD 421
Maternal toxicity: Negative
Fertility effects: Negative
Developmental: Negative

Distillates (petroleum), hydrotreated heavy paraffinic

Rat - Oral
OECD 421
Maternal toxicity: Negative
Fertility effects: Negative
Developmental: Negative

Distillates (petroleum), hydrotreated light paraffinic

Rat - Oral
OECD 421
Maternal toxicity: Negative
Fertility effects: Negative
Developmental: Negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Rat - Oral
OECD 421
Maternal toxicity: Negative
Fertility effects: Negative
Developmental: Negative

Bis (2-hydroxyethyl) tallow alkylamine

Rat - Oral
OECD 422
Maternal toxicity: Positive
Fertility effects: Equivocal
Developmental: Equivocal

3-(isodecyloxy)propylamine

Rat - Oral
OECD 422
Maternal toxicity: Negative
Fertility effects: Negative
Developmental: Negative

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Distillates (petroleum), hydrotreated heavy paraffinic

ASPIRATION HAZARD - Category 1

Distillates (petroleum), hydrotreated light paraffinic

ASPIRATION HAZARD - Category 1

Distillates (petroleum), solvent-dewaxed heavy paraffinic

ASPIRATION HAZARD - Category 1

Potential acute health effects

Eye contact

No known significant effects or critical hazards.

Inhalation

Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Skin contact

Defatting to the skin. May cause skin dryness and irritation.

Ingestion

No known significant effects or critical hazards.

Название продукта/ингредиента

Результат

Product name Castrol Transmax ATF DX III Multivehicle

Product code 469689-TR01 **Page: 10/16**

Version 3.03 **Date of issue** 10/07/2025.

Format Uzbekistan

Language ENGLISH

Uzbekistan

(ENGLISH)

Section 11. Toxicological information

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	No specific data.
Inhalation	May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
Skin contact	Adverse symptoms may include the following: irritation dryness cracking
Ingestion	No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
<u>Potential chronic health effects</u>	
General	No known significant effects or critical hazards.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	
Oral	ATE _{8/90} 8418 mg/kg

Section 12. Ecological information

Environmental effects No known significant effects or critical hazards.

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Result

Acute - EL50

OECD 201

Algae

>100 mg/l [72 hours]

Acute - EL50

OECD 202

Daphnia

>10000 mg/l [48 hours]

Acute - LL50

OECD 203

Fish

>100 mg/l [96 hours]

Chronic - NOEL

OECD 201

Algae

≥100 mg/l [72 hours]

Chronic - NOEL

OECD 211

Daphnia

10 mg/l [21 days]

Distillates (petroleum), hydrotreated heavy

Acute - EL50

Product name Castrol Transmax ATF DX III Multivehicle

Product code 469689-TR01

Page: 11/16

Version 3.03 **Date of issue** 10/07/2025.

Format Uzbekistan

Language ENGLISH

Uzbekistan

(ENGLISH)

Section 12. Ecological information

paraffinic	OECD 201 Algae >100 mg/l [72 hours] Acute - EL50 OECD 202 Daphnia >10000 mg/l [48 hours] Acute - LL50 OECD 203 Fish >100 mg/l [96 hours] Chronic - NOEL OECD 201 Algae ≥100 mg/l [72 hours] Chronic - NOEL OECD 211 Daphnia 10 mg/l [21 days] Acute - EL50
Distillates (petroleum), hydrotreated light paraffinic	OECD 201 Algae >100 mg/l [72 hours] Acute - EL50 OECD 202 Daphnia >10000 mg/l [48 hours] Acute - LL50 OECD 203 Fish >100 mg/l [96 hours] Chronic - NOEL OECD 201 Algae ≥100 mg/l [72 hours] Chronic - NOEL OECD 211 Daphnia 10 mg/l [21 days] Acute - EL50
Distillates (petroleum), solvent-dewaxed heavy paraffinic	OECD 201 Algae >100 mg/l [72 hours] Acute - EL50 OECD 202 Daphnia >10000 mg/l [48 hours] Acute - LL50 OECD 203 Fish >100 mg/l [96 hours] Chronic - NOEL OECD 201 Algae ≥100 mg/l [72 hours] Chronic - NOEL OECD 211 Daphnia 10 mg/l [21 days]

Section 12. Ecological information

Bis (2-hydroxyethyl) tallow alkylamine

Acute - EC50

OECD 201

Algae

0.0538 mg/l [72 hours]

Acute - EC50

OECD 202

Daphnia

0.043 mg/l [48 hours]

Acute - LC50

OECD 203

Fish

0.1 mg/l [96 hours]

Chronic - EC10

OECD 201

Algae

0.0156 mg/l [72 hours]

Chronic - EC10

OECD 211

Daphnia

0.0107 mg/l [21 days]

3-(isodecyloxy)propylamine

Acute - EC50

OECD 201

Algae

0.0544 mg/l [72 hours]

Acute - EC50

OECD 202

Daphnia

1.05 mg/l [48 hours]

Acute - LC50

OECD 203

Fish

2.14 mg/l [96 hours]

Chronic - ErC10

OECD 201

Algae

0.0421 mg/l [72 hours]

Chronic - EC10

OECD 211

Daphnia

0.738 mg/l [21 days]

Persistence and degradability

Not expected to be rapidly degradable.

Product/ingredient name

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), hydrotreated light paraffinic

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Bis (2-hydroxyethyl) tallow alkylamine

3-(isodecyloxy)propylamine

Result

OECD 301F

31% [28 days] - Not readily

OECD 301F

31% [28 days] - Not readily

OECD 301F

31% [28 days] - Not readily

OECD 301F

31% [28 days] - Not readily

OECD 301D

61 to 65% [28 days] - Readily

OECD 301D

68% [28 days]

Bioaccumulative potential

Product name Castrol Transmax ATF DX III Multivehicle

Product code 469689-TR01

Page: 13/16

Version 3.03 **Date of issue** 10/07/2025.

Format Uzbekistan

Language ENGLISH

Uzbekistan

(ENGLISH)

Section 12. Ecological information

This product is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name

Bis (2-hydroxyethyl) tallow alkylamine

LogP_{ow}

3.6

BCF

-

Potential

Low

Mobility in soil

Soil/water partition coefficient

Not available.

Mobility

Spillages may penetrate the soil causing ground water contamination.

Other adverse effects

No known significant effects or critical hazards.

Other ecological information

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	IMDG	IATA
UN number	Not regulated.	Not regulated.
UN proper shipping name	-	-
Transport hazard class(es)	-	-
Packing group	-	-
Environmental hazards	No.	No.
Additional information	-	-

Special precautions for user

Not available.

Section 15. Regulatory information

Regulation according to other foreign laws

REACH Status	For the REACH status of this product please consult your company contact, as identified in Section 1.
United States inventory (TSCA 8b)	All components are active or exempted.
Australia inventory (AIC)	All components are listed or exempted.
Canada inventory	All components are listed or exempted.
China inventory (IECSC)	Not determined.
Japan inventory (CSCL)	At least one component is not listed.
Korea inventory (KECI)	All components are listed or exempted.
Philippines inventory (PICCS)	Not determined.
Taiwan Chemical Substances Inventory (TCSI)	Not determined.

Section 16. Other information

History

Date of printing	10/7/2025
Date of issue/Date of revision	10/7/2025
Date of previous issue	10/7/2025
Version	3.03
Prepared by	Product Stewardship
Key to abbreviations	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006] UN = United Nations Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1
References	Not available.

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the

Product name	Castrol Transmax ATF DX III Multivehicle	Product code	469689-TR01	Page:	15/16
Version	3.03	Date of issue	10/07/2025.	Format	Uzbekistan
				Language	ENGLISH
					(ENGLISH)

Section 16. Other information

material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.