

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

<b>Product name</b>	Castrol Transmax Manual V 75W-80
<b>Product code</b>	469686-DE01
<b>SDS #</b>	469686
<b>Product type</b>	Liquid.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses
General use of lubricants and greases in vehicles or machinery-Industrial
General use of lubricants and greases in vehicles or machinery-Professional

<b>Use of the substance/ mixture</b>	Manual transmission fluid. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------

### 1.3 Details of the supplier of the safety data sheet

<b>Supplier</b>	Castrol Holdings Europe B.V., d'Arcyweg 76, 3198NA Europoort Rotterdam
	Castrol Belgium BV, Langerbuggerkaai 18, 9000 Gent
	+32 (0)800 49312
<b>E-mail address</b>	MSDSadvice@bp.com

### 1.4 Emergency telephone number

<b>EMERGENCY TELEPHONE NUMBER</b>	Carechem: +44 (0) 1235 239 670 (24/7)
---------------------------------------	---------------------------------------

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

<b>Product definition</b>	Mixture
<b>Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]</b>	Aquatic Chronic 2, H411

See Section 16 for the full text of the H statements declared above.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

### 2.2 Label elements

#### Hazard pictograms



<b>Signal word</b>	No signal word.
<b>Hazard statements</b>	H411 - Toxic to aquatic life with long lasting effects.
<b>Precautionary statements</b>	
<b>General</b>	P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand.
<b>Prevention</b>	P273 - Avoid release to the environment.
<b>Response</b>	P391 - Collect spillage.
<b>Storage</b>	Not applicable.

<b>Product name</b>	Castrol Transmax Manual V 75W-80	<b>Product code</b>	469686-DE01	<b>Page:</b>	1/22
<b>Version</b>	10	<b>Date of issue</b>	3 October 2025	<b>Format</b>	Slovenia (Slovenia)
<b>Date of previous issue</b>	10 July 2025.	<b>Language</b>	ENGLISH		

## SECTION 2: Hazards identification

<b>Disposal</b>	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
<b>Hazardous ingredients</b>	Not applicable.
<b>Supplemental label elements</b>	Contains Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl. May produce an allergic reaction.

### EU Regulation (EC) No. 1907/2006 (REACH)

<b>Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles</b>	Not applicable.
-------------------------------------------------------------------------------------------------------------------------------------------	-----------------

### Special packaging requirements

<b>Containers to be fitted with child-resistant fastenings</b>	Not applicable.
<b>Tactile warning of danger</b>	Not applicable.

### 2.3 Other hazards

<b>Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII</b>	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
<b>Product meets the criteria for endocrine disrupting properties according to Regulation (EC) No. 1907/2006.</b>	<input checked="" type="checkbox"/> This substance/mixture does not contain any components that are considered to have endocrine disrupting properties.
<b>Other hazards which do not result in classification</b>	Defatting to the skin.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

**Product definition** Mixture  
 Synthetic base stock. Proprietary performance additives.

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
<input checked="" type="checkbox"/> Decene, homopolymer, hydrogenated	REACH #: 01-2119486452-34 EC: 500-183-1 CAS: 68037-01-4	≥10 - ≤25	Asp. Tox. 1, H304	-	[1]
Dec-1-ene, trimers, hydrogenated	REACH #: 01-2119486452-34 EC: 500-393-3 CAS: 157707-86-3	≥10 - ≤25	Asp. Tox. 1, H304	-	[1]
Dec-1-ene, trimers, hydrogenated	REACH #: 01-2119493949-12 EC: 500-393-3 CAS: 157707-86-3	≥10 - ≤25	Asp. Tox. 1, H304	-	[1]
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl	REACH #: 01-2119493620-38 EC: 931-384-6 CAS: -	≤3	Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 2, H411	ATE [Oral] = 500 mg/kg Eye Irrit. 2, H319: C ≥ 50% Skin Sens. 1, H317: C ≥ 9.39%	[1]
Distillates (petroleum), hydrotreated light paraffinic	REACH #: 01-2119487077-29 EC: 265-158-7 CAS: 64742-55-8 Index: 649-468-00-3	≤3	Asp. Tox. 1, H304	-	[1] [2]
Distillates (petroleum), hydrotreated heavy paraffinic	REACH #: 01-2119484627-25 EC: 265-157-1	≤3	Not classified.	-	[2]

<b>Product name</b> Castrol Transmax Manual V 75W-80	<b>Product code</b> 469686-DE01	<b>Page:</b> 2/22
<b>Version</b> 10	<b>Date of issue</b> 3 October 2025	<b>Format</b> Slovenia
<b>Date of previous issue</b> 10 July 2025.		<b>Language</b> ENGLISH
	<b>(Slovenia)</b>	

## SECTION 3: Composition/information on ingredients

(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	CAS: 64742-54-7 Index: 649-467-00-8 REACH #: 01-2119473797-19 EC: 627-034-4 CAS: 1213789-63-9	≤0.3	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 500 mg/ [1] kg M [Acute] = 10 M [Chronic] = 10
isodecyl methacrylate	REACH #: 01-2119894925-17 EC: 249-978-2 CAS: 29964-84-9 Index: 607-134-00-4	≤0.3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 1, H410	STOT SE 3, H335: C [1] ≥ 10% M [Chronic] = 1
dec-1-ene	REACH #: 01-2119457739-21 EC: 212-819-2 CAS: 872-05-9	≤0.3	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH066	M [Acute] = 1 [1] M [Chronic] = 1

See Section 16 for the full text of the H statements declared above.

### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.

#### Skin contact

Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.

#### Inhalation

If inhaled, remove to fresh air. Get medical attention if symptoms occur.

#### Ingestion

Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if symptoms occur.

#### Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

#### Potential acute health effects

##### Inhalation

Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.

##### Ingestion

No known significant effects or critical hazards.

##### Skin contact

Defatting to the skin. May cause skin dryness and irritation.

##### Eye contact

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

##### Inhalation

Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

##### Ingestion

Ingestion of large quantities may cause nausea and diarrhoea.

##### Skin contact

Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

##### Eye contact

Potential risk of transient stinging or redness if accidental eye contact occurs.

### 4.3 Indication of any immediate medical attention and special treatment needed

#### Notes to physician

Treatment should in general be symptomatic and directed to relieving any effects.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media**

Use foam or all-purpose dry chemical to extinguish.

**Unsuitable extinguishing media**

Do not use water jet. The use of a water jet may cause the fire to spread by splashing the burning product.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture**

In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous combustion products**

Combustion products may include the following:  
carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)

### 5.3 Advice for firefighters

**Special precautions for fire-fighters**

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. This material is toxic to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Special protective equipment for fire-fighters**

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel**

Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment.

**For emergency responders**

Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

**Small spill**

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill**

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

### 6.4 Reference to other sections

See Section 1 for emergency contact information.  
See Section 5 for firefighting measures.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 12 for environmental precautions.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

<b>Product name</b> Castrol Transmax Manual V 75W-80	<b>Product code</b> 469686-DE01	<b>Page:</b> 4/22
<b>Version</b> 10 <b>Date of issue</b> 3 October 2025	<b>Format</b> Slovenia	<b>Language</b> ENGLISH
<b>Date of previous issue</b> 10 July 2025.	<b>(Slovenia)</b>	

## SECTION 7: Handling and storage

<b>Protective measures</b>	Put on appropriate personal protective equipment. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid contact of spilt material and runoff with soil and surface waterways. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Empty containers retain product residue and can be hazardous.
<b>Advice on general occupational hygiene</b>	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
<b>7.2 Conditions for safe storage, including any incompatibilities</b>	Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/containers designed for use with this product. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.
<b>Not suitable</b>	Prolonged exposure to elevated temperature
<b>7.3 Specific end use(s)</b>	
<b>Recommendations</b>	See section 1.2 and Exposure scenarios in annex, if applicable.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
Distillates (petroleum), hydrotreated light paraffinic	<b>Regulation on the protection of workers from the risks related to exposure to carcinogens, mutagens or reprotoxic substances at work (Slovenia) [mineralna olja]</b> Absorbed through skin.
Distillates (petroleum), hydrotreated heavy paraffinic	<b>Regulation on the protection of workers from the risks related to exposure to carcinogens, mutagens or reprotoxic substances at work (Slovenia) [mineralna olja]</b> Absorbed through skin.

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

**Recommended monitoring procedures** Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### Biological exposure indices

Product/ingredient name	Exposure indices
No exposure indices known.	

#### DNELs/DMELs

Not available.

#### PNECs

Not available.

### 8.2 Exposure controls

**Appropriate engineering controls** Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and

<b>Product name</b> Castrol Transmax Manual V 75W-80	<b>Product code</b> 469686-DE01	<b>Page:</b> 5/22
<b>Version</b> 10	<b>Date of issue</b> 3 October 2025	<b>Format</b> Slovenia
<b>Date of previous issue</b> 10 July 2025.		<b>Language</b> ENGLISH
	<b>(Slovenia)</b>	

**SECTION 8: Exposure controls/personal protection**

appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

**Individual protection measures**

**Hygiene measures**

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

**Respiratory protection**

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

**Eye/face protection**

Safety glasses with side shields.

**Skin protection**

**Hand protection**

**General Information:**

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile gloves.

**Breakthrough time:**

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type.

Our recommendations on the selection of gloves are as follows:

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained.

If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.

It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

**Glove Thickness:**

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.

<b>Product name</b> Castrol Transmax Manual V 75W-80	<b>Product code</b> 469686-DE01	<b>Page:</b> 6/22
<b>Version</b> 10	<b>Date of issue</b> 3 October 2025	<b>Format</b> Slovenia
<b>Date of previous issue</b> 10 July 2025.		<b>Language</b> ENGLISH
	<b>(Slovenia)</b>	

## SECTION 8: Exposure controls/personal protection

- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

### Skin and body

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

### Refer to standards:

Respiratory protection: EN 529  
 Gloves: EN 420, EN 374  
 Eye protection: EN 166  
 Filtering half-mask: EN 149  
 Filtering half-mask with valve: EN 405  
 Half-mask: EN 140 plus filter  
 Full-face mask: EN 136 plus filter  
 Particulate filters: EN 143  
 Gas/combined filters: EN 14387

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

**Physical state** Liquid.  
**Colour** Amber.  
**Odour** Not available.  
**Odour threshold** Not available.  
**Melting point/freezing point** Not available.  
**Initial boiling point and boiling range** Not available.  
**Flammability** Not available.  
**Lower and upper explosion limit** Not available.  
**Flash point**  Open cup: >200°C (>392°F) [Cleveland DIN EN ISO 2592]  
**Auto-ignition temperature**

Ingredient name	°C	°F	Method
1-Decene, homopolymer, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159
Dec-1-ene, homopolymer, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	343 to 369	649.4 to 696.2	ASTM D 2159

**Decomposition temperature** Not available.  
**pH** Not applicable.  
**Kinematic viscosity**  Kinematic: 40 mm<sup>2</sup>/s (40 cSt) at 40°C  
 Kinematic: 7.5 to 8.5 mm<sup>2</sup>/s (7.5 to 8.5 cSt) at 100°C

### Solubility

Media	Result
water	Not soluble

**Partition coefficient n-octanol/water (log value)** Not applicable.  
**Vapour pressure**

**SECTION 9: Physical and chemical properties**

Ingredient name	Vapour Pressure at 20 °C			Vapour pressure at 50 °C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Decene, homopolymer, hydrogenated	<0.0041	<0.00055	ASTM E 1194-87			
Dec-1-ene, homopolymer, hydrogenated	<0.0041	<0.00055	ASTM E 1194-87			
Dec-1-ene, homopolymer, hydrogenated Dec-1-ene, oligomers, hydrogenated	<0.0041	<0.00055	ASTM E 1194-87			
Distillates (petroleum), hydrotreated light paraffinic	<0.07501	<0.01	ASTM D 5191			
Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191			

**Density and/or Relative density** <1000 kg/m<sup>3</sup> (<1 g/cm<sup>3</sup>) at 15°C

**Relative vapour density** Not available.

**Particle characteristics**

**Median particle size** Not applicable.

**9.2 Other information**

**Evaporation rate** Not available.

**Explosive properties** Not available.

**Oxidising properties** Not available.

**Pour point** -60 °C

**SECTION 10: Stability and reactivity**

**10.1 Reactivity** No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.

**10.2 Chemical stability** The product is stable.

**10.3 Possibility of hazardous reactions** Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.

**10.4 Conditions to avoid** Avoid all possible sources of ignition (spark or flame).

**10.5 Incompatible materials** Reactive or incompatible with the following materials: oxidising materials.

**10.6 Hazardous decomposition products** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**SECTION 11: Toxicological information**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute toxicity

**Product/ingredient name**

Dec-1-ene, homopolymer, hydrogenated

**Result**

**Rat - Oral - LD50**

>5000 mg/kg  
OECD 423

**Rat - Dermal - LD50**

>2000 mg/kg  
OECD 402

**Rat - Inhalation - LD50 Dusts and mists**

>5.2 mg/l [4 hours]  
OECD 403

Dec-1-ene, trimers, hydrogenated

**Rat - Oral - LD50**

>5000 mg/kg

**Product name** Castrol Transmax Manual V 75W-80

**Product code** 469686-DE01

**Page:** 8/22

**Version** 10 **Date of issue** 3 October 2025

**Format** Slovenia

**Language** ENGLISH

**Date of previous issue** 10 July 2025.

(Slovenia)

**SECTION 11: Toxicological information**

OECD 423

**Rat - Dermal - LD50**

>2000 mg/kg  
OECD 402

**Rat - Inhalation - LD50 Dusts and mists**

>5.2 mg/l [4 hours]  
OECD 403

Dec-1-ene, trimers, hydrogenated

**Rat - Oral - LD50**

>5000 mg/kg  
OECD 423

**Rat - Dermal - LD50**

>2000 mg/kg  
OECD 402

**Rat - Inhalation - LD50 Dusts and mists**

>5.2 mg/l [4 hours]  
OECD 403

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl

**Rat - Oral - LD50**

2000 mg/kg  
OECD 401

Distillates (petroleum), hydrotreated light paraffinic

**Rat - Oral - LD50**

>5000 mg/kg  
OECD 401

**Rabbit - Dermal - LD50**

>5000 mg/kg  
OECD 402

**Rat - Inhalation - LC50 Dusts and mists**

>5.53 mg/l [4 hours]  
OECD 403

(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines

**Rat - Oral - LD50**

1689 mg/kg  
OECD 401

isodecyl methacrylate

**Rat - Oral - LD50**

>5000 mg/kg  
OSHA

**Rabbit - Dermal - LD50**

>3000 mg/kg  
OSHA

dec-1-ene

**Rat - Oral - LD50**

>5000 mg/kg  
OECD 401

**Rabbit - Dermal - LD50**

>2000 mg/kg  
OECD 402

**Rat - Inhalation - LD50 Vapour**

>20 mg/l [4 hours]  
OECD 403

**Acute toxicity estimates**

<b>Product name</b> Castrol Transmax Manual V 75W-80	<b>Product code</b> 469686-DE01	<b>Page:</b> 9/22
<b>Version</b> 10	<b>Date of issue</b> 3 October 2025	<b>Format</b> Slovenia
<b>Date of previous issue</b> 10 July 2025.		<b>Language</b> ENGLISH
	<b>(Slovenia)</b>	

**SECTION 11: Toxicological information**

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Castrol Transmax Manual V 75W-80	19904.2	N/A	N/A	N/A	N/A
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	500	N/A	N/A	N/A	N/A
(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	500	N/A	N/A	N/A	N/A

**Skin corrosion/irritation**

**Product/ingredient name**

**Result**

Dec-1-ene, homopolymer, hydrogenated

**Rabbit - Skin - Non-irritant to skin.**  
OECD 404

Dec-1-ene, trimers, hydrogenated

**Rabbit - Skin - Non-irritant to skin.**  
OECD 404

Dec-1-ene, trimers, hydrogenated

**Rabbit - Skin - Non-irritant to skin.**  
OECD 404

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl

**Rabbit - Skin - Non-irritant to skin.**  
OECD 404

Distillates (petroleum), hydrotreated light paraffinic

**Rabbit - Skin - Non-irritant to skin.**

(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines

**Rabbit - Skin - Visible necrosis**  
OECD 404

isodecyl methacrylate

**Rabbit - Skin - Irritant**

dec-1-ene

**Rabbit - Skin - Mild irritant**  
OECD 404

**Serious eye damage/eye irritation**

**Product/ingredient name**

**Result**

Dec-1-ene, homopolymer, hydrogenated

**Rabbit - Eyes - Non-irritating to the eyes.**  
OECD 405

Dec-1-ene, trimers, hydrogenated

**Rabbit - Eyes - Non-irritating to the eyes.**  
OECD 405

Dec-1-ene, trimers, hydrogenated

**Rabbit - Eyes - Non-irritating to the eyes.**  
OECD 405

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl

**Rabbit - Eyes - Irritant**  
FHSA 16CFR1500

Distillates (petroleum), hydrotreated light paraffinic

**Rabbit - Eyes - Non-irritating to the eyes.**  
OECD 405

(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines

**Rabbit - Eyes - Severe irritant**  
OECD 405

isodecyl methacrylate

**Rabbit - Eyes - Irritant**

dec-1-ene

**Rabbit - Eyes - Non-irritating to the eyes.**  
OECD 405

**Product name** Castrol Transmax Manual V 75W-80

**Product code** 469686-DE01

**Page:** 10/22

**Version** 10 **Date of issue** 3 October 2025

**Format** Slovenia

**Language** ENGLISH

**Date of previous issue** 10 July 2025.

(Slovenia)

**SECTION 11: Toxicological information**

Respiratory corrosion/irritation

Not available.

Respiratory or skin sensitization

**Product/ingredient name**

**Result**

Dec-1-ene, homopolymer, hydrogenated

**Guinea pig - skin**  
OECD 406  
Result: Not sensitising

Dec-1-ene, trimers, hydrogenated

**Guinea pig - skin**  
OECD 406  
Result: Not sensitising

Dec-1-ene, trimers, hydrogenated

**Guinea pig - skin**  
OECD 406  
Result: Not sensitising

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl

**Mouse - skin**  
OECD 429  
Result: Sensitising

Distillates (petroleum), hydrotreated light paraffinic

**Guinea pig - skin**  
OECD 406  
Result: Not sensitising

isodecyl methacrylate

**Mouse - skin**  
OECD 429  
Result: Not sensitising

dec-1-ene

**Guinea pig - skin**  
OECD 406  
Result: Not sensitising

Germ cell mutagenicity

**Product/ingredient name**

**Result**

Dec-1-ene, homopolymer, hydrogenated

**In vitro - Bacteria**  
OECD [Bacterial Reverse Mutation Test]  
Result: Negative

**In vitro - Mammal - species unspecified**  
OECD [In vitro Mammalian Chromosomal Aberration Test]  
Result: Negative

**In vivo - Mammal - species unspecified**  
OECD [Mammalian Erythrocyte Micronucleus Test]  
Result: Negative

Dec-1-ene, trimers, hydrogenated

**In vitro - Bacteria**  
OECD [Bacterial Reverse Mutation Test]  
Result: Negative

**In vitro - Mammal - species unspecified**  
OECD [In vitro Mammalian Chromosomal Aberration Test]  
Result: Negative

**In vivo - Mammal - species unspecified**  
OECD [Mammalian Erythrocyte Micronucleus Test]  
Result: Negative

Dec-1-ene, trimers, hydrogenated

**In vitro - Bacteria**  
OECD [Bacterial Reverse Mutation Test]  
Result: Negative

**In vitro - Mammal - species unspecified**

**SECTION 11: Toxicological information**

	OECD [In vitro Mammalian Chromosomal Aberration Test] <u>Result:</u> Negative
	<b>In vivo - Mammal - species unspecified</b> OECD [Mammalian Erythrocyte Micronucleus Test] <u>Result:</u> Negative
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	<b>In vitro - Bacteria</b> OECD 471 <u>Result:</u> Negative
	<b>In vitro - Mammal - species unspecified</b> OECD 476 <u>Result:</u> Negative
	<b>In vitro - Unspecified - Somatic</b> OECD 474 <u>Result:</u> Negative
Distillates (petroleum), hydrotreated light paraffinic	<b>In vitro - Bacteria</b> OECD [Bacterial Reverse Mutation Test] <u>Result:</u> Negative
	<b>In vitro - Mammal - species unspecified</b> OECD [In vitro Mammalian Chromosomal Aberration Test] <u>Result:</u> Negative
(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	<b>In vitro - Bacteria</b> OECD 471 <u>Result:</u> Negative
	<b>In vitro - Unspecified</b> OECD 473 <u>Result:</u> Negative
	<b>In vitro - Mammal - species unspecified</b> OECD 476 <u>Result:</u> Negative
isodecyl methacrylate	<b>In vitro - Bacteria</b> OECD 471 <u>Result:</u> Negative
	<b>In vitro - Unspecified</b> OECD 473 <u>Result:</u> Negative
	<b>In vitro - Mammal - species unspecified</b> Equivalent to OECD 476 <u>Result:</u> Negative
dec-1-ene	<b>In vitro - Bacteria</b> OECD 471 <u>Result:</u> Negative
	<b>In vitro - Mammalian-Animal</b> OECD 473 <u>Result:</u> Negative
	<b>In vivo - Mammalian-Animal</b> OECD 474 <u>Result:</u> Negative

**Carcinogenicity**

Not available.

**Reproductive toxicity**

**Product/ingredient name**

**Result**

<b>Product name</b> Castrol Transmax Manual V 75W-80	<b>Product code</b> 469686-DE01	<b>Page:</b> 12/22
<b>Version</b> 10	<b>Date of issue</b> 3 October 2025	<b>Format</b> Slovenia
<b>Date of previous issue</b> 10 July 2025.		<b>Language</b> ENGLISH
		<b>(Slovenia)</b>

**SECTION 11: Toxicological information**

Dec-1-ene, homopolymer, hydrogenated	<b>Rat - Oral</b> OECD 415 <u>Maternal toxicity:</u> Negative <u>Fertility effects:</u> Negative <u>Developmental:</u> Negative
Dec-1-ene, trimers, hydrogenated	<b>Rat - Oral</b> OECD 415 <u>Maternal toxicity:</u> Negative <u>Fertility effects:</u> Negative <u>Developmental:</u> Negative
Dec-1-ene, trimers, hydrogenated	<b>Rat - Oral</b> OECD 415 <u>Maternal toxicity:</u> Negative <u>Fertility effects:</u> Negative <u>Developmental:</u> Negative
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	<b>Rat - Oral</b> OECD 421 <u>Maternal toxicity:</u> Positive <u>Fertility effects:</u> Negative <u>Developmental:</u> Negative
Distillates (petroleum), hydrotreated light paraffinic	<b>Rat - Oral</b> OECD 421 <u>Maternal toxicity:</u> Negative <u>Fertility effects:</u> Negative <u>Developmental:</u> Negative
(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	<b>Rat - Oral</b> OECD 421 <u>Maternal toxicity:</u> Positive <u>Fertility effects:</u> Negative <u>Developmental:</u> Negative
isodecyl methacrylate	<b>Rat - Oral</b> OECD 422 <u>Maternal toxicity:</u> Negative <u>Fertility effects:</u> Negative <u>Developmental:</u> Negative
dec-1-ene	<b>Rat - Oral</b> OECD 422 <u>Maternal toxicity:</u> Negative <u>Fertility effects:</u> Negative <u>Developmental:</u> Negative

**Specific target organ toxicity (single exposure)**

<b>Product/ingredient name</b>	<b>Result</b>
Dec-1-ene, homopolymer, hydrogenated	STOT SE 3, H335 (Respiratory tract irritation)
isodecyl methacrylate	STOT SE 3, H335 (Respiratory tract irritation)

**Specific target organ toxicity (repeated exposure)**

<b>Product/ingredient name</b>	<b>Result</b>
Dec-1-ene, homopolymer, hydrogenated	STOT RE 2, H373

**Aspiration hazard**

<b>Product/ingredient name</b>	<b>Result</b>

## SECTION 11: Toxicological information

Dec-1-ene, homopolymer, hydrogenated	ASPIRATION HAZARD - Category 1
Dec-1-ene, trimers, hydrogenated	ASPIRATION HAZARD - Category 1
Dec-1-ene, trimers, hydrogenated	ASPIRATION HAZARD - Category 1
Distillates (petroleum), hydrotreated light paraffinic	ASPIRATION HAZARD - Category 1
(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	ASPIRATION HAZARD - Category 1
dec-1-ene	ASPIRATION HAZARD - Category 1

**Information on likely routes of exposure** Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

### Potential acute health effects

<b>Inhalation</b>	Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.
<b>Ingestion</b>	No known significant effects or critical hazards.
<b>Skin contact</b>	Defatting to the skin. May cause skin dryness and irritation.
<b>Eye contact</b>	No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

<b>Inhalation</b>	May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
<b>Ingestion</b>	No specific data.
<b>Skin contact</b>	Adverse symptoms may include the following: irritation dryness cracking
<b>Eye contact</b>	No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Inhalation</b>	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
<b>Ingestion</b>	Ingestion of large quantities may cause nausea and diarrhoea.
<b>Skin contact</b>	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
<b>Eye contact</b>	Potential risk of transient stinging or redness if accidental eye contact occurs.

### Potential chronic health effects

Not available.

<b>Conclusion/Summary [Product]</b>	Not available.
<b>General</b>	No known significant effects or critical hazards.
<b>Carcinogenicity</b>	No known significant effects or critical hazards.
<b>Mutagenicity</b>	No known significant effects or critical hazards.
<b>Developmental effects</b>	No known significant effects or critical hazards.
<b>Fertility effects</b>	No known significant effects or critical hazards.

## 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

**Conclusion/Summary [Product]** This substance/mixture does not contain any components that are considered to have endocrine disrupting properties.

### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Product/ingredient name	Result
Dec-1-ene, homopolymer, hydrogenated	<b>Acute - EL50</b> Equivalent to OECD 201 Algae >1000 mg/l [72 hours]
	<b>Acute - EL50</b> OECD 202 Daphnia >1000 mg/l [48 hours]
	<b>Chronic - NOELR</b>

<b>Product name</b> Castrol Transmax Manual V 75W-80	<b>Product code</b> 469686-DE01	<b>Page:</b> 14/22
<b>Version</b> 10	<b>Date of issue</b> 3 October 2025	<b>Format</b> Slovenia
<b>Date of previous issue</b> 10 July 2025.		<b>Language</b> ENGLISH
		<b>(Slovenia)</b>

**SECTION 12: Ecological information**

	<p>OECD 211 Daphnia 125 mg/l [21 days]</p> <p><b>Acute - LL50</b> OECD 203 Fish &gt;1000 mg/l [96 hours]</p>
Dec-1-ene, trimers, hydrogenated	<p><b>Acute - EL50</b> Equivalent to OECD 201 Algae &gt;1000 mg/l [72 hours]</p> <p><b>Acute - EL50</b> OECD 202 Daphnia &gt;1000 mg/l [48 hours]</p> <p><b>Chronic - NOELR</b> OECD 211 Daphnia 125 mg/l [21 days]</p> <p><b>Acute - LL50</b> OECD 203 Fish &gt;1000 mg/l [96 hours]</p>
Dec-1-ene, trimers, hydrogenated	<p><b>Acute - EL50</b> OECD 201 Algae &gt;1000 mg/l [72 hours]</p> <p><b>Acute - EL50</b> OECD 202 Daphnia &gt;1000 mg/l [48 hours]</p> <p><b>Chronic - NOELR</b> OECD 211 Daphnia 125 mg/l [21 days]</p> <p><b>Acute - LL50</b> OECD 203 Fish &gt;1000 mg/l [96 hours]</p>
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	<p><b>Acute - ErC50</b> OECD 201 Algae 6.4 mg/l [96 hours]</p> <p><b>Chronic - NOEC</b> OECD 201 Algae 1.7 mg/l [96 hours]</p> <p><b>Acute - EC50</b> OECD 202 Daphnia 91.4 mg/l [48 hours]</p> <p><b>Chronic - EC50</b> OECD 211 Daphnia 0.66 mg/l [21 days]</p> <p><b>Chronic - NOEC</b> OECD 211 Daphnia</p>

**SECTION 12: Ecological information**

	0.12 mg/l [21 days]
	<b>Acute - LC50</b> OECD 203 Fish 24 mg/l [96 hours]
Distillates (petroleum), hydrotreated light paraffinic	<b>Acute - EL50</b> OECD 201 Algae >100 mg/l [72 hours]
	<b>Acute - EL50</b> OECD 202 Daphnia >10000 mg/l [48 hours]
	<b>Acute - LL50</b> OECD 203 Fish >100 mg/l [96 hours]
	<b>Chronic - NOEL</b> OECD 201 Algae ≥100 mg/l [72 hours]
	<b>Chronic - NOEL</b> OECD 211 Daphnia 10 mg/l [21 days]
(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	<b>Acute - ErC50</b> OECD 201 Algae 0.04 mg/l [96 hours]
	<b>Chronic - NOEC</b> OECD 201 Algae 0.01 mg/l [96 hours]
	<b>Chronic - NOEC</b> OECD 211 Daphnia 0.013 mg/l [21 days]
	<b>Acute - LC50</b> EPA OPPTS 850.1085 Fish 0.06 mg/l [96 hours]
isodecyl methacrylate	<b>Acute - ErC50</b> Algae >0.0169 mg/l [72 hours]
	<b>Chronic - NOEC</b> Algae 0.012 mg/l [72 hours]
	<b>Chronic - NOEC</b> Daphnia 0.0542 mg/l [21 days]
	<b>Acute - LC50</b> DIN 38412 Fish 100 mg/l [48 hours]
dec-1-ene	<b>Acute - ErC50</b> OECD 201 Algae

**SECTION 12: Ecological information**

1 to 1.8 mg/l [72 hours]

**Acute - EC50**

OECD 202  
Daphnia  
0.56 to 1 mg/l [48 hours]

**Chronic - NOEC**

OECD 211  
Daphnia  
19.4 mg/l [21 days]

**Acute - LC50**

Fish  
>1.5 mg/l [96 hours]

**Environmental hazards**

Toxic to aquatic life with long lasting effects.  
Based on data available for this or related materials.

**12.2 Persistence and degradability**

Not expected to be rapidly degradable.

**Product/ingredient name**

**Result**

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl

OECD 301B  
7.4% [28 days] - Not readily

Distillates (petroleum), hydrotreated light paraffinic

OECD 301F  
31% [28 days] - Not readily

(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines

OECD 301B  
66% [28 days] - Readily

isodecyl methacrylate

OECD 310  
62% [28 days] - Not readily

dec-1-ene

OECD 301F  
>80% [28 days] - Readily

**12.3 Bioaccumulative potential**

This product is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Dec-1-ene, homopolymer, hydrogenated	>10	-	High
Dec-1-ene, trimers, hydrogenated	>6.5	-	High
Dec-1-ene, trimers, hydrogenated	>10	-	High
(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	4.33	-	High
isodecyl methacrylate	6.45 to 7.44	37	Low
dec-1-ene	5.12	-	High

**12.4 Mobility in soil**

**Soil/water partition coefficient**

Product/ingredient name	logK <sub>oc</sub>	K <sub>oc</sub>
(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	3.43	2699.8
dec-1-ene	2.4	251.256

**Results of PMT and vPvM assessment**

**SECTION 12: Ecological information**

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Dec-1-ene, homopolymer, hydrogenated	No	No	No	No	No	No	No
Dec-1-ene, trimers, hydrogenated	No	No	No	No	No	No	No
Dec-1-ene, trimers, hydrogenated	No	No	No	No	No	No	No
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl	No	No	No	No	No	No	No
Distillates (petroleum), hydrotreated light paraffinic	No	No	No	No	No	No	No
(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	No	No	No	No	No	No	No
isodecyl methacrylate	No	No	No	No	No	No	No
dec-1-ene	No	No	No	No	No	No	No

**Mobility**

Spillages may penetrate the soil causing ground water contamination.

**Conclusion/Summary**

The product does not meet the criteria to be considered as a PMT or vPvM.

**12.5 Results of PBT and vPvB assessment**

**Regulation (EC) No. 1907/2006 [REACH]**

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Dec-1-ene, homopolymer, hydrogenated	No	N/A	N/A	No	N/A	N/A	N/A
Dec-1-ene, trimers, hydrogenated	No	N/A	N/A	No	N/A	N/A	N/A
Dec-1-ene, trimers, hydrogenated	No	N/A	N/A	No	N/A	N/A	N/A
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl	No	N/A	N/A	No	N/A	N/A	N/A
Distillates (petroleum), hydrotreated light paraffinic	No	N/A	N/A	No	N/A	N/A	N/A
(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	N/A	N/A	N/A	Yes	N/A	N/A	N/A
isodecyl methacrylate	No	N/A	No	No	No	N/A	No
dec-1-ene	No	N/A	N/A	No	N/A	N/A	N/A

**Regulation (EC) No. 1272/2008 [CLP]**

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Dec-1-ene, homopolymer, hydrogenated	No	No	No	No	No	No	No
Dec-1-ene, trimers, hydrogenated	No	No	No	No	No	No	No
Dec-1-ene, trimers, hydrogenated	No	No	No	No	No	No	No
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl	No	No	No	No	No	No	No
Distillates (petroleum), hydrotreated light paraffinic	No	No	No	No	No	No	No
(Z)-octadec-9-enylamine, C16-18-(even numbered,	No	No	No	No	No	No	No

## SECTION 12: Ecological information

saturated and unsaturated)-alkylamines	No						
isodecyl methacrylate	No						
dec-1-ene	No						

**Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP]**  The product does not meet the criteria to be considered as a PBT or vPvB.

### 12.6 Endocrine disrupting properties

**Conclusion/Summary [Product]**  This substance/mixture does not contain any components that are considered to have endocrine disrupting properties.

**Other ecological information** Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

**12.7 Other adverse effects** No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

**Hazardous waste** Yes.

#### European waste catalogue (EWC)

Waste code	Waste designation
13 02 08*	other engine, gear and lubricating oils

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

#### Packaging

**Methods of disposal** Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

**Special precautions** This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Empty containers represent a fire hazard as they may contain flammable product residues and vapour. Never weld, solder or braze empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**Slovenia - Hazardous waste** This product is classified as dangerous according to Slovenian waste treatment rules [Ur.l. RS, No. 45/2000 as amended and adapted].

**References** Commission 2014/955/EU  
Directive 2008/98/EC

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
<b>14.1 UN number or ID number</b>	UN3082	UN3082	UN3082	UN3082
<b>14.2 UN proper shipping name</b>	Environmentally hazardous substance, liquid, n.o.s. ((Z)-octadec-9-enylamine)	Environmentally hazardous substance, liquid, n.o.s. ((Z)-octadec-9-enylamine)	Environmentally hazardous substance, liquid, n.o.s.. Marine pollutant ((Z)-octadec-9-enylamine)	<input checked="" type="checkbox"/> ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((Z)-octadec-9-enylamine)
<b>14.3 Transport hazard class(es)</b>	9  	9  	9  	9  
<b>14.4 Packing group</b>	III	III	III	III

**SECTION 14: Transport information**

<b>14.5 Environmental hazards</b>	Yes.	Yes.	Yes.	Yes.
<b>Additional information</b>	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. <b>Hazard identification number</b> 90 <b>Tunnel code</b> -	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. <b>Emergency schedules</b> F-A, S-F	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

**14.6 Special precautions for user** Not available.

**ADR/RID Classification code:** M6

**ADN Classification code:** M6

**14.7 Maritime transport in bulk according to IMO instruments** Not available.

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
Castrol Transmax Manual V 75W-80	95-100	3

**Labelling** Not applicable.

**Other regulations**

**REACH Status** The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

**United States inventory (TSCA 8b)** All components are active or exempted.

**Australia inventory (AIC)** All components are listed or exempted.

**Canada inventory** All components are listed or exempted.

**China inventory (IECSC)** All components are listed or exempted.

**Japan inventory (CSCL)** All components are listed or exempted.

**Korea inventory (KECI)** All components are listed or exempted.

**Philippines inventory (PICCS)** At least one component is not listed.

**Taiwan Chemical Substances Inventory (TCSI)** All components are listed or exempted.

**Explosive precursors** Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

<b>Product name</b> Castrol Transmax Manual V 75W-80	<b>Product code</b> 469686-DE01	<b>Page:</b> 20/22
<b>Version</b> 10	<b>Date of issue</b> 3 October 2025	<b>Format</b> Slovenia
<b>Date of previous issue</b> 10 July 2025.		<b>Language</b> ENGLISH
	<b>(Slovenia)</b>	

## SECTION 15: Regulatory information

### Persistent Organic Pollutants

Not listed.

### EU - Water framework directive - Priority substances

None of the components are listed.

### Seveso Directive

This product is controlled under the Seveso Directive.

### Danger criteria

#### Category

2

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

## SECTION 16: Other information

### Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
 ATE = Acute Toxicity Estimate  
 BCF = Bioconcentration Factor  
 CAS = Chemical Abstracts Service  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 CSA = Chemical Safety Assessment  
 CSR = Chemical Safety Report  
 DMEL = Derived Minimal Effect Level  
 DNEL = Derived No Effect Level  
 EINECS = European Inventory of Existing Commercial chemical Substances  
 ES = Exposure Scenario  
 EUH statement = CLP-specific Hazard statement  
 EWC = European Waste Catalogue  
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
 IATA = International Air Transport Association  
 IBC = Intermediate Bulk Container  
 IMDG = International Maritime Dangerous Goods  
 LogPow = logarithm of the octanol/water partition coefficient  
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
 OECD = Organisation for Economic Co-operation and Development  
 PBT = Persistent, Bioaccumulative and Toxic  
 PNEC = Predicted No Effect Concentration  
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]  
 RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
 RRN = REACH Registration Number  
 SADT = Self-Accelerating Decomposition Temperature  
 SVHC = Substances of Very High Concern  
 STOT-RE = Specific Target Organ Toxicity - Repeated Exposure  
 STOT-SE = Specific Target Organ Toxicity - Single Exposure  
 TWA = Time weighted average  
 UN = United Nations  
 UVCB = Complex hydrocarbon substance  
 VOC = Volatile Organic Compound  
 vPvB = Very Persistent and Very Bioaccumulative  
 Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4 / RRN 01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN 01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN 01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN 01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN 01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8, 64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 / RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN 01-2119474889-13

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

<b>Product name</b>	Castrol Transmax Manual V 75W-80	<b>Product code</b>	469686-DE01	<b>Page:</b>	21/22
<b>Version</b>	10	<b>Date of issue</b>	3 October 2025	<b>Format</b>	Slovenia (Slovenia)
<b>Date of previous issue</b>	10 July 2025.	<b>Language</b>	ENGLISH		

**SECTION 16: Other information**

Classification	Justification
Aquatic Chronic 2, H411	Calculation method

<b>Full text of abbreviated H statements</b>	H226 H302 H304 H314 H315 H317 H318 H319 H335 H373  H400 H410 H411 EUH066	Flammable liquid and vapour. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes severe skin burns and eye damage. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking.
<b>Full text of classifications [CLP/GHS]</b>	Acute Tox. 4 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Asp. Tox. 1 Eye Dam. 1 Eye Irrit. 2 Flam. Liq. 3 Skin Corr. 1B Skin Irrit. 2 Skin Sens. 1B STOT RE 2  STOT SE 3	ACUTE TOXICITY - Category 4 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 ASPIRATION HAZARD - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 3 SKIN CORROSION/IRRITATION - Category 1B SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1B SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

**History**

<b>Date of issue/ Date of revision</b>	03/10/2025.
<b>Date of previous issue</b>	10/07/2025.
<b>Prepared by</b>	Product Stewardship

 **Indicates information that has changed from previously issued version.**

**Notice to reader**

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

<b>Product name</b> Castrol Transmax Manual V 75W-80	<b>Product code</b> 469686-DE01	<b>Page:</b> 22/22
<b>Version</b> 10	<b>Date of issue</b> 3 October 2025	<b>Format</b> Slovenia
<b>Date of previous issue</b> 10 July 2025.		<b>Language</b> ENGLISH
	<b>(Slovenia)</b>	