

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Product name Castrol Transmax Universal 75W-90
Product code 469688-DE04
SDS # 469688
Product type Liquid.

**Use of the substance/
mixture** Gear oils
 For specific application advice see appropriate Technical Data Sheet or consult our company representative.

1.3 Details of the supplier of the safety data sheet

Supplier Castrol Holdings Europe B.V.,
 d'Arcyweg 76, 3198NA
 Europoort
 Rotterdam

Castrol Hellas MAE
 26A, IOANNOU APOSTOLOPOULOU, Chalandri, 15231
 Greece
 +30 210 6887 777

E-mail address MSDSadvice@bp.com

1.4 Emergency telephone number

**EMERGENCY
TELEPHONE NUMBER** Carechem: +44 (0) 1235 239 670 (24/7)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Product definition Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 2, H411
 PBT, EUH440

See Section 16 for the full text of the H statements declared above.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements**Hazard pictograms****Signal word**

Danger

Hazard statements

H411 - Toxic to aquatic life with long lasting effects.
 EUH440 - Accumulates in the environment and living organisms including in humans.

Precautionary statements**General**

P102 - Keep out of reach of children.
 P101 - If medical advice is needed, have product container or label at hand.

Prevention

P201 - Obtain special instructions before use.
 P273 - Avoid release to the environment.

Response

P391 - Collect spillage.

Storage

Not applicable.

Disposal

P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

SECTION 2: Hazards identification

Hazardous ingredients	Not applicable.
Supplemental label elements	Contains Polysulfides, di-tert-Bu and Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl. May produce an allergic reaction.
EU Regulation (EC) No. 1907/2006 (REACH)	
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Not applicable.
Special packaging requirements	
Containers to be fitted with child-resistant fastenings	Not applicable.
Tactile warning of danger	Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	This mixture contains substances that are assessed to be a PBT or a vPvB, refer to Section 3.2.
Product meets the criteria for endocrine disrupting properties according to Regulation (EC) No. 1907/2006.	This substance/mixture does not contain any components that are considered to have endocrine disrupting properties.
Other hazards which do not result in classification	Defatting to the skin.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product definition Mixture
Highly refined base oil (IP 346 DMSO extract < 3%). Synthetic base stock. Proprietary performance additives.

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Polysulfides, di-tert-Bu	REACH #: 01-2119540515-43 EC: 273-103-3 CAS: 68937-96-2	≤5	Skin Sens. 1B, H317 Aquatic Chronic 3, H412	Skin Sens. 1, H317: C ≥ 46%	[1]
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	REACH #: 01-2119493620-38 EC: 931-384-6 CAS: -	≤3	Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 2, H411	ATE [Oral] = 500 mg/kg Eye Irrit. 2, H319: C ≥ 50% Skin Sens. 1, H317: C ≥ 9.39%	[1]
Distillates (petroleum), hydrotreated heavy paraffinic	REACH #: 01-2119484627-25 EC: 265-157-1 CAS: 64742-54-7 Index: 649-467-00-8	≤3	Asp. Tox. 1, H304	-	[1]
Distillates (petroleum), solvent-dewaxed heavy paraffinic	REACH #: 01-2119471299-27 EC: 265-169-7 CAS: 64742-65-0 Index: 649-474-00-6	≤3	Asp. Tox. 1, H304	-	[1]
Distillates (petroleum), hydrotreated light paraffinic	REACH #: 01-2119487077-29 EC: 265-158-7 CAS: 64742-55-8 Index: 649-468-00-3	≤3	Asp. Tox. 1, H304	-	[1]
Distillates (petroleum), solvent-dewaxed light paraffinic	REACH #: 01-2119480132-48 EC: 265-159-2	≤3	Asp. Tox. 1, H304	-	[1]

SECTION 3: Composition/information on ingredients

O,O,O-triphenyl phosphorothioate	CAS: 64742-56-9	≤1	Aquatic Chronic 1, H410 PBT, EUH440	M [Chronic] = 10	[1] [2]
	Index: 649-469-00-9				
	REACH #:				
	01-2119979545-21				
	EC: 209-909-9				
	CAS: 597-82-0				

See Section 16 for the full text of the H statements declared above.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures**4.1 Description of first aid measures**

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if symptoms occur.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Potential acute health effects

Inhalation	Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.
Ingestion	No known significant effects or critical hazards.
Skin contact	Defatting to the skin. May cause skin dryness and irritation.
Eye contact	See: Section 11. Toxicological Information - Potential acute health effects: Eye contact

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects.
---------------------------	---

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media	Use foam or all-purpose dry chemical to extinguish.
Unsuitable extinguishing media	Do not use water jet. The use of a water jet may cause the fire to spread by splashing the burning product.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	Combustion products may include the following: carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide)

5.3 Advice for firefighters

Product name Castrol Transmax Universal 75W-90

Product code 469688-DE04

Page: 3/27

Version 3

Date of issue 23 January 2026

Format Albania
Albania

Language ENGLISH

SECTION 5: Firefighting measures

Special precautions for fire-fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. This material is toxic to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment.
For emergency responders	Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

See Section 1 for emergency contact information.
See Section 5 for firefighting measures.
See Section 8 for information on appropriate personal protective equipment.
See Section 12 for environmental precautions.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid contact of spilt material and runoff with soil and surface waterways. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Empty containers retain product residue and can be hazardous.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Not suitable	Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/containers designed for use with this product. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.
	Prolonged exposure to elevated temperature.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limits****Europe**

No exposure limit value known.

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Recommended monitoring procedures

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Biological exposure indices**Product/ingredient name****Exposure indices**

No exposure indices known.

Derived No Effect Level

No DNELs/DMELs available.

PNECs

Not available.

8.2 Exposure controls**Appropriate engineering controls**

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Individual protection measures**Hygiene measures**

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Eye/face protection

Safety glasses with side shields.

Skin protection**Hand protection****General Information:**

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile gloves.

Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace

SECTION 8: Exposure controls/personal protection

conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained.

If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.

It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

Glove Thickness:

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

Skin and body

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Refer to standards:

Respiratory protection: EN 529
 Gloves: EN 420, EN 374
 Eye protection: EN 166
 Filtering half-mask: EN 149
 Filtering half-mask with valve: EN 405
 Half-mask: EN 140 plus filter
 Full-face mask: EN 136 plus filter
 Particulate filters: EN 143
 Gas/combined filters: EN 14387

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****Appearance**

Physical state	Liquid.
Colour	Amber.
Odour	Not available.
Odour threshold	Not available.
pH	Not applicable.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Pour point	-45 °C
Flash point	Open cup: >180°C (>356°F) [Cleveland]
Evaporation rate	Not available.
Flammability	Not available.
Lower and upper explosion limit	Not available.
Vapour pressure	

Ingredient name	Vapour Pressure at 20 °C		Vapour pressure at 50 °C	
	mm Hg	kPa	Method	mm Hg
Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191	
Polysulfides, di-tert-Bu	0.12	0.016	OECD 104	
Distillates (petroleum), hydrotreated heavy paraffinic	<0.07501	<0.01	ASTM D 5191	
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<0.07501	<0.01	ASTM D 5191	
Distillates (petroleum), hydrotreated light paraffinic	<0.07501	<0.01	ASTM D 5191	

Vapour density	Not available.
Density and/or Relative density	Not available.
Solubility(ies)	<1000 kg/m ³ (<1 g/cm ³) at 15°C

Media	Result
water	Not soluble

Partition coefficient n-octanol/water (log value)	Not applicable.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Kinematic viscosity	Kinematic: 108.1 mm ² /s (108.1 cSt) at 40°C Kinematic: 14.3 to 15.3 mm ² /s (14.3 to 15.3 cSt) at 100°C
Explosive properties	Not available.
Oxidising properties	Not available.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
10.2 Chemical stability	The product is stable.
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.

Product name	Castrol Transmax Universal 75W-90	Product code	469688-DE04	Page:	7/27
Version	3	Date of issue	23 January 2026	Format	Albania Albania
				Language	ENGLISH

SECTION 10: Stability and reactivity

10.4 Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
10.5 Incompatible materials	Reactive or incompatible with the following materials: oxidising materials.
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute toxicityProduct/ingredient nameResult

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl

Rat - Oral - LD50
2000 mg/kg
OECD 401

Distillates (petroleum), hydrotreated heavy paraffinic

Rat - Oral - LD50
>5000 mg/kg
OECD 401

Rabbit - Dermal - LD50
>5000 mg/kg
OECD 402

Rat - Inhalation - LC50 Dusts and mists
>5 mg/l [4 hours]
OECD 403

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Rat - Oral - LD50
>5000 mg/kg
OECD 401

Rat - Dermal - LD50
>2000 mg/kg
OECD 402

Rat - Inhalation - LC50 Dusts and mists
>5.53 mg/l [4 hours]
OECD 403

Distillates (petroleum), hydrotreated light paraffinic

Rat - Oral - LD50
>5000 mg/kg
OECD 401

Rabbit - Dermal - LD50
>5000 mg/kg
OECD 402

Rat - Inhalation - LC50 Dusts and mists
>5.53 mg/l [4 hours]
OECD 403

Distillates (petroleum), solvent-dewaxed light paraffinic

Rat - Oral - LD50
>5000 mg/kg
OECD 401

Rabbit - Dermal - LD50
>5000 mg/kg
OECD 402

Rat - Inhalation - LC50 Dusts and mists
>2.18 mg/l [4 hours]
OECD 403

Acute toxicity estimates

Product name Castrol Transmax Universal 75W-90

Product code 469688-DE04

Page: 8/27

Version 3

Date of issue 23 January 2026

Format Albania
Albania

Language ENGLISH

SECTION 11: Toxicological information

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Castrol Transmax Universal 75W-90 Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	26720.2 500	N/A N/A	N/A N/A	N/A N/A	N/A N/A

Skin corrosion/irritation**Product/ingredient name**

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Distillates (petroleum), hydrotreated light paraffinic

Distillates (petroleum), solvent-dewaxed light paraffinic

Result

Rabbit - Skin - Non-irritant to skin.
OECD 404

Rabbit - Skin - Mild irritant
OECD 404

Rabbit - Skin - Non-irritant to skin.

Rabbit - Skin - Non-irritant to skin.

Rabbit - Skin - Non-irritant to skin.

Serious eye damage/eye irritation**Product/ingredient name**

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Distillates (petroleum), hydrotreated light paraffinic

Distillates (petroleum), solvent-dewaxed light paraffinic

Result

Rabbit - Eyes - Irritant
FHSA 16CFR1500

Rabbit - Eyes - Non-irritating to the eyes.
OECD 405

Rabbit - Eyes - Non-irritating to the eyes.
OECD 405

Rabbit - Eyes - Non-irritating to the eyes.
OECD 405

Rabbit - Eyes - Non-irritating to the eyes.
OECD 405

Respiratory corrosion/irritation

Not available.

Respiratory or skin sensitization**Product/ingredient name**

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Result

Mouse - skin
OECD 429
Result: Sensitising

Guinea pig - skin
OECD 406
Result: Not sensitising

Guinea pig - skin
OECD 406
Result: Not sensitising

SECTION 11: Toxicological information

Distillates (petroleum), hydrotreated light paraffinic

Guinea pig - skin
OECD 406
Result: Not sensitising

Distillates (petroleum), solvent-dewaxed light paraffinic

Guinea pig - skin
OECD 406
Result: Not sensitising

Germ cell mutagenicity**Product/ingredient name**

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl

Result

In vitro - Bacteria
OECD 471
Result: Negative

In vitro - Mammal - species unspecified
OECD 476
Result: Negative

In vitro - Unspecified - Somatic
OECD 474
Result: Negative

Distillates (petroleum), hydrotreated heavy paraffinic

In vitro - Bacteria
Bacterial Reverse Mutation Test
Result: Negative

In vitro - Mammal - species unspecified
In vitro Mammalian Chromosomal Aberration Test
Result: Negative

In vivo - Mammal - species unspecified
Mammalian Erythrocyte Micronucleus Test
Result: Negative

In vitro - Mammal - species unspecified
In vitro Mammalian Cell Gene Mutation Test
Result: Negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic

In vitro - Bacteria
OECD [Bacterial Reverse Mutation Test]
Result: Negative

In vitro - Mammal - species unspecified
OECD [In vitro Mammalian Chromosomal Aberration Test]
Result: Negative

Distillates (petroleum), hydrotreated light paraffinic

In vitro - Bacteria
OECD [Bacterial Reverse Mutation Test]
Result: Negative

In vitro - Mammal - species unspecified
OECD [In vitro Mammalian Chromosomal Aberration Test]
Result: Negative

Distillates (petroleum), solvent-dewaxed light paraffinic

In vitro - Bacteria
OECD [Bacterial Reverse Mutation Test]
Result: Negative

In vitro - Mammal - species unspecified
In vitro Mammalian Chromosomal Aberration Test
Result: Negative

Carcinogenicity**Product/ingredient name****Result**

Product name Castrol Transmax Universal 75W-90

Product code 469688-DE04

Page: 10/27

Version 3

Date of issue 23 January 2026

Format Albania
Albania

Language ENGLISH

SECTION 11: Toxicological information

Distillates (petroleum), hydrotreated heavy paraffinic

Mouse - Dermal - Unspecified

OECD 451

Result: Negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Mouse - Dermal - Unspecified

OECD 451

Result: Negative**Reproductive toxicity****Product/ingredient name**

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl

Result**Rat - Oral**

OECD 421

Maternal toxicity: PositiveFertility effects: NegativeDevelopmental: Negative

Distillates (petroleum), hydrotreated heavy paraffinic

Rat - Oral

OECD 421

Maternal toxicity: NegativeFertility effects: NegativeDevelopmental: Negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Rat - Oral

OECD 421

Maternal toxicity: NegativeFertility effects: NegativeDevelopmental: Negative

Distillates (petroleum), hydrotreated light paraffinic

Rat - Oral

OECD 421

Maternal toxicity: NegativeFertility effects: NegativeDevelopmental: Negative

Distillates (petroleum), solvent-dewaxed light paraffinic

Rat - Oral

OECD 421

Maternal toxicity: NegativeFertility effects: NegativeDevelopmental: Negative**Specific target organ toxicity (single exposure)**

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard**Product/ingredient name**

Distillates (petroleum), hydrotreated heavy paraffinic

Result

ASPIRATION HAZARD - Category 1

Distillates (petroleum), solvent-dewaxed heavy paraffinic

ASPIRATION HAZARD - Category 1

Distillates (petroleum), hydrotreated light paraffinic

ASPIRATION HAZARD - Category 1

Distillates (petroleum), solvent-dewaxed light paraffinic

ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects**Inhalation**

Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.

Ingestion

No known significant effects or critical hazards.

Skin contact

Defatting to the skin. May cause skin dryness and irritation.

Eye contact

See: Section 11. Toxicological Information - Potential acute health effects: Eye contact

Product name Castrol Transmax Universal 75W-90**Product code** 469688-DE04**Page:** 11/27**Version** 3**Date of issue** 23 January 2026**Format** Albania
Albania**Language** ENGLISH

SECTION 11: Toxicological informationSymptoms related to the physical, chemical and toxicological characteristics

Inhalation	May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
Ingestion	No specific data.
Skin contact	Adverse symptoms may include the following: irritation dryness cracking
Eye contact	No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.

Potential chronic health effects

Not available.

Conclusion/Summary [Product]	Not available.
General	No known significant effects or critical hazards.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

11.2 Information on other hazards**11.2.1 Endocrine disrupting properties**

Not available.

Conclusion/Summary [Product]	This substance/mixture does not contain any components that are considered to have endocrine disrupting properties.
-------------------------------------	---

11.2.2 Other information

Not available.

SECTION 12: Ecological information**12.1 Toxicity****Product/ingredient name**

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl

Result**Acute - ErC50**

OECD 201
Algae
6.4 mg/l [96 hours]

Chronic - NOEC

OECD 201
Algae
1.7 mg/l [96 hours]

Acute - EC50

OECD 202
Daphnia
91.4 mg/l [48 hours]

Chronic - EC50

OECD 211
Daphnia
0.66 mg/l [21 days]

Chronic - NOEC

OECD 211
Daphnia
0.12 mg/l [21 days]

Acute - LC50

OECD 203
Fish
24 mg/l [96 hours]

Product name Castrol Transmax Universal 75W-90**Product code** 469688-DE04**Page:** 12/27**Version** 3**Date of issue** 23 January 2026**Format** Albania
Albania**Language** ENGLISH

SECTION 12: Ecological information

Distillates (petroleum), hydrotreated heavy paraffinic

Acute - EL50

OECD 201

Algae

>100 mg/l [72 hours]

Acute - EL50

OECD 202

Daphnia

>10000 mg/l [48 hours]

Acute - LL50

OECD 203

Fish

>100 mg/l [96 hours]

Chronic - NOEL

OECD 201

Algae

≥100 mg/l [72 hours]

Chronic - NOEL

OECD 211

Daphnia

10 mg/l [21 days]

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Acute - EL50

OECD 201

Algae

>100 mg/l [72 hours]

Acute - EL50

OECD 202

Daphnia

>10000 mg/l [48 hours]

Acute - LL50

OECD 203

Fish

>100 mg/l [96 hours]

Chronic - NOEL

OECD 201

Algae

≥100 mg/l [72 hours]

Chronic - NOEL

OECD 211

Daphnia

10 mg/l [21 days]

Distillates (petroleum), hydrotreated light paraffinic

Acute - EL50

OECD 201

Algae

>100 mg/l [72 hours]

Acute - EL50

OECD 202

Daphnia

>10000 mg/l [48 hours]

Acute - LL50

OECD 203

Fish

>100 mg/l [96 hours]

Chronic - NOEL

OECD 201

Algae

≥100 mg/l [72 hours]

Chronic - NOEL

SECTION 12: Ecological information

Distillates (petroleum), solvent-dewaxed light paraffinic

OECD 211
Daphnia
10 mg/l [21 days]**Acute - EL50**OECD 201
Algae
>100 mg/l [72 hours]**Acute - EL50**OECD 202
Daphnia
>10000 mg/l [48 hours]**Acute - LL50**OECD 203
Fish
>100 mg/l [96 hours]**Chronic - NOEL**OECD 201
Algae
≥100 mg/l [72 hours]**Chronic - NOEL**OECD 211
Daphnia
10 mg/l [21 days]**Environmental hazards**

Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Not expected to be rapidly degradable.

Product/ingredient name

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl

ResultOECD 301B
7.4% [28 days] - Not readily

Distillates (petroleum), hydrotreated heavy paraffinic

OECD 301F
31% [28 days] - Not readily

Distillates (petroleum), solvent-dewaxed heavy paraffinic

OECD 301F
31% [28 days] - Not readily

Distillates (petroleum), hydrotreated light paraffinic

OECD 301F
31% [28 days] - Not readily

Distillates (petroleum), solvent-dewaxed light paraffinic

OECD 301F
31% [28 days] - Not readily**12.3 Bioaccumulative potential**

This product is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	LogP _{ow}	BCF	Potential
Polysulfides, di-tert-Bu	5.6	-	High

12.4 Mobility in soil**Soil/water partition coefficient**

Product/ingredient name	logK _{oc}	K _{oc}
O,O,O-triphenyl phosphorothioate	4.7	49128.4

Results of PMT and vPvM assessment**Product name** Castrol Transmax Universal 75W-90**Product code** 469688-DE04**Page:** 14/27**Version** 3**Date of issue** 23 January 2026**Format** Albania
Albania**Language** ENGLISH

SECTION 12: Ecological information

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Polysulfides, di-tert-Bu	No	No	No	No	No	No	No
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	No	No	No	No	No	No	No
Distillates (petroleum), hydrotreated heavy paraffinic	No	No	No	No	No	No	No
Distillates (petroleum), solvent-dewaxed heavy paraffinic	No	No	No	No	No	No	No
Distillates (petroleum), hydrotreated light paraffinic	No	No	No	No	No	No	No
Distillates (petroleum), solvent-dewaxed light paraffinic	No	No	No	No	No	No	No
O,O,O-triphenyl phosphorothioate	No	Yes	No	Yes	No	No	No

Mobility

Spillages may penetrate the soil causing ground water contamination.

Conclusion/Summary

The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment**Regulation (EC) No. 1907/2006 [REACH]**

Product/ingredient name	PBT	P	B	T	vPvB	vP
Polysulfides, di-tert-Bu	No	N/A	N/A	No	N/A	N/A
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	No	N/A	N/A	No	N/A	N/A
Distillates (petroleum), hydrotreated heavy paraffinic	No	N/A	N/A	No	N/A	N/A
Distillates (petroleum), solvent-dewaxed heavy paraffinic	No	N/A	N/A	No	N/A	N/A
Distillates (petroleum), hydrotreated light paraffinic	No	N/A	N/A	No	N/A	N/A
Distillates (petroleum), solvent-dewaxed light paraffinic	No	N/A	N/A	No	N/A	N/A
O,O,O-triphenyl phosphorothioate	Yes	Yes	Yes	Yes	N/A	N/A

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP
Polysulfides, di-tert-Bu	No	No	No	No	No	No
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	No	No	No	No	No	No
Distillates (petroleum), hydrotreated heavy paraffinic	No	No	No	No	No	No
Distillates (petroleum), solvent-dewaxed heavy paraffinic	No	No	No	No	No	No
Distillates (petroleum), hydrotreated light paraffinic	No	No	No	No	No	No
Distillates (petroleum), solvent-dewaxed light paraffinic	No	No	No	No	No	No
O,O,O-triphenyl	Yes	Yes	Yes	Yes	No	No

Product name Castrol Transmax Universal 75W-90**Product code** 469688-DE04**Page:** 15/27**Version** 3**Date of issue** 23 January 2026**Format** Albania
Albania**Language** ENGLISH

SECTION 12: Ecological information

phosphorothioate

Conclusion/Summary
Regulation (EC) No. 1272/2008
[CLP]

Accumulates in the environment and living organisms including in humans.

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]

This substance/mixture does not contain any components that are considered to have endocrine disrupting properties.

Other ecological information

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product****Methods of disposal**

Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Hazardous waste

Yes.

European waste catalogue (EWC)

Waste code	Waste designation
13 02 08*	other engine, gear and lubricating oils

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

Packaging**Methods of disposal**

Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Special precautions

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Empty containers represent a fire hazard as they may contain flammable product residues and vapour. Never weld, solder or braze empty containers. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

References

Commission 2014/955/EU
Directive 2008/98/EC

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (O,O,O-triphenyl phosphorothioate)	Environmentally hazardous substance, liquid, n.o.s. (O,O,O-triphenyl phosphorothioate)	Environmentally hazardous substance, liquid, n.o.s.. Marine pollutant (O,O,O-triphenyl phosphorothioate)	Environmentally hazardous substance, liquid, n.o.s. (O,O,O-triphenyl phosphorothioate)
14.3 Transport hazard class(es)	9  	9  	9  	9  
14.4 Packing group	III	III	III	-
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.

Product name Castrol Transmax Universal 75W-90

Product code 469688-DE04

Page: 16/27

Version 3

Date of issue 23 January 2026

Format Albania
Albania

Language ENGLISH

SECTION 14: Transport information

Additional information	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Hazard identification number 90 Tunnel code -	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Emergency schedules F-A, S-F	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
------------------------	--	---	---	--

14.6 Special precautions for user Not available.

ADR/RID Classification code: M6

ADN Classification code: M6

14.7 Maritime transport in bulk according to IMO instruments Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

[EU Regulation \(EC\) No. 1907/2006 \(REACH\)](#)

[Annex XIV - List of substances subject to authorisation](#)

[Annex XIV](#)

None of the components are listed.

[Substances of very high concern](#)

Ingredient name	Intrinsic property	Status	Reference number	Date of revision
O,O,O-triphenyl phosphorothioate	PBT	Candidate	D(2024) 7663-DC	1/21/2025

[Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles](#)

Product/ingredient name	%	Designation [Usage]
Castrol Transmax Universal 75W-90	≥90	3

Labelling Not applicable.

[Other regulations](#)

REACH Status The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

United States inventory (TSCA 8b) All components are active or exempted.

Australia inventory (AIC) All components are listed or exempted.

Canada inventory At least one component is not listed in DSL but all such components are listed in NDSL.

China inventory (IECSC) All components are listed or exempted.

Japan inventory (CSCL) All components are listed or exempted.

Korea inventory (KECI) All components are listed or exempted.

Philippines inventory (PICCS) At least one component is not listed.

Taiwan Chemical Substances Inventory (TCSI) All components are listed or exempted.

Explosive precursors Not applicable.

[Ozone depleting substances \(EU 2024/590\)](#)

Not listed.

[Prior Informed Consent \(PIC\) \(649/2012/EU\)](#)

Not listed.

Product name	Castrol Transmax Universal 75W-90	Product code	469688-DE04	Page:	17/27
Version	3	Date of issue	23 January 2026	Format	Albania Albania
				Language	ENGLISH

SECTION 15: Regulatory information**Seveso Directive**

This product is controlled under the Seveso Directive.

Danger criteria**Category**

E2

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

SECTION 16: Other information**Abbreviations and acronyms**

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SADT = Self-Accelerating Decomposition Temperature
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVCB = Complex hydrocarbon substance
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative
Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4 / RRN 01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN 01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN 01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN 01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN 01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8, 64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 / RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN 01-2119474889-13

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aquatic Chronic 2, H411 PBT, EUH440	Calculation method On basis of test data

Full text of classifications [CLP/GHS]**Product name** Castrol Transmax Universal 75W-90**Product code** 469688-DE04**Page:** 18/27**Version** 3**Date of issue** 23 January 2026**Format** Albania
Albania**Language** ENGLISH

SECTION 16: Other information

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
PBT	PERSISTENT, BIOACCUMULATIVE AND TOXIC
Skin Sens. 1B	SKIN SENSITISATION - Category 1B

Europe

Full text of abbreviated H statements	H302	Harmful if swallowed.
	H304	May be fatal if swallowed and enters airways.
	H317	May cause an allergic skin reaction.
	H319	Causes serious eye irritation.
	H410	Very toxic to aquatic life with long lasting effects.
	H411	Toxic to aquatic life with long lasting effects.
	H412	Harmful to aquatic life with long lasting effects.
	EUH440	Accumulates in the environment and living organisms including in humans.

Full text of classifications [CLP/GHS]	Acute Tox. 4	ACUTE TOXICITY - Category 4
	Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
	Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
	Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
	Asp. Tox. 1	ASPIRATION HAZARD - Category 1
	Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
	PBT	PERSISTENT, BIOACCUMULATIVE AND TOXIC
	Skin Sens. 1B	SKIN SENSITISATION - Category 1B

History

Date of issue/ Date of revision	23/01/2026.
Date of previous issue	20/02/2025.
Prepared by	Product Stewardship

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

SECTION 16: Other information

SECTION 16: Other information

Not available.	
Rat - Oral - LD50 >5000 mg/kg OECD 401	Distillates (petroleum), hydrotreated heavy paraffinic
Rabbit - Dermal - LD50 >5000 mg/kg OECD 402	Flammability Density and/or Relative density Density and/or Relative density Partition coefficient n-octanol/ water (log value) Kinematic viscosity
Rat - Inhalation - LC50 Dusts and mists >5 mg/l [4 hours] OECD 403	
Rat - Oral - LD50 >5000 mg/kg OECD 401	Distillates (petroleum), solvent-dewaxed heavy paraffinic
Rat - Dermal - LD50 >2000 mg/kg OECD 402	
Rat - Inhalation - LC50 Dusts and mists >5.53 mg/l [4 hours] OECD 403	
Rat - Oral - LD50 >5000 mg/kg OECD 401	Distillates (petroleum), hydrotreated light paraffinic
Rabbit - Dermal - LD50 >5000 mg/kg OECD 402	
Rat - Inhalation - LC50 Dusts and mists >5.53 mg/l [4 hours] OECD 403	
Rat - Oral - LD50 >5000 mg/kg OECD 401	Distillates (petroleum), solvent-dewaxed light paraffinic
Rabbit - Dermal - LD50 >5000 mg/kg OECD 402	
Rat - Inhalation - LC50 Dusts and mists >2.18 mg/l [4 hours] OECD 403	
Conclusion/Summary [Product]	

Skin corrosion/irritation

Result	Product/ingredient name
Rabbit - Skin - Non-irritant to skin. OECD 404	Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl
Rabbit - Skin - Mild irritant OECD 404	Distillates (petroleum), hydrotreated heavy paraffinic
Rabbit - Skin - Non-irritant to skin.	Distillates (petroleum), solvent-dewaxed heavy paraffinic
Rabbit - Skin - Non-irritant to skin.	Distillates (petroleum), hydrotreated light paraffinic
Rabbit - Skin - Non-irritant to skin.	Distillates (petroleum), solvent-dewaxed light paraffinic
Not available.	Conclusion/Summary [Product]

Serious eye damage/eye irritation

Product name Castrol Transmax Universal 75W-90	Product code 469688-DE04	Page: 21/27
Version 3	Date of issue 23 January 2026	Format Albania Albania
		Language ENGLISH

Result	Product/ingredient name
Rabbit - Eyes - Irritant FHSA 16CFR1500	Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl
Rabbit - Eyes - Non-irritating to the eyes. OECD 405	Distillates (petroleum), hydrotreated heavy paraffinic
Rabbit - Eyes - Non-irritating to the eyes. OECD 405	Distillates (petroleum), solvent-dewaxed heavy paraffinic
Rabbit - Eyes - Non-irritating to the eyes. OECD 405	Distillates (petroleum), hydrotreated light paraffinic
Rabbit - Eyes - Non-irritating to the eyes. OECD 405	Distillates (petroleum), solvent-dewaxed light paraffinic

Conclusion/Summary [Product] Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] Not available.

Respiratory or skin sensitization

Result	Product/ingredient name
Mouse - skin OECD 429 <u>Result</u> : Sensitising	Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl
Guinea pig - skin OECD 406 <u>Result</u> : Not sensitising	Distillates (petroleum), hydrotreated heavy paraffinic
Guinea pig - skin OECD 406 <u>Result</u> : Not sensitising	Distillates (petroleum), solvent-dewaxed heavy paraffinic
Guinea pig - skin OECD 406 <u>Result</u> : Not sensitising	Distillates (petroleum), hydrotreated light paraffinic
Guinea pig - skin OECD 406 <u>Result</u> : Not sensitising	Distillates (petroleum), solvent-dewaxed light paraffinic

Skin

Conclusion/Summary [Product] Not available.

Respiratory

Conclusion/Summary [Product] Not available.

Germ cell mutagenicity

Result	Product/ingredient name
In vitro - Bacteria OECD 471 <u>Result</u> : Negative	Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl
In vitro - Mammal - species unspecified OECD 476 <u>Result</u> : Negative	
In vitro - Unspecified - Somatic OECD 474 <u>Result</u> : Negative	
In vitro - Bacteria Bacterial Reverse Mutation Test <u>Result</u> : Negative	Distillates (petroleum), hydrotreated heavy paraffinic

In vitro - Mammal - species unspecified In vitro Mammalian Chromosomal Aberration Test <u>Result:</u> Negative	
In vivo - Mammal - species unspecified Mammalian Erythrocyte Micronucleus Test <u>Result:</u> Negative	
In vitro - Mammal - species unspecified In vitro Mammalian Cell Gene Mutation Test <u>Result:</u> Negative	
In vitro - Bacteria OECD [Bacterial Reverse Mutation Test] <u>Result:</u> Negative	Distillates (petroleum), solvent-dewaxed heavy paraffinic
In vitro - Mammal - species unspecified OECD [In vitro Mammalian Chromosomal Aberration Test] <u>Result:</u> Negative	
In vitro - Bacteria OECD [Bacterial Reverse Mutation Test] <u>Result:</u> Negative	Distillates (petroleum), hydrotreated light paraffinic
In vitro - Mammal - species unspecified OECD [In vitro Mammalian Chromosomal Aberration Test] <u>Result:</u> Negative	
In vitro - Bacteria OECD [Bacterial Reverse Mutation Test] <u>Result:</u> Negative	Distillates (petroleum), solvent-dewaxed light paraffinic
In vitro - Mammal - species unspecified In vitro Mammalian Chromosomal Aberration Test <u>Result:</u> Negative	

Conclusion/Summary [Product] Not available.

Carcinogenicity

Result Mouse - Dermal - Unspecified OECD 451 <u>Result:</u> Negative	Product/ingredient name Distillates (petroleum), hydrotreated heavy paraffinic
Mouse - Dermal - Unspecified OECD 451 <u>Result:</u> Negative	Distillates (petroleum), solvent-dewaxed heavy paraffinic
Conclusion/Summary [Product]	Not available.

Reproductive toxicity

Result Rat - Oral OECD 421 <u>Maternal toxicity:</u> Positive <u>Fertility effects:</u> Negative <u>Developmental:</u> Negative	Product/ingredient name Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl
Rat - Oral OECD 421 <u>Maternal toxicity:</u> Negative <u>Fertility effects:</u> Negative <u>Developmental:</u> Negative	Distillates (petroleum), hydrotreated heavy paraffinic
Rat - Oral OECD 421 <u>Maternal toxicity:</u> Negative <u>Fertility effects:</u> Negative <u>Developmental:</u> Negative	Distillates (petroleum), solvent-dewaxed heavy paraffinic

Rat - Oral OECD 421 <u>Maternal toxicity:</u> Negative <u>Fertility effects:</u> Negative <u>Developmental:</u> Negative	Distillates (petroleum), hydrotreated light paraffinic
Rat - Oral OECD 421 <u>Maternal toxicity:</u> Negative <u>Fertility effects:</u> Negative <u>Developmental:</u> Negative	Distillates (petroleum), solvent-dewaxed light paraffinic
Conclusion/Summary [Product]	Not available.
<u>Specific target organ toxicity (single exposure)</u>	
Not available.	
<u>Specific target organ toxicity (repeated exposure)</u>	
Not available.	
<u>Aspiration hazard</u>	
Result ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1	Product/ingredient name Distillates (petroleum), hydrotreated heavy paraffinic Distillates (petroleum), solvent-dewaxed heavy paraffinic Distillates (petroleum), hydrotreated light paraffinic Distillates (petroleum), solvent-dewaxed light paraffinic
Information on likely routes of exposure	Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.
Result Acute - ErC50 OECD 201 Algae 6.4 mg/l [96 hours]	Product/ingredient name Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl
Chronic - NOEC OECD 201 Algae 1.7 mg/l [96 hours]	
Acute - EC50 OECD 202 Daphnia 91.4 mg/l [48 hours]	
Chronic - EC50 OECD 211 Daphnia 0.66 mg/l [21 days]	
Chronic - NOEC OECD 211 Daphnia 0.12 mg/l [21 days]	
Acute - LC50 OECD 203 Fish 24 mg/l [96 hours]	
Acute - EL50 OECD 201 Algae >100 mg/l [72 hours]	Distillates (petroleum), hydrotreated heavy paraffinic
Acute - EL50 OECD 202 Daphnia >10000 mg/l [48 hours]	

Acute - LL50 OECD 203 Fish >100 mg/l [96 hours]	
Chronic - NOEL OECD 201 Algae ≥100 mg/l [72 hours]	
Chronic - NOEL OECD 211 Daphnia 10 mg/l [21 days]	
Acute - EL50 OECD 201 Algae >100 mg/l [72 hours]	Distillates (petroleum), solvent-dewaxed heavy paraffinic
Acute - EL50 OECD 202 Daphnia >10000 mg/l [48 hours]	
Acute - LL50 OECD 203 Fish >100 mg/l [96 hours]	
Chronic - NOEL OECD 201 Algae ≥100 mg/l [72 hours]	
Chronic - NOEL OECD 211 Daphnia 10 mg/l [21 days]	
Acute - EL50 OECD 201 Algae >100 mg/l [72 hours]	Distillates (petroleum), hydrotreated light paraffinic
Acute - EL50 OECD 202 Daphnia >10000 mg/l [48 hours]	
Acute - LL50 OECD 203 Fish >100 mg/l [96 hours]	
Chronic - NOEL OECD 201 Algae ≥100 mg/l [72 hours]	
Chronic - NOEL OECD 211 Daphnia 10 mg/l [21 days]	
Acute - EL50 OECD 201 Algae >100 mg/l [72 hours]	Distillates (petroleum), solvent-dewaxed light paraffinic
Acute - EL50 OECD 202 Daphnia >10000 mg/l [48 hours]	

Acute - LL50
OECD 203
Fish
>100 mg/l [96 hours]

Chronic - NOEL
OECD 201
Algae
≥100 mg/l [72 hours]

Chronic - NOEL
OECD 211
Daphnia
10 mg/l [21 days]

Result	Product/ingredient name
OECD 301B 7.4% [28 days] - Not readily	Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl
OECD 301F 31% [28 days] - Not readily	Distillates (petroleum), hydrotreated heavy paraffinic
OECD 301F 31% [28 days] - Not readily	Distillates (petroleum), solvent-dewaxed heavy paraffinic
OECD 301F 31% [28 days] - Not readily	Distillates (petroleum), hydrotreated light paraffinic
OECD 301F 31% [28 days] - Not readily	Distillates (petroleum), solvent-dewaxed light paraffinic

Soil/water partition coefficient

Koc	logKoc	Product/ingredient name
49128.4	4.7	O,O,O-triphenyl phosphorothioate

Results of PMT and vPvM assessment

vM	vP	vPvM	T	M	P	PMT	Product/ingredient name
No	No	No	No	No	No	No	Polysulfides, di-tert-Bu
No	No	No	No	No	No	No	Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl
No	No	No	No	No	No	No	Distillates (petroleum), hydrotreated heavy paraffinic
No	No	No	No	No	No	No	Distillates (petroleum), solvent-dewaxed heavy paraffinic
No	No	No	No	No	No	No	Distillates (petroleum), hydrotreated light paraffinic
No	No	No	No	No	No	No	Distillates (petroleum), solvent-dewaxed light paraffinic
No	No	No	Yes	No	Yes	No	O,O,O-triphenyl phosphorothioate

Spillages may penetrate the soil causing ground water contamination.

The product does not meet the criteria to be considered as a PMT or vPvM.

Regulation (EC) No. 1907/2006 [REACH]

Mobility

Conclusion/Summary

	vP	vPvB	T	B	P	PBT	Product/ingredient name
O,O,O-triphenyl phosphorothioate				PBT		Candidate	D(2024) Polysulfides, di-tert-Bu P603-DC
N/A	N/A	N/A	No	N/A	N/A	No	Reaction products of
N/A	N/A	N/A	No	N/A	N/A	No	4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl Distillates (petroleum), hydrotreated heavy paraffinic
N/A	N/A	N/A	No	N/A	N/A	No	Distillates (petroleum), solvent-dewaxed heavy paraffinic
N/A	N/A	N/A	No	N/A	N/A	No	Distillates (petroleum), hydrotreated light paraffinic
N/A	N/A	N/A	No	N/A	N/A	No	Distillates (petroleum), solvent-dewaxed light paraffinic
N/A	N/A	N/A	Yes	Yes	Yes	Yes	O,O,O-triphenyl phosphorothioate

Regulation (EC) No. 1272/2008 [CLP]

	vP	vPvB	T	B	P	PBT	Product/ingredient name
No	No	No	No	No	No	No	Polysulfides, di-tert-Bu
No	No	No	No	No	No	No	Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl Distillates (petroleum), hydrotreated heavy paraffinic
No	No	No	No	No	No	No	Distillates (petroleum), solvent-dewaxed heavy paraffinic
No	No	No	No	No	No	No	Distillates (petroleum), hydrotreated light paraffinic
No	No	No	No	No	No	No	Distillates (petroleum), solvent-dewaxed light paraffinic
No	No	No	Yes	Yes	Yes	Yes	O,O,O-triphenyl phosphorothioate

Accumulates in the environment and living organisms including in humans.

Conclusion/Summary
Regulation (EC) No. 1272/2008
[CLP]

Not available.

This substance/mixture does not contain any components that are
considered to have endocrine disrupting properties.

Conclusion/Summary [Product]

No known significant effects or critical hazards.

12.7 Other adverse effects