

# SAFETY DATA SHEET



Castrol Vecton Long Drain 10W-40 E7

## Section 1. Identification

|                                      |   |
|--------------------------------------|---|
| <b>Product Identifier</b>            | Castrol Vecton Long Drain 10W-40 E7   |
| <b>Product type</b>                  | Liquid.   |
| <b>Code</b>                          | 468510-BE02   |
| <b>SDS #</b>                         | 468510  |
| <b>Product use</b>                   | Engine Oils.<br>For specific application advice see appropriate Technical Data Sheet or consult our company representative. |
| <b>Supplier</b>                      | BP Lubricants USA Inc.<br>1500 Valley Road<br>Wayne, NJ 07470<br>Telephone: 1-888-CASTROL                                   |
| <b>EMERGENCY HEALTH INFORMATION:</b> | 1 (800) 447-8735<br><br>Outside the US: +1 703-527-3887 (CHEMTREC)  |
| <b>Emergency Telephone Number</b>    | Centro Nacional de Control de Intoxicaciones: +506 2223-1028<br>1 (800) 424-9300 CHEMTREC (USA)                             |

## Section 2. Hazard identification

|  |   |
|--|---|
| <b>Classification of the substance or mixture</b>          | SKIN CORROSION/IRRITATION - Category 3<br>AQUATIC HAZARD (LONG-TERM) - Category 3   |
| <b>GHS label elements</b>                                  |   |
| <b>Signal word</b>   | Warning   |
| <b>Hazard statements</b>                                   | H316 - Causes mild skin irritation.<br>H412 - Harmful to aquatic life with long lasting effects.  |
| <b>Precautionary statements</b>                            |   |
| <b>Prevention</b>  | P102 - Keep out of reach of children.<br>P101 - If medical advice is needed, have product container or label at hand.   |
| <b>Response</b>  | P273 - Avoid release to the environment.<br>P332 + P313 - If skin irritation occurs: Get medical attention.   |
| <b>Storage</b>   | Not applicable.   |
| <b>Disposal</b>  | P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.  |
| <b>Other hazards which do not result in classification</b> | Defatting to the skin.<br>USED ENGINE OILS<br>Used engine oil may contain hazardous components which have the potential to cause skin cancer.<br>See Toxicological Information, section 11 of this Safety Data Sheet. |

## Section 3. Composition/information on ingredients

|                          |         |
|--------------------------|---------|
| <b>Substance/mixture</b> | Mixture |
|--------------------------|---------|

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

### Section 3. Composition/information on ingredients

| Ingredient name  | %      | CAS number  |
|--|--------|-------------|
| Distillates (petroleum), hydrotreated heavy paraffinic                                 | ≤3     | 64742-54-7  |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic                              | ≤3     | 64742-65-0  |
| Distillates (petroleum), hydrotreated light paraffinic                                 | ≤3     | 64742-55-8  |
| Distillates (petroleum), solvent-dewaxed light paraffinic                              | ≤3     | 64742-56-9  |
| Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts | ≤3     | 84605-29-8  |
| Phenol, dodecyl-, branched   | ≤0.1   | 121158-58-5 |
| O,O,O-triphenyl phosphorothioate   | ≤0.055 | 597-82-0    |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### Description of necessary first aid measures

##### Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.

##### Skin contact

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur. If skin irritation or rash occurs: Get medical advice/attention.

##### Inhalation

If inhaled, remove to fresh air. Get medical attention if symptoms occur.

##### Ingestion

Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if adverse health effects persist or are severe.

##### Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### Most important symptoms/effects, acute and delayed

##### Potential acute health effects

##### Eye contact

No known significant effects or critical hazards.

##### Inhalation

Vapor inhalation under ambient conditions is not normally a problem due to low vapor pressure.

##### Skin contact

Causes mild skin irritation. Defatting to the skin.

##### Ingestion

Irritating to mouth, throat and stomach.

#### Over-exposure signs/symptoms

##### Eye contact

Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

##### Inhalation

No specific data.

## Section 4. First aid measures

|                     |   |
|---------------------|---|
| <b>Skin contact</b> | Adverse symptoms may include the following:<br>irritation<br>redness<br>dryness<br>cracking |
| <b>Ingestion</b>    | No specific data.   |

### Indication of immediate medical attention and special treatment needed, if necessary

|                            |   |
|----------------------------|---|
| <b>Notes to physician</b>  | Treatment should in general be symptomatic and directed to relieving any effects. |
| <b>Specific treatments</b> | No specific treatment.  |

See toxicological information (Section 11)

## Section 5. Firefighting measures

### Extinguishing media

|                                       |   |
|---------------------------------------|---|
| <b>Suitable extinguishing media</b>   | Use foam or all-purpose dry chemical to extinguish. |
| <b>Unsuitable extinguishing media</b> | Do not use water jet.                               |

### Specific hazards arising from the chemical

Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects.

### Hazardous thermal decomposition products

Combustion products may include the following:  
phosphorus oxides  
metal oxide/oxides  
carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)  
sulfur oxides (SO, SO<sub>2</sub> etc.)

### Special protective actions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

### Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

|                                    |  |
|------------------------------------|--|
| <b>For non-emergency personnel</b> | Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling. |
| <b>For emergency responders</b>    | Entry into a confined space or poorly ventilated area contaminated with vapor, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".   |

### Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

## Section 6. Accidental release measures

### Methods and materials for containment and cleaning up

#### Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilled product. Dispose of via a licensed waste disposal contractor.

## Section 7. Handling and storage

### Precautions for safe handling

#### Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Avoid contact of spilled material and runoff with soil and surface waterways.

#### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. Contaminated work clothing should not be allowed out of the workplace. See also Section 8 for additional information on hygiene measures.

#### Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

#### Not suitable

Prolonged exposure to elevated temperature

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

| Ingredient name   | Exposure limits  |
|---|--|
| Distillates (petroleum), hydrotreated heavy paraffinic    | <b>ACGIH TLV (United States, 1/2023). [Mineral Oil, pure, highly and severely refined]</b><br>TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | <b>ACGIH TLV (United States, 1/2023). [Mineral Oil, pure, highly and severely refined]</b><br>TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction |
| Distillates (petroleum), hydrotreated light paraffinic    | <b>ACGIH TLV (United States, 1/2023). [Mineral Oil, pure, highly and severely refined]</b><br>TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction |

## Section 8. Exposure controls/personal protection

Distillates (petroleum), solvent-dewaxed light paraffinic

**ACGIH TLV (United States, 1/2023).**  
**[Mineral Oil, pure, highly and severely refined]**  
 TWA: 5 mg/m<sup>3</sup> 8 hours. Form: Inhalable fraction

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

### Biological exposure indices

No exposure indices known.

### Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

#### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

Safety glasses with side shields.

#### Skin protection

##### Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

##### Body protection

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when

## Section 8. Exposure controls/personal protection

**Other skin protection**

cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection**

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

## Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

**Appearance**

- Physical state** Liquid.
- Color** Amber. [Light]
- Odor** Not available.
- Odor threshold** Not available.
- pH** Not applicable.
- Melting point/freezing point** Not available.
- Boiling point, initial boiling point, and boiling range** Not available.
- Drop Point** Not available.
- Pour point** -45 °C
- Flash point** Closed cup: >200°C (>392°F) [Pensky-Martens ASTM D 93]
- Evaporation rate** Not available.
- Flammability** Not available.
- Lower and upper explosion limit/flammability limit** Not available.

**Vapor pressure**

| Ingredient name   | Vapor Pressure at 20°C |       |             | Vapor pressure at 50°C |     |        |
|---|------------------------|-------|-------------|------------------------|-----|--------|
|   | mm Hg                  | kPa   | Method      | mm Hg                  | kPa | Method |
| Distillates (petroleum), hydrotreated heavy paraffinic    | <0.07501               | <0.01 | ASTM D 5191 |                        |     |        |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | <0.07501               | <0.01 | ASTM D 5191 |                        |     |        |
| Distillates (petroleum), hydrotreated heavy paraffinic    | <0.07501               | <0.01 | ASTM D 5191 |                        |     |        |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | <0.07501               | <0.01 | ASTM D 5191 |                        |     |        |
| Distillates (petroleum), hydrotreated light paraffinic    | <0.07501               | <0.01 | ASTM D 5191 |                        |     |        |

**Relative vapor density** Not available.

**Relative density** Not available.

## Section 9. Physical and chemical properties and safety characteristics

**Density** <1000 kg/m<sup>3</sup> (<1 g/cm<sup>3</sup>) at 15°C

### Solubility(ies)

| Media | Result      |
|-------|-------------|
| water | Not soluble |

**Solubility in water** Not available.

**Partition coefficient: n-octanol/water** Not applicable.

**Auto-ignition temperature** Not available.

**Decomposition temperature** Not available.

**Viscosity** Kinematic: 96.58 mm<sup>2</sup>/s (96.58 cSt) at 40°C  
Kinematic: 13.9 to 16.3 mm<sup>2</sup>/s (13.9 to 16.3 cSt) at 100°C

### Particle characteristics

**Median particle size** Not applicable.

## Section 10. Stability and reactivity

**Reactivity** No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.

**Chemical stability** The product is stable.

**Possibility of hazardous reactions** Under normal conditions of storage and use, hazardous reactions will not occur.  
Under normal conditions of storage and use, hazardous polymerization will not occur.

**Conditions to avoid** Avoid all possible sources of ignition (spark or flame).

**Incompatible materials** Reactive or incompatible with the following materials: oxidizing materials.

**Hazardous decomposition products** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Aspiration hazard

| Name  | Result                         |
|---|--------------------------------|
| Distillates (petroleum), hydrotreated heavy paraffinic    | ASPIRATION HAZARD - Category 1 |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | ASPIRATION HAZARD - Category 1 |
| Distillates (petroleum), hydrotreated light paraffinic    | ASPIRATION HAZARD - Category 1 |
| Distillates (petroleum), solvent-dewaxed light paraffinic | ASPIRATION HAZARD - Category 1 |

**Information on the likely routes of exposure** Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

### Potential acute health effects

**Eye contact** No known significant effects or critical hazards.

**Skin contact** Causes mild skin irritation. Defatting to the skin.

**Inhalation** Vapor inhalation under ambient conditions is not normally a problem due to low vapor pressure.

## Section 11. Toxicological information

**Ingestion** Irritating to mouth, throat and stomach.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

**Skin contact** Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking

**Inhalation** No specific data.

**Ingestion** No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Inhalation** Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

**Ingestion** Ingestion of large quantities may cause nausea and diarrhea.

**Skin contact** Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

**Eye contact** Potential risk of transient stinging or redness if accidental eye contact occurs.

### Potential chronic health effects

**General** USED ENGINE OILS  
Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.

**Carcinogenicity** No known significant effects or critical hazards.

**Mutagenicity** No known significant effects or critical hazards.

**Developmental effects** No known significant effects or critical hazards.

**Fertility effects** No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

| Route | ATE value       |
|-------|-----------------|
| Oral  | 161974.27 mg/kg |

## Section 12. Ecological information

**Environmental effects** This material is harmful to aquatic life with long lasting effects.

### Toxicity

No testing has been performed by the manufacturer.

### Persistence and degradability

Partially biodegradable.



## Section 12. Ecological information

### Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

### Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** Not available.

**Mobility** Spillages may penetrate the soil causing ground water contamination.

**Other adverse effects** No known significant effects or critical hazards.

**Other ecological information** Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

## Section 13. Disposal considerations

### Disposal methods

The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

|                                   | <b>ADR/RID</b> | <b>ADN</b>     | <b>IMDG</b>    | <b>IATA</b>    |
|-----------------------------------|----------------|----------------|----------------|----------------|
| <b>UN number</b>                  | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| <b>UN proper shipping name</b>    | -              | -              | -              | -              |
| <b>Transport hazard class(es)</b> | -              | -              | -              | -              |
| <b>Packing group</b>              | -              | -              | -              | -              |
| <b>Environmental hazards</b>      | No.            | No.            | No.            | No.            |
| <b>Additional information</b>     | -              | -              | -              | -              |

**Special precautions for user** Not available.

**Transport in bulk according to IMO instruments** Not available.

## Section 15. Regulatory information

### International regulations

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### Other regulations

**Australia inventory (AIC)** All components are listed or exempted.

**Canada inventory** All components are listed or exempted.

**China inventory (IECSC)** Not determined.

**Japan inventory (CSCL)** All components are listed or exempted.

**Korea inventory (KECI)** All components are listed or exempted.

**Philippines inventory (PICCS)** All components are listed or exempted.

**Taiwan Chemical Substances Inventory (TCSI)** All components are listed or exempted.

**United States inventory (TSCA 8b)** All components are active or exempted.

**REACH Status** The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

## Section 16. Other information

### History

**Date of printing** 10/17/2024

**Date of issue/Date of revision** 10/17/2024

**Date of previous issue** 9/11/2023

**Version** 7

**Prepared by** Product Stewardship Group

### Key to abbreviations

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]

UN = United Nations

Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1  
VOC = Volatile Organic Compound

 Indicates information that has changed from previously issued version.

### Notice to reader

## Section 16. Other information

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.